

✓ { 7900 - all codes except } (7875-89)
 - 00 - 01 - 11
 - 02 - 09 - 35
 - 03 - 10

00416 - all codes except
 - 1009 - 3563
 - 3203 - 3713
 - 4073
 - 4093
 - 4533
 - 7213

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

{ 7909-XX }
 { 7904-XX }
 { 45052-00 }
 { 7827-00 }

U.S. Department of Labor-1019
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)
 Shiva Signature Oil Colors

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name Jack Richeson & Co.	Emergency Telephone Number (800) 233-2404
Address (Number, Street, City, State, and ZIP Code) P.O. Box 160	Telephone Number for Information (800) 233-2404
Kimberly, WI 54136-0160	Date Prepared February 13, 2001
	Signature of Preparer (optional) Kelly M. Richeson

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
This product line carries the AP (approved product) seal of the Art & Craft Materials Institute. All formulas have been reviewed by a toxicologist and are considered non-toxic.				

Section III - Physical/Chemical Characteristics

Boiling Point	177° F	Specific Gravity (H ₂ O = 1)	1.07-2.43
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	Heavier than air	Evaporation Rate (Butyl Acetate = 1)	Slower than butyl acetate
Solubility in Water	Insoluble		
Appearance and Odor	Heavy, viscous liquid with characteristic oil paint odor.		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) 211° F Seta-Closed cup	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media CO ₂ , Dry chemical, Foam			
Special Fire Fighting Procedures Water may be ineffective and may casue fire to spread. Use NIOSH/MSHA approved gas mask for fire fighting personnel.			
Unusual Fire and Explosion Hazards Keep containers tightly closed. Vapors may migrate to ignition source.			

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid)
Strong oxidizing agents.

Hazardous Decomposition or Byproducts
CO₂ & CO

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? **Yes** Skin? **No** Ingestion? **No**

Health Hazards (Acute and Chronic)
This paint does not pose a health hazard.

Carcinogenicity: NTP? **Not listed** IARC Monographs? **None** OSHA Regulated? **NO**

Signs and Symptoms of Exposure
Possible dizziness if inhaled in an enclosed area.

Medical Conditions
 Generally Aggravated by Exposure **None Known**

Emergency and First Aid Procedures
Remove to fresh air, wash the skin, and irrigate the eyes. Call a doctor if ingested.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled
Dike the spill; then soak it up with inert absorbent. Keep contaminated materials and rags in approved containers rated for fire containment.

Waste Disposal Method
Dispose in accordance with local, state, and federal laws where permitted.

Precautions to Be Taken in Handling and Storing
Store away from heat in a cool, dry area and use with adequate ventilation.

Other Precautions
Rags and paper products soiled with oils can spontaneously combust. Dispose of properly in safety fire cans. Do not spray, apply or inhale vapors or dust of cadmium colors.

Section VIII — Control Measures

Respiratory Protection (Specify Type)
Dust mask or NIOSH approve respirator for higher concentrations

Ventilation	Local Exhaust	Yes	Special	No
	Mechanical (General)	No	Other	No
Protective Gloves	Yes		Eye Protection	No

Other Protective Clothing or Equipment
None

Work/Hygenic Practices
Handle with care - use good hygenic practices.