00445-1003 1004, 1006, 0000

12-12-03

Material Safety Data Sheet

WINSOR & NEWTON LIQUIN ORIGINAL

Section I

ColArt Americas, Inc 11 Constitution Avenue Piscataway New Jersey 08855-1396 Emergency Telephone Number 1-800-628-3385 Telephone Number for Information 732- 562- 0770

Date prepared 02/10/2003

Section II Hazard Ingredients/Identity Information

Hazardous Components	CAS No.	OSHA PEL	ACGIH TLV	
Low aromatic petroleum hydrocarbons	64742-47-8	no data	no data	
2-Butanone oxime	96-29-7	no data	no data	

Section III Physical/Chemical Characteristics

Boiling Point:	150-200	°C	Specific Gravity	0.89	
Vapour pressure	: no dat	а	Melting Point:	n/a	° C
Vapour density:	no dat	а	Evaporation rate	BuAc=1	< 1
Solubility in water	r:	Insoluble			
Appearance and odour Pale am			er liquid.Low hydrocarbor	odour	

Section IV Fire and Explosion Hazard Data

Flash Point	ca.70 ° C	closed cup	Flammable limits	LEL:	0.9	
		° C	ciosed cup	riammable mints	UEL:	6.0
Extinguishing M	edia	Carbo	n dioxide,dry c	chemical,foam.		
Special Fire Fighting Procedures		Combustible				
Unusual Fire and Explosion Hazards		none				

Section V Reactivity Data

Stability: Unstable:	Unstable :	no	Conditions to avoid :	none
	yes			
Incompatil	pility:	none known		
Hazardous	s Decompo:	sition	no	
Hazardous Polymerisation		no		

Section VI Health Hazard Data

Route of Entry	Inhalation? 🗹 Skin? 🗹 Ingestion? 🗹
Health Hazards:	
Inhalation of large	e quantities of vapour may cause dizziness,headache.
Prolonged contac	t with skin may cause irritation.
Carcinogenicity	: NTP: n/a IARC Monographs: n/a OSHA Regulated n/a
	·—·
Signs and Sym	ptoms of Exposure Nausea, headache.
Medical Condit	tions aggravated by exposure Pre-existing respiratory disorders
First Aid Proce	edures
Eyes:	Wash with water for 10 minutes
Skin:	Wash off with soap and water
Inhalation:	Remove from exposure
Inhalation:	Remove from exposure Give water to drink

Section VII Precautions for Safe Handling and Use

Steps to be taken if material is spilled		Absorb on inert substrate	
Sweep up immedi	ately	***	
Waste Disposal Method	Controlled landfill	_	_
As toxic waste			
Precautions to be taken in	Handling and Sto	rage	
Normal hygiene	·		
Avoid contact with s	kin		
Keep in closed cont	ainers		
Avoid extremes of to	emperature	_	
Other precautions	None		

Page 2 of 3

Section VIII Control Measures

Respiratory protection If large quantities being used NIOSH mask.

Ventilation Ensure good extraction/ventilation

Local exhaust fan

Mechanical Fume hood advisable for large quantities

Protective gloves Not required Eye protection If handling large quantities

Other protective equipment Protective clothing

Work/Hygenic Practices Avoid contact with skin and eyes

Use barrier creams

This product has been evaluated by a toxicologist and is labeled for acute and chronic health hazards in conformity with the Labeling of Hazardous Art Materials Act and Federal regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act.

This product conforms to ASTM D4236 Standard Practice for Labeling Art Materials for Chronic Adverse Health Hazards

DANGER HARMFUL OR FATAL IF SWALLOWED, COMBUSTIBLE, IRRITATING TO SKIN AND EYES. VAPOR HARMFUL. CONTAINS PETROLEUM DISTILLATES. Use only with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

If swallowed,do not induce vomiting.Call a physician or poison control center immediately.Get prompt medical attention.