

00481-1024

Material Safety Data Sheet

Martin/F. Weber Company
<<Close MSDS>>

Date Prepared:
31 October, 2004

For Health Emergencies, CALL A POISON CONTROL CENTER

For Transportation Emergencies ONLY: Call Chem-Tel:
USA, Canada, Puerto Rico, US Virgin Islands: Call 800-255-3924
Outside North America: Call Collect 813-248-0585

SECTION 1 - PRODUCT & COMPANY IDENTIFICATION

1.1 PRODUCT NAME Bob Ross Glazing Medium

1.2 ITEM NUMBERS AND SIZES R6750 - 118ml

1.3 COMPANY IDENTIFICATION Martin/F. Weber Company
2727 Southampton Road
Philadelphia, PA 19154-1293 USA
Phone: 215-677-5600 Fax 215-677-3336
email: info@weberart.com

SECTION 2 - COMPOSITION INFORMATION

COMPONENT	CAS #	MAX. AMOUNT (% Weight)
Petroleum Naptha	8052-41-3	60%

SECTION 3 - HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Appearance Tan translucent liquid slurry

Physical State Liquid Slurry

Odor Mild Solvent Odor

Hazards of Product Combustible material, May be harmful by breathing vapors, May be harmful by skin contact or ingestion. Exposure may result in nausea, headache, confusion or instability

3.2 POTENTIAL HEALTH EFFECTS

Effects of Single Acute Overexposure: May be harmful by ingestion or breathing vapors, May be harmful by skin contact or ingestion. Exposure may result in nausea, headache, confusion or instability.

Chronic, Prolonged or Repeated Overexposure: May be harmful by breathing vapors, Exposure may result in nausea, headache, confusion or instability.

Medical Conditions Aggravated by Exposure:

3.3 POTENTIAL ENVIRONMENTAL EFFECTS

SECTION 4 - FIRST AID PROCEDURES

- 4.1 INHALATION Move to fresh air. If symptoms persist, seek prompt medical attention.
- 4.2 EYE CONTACT Rinse with tap water for 5 - 10 minutes. If irritation persists, seek medical attention.
- 4.3 SKIN CONTACT Wash with soap and water for 5 - 10 minutes. If irritation persists, seek medical attention.
- 4.4 SWALLOWING Don not induce vomiting. Seek prompt medical attention.
- 4.5 NOTES TO PHYSICIAN

SECTION 5 - FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Flash Point - Closed Cup 125°F - 135°F (52°C - 57°C)

Flash Point - Open Cup

Auto-Ignition Temperature

Flammable Limits in Air

5.2 EXTINGUISHING MEDIA Dry Chemical, Foam, Carbon Dioxide , Water Fog

5.3 EXTINGUISHING MEDIA TO AVOID

5.4 SPECIAL FIRE FIGHTING PROCEDURES

5.5 SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS

5.6 UNUSUAL FIRE AND EXPLOSION HAZARDS N/A

5.7 HAZARDOUS COMBUSTION PRODUCTS Thermal Decomposition may yield CO, CO₂, and other unidentified hydrocarbons.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Steps to be Taken if Material is Released or Spilled Small spills may be cleaned up with rags or paper towels and transferred to airtight metal containers for disposal.

SECTION 7 - HANDLING AND STORAGE

7.1 GENERAL HANDLING

Keep containers closed when not in use. Keep away from children. Do not smoke while using. Wash hands immediately after use. Avoid prolonged contact with skin, ingestion and breathing of vapors.

7.2 STORAGE

Do not store near heat of flame.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 EXPOSURE LIMITS

8.2 PERSONAL PROTECTION

Respiratory Protection:

Not required if adequate cross ventilation is maintained.

Ventilation:

Use local exhaust fan to assure adequate cross ventilation in working area and to remove fumes. Avoid vapor buildup.

Eye Protection:

Use goggles or face shield for eye protection

Protective Gloves:

Rubber or vinyl impermeable gloves.

Other Protective Equipment:

Suitable to existing work environment

8.3 ENGINEERING CONTROLS

N/A

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid Slurry
Appearance	Tan translucent liquid slurry
pH	N/A
Solubility in Water (by Weight)	Insoluble
Odor	Mild Solvent Odor
Flash Point - Closed Cup	125°F - 135°F (52°C - 57°C)
Flash Point - Open Cup	
Percent Volatiles	
Boiling Point (760mm Hg)	240°F - 250°F (115°C - 120°C)
Freezing Point	
Specific Gravity (H₂O=1)	.86
Vapor Pressure at 20°C	5mm Hg
Vapor Density (air = 1)	>1
Evaporation Rate (Butyl Acetate = 1)	<1
Melting Point	

SECTION 10 - STABILITY AND REACTIVITY

- 10.1 Stability / Instability** Stable
- Conditions to Avoid:** Heat or Flame , elevated temperature, sparks or sources of ignition.
- Incompatible Materials:** Strong Oxidizing Agents
- 10.2 Hazardous Polymerization** Will not occur.
- 10.3 Inhibitors / Stabilizers**

SECTION 11 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: Combustible material, May be harmful by breathing vapors, May be harmful by skin contact or ingestion. Exposure may result in nausea, headache, confusion or instability

CHRONIC TOXICITY: May be harmful by breathing vapors, Exposure may result in nausea, headache, confusion or instability.

SECTION 12 - ECOLOGICAL INFORMATION

- 12.1 Environmental Fate**
- 12.2 Ecotoxicity**
- 12.3 Further Information**

SECTION 13 - DISPOSAL CONSIDERATIONS

- 13.1 Waste Disposal Method:** Small spills may be picked up with rags or paper towels and transferred to air tight containers for disposal.
- 13.2 Disposal Considerations:** Dispose of in accordance with local, state and federal regulations

SECTION 14 - TRANSPORTATION INFORMATION

- U.S. D.O.T.** Ground Transportation: ORM-D,
Ocean Freight: Paint, Hazard Class 3.3 , Identification Number UN1263,
Packing Group III, Limited Quantity.
DO NOT SHIP via Air Freight without special packaging and labeling.
Contact your air carrier for detailed instructions.

SECTION 15 - REGULATORY INFORMATION

- 15.1 Federal / National**

15.2 State / Local

SECTION 16 - OTHER INFORMATION

The information presented here is current as of the date of this Material Safety Data Sheet. Since use of this information and the product are not under the control of Martin/F. Weber Company, it is the user's obligation to determine conditions of safe use and to carefully read the product label and follow all instructions for safe use of the product.

**General Health &
Safety Information**

▲ Top of Page ▲

<<Close MSDS>>