

OCT-13-2005 THU 04:21 PM colart americas

FAX NO. 7325620941

P. 05

Rec'd 10.13.05

00489-4004

Material Safety Data Sheet

WINSOR & NEWTON THICKENED LINSEED OIL

Section I

ColArt Americas, Inc
11 Constitution Avenue
Piscataway
New Jersey 08855-1396

Emergency Telephone Number 1-800-628-3385
Telephone Number for Information 732- 662- 0770
Date prepared 03/10/2002

Section II Hazard Ingredients/Identity Information

Hazardous Components	CAS No.	OSHA PEL	ACGIH TLV
None			

Section III Physical/Chemical Characteristics

Boiling Point:	> 300 °C	Specific Gravity:	0.9
Vapour pressure:	n/a	Melting Point:	°C
Vapour density:	n/a	Evaporation rate:	n/a
Solubility in water:	insoluble		
Appearance and odour:	Yellow liquid. Vegetable oil odour		

Section IV Fire and Explosion Hazard Data

Flash Point:	> 230 °C closed cup	Flammable limits:	LEL: n/a UEL: n/a
Extinguishing Media:	Carbon dioxide, dry chemical, foam.		
Special Fire Fighting Procedures:	Keep cool.		
Unusual Fire and Explosion Hazards:	Black smoke evolved may effect eyes and lungs.		

Section V Reactivity Data

Stability:	Unstable: <input type="checkbox"/> Stable: <input checked="" type="checkbox"/> yes	Conditions to avoid:	
Incompatibility:	Combustible matter e.g. cotton waste		
Hazardous Decomposition:	Acrolein may be evolved in a fire		
Hazardous Polymerisation:	n/a		

OCT-13-2005 THU 04:22 PM colart americas

FAX NO. 7325620941

P. 06

Section VI Health Hazard Data

Route of Entry	Inhalation? <input type="checkbox"/>	Skin? <input type="checkbox"/>	Ingestion? <input type="checkbox"/>
Health Hazards:			
Prolonged contact with skin could cause dermatitis.			
Carcinogenicity:	NTP: n/a	IARC Monographs:	n/a
	OSHA Regulated	n/a	
Signs and Symptoms of Exposure			
Medical Conditions aggravated by exposure			
First Aid Procedures			
Eyes:	Wash with water for 10 minutes		
	If irritation persists get medical attention		
Skin:	Wash off with soap and water		
Inhalation:	Not applicable		
Ingestion:	Give water to drink		
	Get medical attention		

Section VII Precautions for Safe Handling and Use

Steps to be taken if material is spilled	Absorb on inert substrate
Sweep up immediately	
Waste Disposal Method	According to local regulations
Precautions to be taken in Handling and Storage	
Normal hygiene	
Avoid contact with skin	
Keep in closed containers	
Avoid extremes of temperature	
Other precautions	

OCT-13-2005 THU 04:22 PM colart americas

FAX NO. 7325620941

P. 07

Section VIII Control Measures

Respiratory protection	
Ventilation	n/a
Local exhaust	
Mechanical	
Protective gloves	Eye protection
Other protective equipment	
Work/Hygenic Practices	Avoid ingestion
Use barrier creams	

This product has been evaluated by a toxicologist and is labeled for acute and chronic health hazards in conformity with the Labeling of Hazardous Art Materials Act and Federal regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act.

This product conforms to ASTM D4236 Standard Practice for Labeling Art Materials for Chronic Adverse Health Hazards

DANGER: Rags, Steel wool or Waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container.