



MATERIAL SAFETY DATA SHEET

According to the AFNOR standard T 01-102.

Page 1/3

PEBEO Safety data sheet

Revision date: 05/04/96

version 1

Product: :EXTRA-FINE ACRYLIC - Permanent Primary Yellow

1/ZU2505

1. Identification of the preparation and company

Product name:**EXTRA-FINE ACRYLIC
Permanent Primary Yellow**Society:PEBEO INDUSTRIES
Parc d'activité de Gémenos
Av. du pic de Bertagne BP 106
13881 GEMENOS Cedex
FRANCE

TEL: 42 . 32 . 08 . 08

FAX: 42 . 32 . 01 . 70

2. Composition / information of ingredients

Chemical characterization:water-based paint

<u>Hazardous components:</u>	<u>CAS n°:</u>	<u>CONTENT:</u>	<u>CLASSIFICATION:</u>
Solution of isothiazolone derivatives	0 26172-55-4	0.15%	Xi when > 0.2%
Cadmium Yellow (PY35) (CI : 77205)			

Hazard classification EEC : this product is a preparation.

3. Hazard identification of the preparation

CONTAINS CADMIUM ZINC SULFIDE.

4. First aid measures

Safety precautions:In all case of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.Inhalation: no toxic .Eye contact:

Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Skin contact:

Wash skin thoroughly with soap and water.

Ingestion:

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do not induce vomiting.



PEBEO Safety data sheet

Revision date:05/04/96

Product:EXTRA-FINE ACRYLIC - Permanent Primary Yellow

version 1

1/ZU2505

5. Fire-fighting measures

Extinguishing media:

Water spray, CO2, Foam, dry powder.

Recommendations:

No recommendations.No flammable product.

6. Accidental release measures

Steps to be taken in case material is released or spilled:

Small spills may be collected with absorbent materials. For large spills, flush area with water spray. Prevent runoff from entering drains, sewers or streams.

Waste disposal method:

Incineration. Observe all federal, state and local laws concerning health and environment.

7. Handling and storage

Handling:

Keep container tightly closed..
Avoid skin and eye contact.

Storage:

Observe label precautions. Store in a dry, well ventilated place away from sources of heat and direct sunlight.Keep away from freezing.

8. Exposure controls / personal protection

Engineering measures:Don't swallow for prolonged or repeated contact, use protective gloves.

9. Physical and chemical properties

Physical state	Liquid
pH	9/9.5
Density	1.150
Viscosity	15/22p
Flash point	NA



PEBEO Safety data sheet
Revision date: 05/04/96
Product: EXTRA-FINE ACRYLIC - Permanent Primary Yellow
version 1
1/ZU2505

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

11. Toxicological informations

Contains cadminm, don't swallow.

12. Ecological informations

There are no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

13. Disposal consideration

Do not allow into drains ar water courses.
Observe all federal, state and local laws concerning health and environment.

14. Transport information

Not applicable.

15. Regulatory information

This preparation is not classified as dangerous according to EC Directive 88/379/EEC.
The product is labelled as follows :Comforms to ASTM D4236

16. Other information

The information of this MSDS is based on the present state of our knowledge and current EU and national laws, as the user's working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the product's properties.