

02/01/2002 11:25 7182920406

RONAN PAINTS

PAGE 06

01027-1017

Rwd 02-01-02

MATERIAL SAFETY DATA SHEET

SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : AQUATHANE UV ABSORB FLAT
IDENTIFICATION NUMBER: AQUVFL
PRODUCT USE/CLASS :
DATE PRINTED: 02/01/02

SUPPLIER: T. J. Ronan Paint Corporation
749 East 135th St.
Bronx, NY 10454

MANUFACTURER: T. J. Ronan Paint Corporation
749 East 135th St.
Bronx, NY 10454

CHEMTREC: (800) 424-9300
24 HOUR EMERGENCY HOTLINE

CHEMTREC: (800) 424-9300
24 HOUR EMERGENCY HOTLINE

PREPARER: JD, PHONE: 718-292-1100, PREPARE DATE: 02/01/02

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Table with columns: CHEMICAL NAME, CAS NUMBER, WT. PERCENT, IS LESS THAN, TLV-TWA, TLV-STEL, OCCUPATIONAL EXPOSURE LIMITS (PEL-TWA, PEL-CEILING), SKIN. Rows include N-METHYL-2-PYRROLIDONE, DIETHYLENE GLYCOL MONOBUTYL ETHER, and TRIETHYLAMINE.

(See Section 11 for abbreviation legend)

SECTION III - PHYSICAL DATA

BOILING RANGE : 212 - 453 F
ODOR : LOW
APPEARANCE : CLEAR LIQUID
SOLUBILITY IN H2O : WATER SOLUBLE
VOLATILE BY WEIGHT: 63.6%
VOCS, lbs/gal : 2.71
VAPOR DENSITY : Is heavier than air
SPECIFIC GRAVITY: 1.0545
EVAPORATION RATE: Is slower than Ether
VOLATILE BY VOL.: 68.2%
VOCS, grams/ltr : 325

(See Section XI for abbreviation legend)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N.A.
LOWER EXPLOSIVE LIMIT: 0.9 %
UPPER EXPLOSIVE LIMIT: 24.6 %
EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM WATER FOG
UNUSUAL FIRE AND EXPLOSION HAZARDS: MATERIAL CAN SPLATTER ABOVE 100C/212F.
POLYMER FILM CAN BURN.

(Continued on Page 2)

V-1887

02/01/2002 11:25 7182920406

RUNAN PAINIS

PAGE 01

Product: AQUVFL

Preparation Date: 02/01/02

Page 2

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

SPECIAL FIREFIGHTING PROCEDURES: DO NOT BREATHE FUMES. WEAR SELF-CONTAINED BREATHING APPARATUS (PRESSURE DEMAND, MSHA/NOISH-APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL TO REDUCE PRESSURE.

## SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: INHALATION: VAPOR OR SPRAY MIST CAN CAUSE HEADACHE, NAUSEA, AND IRRITATION OF THE NOSE, THROAT AND LUNGS. SKIN CONTACT: IRRITATING TO SKIN UPON REPEATED OR PROLONGED CONTACT. EYES: LIQUID CONTACT RESULTS IN IRRITATION. MAY CAUSE TEMPORARY CORNEAL CLOUDING. INGESTION: MAY BE HARMFUL IF SWALLOWED.

MEDICAL CONDITIONS PRONE TO AGGRAVATION: NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES: INHALATION: MOVE SUBJECT TO FRESH AIR. EYE CONTACT: FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. SKIN CONTACT: REMOVE SATURATED CLOTHING. WASH WITH SOAP AND WATER. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS. LAUNDRY SATURATED CLOTHING AND CLEAN SHOES BEFORE REUSE. INGESTION: DO NOT INDUCE VOMITING. SLOWLY DILUTE WITH 3 - 4 GLASSES OF MILK OR WATER AND SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION  
INGESTION EYE CONTACT

## SECTION VI - REACTIVITY DATA

HAZARDOUS DECOMPOSITION PRODUCTS: MAY PRODUCE TOXIC FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE AND/OR CARBON DIOXIDE. DECOMPOSITION IS DEPENDENT ON TIME AND TEMPERATURE.

CONDITIONS TO AVOID: ONSET OF DECOMPOSITION IS 177C/350F. AVOID FREEZING.

INCOMPATIBILITY: AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

## SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: LARGE SPILLS: KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY: USE CARE TO AVOID FALLING. DIKE AND CONTAIN SPILL WITH INERT MATERIAL (E.G SAND, EARTH). SMALL SPILLS: TAKE UP WITH AN ABSORBENT MATERIAL AND SEAL TIGHTLY FOR PROPER

(Continued on Page 3)

02/01/2002 11:25 7182920406

RONAN PAINTS

PAGE 08

Product: AQUVFL

Preparation Date: 02/01/02

Page 3

**SECTION VII - SPILL OR LEAK PROCEDURES**

DISPOSAL. TRANSFER LIQUID TO CONTAINERS FOR RECOVERY OR DISPOSAL AND SOLID DIKING MATERIAL TO SEPARATE CONTAINERS FOR DISPOSAL. KEEP SPILLS AND CLEANING RUNOFFS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

WASTE DISPOSAL METHOD: DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

**SECTION VIII - SAFE HANDLING AND USE INFORMATION**

RESPIRATORY PROTECTION: WEAR TO AVOID BREATHING SPRAY MIST, HEATED VAPORS OR FUMES OR IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS (SECTION II). USE A NIOSH - APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE.

VENTILATION: MECHANICAL LOCAL EXHAUST AT THE POINT OF VAPOR OR MIST RELEASE.

PROTECTIVE GLOVES: WEAR IMPERVIOUS GLOVES.

EYE PROTECTION: WEAR CHEMICAL RESISTANT GOGGLES TO PREVENT EYE CONTACT.

OTHER PROTECTIVE EQUIPMENT: WEAR PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT. EYE WASH STATION SHOULD BE AVAILABLE.

HYGIENIC PRACTICES: WASH WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

**SECTION IX - SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID CONTACT WITH VAPORS AND FUMES. AVOID CONTACT WITH EYES SKIN AND CLOTHING. STORAGE TEMPERATURE MAX. 49C/120F; MIN.1C/34F. KEEP FROM FREEZING. STORE AWAY FROM SPARKS AND FLAMES. DO NOT BREATHE SPRAY MIST.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. OBSERVE LABEL PRECAUTIONS.

**SECTION X - HMIS RATINGS**

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0

**SECTION XI - OTHER REGULATIONS**

(Continued on Page 4)

02/01/2002 11:25 7182920406

KUNAN PAINTS

PAGE 09

Product: AQUVFL

Preparation Date: 02/01/02

Page 4

## SECTION XI - OTHER REGULATIONS

## SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT %	IS LESS THAN
TRIETHYLAMINE	121-44-8		5.0 %

PREVIOUS MSDS REVISION DATE: 12/17/01

LEGEND: N.A. - Not Applicable, N.E. - Not Established,  
N.D. - Not Determined

The information contained on this MSDS is to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

&lt;END OF MSDS&gt;