

Recd 03-27-03

01107- all codes except below

Material Safety Data Sheet for R&F Pigment Sticks
OSHA Hazard Communication Standard (29 CFR 1910.1200)
Similar to OSHA Forms 20 and 174U S Department of Labor
Printed Date 03/16/98 at 11:13:2

Manufacturer's Name and Location
 R&F Handmade Paints, Inc.
 506 Broadway
 Kingston, NY 12401
 Contact - Richard Frumess, P resident
 For Information - 1.800.206.8088
 Emergency Telephone # - 1.800.206.8088 or phone your local Poison Control Center
 Preparation Date - 01/14/98

CC97-231DNCUSTOMFCIINE CAD					
-0069	-3214	-4134	-4823	-6584	-7623
-3093	-4093	-4183	-4824	-6913	-7624
-3094	-4094	-4184	-5373	-6914	-7933
-3103	-4123	-4533	-5374	-7213	-7934
-3104	-4124	-4534	-6583	-7214	
-3213	-4133				

Rev.# 00

Confirm all Information Prior to Use

Label Statements for R&F Pigment Sticks

Acute Toxicity - no label required
 Chronic Toxicity - no label required

California Prop 65 Warning Statement

Warning! This product contains an ingredient known to the state of California to cause cancer

Certification Assurance

Conforms to ASTM D-4236

Children's Hazard Warning

Keep Out of Reach of Children

Abbreviations:

- Not Applicable: n/a
- Not Flammable: n/f
- Not Known: n/k
- Repirable Fraction: r
- Permissible Exposure Limit: pel
- Ceiling Value: c
- Not Determined: n/d
- Not Listed: n/l
- ACGIH Threshold Limit Value: tlv

The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given.

TLV Reg. TM, ACGIH

V-1811

Data For All Colors Except Cadmium & Cobalt:**Hazardous Ingredients/Identity/Standards/Content Information**

Ingredient Listing - wax/oil base medium

CAS No. - mixture

OSHA PEL - n/a

ACGIH TLV - n/a

STEL - n/a

% COMP - <95

Ingredient Listing - pigments/colorants

CAS No. - mixture

OSHA PEL - n/a

ACGIH TLV - n/a

STEL - n/a

% COMP - <50

The ingredients in the wax base medium are judged to be non-hazardous, in this form, and are regarded as a trade secrets

Physical/Chemical Characteristics

Boiling Point - >240 degrees C.

Melting Point - <110 degrees F.

Vapor Pressure - n/a

Evaporation Rate - n/a

Odor - odor of wax

Specific Gravity - 0.927-0.970

Vapor Density - n/a

Water Solubility - insoluble

Appearance - colored wax

Fire and Explosion Hazard Data

Flash Point - >240 degrees F.

Flash Point Method - open cup

Lower Flammability Limit - n/l

Upper Flammability Limit - n/l

Extinguishing Medium - foam, dry chemical and CO2

Specialized Fire/Fighting Procedure - none

Unusual Fire and Explosion Hazard - none

Reactivity Data

Stable - yes

Incompatibility - none

Conditions to Avoid - none

Hazardous Polym. - no

Hazardous Decomposing - yes

Health Hazard Data

Not intended for use by children. Keep out of reach of children.

Routes of Entry

Inhalation - yes

Skin - no

Ingestion - n/k

Carcinogen

NTP - not listed

IARC - not listed

OSHA - not listed

Signs/Symptoms of Exposure - not listed

Medical Conditions to Avoid - none

First Aid - normally not needed

Precautions for Safe Handling and Use:

Spill - if heated, allow to cool

Waste Disposal - dispose in an appropriate manner which complies with local regulations

Precautions - do not store near heat, keep cool

Other Precautions - none

Control Measures

Respiratory Protection - normally not needed

Local Exhaust - use local exhaust if pigment sticks are heated

Specific Local Exhaust - normally not needed

Mechanical Exhaust - provide more ventilation if necessary

Other Mechanical Exhaust - normally not needed

Protective Gloves - wear gloves or barrier cream to protect against contact

Eye Protection - normally not needed

Protective Clothing - normally not needed, suggest freshly laundered artist's smock

Work Practices - wash hands and face after use

Page 4