

04-12-05

01571-3093	-3793	-4183
-3094	-3794	-4184
-3103	-4093	-4533
-3104	-4094	-4534
-3203	-4123	-7203
-3204	-4124	-7204
-3713	-4133	-7213
-3714	-4134	-7214
	-4103	-4104

MATERIAL SAFETY DATA SHEET
 OSHA Hazard Communication
 Standard (29 CFR 1910.1200)

SIMILAR TO OSHA FORMS 20 AND 174
 US Department of Labor
 Printed date: 2/17/98 at 11:58:0

PRODUCT NAME: WILLIAMSBURG HANDMADE OIL COLORS
 PRODUCT COLOR: **CADMIUM PIGMENT COLORS**
 PRODUCT NUMBER: SEE LIST
 REGULATORY STATUS: CONFORMS TO ASTM D-4236, LHAMA AND FHSA

SECTION I MANUFACTURER'S NAME AND LOCATION
 COMPANY NAME WILLIAMSBURG ART MATERIALS
 ADDRESS RRI BOX 465E
 CITY, STATE, ZIP EAST MEREDITH NY USA 13757
 Contact Beverly Plansky Title BUSINESS MANAGER
 INFO TEL NO. 1-607-278-6154
 EMERGENCY TEL NO. 1-607-278-6154
 Preparation Date: 02/13/98 REV.#

SECTION II HAZARDOUS INGREDIENTS/ IDENTITY/ STANDARDS/ CONTENT INFORMATION

Ingredient Listing	CAS No.	OSHA PEL	ACGIH TLV	STEL	% COMP
Oil Base Medium	mixture	n/l	n/l	n/l	<70.00
Cadmium compounds	mixture	.005 mg/m3	.002 mg/m3	n/l	<55.00

The other ingredients in the oil base medium are judged to be non-hazardous and are regarded as trade secrets

SECTION III PHYSICAL/ CHEMICAL CHARACTERISTICS

Boiling Point n/a	Deg. F (Cel.)	Spec Grav	.930 @ 68 F.
Melting Point n/a	Deg. F (Cel.)	(H29=I).	
Vapor Pressure n/a		Vapor density n/a	
Evaporation Rate n/a		Water Solubility n/a	
Odor n/a	Appearance	Viscous	

SECTION IV FIRE and EXPLOSION HAZARD DATA

Flash Point >200 F. Deg. F.(Cel) Flash Pt. Method unkwn
 Lower Flam Limit n/l % Upper Flam. Limit n/l
 Exting. Medium Regular foam, water fog, carbon dioxide, dry chemical.
 Specialized Fire Wear a self contained breathing apparatus with a full
 Fighting Proc. facepiece operated in the positive pressure demand mode with appropriate
 turn-out gear and chemical resistant personal protective equipment.
 Unusual Fire & Explosion Hazard May form: acrolein, carbon dioxide and carbon monoxide,
 various hydrocarbons.

SECTION V REACTIVITY DATA

(Unstable) Conditions None known
 Stable (yes/no) yes to avoid
 (Stable)
 Incompat (Avoid) None

V-11119

Haz. Decomp. (y/n) no
 Cond to Avoid none

Haz. Polym. (yes/no) no

Confirm all information prior to use

Abbreviations: Not Applicable N/A.. Not Flammable NIF
 Not Known N/K
 Respirable Fraction R
 Permissible Exposure Limit PEL

Ceiling Value C
 Not Determined N/D
 Not Listed N/L
 Unknown UNKWN
 ACGIH Threshold Limit Value TLV

The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given.

SECTION VI HEALTH HAZARD DATA

Routes of Entry: Inhalation yes
 Skin Yes
 Ingest, Yes

Health Hazards Contains cadmium compounds which may cause cancer by ingestion and inhalation excessive fumes or dust. (Risk of cancer depends on duration and level of exposure.) Effects of ingestion are dumulative due to slow elimination of absorbed Cadium. May cause harm to kidneys, testes and developing fetus. Prolonged or repeated skin contact may cause skin irritation and dermatitis.

NTP Carcinogen YES

IARC Carcinogen Yes

OSHA Carcinogen YES

Signs/Symptoms n/l,

of Exposure

Medical Conditions None

to Avoid

First Aid

If eaten seek medical attention immediately. If skin is irritated, wash with soap and water. If irritation persists, see a physician

SECTION VII

PRECAUTIONS FOR SAFE HANDLING AND USE

spill
 Waste Disp
 Precautions
 Other Precautions

Absorb liquid on vermiculite, floor absorbent or other absorbent material
 Disposal should be in accordance with all applicable local, state and federal regulations.
 Do not store near heat. Keep cool.
 None known

SECTION VIII

CONTROL MEASURES

Resp Protect Normally not needed.
 Local Exhaust Normally not needed
 Spec Local Exh Normally not needed
 Mech Exhaust Normally not needed
 Other Mech Exhaust Normally not needed
 Protect Gloves Wear gloves or use barrier creams to protect skin.
 Eye Protect Normally not needed
 Protect Clothing Freshly-laundered artist's smock.
 Work Practices Wash hands and face after use.

LABEL STATEMENTS FOR WILLIAMSBURG - HANDMADE OIL COLORS

Acute Toxicity None

Chronic Toxicity None

CALIFORNIA PROP 65

WARNING STATEMENT

'WARNING' This product contains a chemical known to the State of California to cause Cancer.

Certification Assurance Conforms to ASTM D-4236
 Children's Hazard Warning **KEEP OUT OF THE REACH OF CHILDREN.**

=====

<u>Confirm all information prior to use</u>			
Abbreviations:	Not Applicable N/A..	Not Flammable NIF	Ceiling Value C
	Not Known N/K		Not Determined N/D
	Respirable Fraction R		Not Listed N/L
Permissible Exposure Limit PEL			Unknown UNKWN
			ACGIH Threshold Limit Value TLV

The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given.

