MATERIAL SAFETY DATA SHEET

Tri-Art Manufacturing Incorporated 4 Harvey Street Kingston, Ontario K7K 5B9

Phone (613) 541-0299

Fax (613) 541-1765

SECTION #1: PRODUCT IDENTIFICATION

Product Identifier:

Tri-Art Finest Quality Artist Acrylic Color & Mediums/Glass Paint/ Techstyle Paint

(High Viscosity, Liquid, Acrylic Mediums) **Artists Paint**

Product Use: Whmis Classification: **MSDS Preparation Date:**

Not Controlled. October 5th, 2011

SECTION 2: HAZARDS IDENTIFICATION

Potential Acute Health

Inhalation

Pigment powders in this paint are not in the form of respirable dusts, hence they do not pose the hazards associated with the inhalation of fine mineral particles. Sanding of dried paint surfaces may result in these pigments becoming airborne and causing respiratory irritation. Under spray painting conditions, exposure may cause respiratory irritation. For paints containing Nickel Compounds it is advisable not to spray apply. Spray may be harmful if inhaled. Over exposure may cause irritation and harm to the respiratory tract. Nickel compounds may pose a cancer hazard.

Eye Contact Prolonged or repeated contact may result in eye irritation.

Skin Contact Prolonged or repeated contact may result in skin irritation.

Ingestion May cause irritation to the gastrointestinal system.

Additional Exposure Existing skin, eye, or respiratory conditions may be aggravated by exposure. Information

Potential Chronic Health Effects Additional information see toxicological information (Section 11).

Additional Exposure Information Existing skin, eye, or respiratory conditions may be aggravated by

exposure. Prolonged exposure to topcoat may result in reproductive

hazard.

SECTION 3: COMPOSITIONS DATA

All Tri-Art Paints, & Mediums, contain ingredients found in the Whmis Ingredient Disclosure List:

INGREDIENTS	%Wt/Wt	C.A.S.#	TLV	LD50 (g/KG)
Propylene Glycol	1.0 - 12.5	57-55-56	NA	20 (RAT)
Texanol	1.0 - 2.0	25265-77-4	NA	< 3.2 (RAT)

Page 1 of 6 Item Numbers: 01604-9001, 01604-9003

In addition, some paints contain product specific compounds that have been identified in the Ingredient Disclosure List:

Products/ Ingredients	%Wt/Wt	C.A.S.#	TLV	LD50 (g/KG)
Bismuth Yellow (All) Alkylaryl Polyether Calcium Molybdate	1.5 - 2.0 2.0 - 4.5	60864-33-7 7789-82-4	NA NA	NA NA
Carbon Black Carbon Black	4.0 - 6.0	1333-86-4	NA	NA
Chrome Green Alkylaryl Polyether Chrome (III) Oxide	1.0 - 1.5 25.0 - 35.0	60864-33-7 1308-38-9	NA 1 mg/m3	NA 5
Cobalt Blue Alkylaryl Polyether CI Pigment Blue 28	2.0 - 3.0 20 - 30	60864-33-7 1345-16-0	NA NA	NA NA
Cobalt Green Alkylaryl Polyether CI Pigment Green 26	2.0 - 3.0 20 - 30	60864-33-7 68187-49-5	NA NA	NA NA
Cobalt Teal Alkylaryl Polyether CI Pigment Green 50	2.0 - 3.0 20 - 30	60864-33-7 68186-85-6	NA NA	NA NA
Burnt Sienna Ferric Oxide	5.0 - 7.0	1309-37-1	10 mg/m3	10 (Rat)
Cadmium Orange C.I. Pigment Orange 20	25 - 30	58339-34-7	NA	NA

SECTION 3: COMPOSITIONS DATA (cont'd)

Products/ Ingredients	%Wt/Wt	C.A.S.#	TLV	LD50 (g/KG)
Cadmium Reds C.I. Pigment Red 108	25 - 30	58339-34-7	NA	NA
Cadmium Yellows C.I. Pigment Yellow 35	20 - 25	8048-07-5	NA	NA
Mars Black Ferric Oxide Alkylaryl Polyether	20 - 25 1.5 - 2.0	1309-37-1 60864-33-7	10 mg/m3 NA	10 (Rat) NA
Naples Yellow Ferric Oxide	20 - 25	1309-37-1	10 mg/m3	10 (Rat)
Nickel Azo Yellow C.I. Pigment Yellow 150	10 - 25	68511-62-6	NA	NA
Paynes Grey Carbon Black	1.0 - 2.0	1333-86-4	NA	NA
Raw Sienna Ferric Oxide	12 – 20	1309-37-1	10 mg/m3	10 (Rat)

Item Numbers: 01604-9001, 01604-9003 Page 2 of 6

Umbers (Burnt and Raw Ferric Oxide Manganite (Mn2O3) Silica, Crystalline	/) 10 - 15 1.5% Max. 1.0% Max	1309-37-1 1317-34-6 14808-60-7	10 ppm 5 mg/m3 0.1 mg/m3	10 (Rat) NA NA
Red Oxide Ferric Oxide Alkylaryl Polyether	25 - 30 1.5 - 2.0	1309-37-1 60864-33-7	10 ppm NA	10 (Rat) NA
Titanium White Alkylaryl Polyether	2.0 - 4.0	60864-33-7	NA	NA
Transparent Gold Oxide Ferric Oxide	8 - 12	1309-37-1	10 ppm	10 (Rat)
Yellow Oxide Ferric Oxide Alkylaryl Polyether	18 - 22 1.5 - 2.0	1309-37-1 60864-33-7	10 ppm NA	10 (Rat) NA
Unbleached Titanium Alkylaryl Polyether	2.0 - 2.5	60864-33-7	NA	NA
	anakat airat in sanaka airat aira		Providental Control of the State of the Stat	
	SECTION	N3: COMPOSITION	DNS DATA	
Interference Colours Mica	7.0 - 9.0	12001-26-2	5 mg/m3	5 (RAT)
	7.0 - 9.0			5 (RAT) 5 (RAT)
Mica Iridescent Bronze, Pale	7.0 - 9.0 Gold, Pearl 7.0 - 9.0	12001-26-2	5 mg/m3	, ,
Mica Iridescent Bronze, Pale Mica Iridescent Copper, Deep Mica	7.0 - 9.0 Gold, Pearl 7.0 - 9.0 Gold 7.0 - 9.0	12001-26-2 12001-26-2 12001-26-2	5 mg/m3 5 mg/m3 5 mg/m3	5 (RAT) 5 (RAT)

NOTES: NA = NOT AVAILABLE

SECTION 4: FIRST AID PROCEDURES

Eye Contact: Flush with clean water for a minimum of 15 minutes. See a

physician after flushing eyes.

Skin Contact: Flush with plenty of water. If irritation develops see a

physician.

Inhalation: If inhaled move to fresh air and call a physician.

Ingestion: May cause abdominal pain. Do not induce vomiting.Product is not

considered toxic in small amounts. Call a physician. Ingestion of

large amounts may require medical attention.

Item Numbers: 01604-9001, 01604-9003 Page 3 of 6

SECTION 5: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification: Not Applicable Flash Point: Not Combustible

Flammable Limits (% vol. in air): LEL: N. App. UEL: N. App.

Extinguishing Media: Not Applicable.

Special Fire Fighting Procedures: Material in paint can splatter above 100C. Dried paint film can burn. If this should occur use carbon dioxide, foam, dry chemical or water to extinguish. Wear full-body protective clothing and self-contained breathing apparatus. Do not direct extinguishing media directly into center of burning pools.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill/ Leak Procedure: Contain spilled paint and clean up. Avoid excessive

inhalation and skin contact.

SECTION 7: HANDLING AND STORAGE PRECAUTIONS

Storage of Paint: Keep from freezing. Keep containers closed.

Keep jar or cylinder tightly closed.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

General Protective and Hygiene Measures

Do not eat, drink, smoke or sniff while working. Wash hands before breaks and at

the end of work.

Respiratory Protection

If spray painting or sanding, wear appropriate government approved mask. Ensure room as adequate ventilation. **For paints containing Nickel**

Compounds it is advisable not to spray apply. Spray may be harmful if

inhaled. Over exposure may cause irritation and harm to the respiratory

tract. Nickel compounds may pose a cancer hazard.

<u>Ventilation</u> For professional (daily) use adequate ventilation is recommended, (i.e.

window fan).

Eye Protection Wear safety glasses (with side shields) or goggles.

Skin Protection Gloves that do not absorb liquids (i.e. rubber or latex) are recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

General Information

Form: Liquid or Paste

Colour: White or Colored Paste; White or Colored Liquid

Odour: Very Mild Ammonia Odour

Change in Condition

Melting Point Undetermined

Item Numbers: 01604-9001, 01604-9003 Page 4 of 6

Boiling Point 100 - 130 Deg. C

Flash Point Not Applicable

Auto Ignition Product is not self-igniting

Danger of Explosion Product does not present an explosion hazard

Specific Gravity: 1.0 - 1.7 (Water = 1.0) Solubility in Water: Dilutable

SECTION 10: STABILITY AND REACTIVITY DATA

Stability: Stable

Incompatibility

Maintain storage between 0 and 30 °C. Avoid strong oxidizing and reducing

agents; strong acids and bases. Keep product away from open flame.

Conditions to Avoid Keep product from freezing or excessive heat.

Hazardous Decomposition Products Low molecular weight hydrocarbons, CO, CO2, NOx, trace HCI and H2S (with

Ultramarine Blue). All are toxic.

SECTION 11: TOXICOLOGICAL INFORMATION

Chronic Effects on Humans

Carcinogenic Effects
Mutagenic Effects
Teratogenic Effects
Developmental Toxicity
See Section 15.
See Section 15.
See Section 15.

Acute Effects on Humans May cause skin, eye and respiratory irritation.

For paints containing Nickel Compounds it is advisable not to spray apply. Spray may be harmful if inhaled. Over exposure may cause irritation and harm to the respiratory tract. Nickel compounds may pose a cancer hazard.

Prolonged exposure to topcoat may result in reproductive hazard.

SECTION 12: ECOLOGICAL INFORMATION

General Notes Information regarding the ecological impact of this product is not known at this

time.

SECTION 13: DISPOSAL CONSIDERATIONS

Paint Disposal: Dispose of paint soaked rags and empty containers in

accordance with regulatory laws.

SECTION 14: TRANSPORT INFORMATION

DOT Regulations Hazard Class - No Hazard Class

Item Numbers: 01604-9001, 01604-9003 Page 5 of 6

SECTION 15: Regulations

WHMIS Not Controlled.

All Tri-Art paints conform to ASTM D-4236. For additional health information in **ASTM D4236**

the U.S. call the National Poison Control Center at 1-800-222-1222. In Canada

call Poison Information at 1-800-268-9017 or 1-877-2233(TTY).

Proposition 65
Paints Containing Cadmium
WARNING! This chemical is known to the state of California to cause cancer.

Paints Containing Cobalt Contains cobalt spinel compounds.

Paints Containing Nickel Contains Nickel Compounds

WARNING! This chemical is known to the state of California to cause cancer.

Topcoats Contains Dipropylene Glycol Monobutyl ether and 1-methyl-2-pyrrolidinone.

WARNING! This product contains a chemical known to the state of California to cause

birth defects or other reproductive harm.

SECTION 16: OTHER INFORMATION

While Tri-Art Mfg. Inc. has prepared this MSDS from a knowledge of the products' components and from supplier information, there is no warranty with respect to the accuracy of this data. We assume no legal responsibility. All data is offered for your consideration, investigation and verification.

Page 6 of 6 Item Numbers: 01604-9001, 01604-9003