

LARSON JUHL
422 3rd St. W.
Ashland, WI 54806
(715) 682-5257

8180 -
8181 -
8167 -
8168 -
8169 -
all codes
8193 -
8166 -

* 17402 - ALL CODES

MSDS Effective Date: 01/10/96
Trade Name: WOOD DUST (UNTREATED)

Recvd 8-17-99

Ingredients/Identity Information

Proprietary: NO
Ingredient: WOOD DUST
Ingredient Sequence Number: 01
NIOSH (RTECS) Number: ZC9850000
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)

Physical/Chemical Characteristics

Appearance And Odor: LIGHT TO DARK COLORED GRANULAR SOLID. COLOR & ODOR ARE DEPENDENT ON WOOD(SUPDAT)
Boiling Point: N/A
Melting Point: N/A
Vapor Density (Air=1): N/A
Specific Gravity: (SUPP DATA)
Evaporation Rate And Ref: NOT APPLICABLE
Solubility In Water: INSOLUBLE
Percent Volatiles By Volume: N/A
pH: N/A

Fire and Explosion Hazard Data

Flash Point: NOT APPLICABLE
Lower Explosive Limit: 40 G/M3
Extinguishing Media: WATER, CO*2, SAND.
Special Fire Fighting Proc: USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP (FP N). USE WATER TO WET DOWN WOOD DUST TO REDUCE LIKELIHOOD OF IGNIT/DISPERSION OF DUST INTO AIR. REMOVE (SUPDAT)
Unusual Fire And Expl Hazrds: WOOD DUST IS A STRONG TO SEVERE EXPLOSION HAZARD IF A DUST "CLOUD" CONTACTS AN IGNITION SOURCE.

Reactivity Data

Stability: YES
Cond To Avoid (Stability): AVOID OPEN FLAME. PRODUCT MAY IGNITE AT TEMPERATURES IN EXCESS OF 400F.
Materials To Avoid: AVOID CONTACT W/OXIDIZING AGENTS & DRYING OILS.
Hazardous Decomp Products: THERMAL OXIDATIVE DEGRADATION OF WOOD PRDCES IRRIT & TOX FUMES & GASES, INCL CO, ALDEHYDES & ORGANIC ACIDS.
Hazardous Poly Occur: NO
Conditions To Avoid (Poly): NOT RELEVANT

V-2628

=====
Health Hazard Data
=====

LD50-LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry - Inhalation: YES
Route Of Entry - Skin: YES
Route Of Entry - Ingestion: NO
Health Haz Acute And Chronic:
ACUTE: SKIN & EYE CONT:WOOD DUST CAN CAUSE EYE IRRIT. VARIOUS SPECIES OF WOOD DUST CAN ELICIT ALLERGIC CONT DERM IN SENSITIZED INDIVIDUALS. INHAL:MAY CAUSE NASAL DRYNESS, IRRIT & OBSTRUCTION. COUGH, WHEEZING & SNEEZING; SINUSITIS & PRLNG COLDS HAVE ALSO BEEN REPORTED.
CHRONIC: WOOD DUST, DEPENDING ON (EFTS OF OVEREXP)
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: YES
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: WOOD DUST:IARC MONOGRAPHS ON EVAL OF CARCIN RISK OF CHEMS TO MAN, VOL 62, PG 35, 1995:GROUP 1.
Signs/Symptoms Of Overexp: HLTH HAZ:SPECIES, MAY CAUSE DERM ON PRLNG, REPETITIVE CONT; MAY CAUSE RESP SENSIT &/OR IRRIT. IARC CLASSIFIES WOOD DUST AS CARCIN TO HUMANS (GRP 1). THIS CLASSIFICATION IS BASED PRIMARILY ON IARC'S EVAL OF INCR RISK IN OCCURRENCE OF ADENOCARCINOMAS OF NASAL CAVITIES & PARANASAL SINUSES ASSOC W/EXPOS TO WOOD DUST.
Med Cond Aggravated By Exp: NONE SPECIFIED BY MANUFACTURER.
Emergency/First Aid Proc:
INGEST: CALL MD IMMEDIATELY (FP N). EYES: FLUSH W/WATER FOR AT LST 15 MINS TO REMOVE DUST PARTICLES. IF IRRIT PERSISTS, GET MED ATTN.
SKIN: IF RASH/PERSISTENT IRRIT/DERM OCCUR, GET MED ADVICE WHERE APPLIC BEFORE RETURNING TO WORK WHERE DUST IS PRESENT.
INHAL: REMOVE TO FRESH AIR. IF PERSISTENT IRRIT, SEV COUGH/BRTHG DFCLTIES OCCUR, GET MED ADVICE BEFORE RETURNING TO WORK WHERE WOOD DUST IS PRESENT.

=====
Precautions for Safe Handling and Use
=====

Steps If Matl Released/Spill: SWEEP OR VACUUM SPILLS FOR RECOVERY OR DISPOSAL; AVOID CREATING DUST CONDITIONS. PROVIDE GOOD VENTILATION WHERE DUST CONDITIONS MAY OCCUR. PLACE RECOVERED WOOD DUST IN A CONTAINER FOR PROPER DISPOSAL.
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.
Waste Disposal Method: DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS (FP N).
Precautions-Handling/Storing: AVOID EYE CONTACT. AVOID REPEATED OR PROLONGED CONTACT W/SKIN. AVOID PROLONGED OR REPEATED BREATHING OF WOOD DUST IN AIR.
Other Precautions: AVOID CONTACT W/OXIDIZING AGENTS & DRYING OILS. AVOID OPEN FLAME.

=====
Control Measures
=====

Respiratory Protection: OTHER PROTECTIVE EQUIPMENT SUCH AS NIOSH/MSHA APPROVED DUST RESPIRATORS MAY BE NEEDED DEPENDING UPON DUST CONDITIONS.

Ventilation: PROVIDE ADEQUATE GENERAL & LOCAL EXHAUST VENTILATION TO MAINTAIN HEALTHFUL WORKING CONDITIONS.

Protective Gloves: IMPERVIOUS GLOVES (FP N).

Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).

Other Protective Equipment: NONE.

Work Hygienic Practices: CAREFUL BATHING & CLEAN CLOTHES ARE INDICATED AFTER EXPOSURE.

Suppl. Safety & Health Data: SPEC GRAV:VARIABLE (DEPENDENT ON WOOD SPECIES & MOISTURE CONTENT). APPEAR/ODOR:SPECIES & TIME SINCE DUST WAS GENERATED.

FIRE FIGHT PROC: BURNED/WET DUST TO OPEN AREA AFTER FIRE IS EXTINGUISHED.

=====
Transportation Data
=====

None

=====
Disposal Data
=====

DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS (FP N).

=====
Label Data
=====

Label Required: YES

Common Name: WOOD DUST (UNTREATED)

Chronic Hazard: YES

Signal Word: CAUTION!

Acute Health Hazard-Slight: X

Contact Hazard-Slight: X

Fire Hazard-None: X

Reactivity Hazard-None: X

Special Hazard Precautions:

ACUTE: SKIN & EYE CONTACT:WOOD DUST CAN CAUSE EYE IRRITATION. VARIOUS SPECIES OF WOOD DUST CAN ELICIT ALLERGIC CONTACT DERMATITIS IN SENSITIZED INDIVIDUALS.

INHALATION: MAY CAUSE NASAL DRYNESS, IRRITATION & OBSTRUCTION. COUGHING, WHEEZING & SNEEZING; SINUSITIS & PROLONGED COLDS HAVE ALSO BEEN REPORTED.

CHRONIC: CANCER HAZARD. CONTAINS WOOD DUST WHICH IS LISTED AS A NASAL CAVITY & PARANASAL SINUS CARCINOGEN (FP N). WOOD DUST, DEPENDING ON SPECIES, MAY CAUSE DERMATITIS, RESPIRATORY DENSITIZATION.

Protect Eye: Y

Protect Skin: Y

Protect Respiratory: Y

Label Emergency Number: (715) 682-5257

Disclaimer:

 Larson Juhl, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. LARSON JUHL, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, LARSON JUHL, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by: Wayne Cameron, Mfg. Eng.
 Phone Number: (715) 682-5257

LARSON · JUHL
 422 3rd St. W.
 Ashland, WI 54806
 (715) 682-5257

WOOD DUST CAUTION!

SAWING, SANDING OR MACHINING WOOD PRODUCTS CAN PRODUCE WOOD DUST WHICH CAN CAUSE A FLAMMABLE OR EXPLOSIVE HAZARD.

WOOD DUST MAY CAUSE LUNG, UPPER RESPIRATORY TRACT, EYE AND SKIN IRRITATION. SOME WOOD SPECIES MAY CAUSE DERMATITIS AND / OR RESPIRATORY ALLERGIC EFFECTS.

- * Avoid dust contact with ignition sources.
- * Sweep or vacuum dust for recovery or disposal.
- * Avoid prolonged or repeated breathing of wood dust in air.
- * Avoid dust contact with eyes and skin.
- * First Aid: If inhaled, remove to fresh air. In case of contact, flush eyes and skin with water. If irritation persists, call physician.

For additional information, see the Material Safety Data Sheet.