

Rev'd 5-05-04 ✓
 MAY-04-04 15:11 FROM:HUNT/CUST.SERVICE
 * Painter Paint Markers *

ID: 7048710116

21312 - all codes except
 - 4050
 - 4051
 - 4055
 9100
 - 9300
 - 9400

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List) SPEEDBALL PAINTERS (water-based)

Section I

Manufacturer's Name Hunt Manufacturing Co.	Emergency Telephone Number 704-872-9511
Address (Number, Street, City, State, and ZIP Code) Speedball Road Statesville, NC 28677	Telephone Number for Information 704-872-9511
	Date Prepared August 16, 2001
	Signature of Preparer (Optional) <i>[Signature]</i>

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Approved for the AP Seal as per the Art and Craft Materials Institute, Inc. (ACMI). Labeling conforms to ASTM D4236.				
Dipropylene Glycol Monomethyl Ether (CAS #34590-94-8)	100ppm	100ppm	N/A	

Note: This product has been evaluated by a toxicologist only as per intended usage. Do not deviate from intended usage!

V.2260

Section III - Physical/Chemical Characteristics

Boiling Point	212-473°F	Specific Gravity (H ₂ O = 1)	1.06-1.38
Vapor Pressure (mm Hg.)	17mmHg	Melting Point	<32°F.
Vapor Density (AIR = 1)	less than 1	Evaporation Rate (Butyl Acetate = 1)	less than 1
Solubility in Water	Dilutable		

Appearance and Odor
 Low viscosity, semi-aromatic odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) Not applicable (N/A)	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A	Special Fire Fighting Procedures wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.		
Unusual Fire and Explosion Hazards Material can spatter above 212°F. Film can burn.			

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Onset of decomposition is 350°F.

Incompatibility (Materials to Avoid) N/A

Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry: N/A Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: N/A NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water. Induce vomiting if large amounts are ingested.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.

Waste Disposal Method Incinerate at a permitted facility according to current local, state and federal regulations.

Precautions to Be Taken in Handling and Storing Keep from freezing - product may coagulate.

Other Precautions N/A

Section VIII - Control Measures

Respiratory Protection (Specify Type) None required with adequate ventilation & normal operating conditions

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

Protective Gloves Impervious Eye Protection Safety glasses

Other Protective Clothing or Equipment N/A

Work Hygienic Practices Use protective cream where excessive skin contact is likely.