

\* Chromark Poster System \*

4140-00  
4144-XX ✓

21317-XXXX

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Chromark Ink

Effective Date 3/14/91

```

*****
*
* Chromark Corporation          EMERGENCY INFORMATION
* 827 So. Bowen                MEDICAL (303) 772-6934
* Longmont, CO 80502-1597
*
*****

```

```

*****
* SECTION I: GENERAL INFORMATION
*****

```

PRODUCT NAME: Chromark Ink  
 PRODUCT CLASS: Water-based Ink

```

*****
* SECTION II: HAZARDOUS INGREDIENTS
*****

```

INGREDIENT	CAS #	%	PEL
Dipropylene Glycol Monomethyl Ether	034590-94-8	10-15	100 ppm OSHA 8 HRS TWA

Water soluble Dye 1 to 5%  
 Various dyes used in different colors: No known hazardous components in dyes. No significant harmful environmental effects are known

```

*****
* SECTION III: PHYSICAL/CHEMICAL DATA
*****

```

BOILING RANGE: 212° - 363° F  
 % VOLATILE BY WEIGHT: 98  
 EVAPORATION RATE: SLOWER THAN ETHYL ETHER  
 VAPOR DENSITY: 1.16 (AIR = 1)  
 VAPOR PRESSURE: 25 MM HG @ 25° F  
 WEIGHT PER GALLON: 7.9 LBS  
 SOLUBILITY IN WATER: INFINITELY

V-923

MATERIAL SAFETY DATA SHEET

PAGE 2

PRODUCT NAME: Chromark Ink

Effective Date 3/14/91

SECTION IV: FIRE AND EXPLOSION DATA

FLASH POINT (TCC): GREATER THAN 167 DEGREES F

EXTINGUISHING MEDIA DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY, FOAM, CLASS BC, ABC FIRE EXTINGUISHER

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN; NOT FLAMMABLE AT ROOM TEMPERATURE BUT WILL COMBUST IF INCLUDED IN FIRE OF OTHER MATERIALS; AS WITH ALL ORGANIC MATERIALS, INCOMPLETE COMBUSTION MAY GENERATE HIGHLY POISONOUS CARBON MONOXIDE AND PERHAPS OTHER TOXIC VAPORS; OXIDES OF NITROGEN AND SULFUR MAY ALSO BE PRODUCED

SECTION V: REACTIVITY DATA

STABILITY: STABLE
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZERS

SECTION VI: HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE/EMERGENCY AND FIRST AID PROCEDURES

EYES: CONTACT WITH EYES MAY BE IRRITATING
FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER. OBTAIN EMERGENCY MEDICAL ATTENTION IF PAIN, BLINKING, TEARS OR REDNESS PERSIST

SKIN: NOT EXPECTED TO PRESENT A SIGNIFICANT SKIN HAZARD UNDER ANTICIPATED CONDITIONS OF NORMAL USE

INHALATION: MAY CAUSE DIZZINESS, DROWSINESS, HEADACHE, NAUSEA AND VOMITING. IF VAPORS OR MIST CAUSE IRRITATION OR DISTRESS, REMOVE TO FRESH AIR. GIVE OXYGEN OR APPLY ARTIFICIAL RESPIRATION IF NEEDED.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Chromark Ink

Effective Date 3/14/91

PAGE 3

PRODUCT NAME: Chromark Ink

INGESTION: IF SWALLOWED, CONSULT A PHYSICIAN IMMEDIATELY. IF LARGE QUANTITY SWALLOWED GIVE LUKEWARM WATER (PINT) IF VICTIM COMPLETELY CONSCIOUS/ALERT. DO NOT INDUCE VOMITING/RISK OF DAMAGE TO LUNGS EXCEEDS POISONING RISK. OBTAIN EMERGENCY MEDICAL ATTENTION

CHRONIC EFFECTS AND MEDICAL CONDITIONS AGGRAVATED BY OVER-EXPOSURE: CHRONIC EFFECTS AND MEDICAL CONDITIONS AGGRAVATED BY OVER-EXPOSURE TO THIS PRODUCT HAVE NOT BEEN ESTABLISHED.

IF ANY SYMPTOMS PERSIST, CONSULT A PHYSICIAN.

CARCINOGEN: THIS PRODUCT IS NOT CONSIDERED A CARCINOGEN BY OSHA, NTP, OR IARC.

\*\*\*\*\*
FOR ADDITIONAL MEDICAL INFORMATION, CALL 1-(303) 772-6934
\*\*\*\*\*

\*\*\*\*\*
SECTION VII: SPILL, LEAK, AND DISPOSAL PROCEDURES
\*\*\*\*\*

SMALL SPILLS: SOAK UP WITH ABSORBENT, SHOVEL INTO WASTE CONTAINER, FLUSH AREA WITH WATER.

LARGE SPILLS: RECOVER LIQUID FOR REPROCESSING OR DISPOSAL.

WASTE DISPOSAL: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE STATE, LOCAL, AND FEDERAL REGULATIONS. MATERIAL COLLECTED WITH ABSORBENT MAY BE DISPOSED IN A PERMITTED LANDFILL IN ACCORDANCE WITH STATE, LOCAL, AND FEDERAL REGULATIONS. EMPTY CONTAINER MAY RETAIN VAPOR OR PRODUCT RESIDUE. OBSERVE ALL LABELED SAFEGUARDS UNTIL CONTAINER IS CLEANED, RECONDITIONED, OR DESTROYED.

DILUTE AQUEOUS WASTE MAY BIODEGRADE. AVOID OVERLOADING/POISONING PLANT BIOMASS. ASSURE EFFLUENT COMPLIES WITH APPLICABLE REGULATIONS.

THIS PART IS FOR CHROMARK WHEN WE ARE MAKING THE INK. SEE SECTION II

MATERIAL SAFETY DATA SHEET

Page 4

PRODUCT NAME: Chromark Ink

Effective Date 3/14/91

\*\*\*\*\* SECTION VIII: PROTECTIVE MEASURES \*\*\*\*\*

EYE PROTECTION:

GOGGLES ARE RECOMMENDED BECAUSE EYE CONTACT MAY CAUSE DISCOMFORT, EVEN THOUGH IT IS UNLIKELY TO CAUSE INJURY

PROTECTIVE GLOVES:

FOR BRIEF CONTACT, NO PRECAUTIONS OTHER THAN CLEAN BODY-COVERING SHOULD BE NEEDED. USE IMPERVIOUS GLOVES WHEN PROLONGED OR FREQUENTLY REPEATED CONTACT COULD OCCUR

RESPIRATORY PROTECTION:

IF VAPORS ARE PRESENT, USE NIOSH OR MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS, AIR LINE RESPIRATOR, OR A SELF-CONTAINED BREATHING APPARATUS.

VENTILATION:

USE VENTILATION ADEQUATE TO KEEP HAZARDOUS INGREDIENTS BELOW THEIR TLV (SEE SECTION II)

OTHER PROTECTIVE EQUIPMENT:

PROTECTIVE CLOTHING NOT NORMALLY NEEDED IN INTENDED USE; TAKE CARE TO PREVENT REPEATED OR PROLONGED CONTACT. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE. EYE WASH STATION SHOULD BE NEAR WORK AREA.

\*\*\*\*\* SECTION IX: SPECIAL PRECAUTIONS \*\*\*\*\*

WASH THOROUGHLY AFTER HANDLING. IF INGESTED, CALL A PHYSICIAN. AVOID EYE CONTAMINATION NO SIGNIFICANT HARMFUL ENVIRONMENTAL EFFECTS ARE KNOWN