

MATERIAL SAFETY DATA SHEET
 (Complies with OSHA Communication Standard 29 CFR 1910.1200 Dept. of Labor)

21706-1006

IDENTITY: REWORKABLE FIXATIVE
 Blue Label Fixatif
 1.802, 1.803

| | |
|--|--|
| Section I | |
| Manufacturer's Name Martin/F. Weber Company | Emergency Telephone Number (215) 677-5600 |
| Address 2727 Southampton Road | Telephone Number for Information (215) 677-5600 |
| Philadelphia, PA 19154-1293 | Date Prepared |

| Section II - Hazardous Ingredients/Identity Information | | | | |
|---|----------|-----------|--------------------------|--------------|
| Hazardous Components (Specific Chemical Identity, Common Name(s)) | OSHA PEL | ACGIH TLV | Other Limits Recommended | % (optional) |
| Resin (Cas not known) | | ---- | | 2 |
| Acetone (67-64-1) | | 750 | | 27 |
| Ethyl Alcohol (64-17-5) | | 1000 | | 25 |
| Methylene Chloride (75-09-2) | | 100 | | 15 |
| Propylene Glycol Methylethen Acetate (108-65-6) | | 100 | | 5 |
| Propane (74-98-6) | | 1000 | | 16 |

DOT SHIPPING - Consumer Commodity ORM-D

V 4475

| Section III - Physical/Chemical Characteristics | | | |
|---|--|---|-----|
| Boiling Point Range | -40 ^o F to 333 ^o F | Specific Gravity (H ₂ O = 1) | 0.8 |
| Vapor Pressure PSIG @ 70 ^o F | 42 | Melting Point Liquid | N/A |
| Vapor Density (AIR = 1) Heavier than Air | 4.0 | Evaporation Rate (Butyl Acetate = 1) | 4.2 |
| Solubility in Water | None | | |
| Appearance and Color | Clear - Solvent odor | | |

| Section IV - Fire and Explosion Hazard Data | | | |
|---|---|------------------|------------------|
| Flash Point (Method Used) | -40 ^o F T.C.C. | Flammable Limits | LEL 1.8 UEL 12.0 |
| Extinguishing Media | Use water fog, dry chemical or carbon dioxide | | |
| Special Fire Fighting Procedures | Aerosol cans may rupture when heated | | |

Unusual Fire and Explosion Hazards
 Heated cans may burst

Section V - Reactivity Data

| | | | |
|-----------|----------|---|---------------------|
| Stability | Unstable | | Conditions to Avoid |
| | Stable | X | High Temperatures |

Incompatibility (Materials to Avoid) None

Hazardous Decomposition or Byproducts In fire will decompose to carbon dioxide and water.

| | | | |
|--------------------------|----------------|---|---------------------|
| Hazardous Polymerization | May Occur | | Conditions to Avoid |
| | Will not Occur | X | None |

Section VI - Health Hazard Data

Route(s) of Entry: Inhalation? Yes Skin? Yes Ingestion? Yes

Health Hazards (Acute and Chronic) May cause dizziness or narcosis in high vapor concentrations. Will cause defatting of skin. Effects are reversible. Long term exposure (years) vapor may cause lung, liver or kidney damage.

Carcinogenicity: NTP? Presently not on any list. IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure Inhalation - Difficulty in breathing. Skin-redness. Ingestion-vomiting.

Medical Conditions Generally Aggravated by Exposure: Heart Disease

Emergency and First Aid Procedures Give oxygen - Do not induce vomiting - Gastric lavage - Wash eyes and skin with water.

Section VII - Precautions for Safe Handling and Use
Steps to be Taken in Case Material is Released or Spilled: Use absorbent sweeping compound to soak up material. Put into container. Dispose as hazardous waste.

Waste Disposal Method Dispose as hazardous waste in accordance with EPA RCRA.

Precautions to be Taken in Handling and Storing Keep away from heat, sparks, or open flame. Store at temperatures below 120° F.

Other Precautions None

Section VIII - Control Measures

Respiratory Protection (Specify Type) Self contained breathing apparatus if above TLV limit exceeding.

| | | | | |
|-------------|----------------------|------|---------|------|
| Ventilation | Local Exhaust | Yes | Special | None |
| | Mechanical (General) | None | Other | None |

Protective Gloves None required if spraying Eye Protection Wear eye protection

Other Protective Clothing or Equipment Long sleeve and long pants