

**21723-1001**A *Newell Rubbermaid* Company**MATERIAL SAFETY DATA SHEET****MSDS # 546****Section One: Identification**

Sanford, L.P.  
2707 Butterfield Road  
Oak Brook, IL 60523 USA  
800-323-0749 or 630-481-2000

EMERGENCY MEDICAL NUMBER:

888-786-0972

Product Name: PrismaColor Myston Workable Fixative  
Product Sizes: 4.75 oz., 12.75 oz.  
Product Class: Aerosols

**Section Two: Hazard Identification**

**DANGER: EXTREMELY FLAMMABLE. TOXIC GASES ARE GIVEN OFF WHEN BURNED, WHICH MAY RESULT IN ACUTE OR DELAYED DAMAGE TO THE LUNGS IF INHALED. VAPOR HARMFUL. EYE IRRITANT. EXPOSURE MAY CAUSE IRRITATION OF THE CHEST, OR DAMAGE TO THE KIDNEYS, OR ANEMIA.**

CONTAINS: ACETONE, CELLULOSE NITRATE

KEEP OUT OF REACH OF CHILDREN.

**Section Three: Composition**

Ingredients	CAS Number	Max. Weight %	PEL/TLV
Acetone	67-64-1	70%	750 ppm
Liquefied Petroleum Gas	68476-85-7	30%	1000 ppm
Propylene Glycol Methyl Ether Acetate	108-65-6	10%	N/A

**Section Four: First Aid Measures**

Inhalation: If exposure to combustion products occurs, get prompt medical attention.

Skin Contact: Wash with soap and water.

Eye Contact: If eye contact occurs, rinse with tap water for 5 - 10 minutes. If irritation persists, seek medical care.

Ingestion: Consult a physician. For further health information, contact a poison control center.

This Material Safety Data Sheet is applicable to the consumer use of the following products: 546, 646

February 19, 2007

Page 1 of 3

A *Newell Rubbermaid* Company**MATERIAL SAFETY DATA SHEET****MSDS # 546****Section Five: Fire Fighting Measures**

Flash Point: 0F Closed Cup (Acetone)

Flammability Limits (% by volume): Lower: 2.5% (Acetone) Upper: 12.8% (Acetone)

Extinguishing Media: Foam, carbon dioxide, dry chemical

Special Fire Fighting Measures: Water may be used to cool closed containers to prevent pressure buildup and possible bursting when exposed to high temperatures. Firemen should wear self-contained respiratory equipment.

Unusual Fire and Explosion Hazards: Extremely flammable. Contents under pressure. Containers may burst at temperatures above 130F.

**Section Six: Accidental Release Measures**

Remove all ignition sources. Evacuate area. Contain liquid; transfer to closed containers. Keep out of water entries.

**Section Seven: Handling and Storage**

Handling: Use only with adequate ventilation.

Storage: Do not store or use near heat or flame. Do not store to temperatures above 120F.

**Section Eight: Exposure Controls and Personal Protection**

Respiratory Protection and Special Ventilation Requirements: NIOSH or Bureau of Mines approved organic vapor-type respirator is required in absence of proper environmental control.

Other Protective Equipment (Gloves, Goggles, Etc.): Impervious gloves and safety glasses recommended.

Work/Hygiene Practices: PRECAUTIONS: Do not smoke when using. Keep away from eyes. Avoid breathing burning fumes, and contact with heat, sparks, and open flame. Vapors can ignite explosively. If using indoors, turn off all pilot lights. Exposure may result in nausea, headache, confusion, or instability. Use only with adequate ventilation.

**Section Nine: Physical and Chemical Properties**

Boiling Point: 133F (Acetone) Melting Point: -140F (Acetone)

Vapor Pressure: 180 mm Specific Gravity: 0.79 (Acetone)

Specific Vapor Density: Heavier than air Evaporation Rate: >1

Solubility in Water: Miscible Reactivity in Water: Non-reactive

Appearance and Odor: Colorless liquid; characteristic odor

**Section Ten: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: Ignition sources or excessive heat

Chemical Incompatibility: Nitric plus acetic acids, nitric plus sulfuric acid, amines, strong oxidizing agents

Hazardous Decomposition: Carbon monoxide, carbon dioxide

Hazardous Polymerization: Will not occur

February 19, 2007

Page 2 of 3

A *Newell Rubbermaid* Company**MATERIAL SAFETY DATA SHEET****MSDS # 546****Section Eleven: Toxicological Information**

IARC Monographs:	No
National Toxicology Program:	No
OSHA Regulated:	No
Effects/Symptoms of Acute Exposure:	If cross-ventilation is not adequate, eye watering, headache, nausea, dizziness, and loss of coordination may occur. Deliberate inhalation may be harmful or fatal.
Effects/Symptoms of Chronic Exposure:	Repeated and prolonged overexposure may lead to permanent brain damage and nervous system damage.
Medical Conditions Usually Aggravated By Overexposure of This Product:	Unknown

**Section Twelve: Ecological Information**

Not available

**Section Thirteen: Disposal Considerations**

Dispose in accordance with Federal, State, and Local Regulations

**Section Fourteen: Transport Information**

DOT:	ORM-D Consumer Commodity
IATA:	Consumer Commodity, 9, ID8000, packing instruction 910
IMO:	Aerosols, Class 2.1, UN1950 Limited Quantities, EmS# 2-13

**Section Fifteen: Regulatory Information**

## TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency's Toxic Substances Control Act Inventory. However, all components used in the manufacture of this product are included in the TSCA Inventory.

**Section Sixteen: Other Information**

HMIS Code	
Health	2
Flammability	4
Reactivity	0
Personal Protection	1

0=Minimal / 4 = Severe

Sanford Corporation is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D-4236.

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

February 19, 2007

Page 3 of 3