



Daige, Inc.
1 Albertson Avenue
Albertson, New York 11507

(800) 645-3323
fax (516) 621-1916
info@daige.com

Material Safety Data Sheet MX II Adhesive

Date Prepared: 6/11/05 Replaces Sheet Dated: 1/3/05

SECTION 2: HAZARDOUS INGREDIENTS IDENTITY

HAZARDOUS COMPONENT(S):	OSHA PEL	ACGIH TLV	OTHER LIMITS	CAS NO.

SARA TITLE III

Section 313: This product does not contain regulated levels of any toxic chemical subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372.

SECTION 3: PHYSICAL AND CHEMICAL CHARACTERISTICS

- 1) Boiling Point: N/A
- 2) Specific Gravity: Approx. 0.9 at 25°C
- 3) Vapor Pressure: N/A
- 4) Vapor Density: N/A
- 5) Solubility in Water: Negligible
- 6) Reactivity with Water: N/A
- 7) Appearance and Odor: Light amber in color with slight resinous odor.
- 8) Melting Point: N/A

SECTION 4: FIRE AND EXPLOSION DATA

- 1) Flash Point: Greater than 400°F
- 2) Method Used: SETA
- 3) Auto Ignition Temp: N/A
- 4) Extinguisher media: Dry chemical, CO₂, chemical foam
- 5) Flammable Limits / % Volume in Air: N/A
Lower: Upper:
- 6) Special Fire Fighting Procedures: Self-contained apparatus and protective clothing should be worn in fighting fires involving chemicals
- 7) Unusual Fire and Explosion Hazards: None Known

N/A = NOT APPLICABLE

M-120 ADHESIVE

Page 2 of 3

SECTION 5: PHYSICAL/CHEMICAL HAZARDS (REACTIVITY DATA)

- 1) Stability: Stable: Unstable:
- 2) Conditions to Avoid: N/A
- 3) Incompatibility (Materials to Avoid): Oxidizing materials can cause a reaction
- 4) Hazardous Decomposition Products: As with any other organic material, combustion will produce carbon dioxide and probably carbon monoxide.
- 5) Hazardous Polymerization: May occur Will not occur

SECTION 6: HEALTH HAZARDS

- 1) If burned by contact with molten material, cool as quickly as possible with water and see a physician for removal of adhering material and treatment of burn.
- 2) Signs and Symptoms of Exposure: If heated to decomposition, fumes generated may result in irritation of nose, eyes, throat and respiratory tract.
- 3) Chemicals Listed as Carcinogen or Potential Carcinogen:
National Toxicology Program: Yes No
I.A.R.C. Monographs: Yes No OSHA: Yes No

SECTION 7: EMERGENCY AND FIRST AID PROCEDURES:

If Symptoms of Overexposure Develop, Always Seek Immediate Medical Attention.

ROUTES OF ENTRY:

NOTE: MOLTEN MATERIAL MAY CAUSE THERMAL BURNS:

- 1) Inhalation(Breathing): Remove subject to fresh air
- 2) Eye Contact: Flush with plenty of water for at least 15 minutes
- 3) Skin Contact: Wash exposed area with soap and water. Launder contaminated clothing before reuse.
- 4) Ingestion (Swallowing): Induce vomiting. No adverse health effects are anticipated. Consult a physician.

SECTION 8: SPECIAL PRECAUTIONS AND SPILL / LEAK PROCEDURES:

- 1) Precautions to be Taken in Handling and Storage: No special precautions are known.
- 2) Other Precautions: Molten product may cause thermal burns. Vapors and fumes may cause eye, nose, throat and respiratory tract irritation.
- 3) Steps to be Taken in Case Material is Released or Spilled: Collect and contain for salvage or disposal.
- 4) Waste Disposal Methods (Always Consult Federal, State, Regional, and Local Regulations Pertaining to This Material Before Using Any Method Suggested Here): Incineration
- 5) Consult Local Waste Disposal Professionals.

N/A - NOT APPLICABLE