

07/13/2006 09:57 8159622037

TESTORS

PAGE 06/09

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

25068-1009
-1039

Telephone number:(815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: \*(800) 424-9300 Page 1 of 4
\*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 3/09/2005

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)
\*\*\*\*\*

SECTION I - PRODUCT IDENTIFICATION

PRODUCT IDENTITY (TRADE NAME): Visions ColorArtz Fabric Water-Base Pouch Paint
(VF000 - VF999)
(This MSDS covers all products listed on page 4.)

SECTION II - HAZARDOUS INGREDIENTS & COMPOSITION INFORMATION

Table with 5 columns: SPECIFIC CHEMICAL NAME, CAS #, % WT, OSHA PEL/TWA, ACGIH TLV/TWA. Row 1: Carbon Black Pigment\*\*, 1333-86-4, 0.1-3.0, 3.5 mg/cu.m., 3.5 mg/cu.m.

\*\* Contained at levels 0.1% or greater in products identified with a "+" on page 4.

Non-Hazardous and Other Not Avail. Balance
Ingredients Below Reportable Levels

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 to 369 deg.F SPECIFIC GRAVITY (Water=1): 1.080 (TYP)
GALLON WEIGHT OF VAPOR PRESSURE:17.0 mm Hg @ 20 deg.C (calc.)
PRODUCT (Lbs/Gal): 9.00 (TYP) VAPOR DENSITY: Lighter than air.
PERCENT VOLATILES EVAPORATION RATE: Slower than Ethyl Ether.
(By Volume): 78.9 (TYP)

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (SFCC): > 200 deg. F
OSHA FLAMMABILITY CLASSIFICATION: Combustible Liquid - CLASS IIIIB
FLAMMABLE LIMITS (calc.) IN AIR: LEL 2.6, UEL 12.5
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, dry chemical or water fog.
SPECIAL FIRE FIGHTING PROCEDURES: A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Overexposure to decomposition products may cause a health hazard.

07/13/2006 09:57 8159622037

TESTORS

PAGE 07/09

MATERIAL SAFETY DATA SHEET  
THE TESTOR CORPORATION  
440 BLACKHAWK PARK AVENUE  
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)  
24 hour Chemtrec telephone number: \*(800) 424-9300

Page 2 of 4

Date prepared: 3/09/2005

\*\*\*\*\*

Product Identity: Visions Fabric Water-Base Pouch Paint (VF000-VF999)

-----  
**SECTION V - SPILL OR LEAK PROCEDURES**  
-----

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**

Contain spilled product by diking. Provide adequate ventilation. Equip emergency responders with appropriate personal protection equipment. Take up spill with an absorbent material and place in non-leaking container Seal container for proper disposal.

**WASTE DISPOSAL METHOD:**

No special method. Dispose of in accordance with local state, and federal regulations regarding disposal of non-hazardous materials.

-----  
**SECTION VI - HEALTH HAZARD DATA**  
-----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? YES\* OSHA REGULATED? NO

**EFFECTS OF OVEREXPOSURE:**

**EYE CONTACT:** Causes irritation and pain, seen as excess tearing and blinking with marked excess redness and swelling of the conjunctiva.

**SKIN CONTACT:** Prolonged and repeated liquid contact may result in skin irritation and dermatitis. May be absorbed through the skin.

**BREATHING:** Vapors or mist may cause irritation to the eyes and respiratory tract. High concentrations may cause headache, dizziness, nausea, vomiting and malaise.

**SWALLOWING:** May cause irritation of the gastrointestinal tract and may also cause effects resembling those from inhalation of vapor.

**CHRONIC OVEREXPOSURE:** Overexposures to Ethylene Glycol Monobutyl Ether and Diethylene Glycol Monobutyl Ether may cause secondary injury to the kidney and liver.

\*Products identified with a "+" on page 4 contain Carbon Black which is an IARC Group 2B-possible carcinogen.

-----  
**SECTION VII EMERGENCY AND FIRST AID PROCEDURES**  
-----

**EYE CONTACT:** Wash immediately with plenty of water for 15 minutes while holding eye lids open. Call a physician.

**SKIN CONTACT:** Remove any contaminated clothing and wash skin with soap and water thoroughly. If irritation persists, get medical attention.

**BREATHING:** Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

**SWALLOWING:** If victim is conscious, give two glasses of water to drink. Call a physician immediately.

07/13/2006 09:57 8159622037

TESTORS

PAGE 08/09

MATERIAL SAFETY DATA SHEET  
THE TESTOR CORPORATION  
440 BLACKHAWK PARK AVENUE  
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)  
24 hour Chemtrec telephone number: \*(800) 424-9300

Page 3 of 4

Date prepared: 3/09/2005

\*\*\*\*\*  
Product Identity: Visions Fabric Water-Base Pouch Paint (VF000-VF999)

-----  
**SECTION VIII- REACTIVITY DATA**  
-----

STABILITY: Stable.

CONDITIONS TO AVOID: None.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents, and alkalies.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and/or carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

-----  
**SECTION IX SPECIAL PROTECTION INFORMATION**  
-----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors, mists and/or dusts. If exposure may or does exceed occupational exposure limits (Section II) use a NIOSH-approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air purifying respirator with appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s). Heavy solvent vapors should be removed from the lower levels of area, and all ignition sources (non-explosion proof equipment) should be eliminated if flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.  
Chemical Safety Shoes. Protective Clothing.

-----  
**SECTION X SPECIAL PRECAUTIONS**  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions. Do not get in eyes. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.

This product is packaged and sold as a consumer good. This information is believed to be reliable and accurate, as of the date indicated. It is supplied on the condition that recipients will make their own determination as to its suitability and completeness for their purposes. The Testor Corporation assumes no responsibility for any damages resulting from reliance on this information.

07/13/2006 09:57 8159622037

TESTORS

PAGE 09/09

MATERIAL SAFETY DATA SHEET  
 THE TESTOR CORPORATION  
 440 BLACKHAWK PARK AVENUE  
 ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)  
 24 hour Chemtrec telephone number: \*(800) 424-9300

Page 4 of 4

Date prepared: 3/09/2005

\*\*\*\*\*  
 Product Identity: Visions Fabric Water-Base Pouch Paint (VF000-VF999)

## Stock Numbers and Description

VF000 White  
 VF008 Bisque  
 VF045 Lemon Yellow  
 VF067 Saffron  
 VF126 Apricot  
 VF164 Orange  
 VF200 Misty Pink  
 VF266 Cinnabar  
 VF263 Calico Red  
 VF270 Real Red  
 VF295+ Barn Red  
 VF300 Baby Pink  
 VF305 Lilac  
 VF323 Mauve  
 VF330 Fuschia  
 VF361+ Burgundy  
 VF368 Purple  
 VF415 Baby Blue  
 VF430 Blueberry  
 VF431 True Blue  
 VF443 Cool Blue  
 VF480+ Royal Blue  
 VF520 Turquoise  
 VF524 Glen Green  
 VF570 Teal  
 VF574 Real Green  
 VF577 Basil  
 VF584+ Pine Green  
 VF617 Tea Dye  
 VF619+ Raw Sienna  
 VF630 Gold  
 VF640 Copper  
 VF688+ Burnt Umber  
 VF833+ Slate Gray  
 VF835 Silver  
 VF999+ Black

+ Products that contain Carbon Black 0.1% or greater.

08/16/2006 10:07

8159622037

TESTORS

PAGE 10/12

MATERIAL SAFETY DATA SHEET  
THE TESTOR CORPORATION  
440 BLACKHAWK PARK AVENUE  
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)  
24 hour Chemtrec telephone number: \* (800) 424-9300 Page 1 of 3  
\*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING  
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 3/3/2005

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard  
\*\*\*\*\*)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT IDENTITY (TRADE NAME): #8822V ColorArtz AeroSource Propellant by Visions  
(10 OZ., 8 oz., 6 oz., 3 oz.)

SECTION II - HAZARDOUS INGREDIENTS

SPECIFIC CHEMICAL NAME	CAS #	% WT	OSHA PEL/TWA	ACGIH TLV/TWA
1,1,1,2-Tetrafluoroethane	811-97-2	100	Not Estab.	1000 ppm.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: -15.1 deg.F	SPECIFIC GRAVITY (Water=1): 1.22 (60 deg.F)
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 10.1(60 deg.F)	VAPOR PRESSURE : 71 PSIG @ 70 deg.F
PERCENT VOLATILES (By Volume): 100	VAPOR DENSITY: Heavier than air.
	EVAPORATION RATE: Faster than Ethyl Ether.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (SFCC): N/A Gas  
 OSHA FLAMMABILITY CLASSIFICATION : Flammable Liquid - CLASS IA  
 FLAMMABLE LIMITS (calc.) IN AIR: LEL N/A ,UEL N/A  
 EXTINGUISHING MEDIA: Water spray or fog, Alcohol resistant foam, carbon dioxide or dry chemical.  
 SPECIAL FIRE FIGHTING PROCEDURES: Keep container cool with water spray. Avoid Breathing vapors.  
 UNUSUAL FIRE AND EXPLOSION HAZARDS: Self contained breathing apparatus is required if container ruptures and contents are released under fire conditions. Heat may cause bursting.  
 fire conditions. Heat may cause bursting.

02/16/2006 10:07

8159622037

TESTORS

PAGE 11/12

MATERIAL SAFETY DATA SHEET  
THE TESTOR CORPORATION  
440 BLACKHAWK PARK AVENUE  
ROCKFORD, ILLINOIS 61104

Telephone number:(815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)  
24 hour Chemtrec telephone number: \*(800) 424-9300

Page 2 of 3

Date prepared: 3/3/2005

\*\*\*\*\*

Product Identity: #8822V ColorArtz AeroSource Propellant by Visions

----- SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Turn off valve and provide adequate ventilation, especially in low places where heavy vapors might collect.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local, state, and federal regulations.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? NO OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Contact with liquefied gas or gas under pressure may cause burning due to freezing effect. Short term vapor contact may result in slight eye irritation.

SKIN CONTACT: Contact with liquefied gas or gas under pressure may cause burning due to freezing effect.

BREATHING: Inhalation of high vapor concentrations is harmful and may cause heart irregularities, unconsciousness or death. Initial symptoms at high concentrations are disorientation, incoordination, nausea, and anesthetic effects such as dizziness, headache and confusion.

SWALLOWING: Ingestion is not considered a potential route of exposure.

CHRONIC OVEREXPOSURE: Individuals with pre-existing heart disease may have increased susceptibility to the toxicity of excessive exposures.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding eye lids open. Call a physician.

SKIN CONTACT: Wash immediately with mild soap and water. Treat burned or frostbitten skin by immersing in lukewarm water. If skin is not burned, keep warm and stimulate with massage. Call a physician.

BREATHING: Remove to fresh air. In case of unconsciousness, apply artificial respiration and/or oxygen as indicated. Call a physician.

SWALLOWING: Ingestion is not considered a potential route of exposure.

08/16/2005 10:07 8159622037

TESTORS

PAGE 12/12

MATERIAL SAFETY DATA SHEET  
THE TESTOR CORPORATION  
440 BLACKHAWK PARK AVENUE  
ROCKFORD, ILLINOIS 61104

Telephone number:(815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)  
24 hour Chemtrec telephone number: \*(800) 424-9300

Page 3 of 3

Date prepared: 3/3/2005

\*\*\*\*\*

Product Identity: #8922V ColorArtz AeroSource Propellant by Visions

----- SECTION VIII- REACTIVITY DATA -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Avoid contact with strong oxidizers,  
alkalines and powdered metals.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce carbon monoxide when oxidized  
with a deficiency of oxygen.

HAZARDOUS POLYMERIZATION: Will not occur.

----- SECTION IX SPECIAL PROTECTION INFORMATION -----

RESPIRATORY PROTECTION: If the AEL (1000 ppm.) of the product is  
exceeded, a NIOSH/MSHA approved air supplied respirator  
is advised in absence of proper environmental control.  
OSHA regulations also permit other NIOSH/MSHA respirators  
under specific conditions.

VENTILATION: If the product is used in a confined area, provide sufficient  
mechanical (general and/or local exhaust) ventilation to  
maintain exposure below 1000 ppm. Explosion proof equipment is  
advised.

PROTECTIVE GLOVES: Solvent resistant are recommended for liquid contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: As required to avoid skin contact or breathing  
vapors.

----- SECTION X SPECIAL PRECAUTIONS -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.  
Store away from ignition sources in a cool well ventilated area. Handle  
as extremely flammable liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is  
believed to be reliable and accurate, as of the date indicated. It is supplied  
on the condition that recipients will make their own determination as to its  
suitability and completeness for their purposes. The Testor Corporation assumes  
no responsibility for any damages resulting from reliance on this information.