

6.28-04✓

25311-1904

25311-4964 -4967
-4966**MATERIAL SAFETY DATA SHEET****CREATEX
COLORS**14 Airport Park Road
East Granby, CT. 06026
(860) 653-5505
(860) 653-0643 fax**PRODUCT IDENTIFICATION**

IDENTITY: (As used on label)		Synonyms:
Auto Air Transparent Orange (Item #4233)		---
Chemical family:	Formula	
---	Aqueous dispersion of organic pigment, mica, and acrylic polymer.	

HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	OSHA/PEL
Not a hazardous material as outlined by the OSHA Hazard Communication standards Meets ASTM D-2436 Standards			

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling /melting point: 200°-215° F
Solubility in water: water expendable
Vapor pressure (mm Hg): NA
Vapor density: 1
Specific Gravity (H₂O-1): 1.1
Evaporation Rate: (BuAct=1): 1
Appearance and Odor: Orange liquid, slight acrylic odor

FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water or CO ₂ foam
Fire fighting Procedures: Standard fire fighting procedures
Unusual Fire and Explosion Hazards: Product itself is non-flammable, will not support combustion.

REACTIVITY DATA

Stability: (X) Stable () Unstable Conditions to avoid: none found
Incompatibility (materials to avoid) : NA
Hazardous Decomposition or Byproducts: Thermal decomposition
Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: NA

Continued on back

HEALTH INFORMATION

Primary Route of Exposure:			
Inhalation:	Skin: X	Ingestion:	Eyes:
Carcinogen:	IARC: no	NTP: no	OSHA: no
Signs and Symptoms of Exposure: none found			
Medical Conditions Generally Aggravated by Exposure: none found			
Emergency and First Aid Procedures: <u>Eye Contact</u> , flush with water for 10 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>don't</i> induce vomiting. Call physician.			

SPECIAL PROTECTION DATA

Respiratory Protection: No special respiratory protection equipment is recommended under normal conditions of anticipated use with adequate ventilation. If mists are generated, wear a NIOSH/MSHA approved respirator.
Ventilation: Always use with adequate ventilation
Protective Gloves: use rubber gloves if handling.
Other Protective Clothing: No special clothing normally required. Where use can result in skin contact, wash thoroughly before eating, drinking, smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill: Dike and contain spill with inert material (sand, earth, etc.) Transfer liquid to containers for recovery or disposal. Wash area with soap and water. Keep spill out of sewers and open bodies of water.
Storing/Handling: Keep container closed when not in use.
Waste Disposal Method: Sanitary landfill in accordance with local, state, and federal regulations.
Other Precautions: none

MATERIAL SAFETY DATA SHEET

25311-1704 -1709

-1706

-1707

**AUTO-AIR
COLORS™**

PRODUCT IDENTIFICATION

Revision Date: 05/01/06

IDENTITY (As used on label)		Synonyms:
Auto Air Flash Reducer - Fast Dry Item # 4011		
Chemical Family:	Formula	
	CH ₃ OCH ₂ CH(OH)CH ₃	

HAZARDOUS INGREDIENTS

COMPONENT	CAS#	%	OSHA/PEL
Not a hazardous material as outlined by the OSHA Hazard Communication standards Meets ASTM D-2436 Standards			

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling/Melting Point: 200° - 215° F
Solubility in Water: water expendable
Vapor Pressure (mm Hg): N/A
Vapor Density: 1
Specific Gravity (H ₂ O-1) : 1.1
Evaporation Rate: (BuAct=1): 1
Appearance and Odor: Colorless liquid with slight sweet ether odor

FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water fog or fine spray, carbon dioxide, dry chemical, foam.
Fire Fighting Procedures: Standard fire fighting procedures
Unusual Fire and Explosion Hazards: Product itself is non-flammable, will not support combustion.

REACTIVITY DATA

Stability: (X) Stable () Unstable Conditions to avoid: none found
Incompatibility (materials to avoid): N/A
Hazardous Decomposition of Byproducts: Thermal decomposition
Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: NA

Continued on back

Auto Air Colors - 14 Airport Park Road, East Granby, CT 06026
800.509.6563 phone 860.653.0643 fax

HEALTH INFORMATION

Primary Route of Exposure: Inhalation: Skin: X Ingestion: Eyes:
Carcinogen: IARC: no NTP: no OSHA: no
Signs and Symptoms of Exposure: none found
Medical Conditions Generally Aggravated by Exposure: none found
Emergency and First Aid Procedure: Eye Contact: Flush with water for 10 minutes and consult physician if irritation persists. Ingestion: If victim is conscious, give water. <i>Do not</i> induce vomiting unless directed to by medical personnel. Call physician. Skin: Wash off in flowing water or shower. Inhalation: Remove to fresh air if effect occur. Consult a physician. NOTE TO PHYSICIAN: No specific antidote. Supportive care. Treatment based on judgment of the physician in response to reactions of the patient.

SPECIAL PROTECTION DATA

Respiratory Protection: No special respiratory protection equipment is recommended under normal conditions of anticipated use with adequate ventilation. If mists are generated, wear a NIOSH/MSHA approved respirator.
Ventilation: Always use with adequate ventilation.
Protective Gloves: Use rubber gloves if handling.
Other Protective Clothing: Avoid direct contact with skin or eyes. If splashing risk exists, wear safety glasses.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill: Dike and contain spill with inert material (sand, earth, etc.). Transfer liquid to containers for recovery or disposal. Wash area with soap and water. Keep spill out of sewers and open bodies of water.
Storing/Handling: Keep container closed when not in use.
Waste Disposal Method: Sanitary landfill in accordance with local, state and federal regulations.
Other Precautions: none

MATERIAL SAFETY DATA SHEET

25311-7174
-7176
-7177



PRODUCT IDENTIFICATION

Revision Date: 05/01/06

IDENTITY (As used on label)		Synonyms:	
Auto Air Transparent Apple Green Item # 4237			
Chemical Family:	Formula		
	Aqueous dispersion of organic pigment, mica and acrylic polymer.		

HAZARDOUS INGREDIENTS

COMPONENT	CAS#	%	OSHA/PEL
Not a hazardous material as outlined by the OSHA Hazard Communication standards Meets ASTM D-2436 Standards			

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling/Melting Point: 200° - 215° F
Solubility in Water: water expendable
Vapor Pressure (mm Hg): N/A
Vapor Density: 1
Specific Gravity (H ₂ O-1): 1.1
Evaporation Rate: (BuAct=1): 1
Appearance and Odor: Light Green liquid, slight acrylic odor

FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water or CO ₂ foam
Fire Fighting Procedures: Standard fire fighting procedures
Unusual Fire and Explosion Hazards: Product itself is non-flammable, will not support combustion.

REACTIVITY DATA

Stability: (X) Stable () Unstable Conditions to avoid: none found
Incompatibility (materials to avoid): N/A
Hazardous Decomposition of Byproducts: Thermal decomposition
Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: NA

Continued on back

Auto Air Colors - 14 Airport Park Road, East Granby, CT 06026

800.509.6563 phone 860.653.0643 fax

HEALTH INFORMATION

Primary Route of Exposure:			
Inhalation:	Skin: X	Ingestion:	Eyes:
Carcinogen:			
IARC: no	NTP: no	OSHA: no	
Signs and Symptoms of Exposure:			
none found			
Medical Conditions Generally Aggravated by Exposure:			
none found			
Emergency and First Aid Procedure:			
<u>Eye Contact:</u> Flush with water for 10 minutes and consult physician if irritation persists.			
<u>Ingestion:</u> If victim is conscious, give water. DON'T induce vomiting. Call physician.			

SPECIAL PROTECTION DATA

Respiratory Protection:
No special respiratory protection equipment is recommended under normal conditions of anticipated use with adequate ventilation. If mists are generated, wear a NIOSH/MSHA approved respirator.
Ventilation:
Always use with adequate ventilation.
Protective Gloves:
Use rubber gloves if handling.
Other Protective Clothing:
No special clothing normally required. Where use can result in skin contact, wash thoroughly before eating, drinking, smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill:
Dike and contain spill with inert material (sand, earth, etc.). Transfer liquid to containers for recovery or disposal. Wash area with soap and water. Keep spill out of sewers and open bodies of water.
Storing/Handling:
Keep container closed when not in use.
Waste Disposal Method:
Sanitary landfill in accordance with local, state and federal regulations.
Other Precautions:
none

6.28.04 ✓

MATERIAL SAFETY DATA SHEET

25311-3984
-3986
-3987

**CREATEX
COLORS**

14 Airport Park Road
East Granby, CT. 06026
(860) 653-5505
(860) 653-0643 fax

PRODUCT IDENTIFICATION

IDENTITY: (As used on label)		Synonyms:
Auto Air Transparent Fire Red (Item #4234)		---
Chemical family:	Formula	
---	Aqueous dispersion of organic pigment, mica, and acrylic polymer.	

HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	OSHA/PEL
Not a hazardous material as outlined by the OSHA Hazard Communication standards Meets ASTM D-2436 Standards			

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling /melting point: 200°-215° F
Solubility in water: water expendable
Vapor pressure (mm Hg): NA
Vapor density: 1
Specific Gravity (H₂O-1): 1.1
Evaporation Rate: (BuAct=1): 1
Appearance and Odor: Red liquid, slight acrylic odor

FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water or CO ₂ foam
Fire fighting Procedures: Standard fire fighting procedures
Unusual Fire and Explosion Hazards: Product itself is non-flammable, will not support combustion.

REACTIVITY DATA

Stability: (X) Stable () Unstable Conditions to avoid: none found
Incompatibility (materials to avoid) : NA
Hazardous Decomposition or Byproducts: Thermal decomposition
Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: NA

Continued on back

HEALTH INFORMATION

Primary Route of Exposure:			
Inhalation:	Skin: X	Ingestion:	Eyes:
Carcinogen:	IARC: no	NTP: no	OSHA: no
Signs and Symptoms of Exposure: none found			
Medical Conditions Generally Aggravated by Exposure: none found			
Emergency and First Aid Procedures: <u>Eye Contact</u> , flush with water for 10 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>don't</i> induce vomiting. Call physician.			

SPECIAL PROTECTION DATA

Respiratory Protection: No special respiratory protection equipment is recommended under normal conditions of anticipated use with adequate ventilation. If mists are generated, wear a NIOSH/MSHA approved respirator.
Ventilation: Always use with adequate ventilation
Protective Gloves: use rubber gloves if handling.
Other Protective Clothing: No special clothing normally required. Where use can result in skin contact, wash thoroughly before eating, drinking, smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill: Dike and contain spill with inert material (sand, earth, etc.) Transfer liquid to containers for recovery or disposal. Wash area with soap and water. Keep spill out of sewers and open bodies of water.
Storing/Handling: Keep container closed when not in use.
Waste Disposal Method: Sanitary landfill in accordance with local, state, and federal regulations.
Other Precautions: none

6-28-04v

MATERIAL SAFETY DATA SHEET**CREATEX
COLORS**

25311-4564	-4567
-4566	

14 Airport Park Road
East Granby, CT. 06026
(860) 653-5505
(860) 653-0643 fax

PRODUCT IDENTIFICATION

IDENTITY: (As used on label)		Synonyms:
Auto Air Transparent Yellow (Item #4231)		---
Chemical family:	Formula	
---	Aqueous dispersion of organic pigment, mica, and acrylic polymer.	

HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	OSHA/PEL
Not a hazardous material as outlined by the OSHA Hazard Communication standards Meets ASTM D-2436 Standards			

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling /melting point: 200°-215° F
Solubility in water: water expendable
Vapor pressure (mm Hg): NA
Vapor density: 1
Specific Gravity (H₂O-1): 1.1
Evaporation Rate: (BuAct=1): 1
Appearance and Odor: Yellow liquid, slight acrylic odor

FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water or CO ₂ foam
Fire fighting Procedures: Standard fire fighting procedures
Unusual Fire and Explosion Hazards: Product itself is non-flammable, will not support combustion.

REACTIVITY DATA

Stability: (X) Stable () Unstable Conditions to avoid: none found
Incompatibility (materials to avoid) : NA
Hazardous Decomposition or Byproducts: Thermal decomposition
Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: NA

Continued on back

HEALTH INFORMATION

Primary Route of Exposure:			
Inhalation:	Skin: X	Ingestion:	Eyes:
Carcinogen:	IARC: no	NTP: no	OSHA: no
Signs and Symptoms of Exposure: none found			
Medical Conditions Generally Aggravated by Exposure: none found			
Emergency and First Aid Procedures: <u>Eye Contact</u> , flush with water for 10 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>don't</i> induce vomiting. Call physician.			

SPECIAL PROTECTION DATA

Respiratory Protection: No special respiratory protection equipment is recommended under normal conditions of anticipated use with adequate ventilation. If mists are generated, wear a NIOSH/MSHA approved respirator.
Ventilation: Always use with adequate ventilation
Protective Gloves: use rubber gloves if handling.
Other Protective Clothing: No special clothing normally required. Where use can result in skin contact, wash thoroughly before eating, drinking, smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill: Dike and contain spill with inert material (sand, earth, etc.) Transfer liquid to containers for recovery or disposal. Wash area with soap and water. Keep spill out of sewers and open bodies of water.
Storing/Handling: Keep container closed when not in use.
Waste Disposal Method: Sanitary landfill in accordance with local, state, and federal regulations.
Other Precautions: none

6.28-04 ✓

MATERIAL SAFETY DATA SHEET25311-5924 -5927
-5926**CREATEX
COLORS**14 Airport Park Road
East Granby, CT. 06026
(860) 653-5505
(860) 653-0643 fax**PRODUCT IDENTIFICATION**

IDENTITY: (As used on label)		Synonyms:
Auto Air Transparent Blue (Item #4241)		---
Chemical family:	Formula	
---	Aqueous dispersion of organic pigment, mica, and acrylic polymer.	

HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	OSHA/PEL
Not a hazardous material as outlined by the OSHA Hazard Communication standards Meets ASTM D-2436 Standards			

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling /melting point: 200°-215° F
Solubility in water: water expendable
Vapor pressure (mm Hg): NA
Vapor density: 1
Specific Gravity (H₂O-1): 1.1
Evaporation Rate: (BuAct=1): 1
Appearance and Odor: Blue liquid, slight acrylic odor

FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water or CO ₂ foam
Fire fighting Procedures: Standard fire fighting procedures
Unusual Fire and Explosion Hazards: Product itself is non-flammable, will not support combustion.

REACTIVITY DATA

Stability: (X) Stable () Unstable Conditions to avoid: none found
Incompatibility (materials to avoid) : NA
Hazardous Decomposition or Byproducts: Thermal decomposition
Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: NA

Continued on back

HEALTH INFORMATION

Primary Route of Exposure:			
Inhalation:	Skin: X	Ingestion:	Eyes:
Carcinogen:	IARC: no	NTP: no	OSHA: no
Signs and Symptoms of Exposure: none found			
Medical Conditions Generally Aggravated by Exposure: none found			
Emergency and First Aid Procedures: <u>Eye Contact</u> , flush with water for 10 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>don't</i> induce vomiting. Call physician.			


SPECIAL PROTECTION DATA

Respiratory Protection: No special respiratory protection equipment is recommended under normal conditions of anticipated use with adequate ventilation. If mists are generated, wear a NIOSH/MSHA approved respirator.
Ventilation: Always use with adequate ventilation
Protective Gloves: use rubber gloves if handling.
Other Protective Clothing: No special clothing normally required. Where use can result in skin contact, wash thoroughly before eating, drinking, smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill: Dike and contain spill with inert material (sand, earth, etc.) Transfer liquid to containers for recovery or disposal. Wash area with soap and water. Keep spill out of sewers and open bodies of water.
Storing/Handling: Keep container closed when not in use.
Waste Disposal Method: Sanitary landfill in accordance with local, state, and federal regulations.
Other Precautions: none

6.28-04v

MATERIAL SAFETY DATA SHEET

14 Airport Park Road
East Granby, CT. 06026
(860) 653-5505
(860) 653-0643 fax

PRODUCT IDENTIFICATION

IDENTITY: (As used on label)		Synonyms:
Auto Air Transparent Black (Item #4249)		---
Chemical family:	Formula	
---	Aqueous dispersion of organic pigment, mica, and acrylic polymer.	

HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	OSHA/PEL
Not a hazardous material as outlined by the OSHA Hazard Communication standards Meets ASTM D-2436 Standards			

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling /melting point: 200°-215° F
Solubility in water: water expendable
Vapor pressure (mm Hg): NA
Vapor density: 1
Specific Gravity (H₂O-1): 1.1
Evaporation Rate: (BuAct=1): 1
Appearance and Odor: Black liquid, slight acrylic odor

FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water or CO ₂ foam
Fire fighting Procedures: Standard fire fighting procedures
Unusual Fire and Explosion Hazards: Product itself is non-flammable, will not support combustion.

REACTIVITY DATA

Stability: (X) Stable () Unstable Conditions to avoid: none found
Incompatibility (materials to avoid) : NA
Hazardous Decomposition or Byproducts: Thermal decomposition
Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: NA

Continued on back

HEALTH INFORMATION

Primary Route of Exposure:			
Inhalation:	Skin: X	Ingestion:	Eyes:
Carcinogen:	IARC: no	NTP: no	OSHA: no
Signs and Symptoms of Exposure: none found			
Medical Conditions Generally Aggravated by Exposure: none found			
Emergency and First Aid Procedures: <u>Eye Contact</u> , flush with water for 10 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>don't</i> induce vomiting. Call physician.			

SPECIAL PROTECTION DATA

Respiratory Protection: No special respiratory protection equipment is recommended under normal conditions of anticipated use with adequate ventilation. If mists are generated, wear a NIOSH/MSHA approved respirator.
Ventilation: Always use with adequate ventilation
Protective Gloves: use rubber gloves if handling.
Other Protective Clothing: No special clothing normally required. Where use can result in skin contact, wash thoroughly before eating, drinking, smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill: Dike and contain spill with inert material (sand, earth, etc.) Transfer liquid to containers for recovery or disposal. Wash area with soap and water. Keep spill out of sewers and open bodies of water.
Storing/Handling: Keep container closed when not in use.
Waste Disposal Method: Sanitary landfill in accordance with local, state, and federal regulations.
Other Precautions: none

6-28-04v

MATERIAL SAFETY DATA SHEET

CREATEX
COLORS25311-1734 -1737
-173614 Airport Park Road
East Granby, CT. 06026
(860) 653-5505
(860) 653-0643 fax

PRODUCT IDENTIFICATION

IDENTITY: (As used on label)		Synonyms:
Auto Air Transparent White (Item #4230)		---
Chemical family:	Formula	
---	Aqueous dispersion of organic pigment, mica, and acrylic polymer.	

HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	OSHA/PEL
Not a hazardous material as outlined by the OSHA Hazard Communication standards Meets ASTM D-2436 Standards			

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling /melting point: 200°-215° F
Solubility in water: water expendable
Vapor pressure (mm Hg): NA
Vapor density: 1
Specific Gravity (H ₂ O-1): 1.1
Evaporation Rate: (BuAct=1): 1
Appearance and Odor: White colored liquid, slight acrylic odor

FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water or CO ₂ foam
Fire fighting Procedures: Standard fire fighting procedures
Unusual Fire and Explosion Hazards: Product itself is non-flammable, will not support combustion.

REACTIVITY DATA

Stability: (X) Stable () Unstable Conditions to avoid: none found
Incompatibility (materials to avoid) : NA
Hazardous Decomposition or Byproducts: Thermal decomposition
Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: NA

Continued on back

HEALTH INFORMATION

Primary Route of Exposure:			
Inhalation:	Skin: X	Ingestion:	Eyes:
Carcinogen:	IARC: no	NTP: no	OSHA: no
Signs and Symptoms of Exposure: none found			
Medical Conditions Generally Aggravated by Exposure: none found			
Emergency and First Aid Procedures: <u>Eye Contact</u> , flush with water for 10 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>don't</i> induce vomiting. Call physician.			

SPECIAL PROTECTION DATA

Respiratory Protection: No special respiratory protection equipment is recommended under normal conditions of anticipated use with adequate ventilation. If mists are generated, wear a NIOSH/MSHA approved respirator.
Ventilation: Always use with adequate ventilation
Protective Gloves: use rubber gloves if handling.
Other Protective Clothing: No special clothing normally required. Where use can result in skin contact, wash thoroughly before eating, drinking, smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill: Dike and contain spill with inert material (sand, earth, etc.) Transfer liquid to containers for recovery or disposal. Wash area with soap and water. Keep spill out of sewers and open bodies of water.
Storing/Handling: Keep container closed when not in use.
Waste Disposal Method: Sanitary landfill in accordance with local, state, and federal regulations.
Other Precautions: none