

MATERIAL SAFETY DATA SHEET

25311-3006
-3007**AUTO-AIR
COLORS™**

PRODUCT IDENTIFICATION

Revision Date: 05/01/06

IDENTITY (As used on label)		Synonyms:
Auto Air Direct to Metal Primer Item # 4009		
Chemical Family:	Formula	

HAZARDOUS INGREDIENTS

COMPONENT	CAS#	%	OSHA/PEL
Not a hazardous material as outlined by the OSHA Hazard Communication standards Meets ASTM D-2436 Standards			

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling/Melting Point: as water
Solubility in Water: water expendable
Vapor Pressure (mm Hg): N/A
Vapor Density: 1
Specific Gravity (H ₂ O-1) : 1.0
Evaporation Rate: (BuAct=1): n/a
Appearance and Odor: White liquid

FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water fog or fine spray, carbon dioxide, dry chemical, foam.
Fire Fighting Procedures: Standard fire fighting procedures
Unusual Fire and Explosion Hazards: None known

REACTIVITY DATA

Stability: (X) Stable () Unstable Conditions to avoid: none found
Incompatibility (materials to avoid): N/A
Hazardous Decomposition of Byproducts: Thermal decomposition
Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: NA

Continued on back

Auto Air Colors - 14 Airport Park Road, East Granby, CT 06026
800.509.6563 phone 860.653.0643 fax

HEALTH INFORMATION

Primary Route of Exposure:			
Inhalation:	Skin: X	Ingestion:	Eyes:
Carcinogen:			
IARC: no	NTP: no	OSHA: no	
Signs and Symptoms of Exposure:			
none found			
Medical Conditions Generally Aggravated by Exposure:			
none found			
Emergency and First Aid Procedure:			
<u>Eye Contact:</u> Flush with water for 15 minutes and consult physician if irritation persists.			
<u>Ingestion:</u> If swallowed, call physician.			
<u>Skin:</u> Wash off in flowing water or shower.			
<u>Inhalation:</u> Remove to fresh air if effect occur. Consult a physician.			

SPECIAL PROTECTION DATA

Respiratory Protection:
Wear a NIOSH/MSHA respirator whenever exposure to fumes and vapors exceed the TLV recommendation.
Ventilation:
Exhaust ventilation should always be provided to prevent routine inhalation and build up of heavy solvent vapors on floor. Maintain air below TLV recommendation.
Protective Gloves:
Impermeable gloves for prolonged and repeated skin contact.
Other Protective Clothing:
Wear chemical goggles or face shield for splash protection. Protect from contact with skin.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill:
Dike and contain spill with inert material (sand, earth, etc.). Transfer liquid to containers for recovery or disposal. Wash area with soap and water. Keep spill out of sewers and open bodies of water.
Storing/Handling:
Keep container closed when not in use.
Waste Disposal Method:
Sanitary landfill in accordance with local, state and federal regulations.
Other Precautions:
none