

## MATERIAL SAFETY DATA SHEET

25311-9346

-9347

**AUTO-AIR  
COLORS™**

## PRODUCT IDENTIFICATION

Revision Date: 05/01/06

IDENTITY (As used on label)		Synonyms:
Auto Air Sparklescent Bada Bling Silver Item # 4590		
Chemical Family:	Formula	
	Aqueous dispersion of organic pigment, mica and acrylic polymer.	

## HAZARDOUS INGREDIENTS

COMPONENT	CAS#	%	OSHA/PEL
Not a hazardous material as outlined by the OSHA Hazard Communication standards Meets ASTM D-2436 Standards			

## PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling/Melting Point: 200° - 215° F
Solubility in Water: water expendable
Vapor Pressure (mm Hg): N/A
Vapor Density: 1
Specific Gravity (H <sub>2</sub> O-1) : 1.1
Evaporation Rate: (BuAct=1): 1
Appearance and Odor: Pearlescent-like Silver liquid, slight acrylic odor

## FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water or CO <sub>2</sub> foam
Fire Fighting Procedures: Standard fire fighting procedures
Unusual Fire and Explosion Hazards: Product itself is non-flammable, will not support combustion.

## REACTIVITY DATA

Stability: (X) Stable ( ) Unstable Conditions to avoid: none found
Incompatibility (materials to avoid): N/A
Hazardous Decomposition of Byproducts: Thermal decomposition
Hazardous Polymerization: ( ) may occur (X) will not occur Conditions to avoid: NA

Continued on back

Auto Air Colors - 14 Airport Park Road, East Granby, CT 06026  
800.509.6563 phone 860.653.0643 fax

## HEALTH INFORMATION

<b>Primary Route of Exposure:</b>			
Inhalation:	Skin: X	Ingestion:	Eyes:
<b>Carcinogen:</b>			
IARC: no	NTP: no	OSHA: no	
<b>Signs and Symptoms of Exposure:</b>			
none found			
<b>Medical Conditions Generally Aggravated by Exposure:</b>			
none found			
<b>Emergency and First Aid Procedure:</b>			
<u>Eye Contact:</u> Flush with water for 10 minutes and consult physician if irritation persists.			
<u>Ingestion:</u> If victim is conscious, give water. DON'T induce vomiting. Call physician.			

## SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> No special respiratory protection equipment is recommended under normal conditions of anticipated use with adequate ventilation. If mists are generated, wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> Always use with adequate ventilation.
<b>Protective Gloves:</b> Use rubber gloves if handling.
<b>Other Protective Clothing:</b> No special clothing normally required. Where use can result in skin contact, wash thoroughly before eating, drinking, smoking.

## SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> Dike and contain spill with inert material (sand, earth, etc.). Transfer liquid to containers for recovery or disposal. Wash area with soap and water. Keep spill out of sewers and open bodies of water.
<b>Storing/Handling:</b> Keep container closed when not in use.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state and federal regulations.
<b>Other Precautions:</b> none