

Jul 05 2006 12:44PM HP LASERJET 3200

P. 1

Naultian

25328-XXXX

**MATERIAL SAFETY DATA SHEET**

MANUFACTURER'S NAME:  
 Badger Air-Brush Co.  
 9128 West Belmont Ave  
 Franklin Park IL 60131

EMERGENCY TELEPHONE NUMBER:  
 314-843-2523

INFORMATION TELEPHONE NUMBER:  
 314-843-2523

DATE OF PREPARATION:  
 February 28, 1999

**SECTION I - PRODUCT IDENTIFICATION**

PRODUCT NUMBER: 10 - 00 SERIES  
 PRODUCT NAME: BADGER Airbrush Paint  
 PRODUCT CLASS: Water Base Acrylic

**SECTION II - HAZARDOUS INGREDIENTS**

INGREDIENT	CAS NUMBER	WEIGHT PERCENT	OCCUPATIONAL EXPOSURE LIMITS	VAPOR PRESSURE mm Hg @ TEMP
------------	------------	----------------	------------------------------	-----------------------------

NO HAZARDOUS INGREDIENTS ABOVE REPORTABLE LEVELS  
 NON - HAZARDOUS / NON - TOXIC

**SECTION III - PHYSICAL DATA**

BOILING RANGE: >212 °F  
 EVAPORATION RATE: Same as water  
 VAPOR DENSITY: Heavier than air  
 VOLATILE by VOLUME: 67%  
 WEIGHT/GAL: 8.6 - 11.0 lbs.

**SECTION IV - FIRE AND EXPLOSION DATA**

FLAMMABILITY CLASSIFICATION: NON FLAMMABLE , NON COMBUSTIBLE  
 FLASH POINT: >230°F  
 LEL: NONE  
 EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER

UNUSUAL FIRE AND EXPLOSION HAZARDS:  
 NONE KNOWN

**SPECIAL FIREFIGHTING PROCEDURES:**

WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE DEMAND WHEN FIGHTING FIRES. USE WATER FOG NOZZLES TO COOL CLOSED CONTAINERS.

**SECTION V - HEALTH HAZARD DATA****EFFECTS OF OVEREXPOSURE:**

EYES - MAY CAUSE SLIGHT IRRITATION  
 SKIN - MAY CAUSE SLIGHT IRRITATION  
 INHALATION - MAY CAUSE SLIGHT IRRITATION  
 INGESTION - CONSULT PHYSICIAN. DO NOT TAKE INTERNALLY

PRIMARY ROUTES OF ENTRY: INHALATION OF SPRAY MIST

Jul 05 2006 12:44PM HP LASERJET 3200

p. 2

*Nail Flair***EMERGENCY FIRST AID PROCEDURES:**

**EYES** - FLUSH WITH WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION.  
**SKIN** - REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA WITH SOAP AND WATER.  
**INHALATION** - MOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IF NEEDED.  
**INGESTION** - INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

**SECTION VI - REACTIVITY DATA**

**STABILITY:** STABLE  
**HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR  
**HAZARDOUS DECOMPOSITION PRODUCTS:** BURNING CAN PRODUCE CO<sub>2</sub> AND CO.  
**CONDITIONS TO AVOID:** AVOID EXCESSIVE HEAT  
**INCOMPATIBILITY:** AVOID CONTACT WITH MATERIALS CONTAINING PHOSPHORUS OR OXIDIZERS.

**SECTION VII - SPILL OR LEAK PROCEDURE**

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**  
 MOISTEN MATERIAL WITH WATER AND ABSORB.  
 DISCARD INTO PROPER WASTE CONTAINER.

**WASTE DISPOSAL METHOD:**  
 MATERIAL MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

**SECTION VIII - SAFE HANDLING & USE INFORMATION**

**RESPIRATORY PROTECTION:**  
 IF TLV OF PRODUCT OR ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL.

**VENTILATION:** PROVIDE SUFFICIENT MECHANICAL VENTILATION TO MAINTAIN EXPOSURE BELOW TLV

**PROTECTIVE GLOVES:** WEAR RESISTANT GLOVES

**EYE PROTECTION:** CHEMICAL SPLASH GOGGLES SUGGESTED, OTHER GLASSES PERMITTED

**OTHER PROTECTIVE EQUIPMENT:** IMPERVIOUS CLOTHING & BOOTS PREVENT REPEATED SKIN CONTACT

**HYGIENIC PRACTICES:** WASH WITH SOAP AND WATER AFTER USE BEFORE EATING OR SMOKING

**SECTION IX - SPECIAL PRECAUTIONS**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**  
 STORE IN DRY AREA. KEEP CONTAINERS TIGHTLY CLOSED. PROTECT FROM PHYSICAL DAMAGE.  
 EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES - ALL HAZARD PRECAUTIONS GIVEN IN DATA SHEET MUST BE OBSERVED. STORE BELOW 120°F.

**OTHER PRECAUTIONS:**  
 KEEP FROM FREEZING. FROZEN MATERIAL MAY EXPAND AND CAUSE RUPTURE OF CONTAINER.

**HAZARD RATING:**

**TOXICITY 0**  
**REACTIVITY 0**  
**FIRE 0**  
**REACTIVITY 0**

VOC: LESS THAN 0.35 Lbs./Gal.