

01/22/2002 19:48 8159622037

TESTORS

PAGE 06/09

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

25331-XXXX

Telephone number:(815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300
*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 3/09/2005

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT IDENTITY (TRADE NAME): Visions ColorArtz Fabric Water-Base Pouch Paint
(VF000 - VF999)
(This MSDS covers all products listed on page 4.)

SECTION II - HAZARDOUS INGREDIENTS & COMPOSITION INFORMATION

Table with 5 columns: SPECIFIC CHEMICAL NAME, CAS #, % WT, OSHA PEL/TWA, ACGIH TLV/TWA. Row 1: Carbon Black Pigment**, 1333-86-4, 0.1-3.0, 3.5 mg/cu.m., 3.5 mg/cu.m.

** Contained at levels 0.1% or greater in products identified with a "+" on page 4.

Non-Hazardous and Other Ingredients Below Reportable Levels Not Avail. Balance

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 to 369 deg.F
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 9.00 (TYP)
PERCENT VOLATILES (By Volume): 78.9 (TYP)
SPECIFIC GRAVITY (Water=1): 1.080 (TYP)
VAPOR PRESSURE:17.0 mm Hg @ 20 deg.C (calc.)
VAPOR DENSITY: Lighter than air.
EVAPORATION RATE: Slower than Ethyl Ether.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (SFCC): > 200 deg. F
OSHA FLAMMABILITY CLASSIFICATION: Combustible Liquid - CLASS IIIB
FLAMMABLE LIMITS (calc.) IN AIR: LEL 2.6, UEL 12.5
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, dry chemical or water fog.
SPECIAL FIRE FIGHTING PROCEDURES: A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Overexposure to decomposition products may cause a health hazard.

01/22/2002 19:48

8159622037

TESTORS

PAGE 07/09

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 2 of 4

Date prepared: 3/09/2005

Product Identity: Visions Fabric Water-Base Pouch Paint (VF000-VF999)

----- SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Contain spilled product by diking. Provide adequate ventilation. Equip emergency responders with appropriate personal protection equipment. Take up spill with an absorbent material and place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

No special method. Dispose of in accordance with local state, and federal regulations regarding disposal of non-hazardous materials.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? YES* OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Causes irritation and pain, seen as excess tearing and blinking with marked excess redness and swelling of the conjunctiva.

SKIN CONTACT: Prolonged and repeated liquid contact may result in skin irritation and dermatitis. May be absorbed through the skin.

BREATHING: Vapors or mist may cause irritation to the eyes and respiratory tract. High concentrations may cause headache, dizziness, nausea, vomiting and malaise.

SWALLOWING: May cause irritation of the gastrointestinal tract and may also cause effects resembling those from inhalation of vapor.

CHRONIC OVEREXPOSURE: Overexposures to Ethylene Glycol Monobutyl Ether and Diethylene Glycol Monobutyl Ether may cause secondary injury to the kidney and liver.

*Products identified with a "+" on page 4 contain Carbon Black which is an IARC Group 2B-possible carcinogen.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap and water thoroughly. If irritation persists, get medical attention.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: If victim is conscious, give two glasses of water to drink. Call a physician immediately.

01/22/2002 19:48 8159622037

TESTORS

PAGE 08/09

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 3 of 4

Date prepared: 3/09/2005

Product Identity: Visions Fabric Water-Base Pouch Paint (VF000-VF999)

----- SECTION VIII- REACTIVITY DATA -----

STABILITY: Stable.

CONDITIONS TO AVOID: None.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents, and alkalies.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and/or carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

----- SECTION IX SPECIAL PROTECTION INFORMATION -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors, mists and/or dusts. If exposure may or does exceed occupational exposure limits (Section II) use a NIOSH-approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air purifying respirator with appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s). Heavy solvent vapors should be removed from the lower levels of area, and all ignition sources (non-explosion proof equipment) should be eliminated if flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- SECTION X SPECIAL PRECAUTIONS -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions. Do not get in eyes. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.

This product is packaged and sold as a consumer good. This information is believed to be reliable and accurate, as of the date indicated. It is supplied on the condition that recipients will make their own determination as to its suitability and completeness for their purposes. The Testor Corporation assumes no responsibility for any damages resulting from reliance on this information.

01/22/2002 19:48 8159622037

TESTORS

PAGE 09/09

MATERIAL SAFETY DATA SHEET
 THE TESTOR CORPORATION
 440 BLACKHAWK PARK AVENUE
 ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
 24 hour Chemtrec telephone number: *(800) 424-9300

Page 4 of 4

Date prepared: 3/09/2005

 Product Identity: Visions Fabric Water-Base Pouch Paint (VF000-VF999)

Stock Numbers and Description

VF000 White
 VF008 Bisque
 VF045 Lemon Yellow
 VF067 Saffron
 VF126 Apricot
 VF164 Orange
 VF200 Misty Pink
 VF266 Cinnabar
 VF263 Calico Red
 VF270 Real Red
 VF295+ Barn Red
 VF300 Baby Pink
 VF305 Lilac
 VF323 Mauve
 VF330 Fuschia
 VF361+ Burgundy
 VF369 Purple
 VF415 Baby Blue
 VF430 Blueberry
 VF431 True Blue
 VF443 Cool Blue
 VF480+ Royal Blue
 VF520 Turquoise
 VF524 Glen Green
 VF570 Teal
 VF574 Real Green
 VF577 Basil
 VF584+ Pine Green
 VF617 Tea Dye
 VF619+ Raw Sienna
 VF630 Gold
 VF640 Copper
 VF688+ Burnt Umber
 VF833+ Slate Gray
 VF835 Silver
 VF999+ Black

+ Products that contain Carbon Black 0.1% or greater.