

06/23/2006 12:49

5304590528

HANCY MFG CO

PAGE 01

HANSEE Pounce Powder # 505

28910-2150

*Charcoal
Pounce Powder*

Pg. 1 of 1

MATERIAL SAFETY DATA SHEET

I. CHEMICAL IDENTIFICATION

NAME: Pounce Powder/LUMP CHARCOAL MESQUITE NATURAL CHUNK CAS NO. 16291-96-6
DESCRIPTION: BLACK: SOLID CHUNKS ODORLESS RTECS NO. FL7243500

OTHER DESIGNATIONS

Lump wood Charcoal.
Mesquite Charcoal

MANUFACTURER

Hancy Mfg Co
5324 Pheasant Lane
Montague, CA 96064

EMERGENCY PROCEDURE

Notify your supervisor
or call your local
poison control center.

II. HAZARDOUS INGREDIENTS

Ingredient	Concentration	Worker Exposure Limit
Char Dust	Varies	*2 mg/m3 (Respirational)

*Based on coal dust TLV-TWA established by ACGIH (1985-86).

None of the ingredients of this product are on the IARC, NTP, or OSHA carcinogen list.
Char dust is produced as a result of lump breakage.

III. PHYSICAL DATA

Melting Point: Greater than 3000 degrees C
Solubility in Water: Insoluble
Color/Form: Black, Solid Chunks

IV. FIRE AND EXPLOSION HAZARD DATA

This product consists of some combustible materials. To extinguish fire, use water spray, foam, dry chemical or carbon dioxide.

V. HEALTH HAZARD DATA

Repeated (chronic) or prolonged overexposure to the dust may cause coughing, shortness of breath and occupational lung disease. No medical conditions are known to be aggravated by exposure to this product. Due to the packaging and probable use conditions, the likelihood of any chronic effects are low.
First Aid: EYE CONTACT - Flush eyes immediately with plenty of water. SKIN CONTACT - Wash exposed area with soap and water. INGESTION - Not an apparent hazard. INHALATION - If breathing problems develop, remove to fresh air. Dust may irritate eyes. Possible sensitizer.

VI. REACTIVITY DATA

Stable under normal use and storage conditions. Incomplete combustion may form carbon monoxide.

VII. SPILL OR LEAK PROCEDURES

Keep container closed when not in use to avoid spillage.

VIII. SPECIAL PROTECTION INFO

Hygienic Practices: In an occupational exposure, wear safety glasses, gloves and dust respirator.
Engineering Controls: Use general ventilation to minimize exposure to dust.
Work Practices: Avoid eye contact and inhalation of dust.

IX. SPECIAL PRECAUTIONS

WARNING: DO NOT USE FOR INDOOR HEATING OR COOKING UNLESS VENTILATION IS PROVIDED FOR EXHAUSTING FUMES TO OUTSIDE. TOXIC FUMES MAY ACCUMULATE AND CAUSE DEATH. STORE AWAY FROM OPEN FLAMES AND MOISTURE.