

18/38/2882 17:04 614-791-9284

TRADE MARKETING

PAGE 82
30433-All
Page 1 of 6
SKUS

Mayco Colors - MSDS Sheets

11-11-03

? 30409 - All Skus
OXM 99



Manufacturers of high quality ceramic glazes, acrylic stains, brushes, molds and accessories for ceramists worldwide.

Ceramic Hobbyists	Potter or Artist	School or Art Teacher	Finishedware Producer or Mfr	Traditional Studio / Dealer	Contemporary Studio	Distributor
-------------------	------------------	-----------------------	------------------------------	-----------------------------	---------------------	-------------

Home Page | About Mayco | F A Q | Health and Safety | Contact Us

[Ceramic Glaze MSDS Sheets](#) | [Health & Safety Guidelines](#) | [Coloramic Sprays MSDS Sheets](#)

Ceramic Glazes MSDS #4

[MSDS 1 & 2](#) | [MSDS 3](#) | [MSDS 4](#) | [MSDS 5 & 7](#) | [MSDS 6](#) | [MSDS 8](#) | [MSDS 9](#)
[MSDS 10](#) | [MSDS 11](#) | [MSDS 12](#) | [MSDS 13](#) | [MSDS 14](#) | [MSDS 15](#) | [MSDS 16](#)

SECTION 1
CHEMICAL PRODUCT AND COMPANY INFORMATION

Prepared January 1, 2001

Supersedes: All previous

Manufacturer:
 MAYCO COLORS division of Coloramics, LLC
 4077 Weaver Ct. South
 Hilliard, Ohio 43026
 United States of America

Distributor USA _____ Local Phone _____

EC _____ Local Phone _____

Australia _____ Local Phone _____

IN CASE OF EMERGENCY PLEASE CONTACT YOUR LOCAL POISON CONTROL CENTER

Prepared by: MSDS department
 Information Telephone Number: 614-876-1171
 Ceramic Glaze and underglazes and Miscellaneous.

- Astro Gem Glazes AS-510 through AS-539, AS-541, AS-545 through 54, AS-552
- Fired Antiques FA-75 through FA-78
- Lead Free Glazes L-1 through L-77
- One Stroke Colors OS-001 through OS-043, OS-047 through OS-060
- Underglazes UG-1 through UG-95
- Ceramic Glaze(s) AG-206, 430, 501, E-920, 940, 941
- Miscellaneous Wax Resist AC-302 (formerly MP-2), Mayco Mask AC-303 (formerly MP-3), Mayco Media AC-304 (formerly MP-4), Mender Adhesive AC-305 (formerly Blue Lace Mender MP-5), Klay Klutch AC-306 (formerly MP-6)
- Stoneware Glazes 358 through 364
- Luster Astro Gems LA 990 through 992
- Series 2000 Glazes *S-2101-2137 and S-2200-2217, S-2501, S-2560 - S-2583, S-2401 through 2427

http://www.maycocolors.com/safety/glaze_msdms/msds04.htm

10-30-02

V 2872

10/30/2002 17:04 614-791-9204

TRADE MARKETING

PAGE 03

Mayco Colors - MSDS Sheets

Page 2 of 6

*Excluding : S-2104, 2105, 2122, 2130, 2203, 2204, 2205, 2420, 2576

Stroke and Coat Series	All Stroke and Coat (SC's)
Wonder Gem Series	All Wonder Gems (WG's)
Crystalites	S-2701 through S-2718
Roll a Coat	SC-210
Elements	EL-101 through EL-112
Classic Crackles	CC-500 through CC-507

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS	ACGIH TLV	OSHA PEL
Alumina Silicate	1352-58-7	NA	NA
Bentonite / Clay	1302-78-9	NA	NA
Water	7732-18-5	NA	NA

SECTION 3 HAZARDS IDENTIFICATION

Crystalline Silica may be present.

(OSHA PEL .1mg/m3)

Route(s) of Entry: Ingestion, absorption through the skin is negligible.

Inhalation only if sprayed.

Health Hazards (acute and chronic): Prolonged inhalation of silica, in excess of TLV, over an extended period of time may result in injury to the lungs.

SECTION 4 FIRST AID MEASURES

If inhaled: Remove from exposure.

If on skin: Wash skin with soap and water.

If in eyes: Flush eyes with large quantities of water for at least 15 minutes. If irritation persists after washing, contact a physician.

If swallowed: Dilute by drinking water.

SECTION 6 FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARD DATA

Flash Point (method used): N/A.

LEL: N/A

http://www.maycocolors.com/safety/glaze_msdms/msds04.htm

10-30-02

10/30/2002 17:04

614-791-9204

TRADE MARKETING

PAGE 04

Mayco Colors - MSDS Sheets

Page 3 of 6

UEL: N/A Flammable Limits: N/A

Extinguishing Media: None required, not combustible.

Special Fire Fighting Procedures: None

Unusual Fire and Explosion Hazards: None

SECTION 6
ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: Uncontaminated material may be recovered and re-used. If contaminated, scoop, vacuum, or wash into a receptacle for disposal.

Waste Disposal Method: Follow Federal or State and Local regulations for disposal. Testing of the waste may be required to determine status under the hazardous waste regulations.

SECTION 7
HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING AND USE

Engineer Control - None

Work practices- Store away from feed and food. Do not smoke, eat or drink while handling.

Procedure / equipment- None

Procedure for leaks or spills: Uncontaminated material may be recovered and re-used. If contaminated, scoop, vacuum, or wash into a receptacle for disposal.

Waste Disposal Method: Follow Federal or State and Local regulations for disposal.

SECTION 8
EXPOSURE CONTROLS / PERSONAL PROTECTION

Use of the following protective measures are strongly recommended if the glazes are to be applied by spraying.

The Work/Hygienic Practices apply regardless of the method of application. Respiratory Protection (Specify Type): Use a NIOSH approved dust and/or fume respirator as necessary

Ventilation: Local Exhaust - for spraying

Protective Gloves: N/A

Eye Protection: for spraying

Other Protective Clothing or Equipment: Wear appropriate clean, protective clothing such as, but not limited to, overalls, smocks, and aprons. Work/Hygienic Practices: Food, beverages, and smoking materials should not be in the work area. Hygiene is very important. Wash thoroughly before eating, drinking, smoking, or applying cosmetics.

http://www.maycocolors.com/safety/glaze_msdmsds04.htm

10.30.02

10/30/2002 17:04 614-791-9204

TRADE MARKETING

PAGE 05

Mayco Colors - MSDS Sheets

Page 4 of 6

**SECTION 9
PHYSICAL AND CHEMICAL PROPERTIES****Appearance :** Various colors.**Odor and odor threshold:** Negligible**Ph:** Not available**Boiling Point:** None**Vapor Pressure:** NA**Vapor Density:** NA**Melting Point:** above 1000oF**Specific Gravity (H2O=1):** 1.4 to 1.6**Flammable Limits:** None**Explosive limits:** None**Partition Coefficient:** None**Oxidizing Properties:** None**Solubility in Water:** Negligible**Percent Volatile by Volume:** None**Evaporation Rate:** None**Freezing point:** NA**Flash Point:** None**Auto ignition temperature:** None**SECTION 10
STABILITY AND REACTIVITY DATA****Incompatibility (material to avoid):** Avoid fumes from firing by venting kiln area.**Stability:** Stable (conditions to avoid: N/A)**Hazardous Decomposition or Byproducts:** Not available**Hazardous Polymerization:** Will not occur**Conditions to avoid:** Fumes from firing in kiln. Inhalation of spray.**SECTION 11
TOXICOLOGICAL INFORMATION**http://www.maycocolors.com/safety/glaze_msdmsds04.htm

10.30.02

10/30/2002 17:04 614-791-9204

TRADE MARKETING

PAGE 05

Mayco Colors - MSDS Sheets

Page 5 of 6

Hazard to Human: None during normal use. Harmful if inhaled or swallowed.

DO NOT SPRAY APPLY

If glaze is spray applied the following warnings apply: Warning: Contains Quartz.

1. Possible cancer agent based on tests with laboratory animals.
2. Exposure may cause lung damage.
3. Keep out of reach of children; avoid inhalation.

This product contains chemicals known to the State of California to cause cancer.

Health Hazards (acute and chronic): Prolonged inhalation of silica, in excess of TLV, over an extended period of time may result in injury to the lungs.

Additional information: Frits are fused silica glass like substances. The bioavailability may be limited because of the physical nature of the frit.

**SECTION 12
ECOLOGICAL INFORMATION**

Mobility: Not Available

Persistence/degradability: Not Available

Bioaccumulation: Not Available

Ecotoxicity: Not Available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal Method: Follow your Federal or State and Local regulations for disposal. Lead is listed in US-EPA Code of Federal Regulations 40, Part 261.24. Testing of the waste may be required to determine status under the hazardous waste regulations.

Waste from residue/unused product: Can be landfilled according to local regulations.

Contaminated packing: Can be landfilled according to local regulations.

**SECTION 14
TRANSPORTATION INFORMATION**

UN Number: None for this product.

**SECTION 15
REGULATORY INFORMATION**

Silica is listed by California, Proposition 65

Silica is listed on the IARC, OSHA or NTP carcinogen list.

All ingredients are on U.S. TSCA / EC / AICS / DSL Inventory.

See local requirements.

http://www.maycocolors.com/safety/glaze_msdmsds04.htm

10.30.02

10/30/2002 17:04 614-791-9204

TRADE MARKETING

PAGE 07

Mayco Colors - MSDS Sheets

Page 6 of 6

EU Status: Symbol- None**WHMIS Status : Not Controlled****SECTION 16
ADDITIONAL INFORMATION**

This information is furnished with out warranty, representation, inducement or license of any kind, except that it is accurate to the best of knowledge of COLORAMICS, LLC or obtained from sources believed to be accurate. COLORAMICS, LLC does not assume any legal responsibility for use or reliance on same. Customers are encouraged to conduct thier own tests before using any product. Read the product label. For more information in AUSTRALIA see web sight www.nohsc.gov.au

http://www.maycocolors.com/safety/glaze_msdms/msds04.htm

10.30.02