

* E-Z Cut ClsrM Str Kit *

40409-1001

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety & Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

Recd C4-09-03

IDENTITY (As Used on Label and List)		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.			
Printing Block					
Section I					
Manufacturer's Name Blumberg Company, Inc.		Emergency Telephone Number 978-465-0409			
Address (Number, Street, City, State, and Zip Code) 75 Parker Street		Telephone Number for Information 978-465-0409			
Newburyport, MA 01950		Date Prepared December 1, 2001			
		Signature of Preparer (optional) Ludwig Blumberg			
Section II - Hazardous Ingredients/Identify Information					
Hazardous Components (Specific Chemical Identity)		CAS #	OSHA PEL	ACGIH TLV	Other Limits Recommended
Vegetable Oil		None	N/A	N/A	None
Lime		58398-71-3	N/A	N/A	None
Titanium Dioxide		None	N/A	N/A	None
SARA Title III, Sec. 311 Compliance Does Not Apply					
Section III - Physical/Chemical Characteristics					
Bolling Point		Specific Gravity (H ₂ O=1)			
Solid	N/A			N/A	
Vapor Pressure (mm Hg.)	N/A	Melting Point		None	
Vapor Density (A/R=1)	N/A	Evaporation Rate (Butyl Acetate=1)		N/A	
Solubility in Water	None	PH		N/A	
Appearance		Odor		Nil	
Elastomeric Pliable Solid	White				
Section IV - Fire and Explosion Hazard Data					
Flash Point (Method Used)	N/A	Flammable Limits		LEL	UEL
		N/A			
Extinguishing Media Dry Chemical, CO2, Foam, Water Fog					
Special Fire Fighting Procedures Use Respirators					
Use Water to Keep Containers Cool					
Unusual Fire and Explosion Hazards Material Will Burn, Will Not Ignite Readily					

V-561

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard, 29 CFR 1910.1200
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved OMB No. 1218-0072

40305-XXXX

IDENTITY (As Used on Label and List) Water Soluble Screen Printing Ink G40305-(1003-9306)		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.	
Section I Manufacturer's Name Dick Blick Art Materials		Emergency Telephone Number 800-828-4548	
Address (Number, Street, City, State, and ZIP Code) PO Box 1267 Galesburg, IL 61402-1267		Telephone Number for Information 800-828-4548	
Date Prepared: October 17, 2007		Signature of Preparer (optional)	

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)):	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
VOC: 106-134 grams per litre (.88-1.12 lbs. per gallon)				
Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.				

Section III - Physical/Chemical Characteristics

Boiling Point	212°F-369°F	Specific Gravity (H ₂ O = 1)	1.11-1.57
Vapor Pressure (mm Hg.)	N/A	Melting Point	<32°F
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	Semi-paste with slight odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A			
Special Fire Fighting Procedures Wear self-contained breathing apparatus (pressure-demand MSHA/NIOSH approved or equivalent) and full protective gear.			
Unusual Fire and Explosion Hazards Material can spatter above 212°F. Film can burn.			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V - Reactivity Data

Screen Drawing Fluid

Page 2

Stability	Unstable	Stable ✓	Conditions to Avoid Onset of decomposition is 350°F
Incompatibility (<i>Materials to Avoid</i>) N/A			
Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen			
Hazardous Polymerization	May Occur	Will Not Occur ✓	Conditions to Avoid N/A

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards (<i>Acute and Chronic</i>) N/A			
Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure N/A			
Medical Conditions Generally Aggravated by Exposure None known			
Emergency and First Aid Procedures Contact with eyes may cause slight irritation: Flush with water.			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.
Waste Disposal Method Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.
Precautions to Be taken in Handling and Storing Keep from freezing-product may coagulate
Other Precautions N/A

Section VIII - Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with adequate ventilation & normal usage conditions.			
Ventilation	Local Exhaust N/A	Special N/A	
	Mechanical (<i>General</i>) N/A	Other N/A	
Protective Gloves Impervious	Eye Protection Safety Glasses or goggles		
Other Protective Clothing or Equipment N/A			
Work/Hygienic Practices Use protective cream where excessive skin contact is likely.			