

SEP. 2.2004 12:23PM STARKEY CHEMICAL

43303-1007
-1009

✓ 09-03-04

MATERIAL SAFETY DATA SHEET

SCREEN WASH

ATTN: MARY @
DICK BLICK

[3] 800-522-5786

SECTION I - IDENTIFICATION

MANUFACTURER'S NAME..... STARKEY CHEMICAL PROCESS COMPANY
9600 W OGDEN AVE
LAGRANGE, IL 60525
1-800-323-3040
EMERGENCY PHONE NUMBER... 24 HOUR INFOTRAC 1-800-535-5053
RESELLER'S NAME..... n/a
EFFECTIVE DATE..... n/a
REVISED DATE..... 5/90 [Revised Date Only: 01/02/02
PRODUCT IDENTIFIER..... SBI
TRADE NAME..... SCREEN WASH
CHEMICAL FAMILY..... n/a

SECTION II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	HAZARDOUS INGREDIENT PERCENT	TLV (Units)	HAZARDOUS INGREDIENT CAS/NA/UN NUMBERS
Xylene*	100%	100 ppm	cas 1330-20-7

SPECIAL... *This chemical is subject to S.A.R.A. Title III section 313 part 372 reporting. VOC 100% 7.26#/GAL

SECTION III - PHYSICAL DATA

BOILING POINT..... 282 - 286° F
FREEZING POINT..... n/a
VOLATILITY/VOL(%)..... 100%
MELTING POINT..... n/a
VAPOUR PRESSURE..... 6.6 mmHg
VAPOUR DENSITY (air=1)... 3.7
SOLUBILITY IN H2O..... negligible
ODOUR AND APPEARANCE.... clear, little color if any; characteristic odor
SPECIFIC GRAVITY..... .870
EVAPORATION RATE..... .80
pH..... n/a

V-3940

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT AND METHOD OF DETERMINATION... 81°F Tag Closed Cup
LOWER EXPLOSION LIMIT(% BY VOL)... 1.0
UPPER EXPLOSION LIMIT(% BY VOL)... 7.0
MEANS OF EXTINCTION..... Dry Chemical or Foam, water may be ineffective as extinguishing agent.
DR FIRE..... Use self-contained breathing apparatus. Water may be used as cooling agent for other containers. Do not spread burning liquid with water used for cooling purposes.

SEP. 2.2004 12:23PM

STARKEY CHEMICAL

NO.226 P.2

MATERIAL SAFETY DATA SHEET

SCREEN WASH

EXPLOSION DATA..... Material is flammable! May be ignited by heat, sparks, flame or static electricity.

SECTION V - HEALTH HAZARD DATA

Routes of Entry: Skin Contact, Skin Absorption, Eye, Inhalation, Ingestion. Acute and Chronic Effects: Intentional misuse by deliberately concentrating or inhaling may be harmful or fatal. Symptoms: SKIN: redness, burning, drying & cracking. EYES: burning or tearing. INHALATION: irritation of nose & throat, dizziness, fatigue. INGESTION: irritation to digestive tract, loss of coordination, fatigue, drowsiness. Sensitization to Material: Pre-existing liver and/or kidney disorders may be aggravated. Specific First Aid Procedures: In case of inhalation, move to a ventilated area. Support or restore breathing. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If ingested, material is slightly toxic & an aspiration hazard. Seek medical attention.

SECTION VI - REACTIVITY DATA

Chemical Stability: stable. Conditions of Reactivity: heat, sparks, flame & static electricity. Incompatible Materials: strong oxidizing agents, acids, bases, selected amines. Hazardous Decomposition Products: Thermal decomposition in presence of air may yield carbon monoxide and/or carbon dioxide. Hazardous Polymerization: will not occur. Polymerization-Avoid: none.

SECTION VII - SPILL OR LEAK PROCEDURE

Leak and Spill Procedures: Eliminate all sources of ignition. If indoors, ventilate. Use sand or other inert material to dam or contain spill. Do not flush into sewers or waterways. Waste Disposal: Dispose of in accordance with federal, state, county & local regulations.

SECTION VIII - SPECIAL PROTECTION

Respiratory Protection: Depending on airborne concentrations, use respirator or mask. Ventilation: Use ventilation or exhaust systems to keep concentrations below 100 ppm. Protective Gloves: impermeable. Eye Protection: safety glasses.

SEP. 2.2004 12:24PM

STARKEY CHEMICAL

NO.226 P.3

MATERIAL SAFETY DATA SHEET

SCREEN WASH

OTHER PROTECTIVE EQUIPMENT..... Use impermeable aprons. Safety showers & eye wash stations are recommended.

HANDLING PROCEDURES AND EQUIPMENT..... Keep containers tightly closed, cool, dry and away from sources of ignition. Empty containers retain residue & can be dangerous. Do not expose empty containers to heat, flame, sparks or other sources of ignition. Do not eat, drink or smoke in work area. Wash hands thoroughly after use.

=====
SECTION IX - SPECIAL PRECAUTIONS
=====

HAZARD CLASS.....	Flammable Liquid	2	HMIS HEALTH
DOT SHIPPING NAME...	Xylene	3	HMIS FLAMMABILITY
UN NUMBER.....	1307	0	HMIS REACTIVITY
NA #.....	n/a	B	HMIS PERSONAL PROTECTION

OTHER..... If packaged in 1 gallon container or less, this product is LIMITED QUANTITY and is exempt from marking except that the flash point (81°F) must be marked on the outside of the shipping carton. If packaged in greater than 1 gallon container, full marking is required.

WARNING: This product contains a product known to the State of California to cause cancer, birth defects and other reproductive harm! This "warning" is generated due to the fact that there is lead present in the solder in the metal can. This is not applicable if the container is plastic.

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.