

#330/#200/#300/#120/#130
 DECOCOLOR OPAQUE PAINT MARKERS

44907-1009

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standards must be consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name UCHIDA OF AMERICA, CORP.	Emergency Telephone Number 213-632-0333
Address (Number, Street, City, State, and ZIP Code) 1027 E. BURGROVE STREET, CARSON, CALIFORNIA 90746	Telephone Number for Information 213-632-0333
	Date Prepared APRIL 16, 1991
	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
PIGMENTS: COLORED PIGMENTS				10
VEHICLE: RESINS				30
SOLVENTS: XYLENE		100 (ppm)		40
OTHERS: TITANIUM OXIDE				20

CONFORMS TO CONSUMER SAFETY ACT REGULATIONS CFR-16 PART 1500

Section III — Physical/Chemical Characteristics

Boiling Point	280	Specific Gravity (H ₂ O = 1)	N/A
Vapor Pressure (mm Hg.) (at 68°F)	7	Melting Point	60-75
Vapor Density (AIR = 1)	4	Evaporation Rate (Butyl Acetate = 1)	N/A

Solubility in Water
INSOLUBLE

Appearance and Odor
PETROLEUM SOLVENT ODOR.

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	105°F TAG OPEN	Flammable Limits	-N/A	LEL	UEL
Extinguishing Media	CO ₂ or CHEMICAL FORM				
Special Fire Fighting Procedures	N/A				

Unusual Fire and Explosion Hazards

Item Numbers: 44907-1009 N/A

1-14

#330/#200/#300/#120/#130 DECOCOLOR OPAQUE PAINT MARKERS

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid	N/A
	Stable	X	PROLONGED TEMPERATURE AT 110°F	

Incompatibility (Materials to Avoid)

Hazardous Decomposition or Byproducts

Hazardous Polymerization	May Occur		Conditions to Avoid	N/A
	Will Not Occur	X		

Section VI — Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
N/A			
Health Hazards (Acute and Chronic)	N/A		

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
N/A			

Signs and Symptoms of Exposure

N/A

Medical Conditions

Generally Aggravated by Exposure ANESTHESIA WITHOUT ADEQUATE VENTILATION WHEN USED IN VERY LARGE QUANTITIES.

Emergency and First Aid Procedures

IF INGESTED, DO NOT INDUCE VOMITING, CALL PHYSICIAN.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

ADEQUATE VENTILATION, TREAT AS FLAMMABLE SOLVENT OR PAINT SPILL.

Waste Disposal Method

WITH OTHER PETROLEUM PRODUCTS.

Precautions to Be Taken in Handling and Storing

DO NOT STORE NEAR HEAT SOURCE

Other Precautions

N/A

Section VIII — Control Measures

Respiratory Protection (Specify Type)

AVOID PROLONGED INHALATION OF CONCENTRATED VAPOR

Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (General)	N/A	Other	N/A

Protective Gloves	N/A	Eye Protection	N/A
-------------------	-----	----------------	-----

Other Protective Clothing or Equipment

N/A

2-14

Work/Hygiene Practices

N/A

Feb-01-2001 10:07 {45175-xxxx}
{45176-xxxx}

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements. *Rwd02-02-01*

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

43215-xxxx

IDENTITY (As Used on Label and List) SPEEDBALL Permanent Acrylic Screen Inks (4620-4637, 4640-4657, 4660-4689, 46210-46212, 46410-46412 & 46610-46612)

Section I

Manufacturer's Name SPEEDBALL ART PRODUCTS 2226 SPEEDBALL ROAD STATESVILLE, NC 28677	Emergency Telephone Number 704-838-1475
	Telephone Number for Information 704-838-1475
	Date Prepared 7-14-98
	Signature of Preparer (optional) <i>[Signature]</i>

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
---	----------	-----------	--------------------------	--------------

Approved for the AP Seal (Non-toxic) by the Art & Creative Materials Institute, Inc. - (ACMI)
Product labeling conforms to ASTM D4236.

Note: This product has been evaluated by a Toxicologist only as per intended usage.
Do not deviate from intended usage!

VOC: 158 - 239 grams per liter
(1.32 - 1.99 lbs. per gal.)

Section III — Physical/Chemical Characteristics

Boiling Point	212-360°F	Specific Gravity (H ₂ O = 1)	1.02 to
Vapor Pressure (mm Hg.)	unknown	Melting Point	<32°F.
Vapor Density (AIR = 1)	less than 1	Evaporation Rate (Butyl Acetate = 1)	less than

Solubility in Water: Dilutable
Appearance and Odor: Colored semi-paste with low odor

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) Not applicable (N/A)	Flammable Limits N/A	LEL N/A	UEL N/A
---	-------------------------	------------	------------

Extinguishing Media: N/A
Special Fire Fighting Procedures: wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards: Material can spatter above 212°F. Film can burn.

3-14

Stability	Unstable		Conditions to Avoid	Onset of decomposition is 350°F.
	Stable	X		

Incompatibility (Materials to Avoid) - N/A

Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen.

Hazardous Polymerization	May Occur		Conditions to Avoid	N/A
	Will Not Occur	X		

Section VI — Health Hazard Data

Route(s) of Entry: N/A Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: N/A NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled
 Floor may be slippery; use care to avoid falling. No special handling required

under normal conditions: For large quantities (more than a quart) transfer to containers for disposal & keep out of municipal sewers & open bodies of water.

Waste Disposal Method
 No special handling required under normal use conditions. Incinerate large quantities (more than a quart) at a permitted facility according to local, state & federal regulations.

Precautions to Be Taken in Handling and Storing
 Keep from freezing - product may coagulate.

Other Precautions N/A

Section VIII — Control Measures

Respiratory Protection (Specify Type)
 None required with adequate ventilation & normal operating conditions.

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

Protective Gloves Impervious Eye Protection Safety glasses

Other Protective Clothing or Equipment N/A

Work/Hygiene Practices
 Use protective cream where excessive skin contact is likely.

4-14

98-1-251 version 1.001
1-3859 251
707/91

45177-04
-05
-06
-07

MATERIAL SAFETY DATA SHEET

H. B. Fuller Company
1200 Walters Boulevard
Madnaia Heights, Minnesota 55110

Date: 07 February 1991

Prepared by: Industrial Hygiene
Telephone Number: 612/481-3300

Emergency Medical Telephone Number: 800/228-5635

PRODUCT IDENTIFICATION

H. B. Fuller Company Name: PA-3859 251
Product Class: SYNTHETIC RESIN based product in water
DOT Proper Shipping Name: Not a regulated material

WARNING STATEMENTS

No specific warnings for normal use conditions.

PRECAUTIONARY MEASURES

Avoid temperature extremes in storage.

EMERGENCY AND FIRST AID PROCEDURES

FIRST AID:

- If in eye: Flush immediately with water for 15 minutes. Consult a physician if irritation persists.
- If on skin: Wash affected area with soap and water. Launder contaminated clothing before reuse.
- If vapors inhaled: Remove subject to fresh air.
- In case of fire: This product is non-flammable in the liquid state. Use water spray, foam, dry chemical or carbon dioxide on dried product.
- Spill or Leak: Contain and remove with inert absorbent. Keep spill out of sewers.

V-1108

HAZARDOUS INGREDIENTS

Material Name/CAS #	Level In Product	OSHA PEL	ACGIH TLV (1988,1989)
Residual vinyl acetate monomer (108-05-4)	<0.5%	10 ppm	10 ppm
Flash point, F: 18			
LEL, %: 2.6			
Vapor pressure, in mm Hg @ 20 C: 92			
OSHA STEL: 20 ppm			
ACGIH STEL: 20 ppm			

This MSDS is prepared to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200). Unlisted ingredients are not 'Hazardous' per this OSHA Standard and are considered to be trade secrets of the H. B. Fuller Company. Identities of trade secret ingredients will be made available following the procedures specified in the standard.

5-14

39, 251, version 1.001
 07/91

OCCUPATIONAL CONTROL PROCEDURES

Eye Protection: Wear safety glasses to reduce the potential for eye contact; chemical safety goggles are appropriate if splashing is likely. Have eye washes available where eye contact can occur.

Skin Protection: Prevent prolonged or repeated contact by using rubber gloves and appropriate protective clothing. Launder contaminated clothing before reuse.

Respiratory Protection: Not normally required.

Ventilation: Standard industrial ventilation.

FIRE PROTECTION

Flash Point/Method: Non-flammable

Appropriate Extinguishers: Non-flammable in liquid state; use water spray, foam, dry chemical or carbon dioxide on dried product.

Special Fire Fighting Procedures: Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

Unusual Fire and Explosion Hazards: There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.

REACTIVITY DATA

Stability: Stable

Incompatibility: Not established

Hazardous Decomposition Products: Incomplete combustion can yield low molecular weight hydrocarbons, carbon monoxide

Hazardous Polymerization: Will not occur.

EFFECTS OF OVEREXPOSURE

Eyes: Direct eye contact with the product may cause irritation.

Skin: Prolonged or repeated contact with liquid product may cause irritation.

Inhalation: Exposure to vapors in poorly ventilated areas may cause irritation of the nose, throat and respiratory tract.

Chronic: Vinyl acetate has been shown to cause cancer in tests with laboratory animals. Overexposure may increase cancer risk. Overexposure to vinyl acetate should not occur with normal handling and use.

Existing Health Conditions Affected by Exposure: No known effects on other illnesses.

6-14

251, version 1.001

91.

PHYSICAL DATA

Physical State: Liquid
Weight per Gallon: 8.9 lbs.
Viscosity: 5750 cps
% Solids by Weight: 30
pH: 7
Boiling Range: Greater than 200 F
Soluble in Water: Miscible

SPILL, LEAK & DISPOSAL INFORMATION

Spill or Leak Procedures: Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds or water systems.

Waste Disposal: -----To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It does not contain any added raw materials with known levels of TCLP constituents as identified in section 261.24 of the U.S. EPA Hazardous Waste Regulation. Leachate tests have not been performed. State or local hazardous waste regulations may apply if they are different from the federal regulation. Solidify and dispose of in an approved landfill. For additional waste disposal assistance, consult H.B. Fuller Environmental Services at 612/481-1588.

STORAGE

Protect from freezing - product stability may be affected.

ADDITIONAL INFORMATION

In storage, monomer vapors will migrate from the emulsion and establish an equilibrium between the headspace in the storage container and the liquid emulsion. Levels in excess of acceptable exposures can accumulate in non-vented headspaces above the emulsion. All procedures appropriate for a confined space entry should be completed prior to performing any work in a bulk storage tank.

REGULATORY INFORMATION**TSCA**

All components of this product are registered under the regulations of the Toxic Substances Control Act.

7-14

NA - not applicable
NE - not established

8859 251 version 1.001
07/91

SARA TITLE III

Section 313: This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372:

Chemical Name	CAS Number	Percentage
Vinyl acetate	108-05-4	<0.5

This information must be included in all MSDS that are copied and distributed for this material.

8-14

MATERIAL SAFETY DATA SHEET

No. 104

43314-XXXX

Rev. 2

MAR 29 1988

I. General Information		
ULANO CORPORATION	718-622-5200	6311-06 -07
255 BUTLER STREET, BROOKLYN, N.Y. 11217		43314-1007
PRODUCT OR TRADE NAME: ULANO GEL #23		-1009
II - HAZARDOUS INGREDIENTS		
Not applicable	%	HAZARD DATA
III. Physical Data		
Boiling Point (°F) N.A.	Specific Gravity (H ₂ O = 1) approx. 1	
Vapor Pressure (mm Hg.) N.A.	Percent Volatile By Volume (%) 85	
Vapor Density (Air = 1) N.A.	Evaporation Rate (H ₂ O = 1) 1	
Solubility in Water Soluble or dispersible	pH 7-8	
Appearance & Odor grey colored paste - nearly odorless		
IV. Fire & Explosion Hazard Data		
Flash Point (Test Method) Not flammable	Auto Ignition Temperature N.A.	
Flammable Limits N.A.	LEL N.A.	UEL N.A.
Extinguishing Media Not necessary		
Special Fire Fighting Procedures None		
Unusual Fire & Explosion Hazards None	9-14	

V-4330

V. Health Hazard Data

4

Overexposure can result in skin and eye irritation.

PRIMARY ROUTES OF ENTRY	<input type="checkbox"/> Inhalation	<input type="checkbox"/> Ingestion	CARCINOGEN LISTED IN	<input type="checkbox"/> NTP	<input type="checkbox"/> OSHA
	<input type="checkbox"/> Skin Absorption	<input checked="" type="checkbox"/> Not Hazardous		<input type="checkbox"/> IARC Monograph	<input checked="" type="checkbox"/> Not Listed

Emergency First Aid
 Skin and eye - In case of contact, flush with plenty of water. If irritation results, call a physician.

VI. Reactivity Data

Stability	<input checked="" type="checkbox"/> Unstable <input type="checkbox"/> Stable	Conditions To Avoid	None
Incompatibility		Materials To Avoid	None
Hazardous Polymerization	<input checked="" type="checkbox"/> May Occur <input type="checkbox"/> Will Not Occur	Conditions To Avoid	None
Hazardous Decomposition Products		None	

VII. Environmental Protection Procedures

Spill Response
 Small spills may be rinsed down the drain. Large spills, absorb onto solid material.

Waste Disposal Method
 Dispose of in accordance with state and local regulations.

VIII. Special Protection Information

Eye Protection	Goggles	Skin Protection	plastic gloves
Respiratory Protection (Specific Type)	None	Ventilation Recommended	Normal
Other Protection	Protective apron		

IX. Special Precautions

Handling & Storage
 None

Other Precautions
 None

10-14

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, Ulano Corp. makes no warranty with respect thereto and disclaims all liability from reliance thereon.

MATERIAL SAFETY DATA SHEET

No. 105

43310-XXXX

MAR 29 1988

Rev. 2

I. General Information

ULANO CORPORATION

718-622-5200

43310-1007
-1009

255 BUTLER STREET, BROOKLYN, N.Y. 11217

PRODUCT OR TRADE NAME: ULANO STENCIL REMOVER #4
Active ingredient: Sodium metaperiodate

II - HAZARDOUS INGREDIENTS

	%	HAZARD DATA
Not applicable		

III. Physical Data

Boiling Point (°F) 212	Specific Gravity (H ₂ O = 1) 1
Vapor Pressure (mm Hg.)	Percent Volatile By Volume (%) 96
Vapor Density (Air = 1)	Evaporation Rate (H ₂ O = 1) 1
Solubility in Water Infinite	pH 4.2
Appearance & Odor Light blue color - odorless	

IV. Fire & Explosion Hazard Data

Flash Point (Test Method) Not flammable	Auto Ignition Temperature Not flammable
Flammable Limits N.A.	LEL N. A. UEL N.A.
Extinguishing Media N.A.	
Special Fire Fighting Procedures N.A.	
Unusual Fire & Explosion Hazards N.A.	11-14

V-4930

Health Hazard Data 5

Overexposure can result in skin and eye irritation.

PRIMARY ROUTES OF ENTRY

- Inhalation
 Skin Absorption
 Ingestion
 Not Hazardous

CARCINOGEN LISTED IN

- NTP
 IARC Monograph
 OSHA
 Not Listed

Emergency First Aid

Skin and eye - In case of contact, flush with plenty of water. If irritation results, consult a physician.

VI. Reactivity Data

Stability	<input checked="" type="checkbox"/> Stable	Unstable	Conditions To Avoid	None
Incompatibility			Materials To Avoid	Reducing agents
Hazardous Polymerization	<input checked="" type="checkbox"/> Will Not Occur	May Occur	Conditions To Avoid	
Hazardous Decomposition Products			Iodine, iodine oxides, oxygen.	

VII. Environmental Protection Procedures

Spill Response Small spills may be rinsed down the drain. Large spills, absorb onto solid material.

Waste Disposal Method

Dispose of in accordance with state and local regulations.

VIII. Special Protection Information

Eye Protection	Goggles	Skin Protection	Plastic gloves
Respiratory Protection (Specific Type)	None	Ventilation Recommended	Normal
Other Protection	Protective apron.		

IX. Special Precautions

Handling & Storage

None

Other Precautions

None

12-14

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, Ulano Corp. makes no warranty with respect thereto and disclaims all liability from reliance thereon.

FEB-12-2001 15:38

(Black Cat India one)

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.


7000-01
-02
-05
-06

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

21101-XXXX

IDENTITY (As Used on Label and List) SPEEDBALL Super Black India Ink (3268, 3338, 32110, 3378, 3231, 3398 & 3251)
SPEEDBALL Black Waterproof Ink

Section I Revd 02-12-01

Manufacturer's Name  P. O. Box 5157 Slateville, NC 28887 ©1997 Speedball Art Products Company	Emergency Telephone Number 704-838-1475
	Telephone Number for Information 704-838-1475
	Date Prepared 1/29/98
	Signature of Preparer (optional) <i>[Signature]</i>

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Certified non-toxic as per ASTM D4236. Approved for the AP Seal as per the Art and Craft Materials Institute, Inc. (ACMI)				

21101-2002
-2003
-2004
-2006
-2007

Section III — Physical/Chemical Characteristics

Boiling Point	212-374°F	Specific Gravity (H ₂ O = 1)	1.1
Vapor Pressure (mm Hg.)	17mmHg	Melting Point	<32°F.
Vapor Density (AIR = 1)	less than 1	Evaporation Rate (Butyl Acetate = 1)	less than 1
Solubility in Water	Dilutable		
Appearance and Odor	Thick paste/Acrylic emulsion odor		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	Not applicable (N/A)	Flammable Limits	N/A	LEL	N/A	UEL	N/A
Extinguishing Media	N/A						
Special Fire Fighting Procedures	wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.						
Unusual Fire and Explosion Hazards	Material can spatter above 212°F. Film can burn.						

13-14

FEB-12-2001 15:38

P.03/25

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid Onset of decomposition is 350°F.
	Stable	X	

Incompatibility (Materials to Avoid) N/A

Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen.

Hazardous Polymerization	May Occur		Conditions to Avoid N/A
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry: N/A Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: N/A NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled
Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.

Waste Disposal Method
Incinerate at a permitted facility according to current local, state and federal regulations.

Precautions to Be Taken in Handling and Storing
Keep from freezing - product may coagulate.

Other Precautions N/A

Section VIII — Control Measures

Respiratory Protection (Specify Type)
None required with adequate ventilation & normal operating conditions.

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

Protective Gloves Impervious Eye Protection Safety glasses 14-14

Other Protective Clothing or Equipment N/A

Work/Hygienic Practices
Use protective cream where excessive skin contact is likely.