


May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

44924-1409



IDENTITY (As Used on Label and List)
SPEEDBALL Textile Inks (4560 to 4697, 47500 to 47541, 45650 to 45652, 45750 to 45752, Section I 4-10-03 Night glo inks as well 47520 to 47523)

Manufacturer's Name  P. O. Box 5157 Statesville, NC 28687 ©1997 Speedball Art Products Company	Emergency Telephone Number	704-838-1475
	Telephone Number for Information	704-838-1475
	Date Prepared	3/11/02
	Signature of Preparer (optional)	<i>[Handwritten Signature]</i>

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (approx)
Approved for the AP Seal (Non-toxic) by the Art & Creative Materials Institute, Inc. (ACMI)				
Product labeling conforms to ASTM D4236.				

Note: This product has been evaluated by a Toxicologist only as per intended usage.
Do not deviate from intended usage!

VOC: 85-199 grams per liter
(0.71-1.66 lbs. per gal.)

Section III — Physical/Chemical Characteristics

Boiling Point	212 to 369°F.	Specific Gravity (H ₂ O = 1)	1.0 to 1
Vapor Pressure (mm Hg.)	17mmHg	Melting Point	<32°F.
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1

Solubility in Water Dilutable

Appearance and Odor High viscosity/Acrylic Emulsion Odor

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	Not applicable (N/A)	Flammable Limits	N/A	LEL	N/A	UEL	N/A
---------------------------	----------------------	------------------	-----	-----	-----	-----	-----

Extinguishing Media N/A

Special Fire Fighting Procedures wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards Material can spatter above 212°F. Film can burn.

(Reproduce locally)

OSHA 174, Sept. 1985

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid Onset of decomposition is 350°F.
	Stable	X	

Incompatibility (Materials to Avoid) N/A

Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen.

Hazardous Polymerization	May Occur		Conditions to Avoid N/A
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry: N/A Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: N/A NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled
Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.

Waste Disposal Method
Incinerate at a permitted facility according to current local, state and federal regulations.

Precautions to Be Taken in Handling and Storing
Keep from freezing - product may coagulate.

Other Precautions N/A

Section VIII — Control Measures

Respiratory Protection (Specify Type)
None required with adequate ventilation & normal operating conditions.

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

Protective Gloves Impervious Eye Protection Safety glasses

Other Protective Clothing or Equipment N/A

Work/Hygiene Practices
Use protective cream where excessive skin contact is likely.

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List)
 SPEEDBALL Diazo Photoemulsion (Part of #4558 Kit) 4559 + 4579

Section I



P. O. Box 5157
 Statesville, NC 28687
 ©1997 Speedball Art Products Company

Manufacturer's Name	Emergency Telephone Number 704-838-1475
ZIP Code)	Telephone Number for Information 704-838-1475
	Date Prepared 2/6/02
	Signature of Preparer (optional) <i>[Signature]</i>

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (conc)
Certified non-toxic as per ASTM D4236. Approved for the AP Seal as per the Art and Craft Materials Institute, Inc. (ACMI)				
Ethyl Alcohol (CAS #64-17-5)	NA	1000ppm	NA	4

Section III — Physical/Chemical Characteristics

Boiling Point	212°F.	Specific Gravity (H ₂ O = 1)	1.1
Vapor Pressure (mm Hg.)	NA	Melting Point	<32°F.
Vapor Density (AIR = 1)	less than 1	Evaporation Rate (Butyl Acetate = 1)	less than
Solubility in Water	Dilutable		
Appearance and Odor	Light blue appearance with faint odor.		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
Not applicable (N/A)	N/A	N/A	N/A
Extinguishing Media	N/A		
Special Fire Fighting Procedures	wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.		
Unusual Fire and Explosion Hazards	Material can spatter above 212°F. Film can burn.		

Stability		Unstable	Conditions to Avoid
		Stable	Onset of decomposition is 350°F.
		X	
Incompatibility (Materials to Avoid) N/A			
Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen.			
Hazardous Polymerization		May Occur	Conditions to Avoid
		Will Not Occur	N/A
		X	
Section VI — Health Hazard Data			
Route(s) of Entry:		Inhalation?	Skin? Ingestion?
N/A			
Health Hazards (Acute and Chronic) N/A			
Carcinogenicity: N/A NTP? IARC Monographs? OSHA Regulated?			
Signs and Symptoms of Exposure N/A			
Medical Conditions Generally Aggravated by Exposure N/A			
Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water.			
Section VII — Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material Is Released or Spilled			
Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.			
Waste Disposal Method			
Incinerate at a permitted facility according to current local, state and federal regulations.			
Precautions to Be Taken in Handling and Storage			
Keep from freezing - product may coagulate.			
Other Precautions N/A			
Section VIII — Control Measures			
Respiratory Protection (Specify Type)			
None required with adequate ventilation & normal operating conditions.			
Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other
Protective Gloves		Eye Protection	
Impermeous		Safety glasses	
Other Protective Clothing or Equipment N/A			
Work/Hygiene Practices			
Use protective cream where excessive skin contact is likely.			



Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) **SPEEDBALL Diazo Sensitizer (Part of #4558 Kit) 4559 + 4578**

Section I

Manufacturer's Name P. O. Box 5157 Statesville, NC 28687 ©1997 Speedball Art Products Company	Emergency Telephone Number 704-838-1475
	Telephone Number for Information 704-838-1475
	Date Prepared 6/29/02
	Signature of Preparer (optional) <i>[Signature]</i>

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Polymethylene-p-Diazo Benzene Dye (CAS #71550-45-3)	N/A	N/A	N/A	
Phosphoric Acid (CAS #7664-38-2)	1mg/m3	1mg/m3	N/A	15

(Will irritate skin & eyes and may produce allergic reaction by skin contact.)

Section III — Physical/Chemical Characteristics

Boiling Point	200°	Specific Gravity (H ₂ O = 1)	1.4
Vapor Pressure (mm Hg.)	Unknown	Decomposition	
Vapor Density (AIR = 1)	Unknown	Melting Point	[32°F.
Solubility in Water	Infinite	Evaporation Rate (Butyl Acetate = 1)	Unknown

Appearance and Odor
 Brown paste with no odor.

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) None	Flammable Limits N/A	LEL N/A	UEL N/A
--------------------------------	----------------------	---------	---------

Extinguishing Media
 Not applicable

Special Fire Fighting Procedures
 If material is within a fire area, CO2, water or dry powder can be used.

Unusual Fire and Explosion Hazards
 Material slowly darkens with heat and may liberate acidic fumes and nitrogen gas.

Wash with water.

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-C072



IDENTITY (As Used on Label and List)

SPEEDBALL Screen Drawing Fluid (4531 & 4571)

Section I

Manufacturer's Name

SPEEDBALL ART PRODUCTS
 2226 SPEEDBALL ROAD
 STATESVILLE, NC 28677

Emergency Telephone Number

704-838-1475

Telephone Number for Information

704-838-1475

Date Prepared

6/29/02

Signature of Preparer (optional)

[Handwritten Signature]

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
---	----------	-----------	--------------------------	--------------

Approved for the AP Seal (Non-Toxic) as per the Art & Creative Materials Institute, Inc. (ACMI). Product labeling conforms to ASTM D4236.

Note: This product has been evaluated by the Toxicologist only as per intended usage. Do not deviate from intended usage!

V.O.C.: 0

Section III — Physical/Chemical Characteristics

Boiling Point	212°F.	Specific Gravity (H ₂ O = 1)	1.19
Vapor Pressure (mm Hg.)	Unknown	Melting Point	<32°F.
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1

Solubility in Water
 Dilutable

Appearance and Odor
 Translucent Blue Color with a slight odor

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
Not applicable (N/A)	N/A	N/A	N/A

Extinguishing Media
 N/A

Special Fire Fighting Procedures
 wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards
 Material can spatter above 212°F. Film can burn.

Stability	Unstable		Conditions to Avoid Onset of decomposition is 350°F.
	Stable	X	

Incompatibility (Materials to Avoid) N/A

Hazardous Decomposition or Byproducts
Oxides of carbon and nitrogen.

Hazardous Polymerization	May Occur		Conditions to Avoid N/A
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry: N/A Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: N/A NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled
Floor may be slippery; use care to avoid falling. No special handling required under normal use conditions. For large quantities (quart or more), transfer to containers for recovery or disposal and keep out of municipal sewers & open bodies of water.

Waste Disposal Method
No special handling required under normal use conditions. Incinerate large quantities (quart or more) at a permitted facility according to local, state & Fed. regulation.

Precautions to Be Taken in Handling and Storing
Keep from freezing - product may coagulate.

Other Precautions N/A

Section VIII — Control Measures

Respiratory Protection (Specify Type)
None required with adequate ventilation & normal operating conditions.

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

Protective Gloves Impervious Eye Protection Safety glasses

Other Protective Clothing or Equipment N/A

Work Hygienic Practices
Use protective cream where excessive skin contact is likely.

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)
SPEEDBALL Screen Filler (4530 & 4570)

Section I

Manufacturer's Name

SPEEDBALL ART PRODUCTS
2226 SPEEDBALL ROAD
STATESVILLE, NC 28677

Emergency Telephone Number

704-838-1475

Telephone Number for Information

704-838-1475

Date Prepared

6/29/02

Signature of Preparer (optional)

[Handwritten Signature]

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
---	----------	-----------	--------------------------	--------------

Approved for the AP Seal. (Non-toxic) by the Art & Creative Materials Institute, Inc. (ACMI)

Product labeling conforms to ASTM 4236.

Note: This product has been evaluated by a Toxicologist only as per intended usage.

Do not deviate from intended usage!

VOC: 0.20 lbs. per gal.

24 grams per liter

Section III — Physical/Chemical Characteristics

Boiling Point	212°F.	Specific Gravity (H ₂ O = 1)	1.2
Vapor Pressure (mm Hg.)	Unknown	Melting Point	<32°F.
Vapor Density (AIR = 1)	less than 1	Evaporation Rate (Butyl Acetate = 1)	less than 1

Solubility in Water

Dilutable

Appearance and Odor

Red Oxide Color with slight odor

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
Not applicable (N/A)	N/A	N/A	N/A

Extinguishing Media

N/A

Special Fire Fighting Procedures

wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards

Material can spatter above 212°F. Film can burn.

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid Onset of decomposition is 350°F.
	Stable	X	

Incompatibility (Materials to Avoid) N/A

Hazardous Decomposition or Byproducts

Oxides of carbon and nitrogen.

Hazardous Polymerization	May Occur		Conditions to Avoid N/A
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry: N/A Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: N/A NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Floor may be slippery; use care to avoid falling. No special handling required under normal use conditions. For large quantities (quart or more), transfer to containers for recovery or disposal and keep out of municipal sewers and open bodies of water.

Waste Disposal Method

No special handling required under normal use conditions. Incinerate large quantities (quart or more) at a permitted facility according to local, state & Fed regulati

Precautions to Be Taken in Handling and Storing Keep from freezing - product may coagulate.

Other Precautions N/A

Section VIII — Control Measures

Respiratory Protection (Specify Type) None required with adequate ventilation & normal operating conditions.

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

Protective Gloves Impervious Eye Protection Safety glasses

Other Protective Clothing or Equipment N/A

Work/Hygienic Practices Use protective cream where excessive skin contact is likely.