

Rec'd 10-18-05 (For Printing Ink and Related Materials) 47200 - 8050

Date: September 15, 2005

47200-8050

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company
P.O. Box 7027
728 North Yale
Villa Park, IL 60181

EMERGENCY PHONE: 800-535-5053

PRODUCT CLASS: Oil Base Ink
TRADE NAME: Litho Burnt Umber

MANUFACTURERS CODE:
1925

SECTION II - HAZARDOUS INGREDIENTS

.0004 Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range: 200 degrees F
Vapor Density: Heavier than air
Liquid Density:
Appearance: Umber
Type of Odor:
Evaporation Rate: Slower than ether
Percent Volatile Wt: N/A

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

Oil Base Ink Litho Burnt Umber 1925

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.