

750

1-14-03

Best EASEL Oil  
52801-1006

**MATERIAL SAFETY DATA SHEET**  
Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 8/23/96

**SECTION 1**

SUNNYSIDE CORPORATION  
225 CARPENTER AVENUE  
WHEELING, ILLINOIS 60090  
EMERGENCY TELEPHONE (847) 541-5700 (800) 424-9300

FOR INFORMATION: (847) 541-5700  
- SUNNYSIDE CORPORATION  
- CHEM TREC

Product Class: Petroleum Hydrocarbon/Linseed Oil  
Trade Name: ANTI-SPALLING COMPOUND

Manufacturer's Code: 750  
NPCA HMIS: Health: 1  
Flammability: 2  
Reactivity: 0

Product Appearance and Odor: Clear, amber-colored liquid; petroleum odor.

**SECTION 2 - HAZARDOUS INGREDIENTS**

**OCCUPATIONAL EXPOSURE LIMITS**

INGREDIENT	CAS #	PERCENT	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)	VAPOR PRESSURE
Boiled Linseed Oil	66071-03-2		Not Est.	Not Est.	Not Est.	Not Est.	3.28 MM Hg @ 68° F.
Mineral Spirits	64742-88-7		100 PPM (For Stoddard Solvent - CAS #8052-41-3)		100 PPM		2.0 MM Hg @ 20° C.

NOTE: Boiled Linseed Oil is not a hazardous material under Department of Labor definitions. It contains not over 0.05% each of Cobalt and Manganese dryer expressed as metal content.

**SECTION 3 - EMERGENCY AND FIRST AID PROCEDURES**

**Eye Contact:** Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. - Flush skin with water. Follow by washing with mild soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. Discard footwear which cannot be decontaminated.

**Inhalation:** Remove victim to fresh air and if breathing is difficult, oxygen should be provided by qualified personnel. Give artificial respiration if not breathing. Get medical attention.

**Ingestion:** Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

**SECTION 4 - PHYSICAL DATA**

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range: 211° F. (I.B.P.)  
Evaporation Rate: Slower than ether  
Weight Per Gallon: 7.22 lbs. -  
Solubility in Water: Negligible, less than 2.5%

Vapor Density:  
% Volatile By Volume: Heavier than air  
Approx. 50%

V-3586

**SECTION 5 - FIRE AND EXPLOSION DATA**

Flammability Classification:	Combustible Liquid - Class II.
Flash Point:	102°F Tag, Closed Cup
Lower Explosive Limit:	0.9%
Extinguishing Media:	Carbon dioxide, foam, dry chemical, water spray. Do not use direct water stream; it will spread fire.
Unusual Fire and Explosion Hazards:	DANGER: RAGS, STEEL WOOL OR WASTE SOAKED WITH BOILED LINSEED OIL MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER. The time frame and conditions under which materials may spontaneously catch fire are unpredictable. If rags or other application materials (including any materials containing linseed oil mixtures) are to be set aside, even for short periods of time, they should be placed in sealed, water-filled metal containers until final disposal. Do not store with strong oxidizing materials.
Special Fire Fighting Procedures:	Use air-supplied rescue equipment for enclosed areas. Cool exposed containers with water.

**SECTION 6 - HEALTH HAZARD DATA**

THRESHOLD LIMIT VALUE:	See Section 2.
EFFECTS OF OVEREXPOSURE	
Primary Routes of Entry:	Inhalation
Eye Contact:	May cause irritation, discomfort, redness and swelling of the eye.
Skin Contact:	Liquid is slightly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis.
Inhalation:	Vapors may cause irritation to nose, throat and respiratory tract. Breathing of high vapor concentrations may result in headaches, dizziness and other signs of nervous system depression. These effects have been observed after misuse or abuse of this product. When use in a reasonable and foreseeable manner, no adverse effects are anticipated from exposure to this product.
Ingestion:	Ingestion may result in vomiting, aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.
Chronic:	Repeated skin contact may aggravate an existing dermatitis (skin condition).
Carcinogenicity:	Components of this product have not been identified as carcinogens by NTP, IARC, or OSHA.
Medical Conditions Aggravated by Exposure:	Conditions aggravated by exposure may include skin disorders and respiratory (asthma-like) disorders.

**SECTION 7 - REACTIVITY DATA**

Stability:	Stable
Conditions to Avoid:	Heat, sparks and flame.
Incompatibility (Materials to Avoid):	Strong oxidizing agents like liquid chlorine or concentrated oxygen.
Hazardous Decomposition Products:	Thermal decomposition may yield carbon dioxide and carbon monoxide. Aldehydes (including acrolein) may be produced from atmospheric oxidation and/or degradation under severe pressure.
Hazardous Polymerization:	Will not occur.

**SECTION 8 - SPILL OR LEAK PROCEDURES**

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapor or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use sand for small spills. Do not use oil dri or clay which may contribute to spontaneous combustion. Keep spilled material out of sewers, ditches and bodies of water.

Waste disposal method: Incinerate under safe conditions; dispose of in accordance with local, state and federal regulations.

Trade Name: ANTI-SPALLING COMPOUND

Page 3 of 3

**SECTION 9 - SAFE HANDLING AND USE INFORMATION**

Respiratory Protection: Appropriate vapor canister, self-contained breathing apparatus or supplied-air hose mask, if needed.

Ventilation: Sufficient, in volume and pattern, to keep workroom concentration below current applicable OSHA safety and health requirements. See Section 2. Use explosion-proof equipment. No smoking.

Protective Gloves: Rubber or neoprene.

Eye Protection: Chemical safety goggles.

Other Protective Equipment: Impervious clothing or boots, if needed, if needed to prevent prolonged skin contact.

**SECTION 10 - SPECIAL PRECAUTIONS**

Dept. of Labor Storage Category: Combustible Liquid - Class II

Hygienic Practices: Keep away from heat, sparks and open flame. Keep containers closed when not in use. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact.

Additional Precautions: Ground containers when transferring liquid to prevent static accumulation and discharge. Rags and waste paper containing this material may heat and burn spontaneously. Waste materials should therefore be promptly disposed of by discarding in a sealed, water-filled container immediately.

Additional information regarding safe handling of products with static accumulation potential can be ordered by contacting the American Petroleum Institute (API) for API Recommended Practice 2003, entitled "Protection Against Ignitions Arising Out of Static, Lighting, and Stray Currents" (American Petroleum Institute, 1720 L Street Northwest, Washington, DC 20005), or the National Fire Protection Association (NFPA) for NFPA 77 entitled "Static Electricity" (National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101).

Empty Container Warning: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

**SECTION 11 - ADDITIONAL INFORMATION**

This product contains the following toxic chemical(s) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOXIC CHEMICAL	CAS #	APPROXIMATE % BY WEIGHT
NONE	NONE	NONE

SARA Title III Hazard Categories: Immediate (Acute) Health, Delayed (Chronic) Health, Fire.

California Proposition 65: This product contains trace amounts of Benzene, a chemical known to the State of California to cause cancer, and trace amounts of Toluene, a chemical known to the State of California to cause birth defects or other reproductive harm.

**TRANSPORTATION**

U.S. D.O.T. Proper Shipping Name: Combustible Liquid, NOS (Contains Petroleum Distillates)

U.S. D.O.T. Hazard Class & Packing Group: Combustible Liquid, III

U.S. D.O.T. Identification Number: NA 1993

Refer to 40 CFR for possible exceptions and exemptions.