

06/21/2006 09:24 FAX 530 365 6483

YALEY ENTERPRISES

002

61496-1001
-1011

Premium Wax

PARAFFIN WAX

MATERIAL SAFETY DATA SHEET

The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product, or the hazards related to its use.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.

MANUFACTURER

YALEY ENTERPRISES
7664 AVIANCA DR.
REDDING CA 96002
(530) 365-5252

EMERGENCIES

Transportation emergencies: CHEMTREC
Phone: (800) 424-9300 Continental U.S.

Health emergencies: Call LOS ANGELES POISON
INFORMATION CENTER, (800) 356-3129 (24 hrs)

PRODUCT IDENTIFICATION

Product Name: Luxco Fully Refined Paraffin Wax 125,
128, 130, 135, 140, 143, 144, 145, 150, 150T, 160,
2005, 2015, 3005, 3015, 6530-A/B, 9005, 9015, 9025
Generic Name: Paraffin wax
Chemical Family: Petroleum hydrocarbon
DOT Proper Shipping Name: Not applicable
DOT Hazard Classification: Not applicable
CAS Number: 64742-43-4

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: > 600 °F
Melting Point: 125-170 °F
Density @ 25 °C: 0.90 g/ml
Vapor Pressure (mm Hg): negligible
Vapor Density (air=1): negligible
Viscosity @ 100 °C (cSt): 3.5-8.0
Appearance: off-white to white solid
Odor: none

HAZARDOUS INGREDIENTS

Component	Percent	Exposure Limit	Agency	Type
None			ACGIH OSHA	TWA TWA

The identities of ingredients that are trade secrets are excluded from this list. Exposure limit is for fumes.

FIRST AID PROCEDURES**EYE CONTACT:**

If irritation or redness develops from exposure to fumes generated during hot melt processing operations, move victim away from exposure and into fresh air. Flush eyes with clean water. If irritation or redness persists, seek medical attention. For contact with molten material, gently open eyelids and flush affected eye(s) with cold water. Seek immediate medical attention.

SKIN CONTACT:

Cool solid material is not expected to cause skin irritation. Thermal burns may result from contact with hot material. If hot melted material gets on the skin, quickly cool in water. See a doctor for extensive burns. Do not try to peel the solidified material from the skin or use solvents or thinners to dissolve it. The use of vegetable oil or mineral oil is recommended for removal of this material from the skin.

INHALATION (BREATHING):

If respiratory symptoms develop from exposure to fumes emitted by the molten material, move victim away from source of exposure and into fresh air. Inhalation may produce nausea and irritation of the upper respiratory tract. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

INGESTION (SWALLOWED):

No first aid is normally required; however, if swallowed, and symptoms develop, seek medical attention.

08/21/2006 09:25 FAX 530 365 6483

YALEY ENTERPRISES

003

Premium wax

BRAND NAME: Fully Refined Paraffin Wax 140
GENERIC NAME: Paraffin wax
CHEMICAL FAMILY: Petroleum hydrocarbon
CAS NUMBER: 64742-43-4
FDA COMPLIANCE: Yes, 21CFR172.886, 21CFR178.3710
NSF CERTIFICATION:
DESCRIPTION: White translucent solid

TYPICAL PROPERTIES: The following properties are typical of normal production but are not intended for the preparation of specifications.

PROPERTY	TEST METHOD	SPECIFICATION		TYPICAL VALUE
		MIN	MAX	
Melting Point, °F	ASTM D87	136	140	138
Oil Content, %	ASTM D721		0.5	0.3
Saybolt Color	ASTM D156	+25		+28
Needle Penetration: @ 77 °F	ASTM D1321			14
@ 100 °F				
Kinematic Viscosity, cSt @ 212 °F	ASTM D445	3.9	4.3	4.1
Odor				Nil

PACKAGING

Bulk Liquid: 40,000 lbs minimum

Slabs:

11-lb slabs, 5 slabs/carton on pallets (2200 lbs per pallet), or 2200-lb Gaylord box.

APPLICATIONS

Paper packaging, candles, chlorinated waxes, cosmetics, rubber antioxidants, lumber end seal, adhesives, protective coatings, electrical insulation, sculpture wax, modeling clay, food additives, cheese dipping, crayons, moisture barriers, polishes, sealants, lipsticks, drinking cups.

The information herein is believed to be reliable. However, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to merchantability of the material or its fitness for any purpose. The manufacturer shall not be liable for consequential damages or for damage to persons or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent.

06/21/2006 09:25 FAX 530 365 6483

YALEY ENTERPRISES

004

PRIMARY ROUTE(S) OF EXPOSURE**EYE CONTACT:**

Prolonged or repeated exposure to fumes or vapors emitted by the molten material may cause tearing. Contact with the molten material may cause thermal burns.

SKIN CONTACT:

This material may cause mild skin irritation. Prolonged or repeated contact may cause redness and burning. Contact with the molten material may cause thermal burns. No harmful effects are expected from skin absorption of this material.

INHALATION (BREATHING):

Inhalation of the solid material is unlikely. However, fumes from the molten material may cause irritation of the nose and throat.

INGESTION (SWALLOWING):

While this material has a low degree of toxicity, ingestion of excessive quantities may cause diarrhea.

NOTE: This material has not been identified as a carcinogen by NTP, IARC, or OSHA.

PROTECTIVE INFORMATION:**VENTILATION:**

If current ventilation practices are not adequate to minimize exposure, additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used.

RESPIRATORY PROTECTION:

No respiratory protection is required when working with the solid material. Protection from fumes emitted from molten material may be necessary. If airborne concentrations exceed recommended exposure limits (see Hazardous Ingredients section), a suitable filter-type respirator should be worn.

PROTECTIVE GLOVES:

The use of gloves impermeable to the specific material handled is advised to prevent skin contact and possible irritation. The use of heat resistant gloves is recommended.

EYE PROTECTION:

Approved eye protection to safeguard against potential eye contact, irritation or injury during hot melt processing operations is recommended.

OTHER PROTECTIVE EQUIPMENT:

It is suggested that a source of clean water be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

REACTIVITY DATA

STABILITY: Stable under normal conditions of storage and handling.

CONDITIONS TO AVOID: Avoid contact with any source of heat.

MATERIAL INCOMPATIBILITY: Avoid contact with strong oxidizing agents.

DECOMPOSITION PRODUCTS: Thermal decomposition in the presence of air may yield major amounts of oxides of carbon and minor amounts of oxides of sulfur and nitrogen. Paraffin wax fumes have an assigned ACGIH TLV of 2 mg/m³.

POLYMERIZATION: Will not occur.

FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS: N/D

LEL AND UEL: Not determined

FLASH POINT: ≥ 455 °F (COC)

UNUSUAL HAZARDS: Auto ignition may occur above 340 °C.

STORAGE AND HANDLING**STORAGE:**

Store in a cool, dry location. Keep away from incompatible materials (see Reactivity section). Contact with any source of heat may cause melting.

SPILLS AND LEAKS:

Sweep up and package appropriately for disposal. For molten material, absorb with sand or inert absorbent material. Notify appropriate federal, state and local agencies. If spill of any amount is made into or upon U.S. navigable waters, the contiguous zone, or adjoining shorelines, notify the National Response Center, phone number (800) 424-8802.

WASTE DISPOSAL METHOD:

Dispose of product in accordance with local, county, state,

FIRE FIGHTING PROCEDURES**EXTINGUISHING MEDIA:**

Extinguish with dry chemical, CO₂, water spray, foam, sand or earth. Water and foam may cause frothing.

FIRE FIGHTING PROCEDURES:

Water spray may be useful in minimizing vapors and cooling containers exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes. Move undamaged containers from fire area if it can be done without risk. Wear self-contained breathing apparatus.

NOTE: This material may burn, but will not ignite easily.

06/21/2006 09:25 FAX 530 365 6493

YALEY ENTERPRISES

☑ 005

MOLD SEALER

Page 1 of 3

YALEY ENTERPRISES
 7664 AVIANCA DR.
 REDDING CA 96002
 ☎ (530) 365-5252

Date April 5, 1991

Product Identification:

Material No: RV4111-1, *AND OTHERS*Material Names: Elastic Sealing Tape RC40 Bulk, *RC22, RC17, P14, P14BR, P18, P24*

Material Descriptions: Mixture of rubber, resin and inert fillers.

Warning Statements:

Non-Hazardous Material

Precautionary Measures:

Normal chemical hygiene should be adequate, to handle this material. Wash thoroughly after exposure, avoid contact with eyes, do not ingest.

HAZARDOUS INGREDIENTS: None

Material Name/CAS #	☒	OSHA PEL	ACGIH TLV
---------------------	---	----------	-----------

This MSDS is prepared to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200). Unlisted ingredients are not 'hazardous' per this OSHA standard and are considered to be trade secrets.

EMERGENCY AND FIRST AID PROCEDURES:

FIRST AID:

Ingestions: Not expected to be toxic. Contact physician if large quantity is ingested.

Skins: Wash with soap and water.

Eyes: Remove contaminant, flush eyes with water. See physician if irritation persists.

OTHER EMERGENCY:

In case of fire: Extinguish with water or other extinguisher suitable for class "A" fires.

Spill or leaks: Material poses no special threat if spilled or leaked.

06/21/2006 09:25 FAX 530 365 6493

YALEY ENTERPRISES

006

MSDS for RU 6111-1

Page 2 of 3

OCCUPATIONAL CONTROL PROCEDURES:

Eye Protection: Not normally required.
Skin Protection: Not normally required.
Respiratory Protection: Not normally required.
Ventilation: Not normally required.

FIRE PROTECTION:

Flash Point / Method: 375°F/CDC

Appropriate Extinguishers: Water, treat as Class "A" fire.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus when fighting fires.

Unusual Fire and Explosion Hazard: None known.

REACTIVITY DATA:

Stability: Stable

Incompatibility: Not established

Hazardous Decomposition Products: Carbon Monoxide and other unidentified organic compounds when burning.

EFFECT OF OVEREXPOSURE:

Eyes: Reversible irritation

Skin: No known effects

Inhalation: Not applicable

Chronic: No known effects

Existing Health Conditions Affected by Exposure: No known conditions are aggravated by exposure to this product.

PHYSICAL DATA:

Physical State: Solid
Specific Gravity: 1.53 @ 77°F
Viscosity: Not applicable
pH: Not applicable

06/21/2006 09:25 FAX 530 365 6483

YALEY ENTERPRISES

P.4

007

Page 3 of 3

MSDS For RV 6 4111-1

SPILL, LEAK & DISPOSAL INFORMATION:

Spill or leak procedures: Sweep or scrape up and place in appropriate container for disposal.

Waste Disposal: Observe all Federal, State and Local regulations when disposing of the material. For assistance contact the District Director of the Environmental Protection Agency. local hazardous waste regulations may apply if they are different from the federal regulation. Dispose of in an approved industrial landfill.

Storage: No special requirements for storage.

06/21/2006 09:25 FAX 530 365 6483

YALEY ENTERPRISES

☑ 008

MATERIAL SAFETY DATA SHEET

MSDS Name: T1-RD6615 RED

Revision Date: 01/31/05
Page Number: 1 of 6**SECTION I - PRODUCT AND COMPANY INFORMATION**Product Name: T1-RD6615 RED
CAS Number: MIXTURE
HMIS Rating: Health: 1 Fire: 1 Reactivity: 0Company Identification: **YALEY ENTERPRISES, INC.**
7664 Avianca Drive
Redding, CA 96002

Chemtrec (24 hr. Emergency) (800) 424-9300

Product Class: SYNTHETIC ORGANIC COLORANT
Trade Name: RED
Product Code: T1-RD6615**SECTION II - INGREDIENT AND HAZARD INFORMATION**

Ingredient Name	CAS Number	Percent
(No hazardous ingredients known at this time.)		

SECTION III - HAZARDS IDENTIFICATION**EYE CONTACT**
May cause irritation.**SKIN CONTACT**
May cause irritation.**INHALATION HAZARDS**
Treat as a nuisance dust. Avoid breathing.**INGESTION HAZARDS**
Small amounts swallowed are not likely to cause injury. Not a hazard in normal industrial use.**TARGET ORGANS**
No organs affected.**CANCER HAZARDS**
No hazards associated with this product.**SECTION IV - FIRST AID MEASURES**

06/21/2006 09:25 FAX 530 365 6483

YALEY ENTERPRISES

☑ 009

MATERIAL SAFETY DATA SHEET

MSDS Name: T1-RD6615 RED

Revision Date: 01/31/05

Page Number: 2 of 6

EYE CONTACT

Immediately flush with water for at least 15 minutes while holding eyelids open. Call a physician.

SKIN CONTACT

Practice good industrial hygiene. Wash with soap and water.

INHALATION

Remove to fresh air. Treat symptoms. Call a physician.

INGESTION

Do not induce vomiting. Give water. Call a physician.

SECTION V - FIRE-FIGHTING MEASURES

Flammability Class	NA
Flash Point:	None
Explosive Range:	None
	None

FLAMMABLE PROPERTIES

During a fire, irritating and toxic gases may be formed. Do not breathe smoke or fumes. Wear suitable protective equipment.

EXTINGUISHING MEDIA

Use dry chemical, alcohol foam, carbon dioxide or water spray when fighting fires involving this material.

FIRE FIGHTING INSTRUCTIONS

Keep unnecessary people away. Isolate area. Stay upwind. Wear self-contained breathing apparatus.

SECTION VI - ACCIDENTAL RELEASE MEASURES**CONTAINMENT**

This material is hydrophobic and should be prevented from entering the sewer system.

CLEAN-UP

Place in an appropriate recovery or salvage drum for disposal.

CERCLA/SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (TITLE III)

This is not a regulated material under 40 CFR 117, 302. Notification of spills is not required.

EVACUATION

06/21/2006 09:26 FAX 530 365 6483

YALEY ENTERPRISES

☐ 010

MATERIAL SAFETY DATA SHEET

MSDS Name: T1-RD6615 RED

Revision Date: 01/31/05
Page Number: 3 of 6

Not normally necessary. Refer to your organization's Release Response Procedures.

SECTION VII - HANDLING AND STORAGE**HANDLING**

Use in a well ventilated area. Improper handling may lead to dust cloud formation which, as with any organic dust, may be an explosion hazard.

STORAGE

Store in a dry area.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION**Occupational Exposure Limits**

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

Although no exposure limit has been established for this product, the OSHA PEL for nuisance dust of 15 mg/m³ total dust and 5 mg/m³ respirable dust is recommended. In addition, the ACGIH TLV for nuisance dust is 10 mg/m³.

ENGINEERING CONTROLS

General ventilation is recommended. Additional local exhaust ventilation is recommended where dusts, mists, or vapors may be released.

RESPIRATORY PROTECTION

A NIOSH approved dust mask is recommended.

PERSONAL PROTECTIVE EQUIPMENT

Where contact is likely, chemical resistant gloves and safety glasses or goggles are recommended.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form:	Powder
Appearance/Color:	Red
Odor:	Odorless
Solubility (in water):	Insoluble
Boiling Range:	None
Evaporation Rate:	Non Volatile
Vapor Density:	Non Volatile
% Volatile Weight	0.%

06/21/2006 09:26 FAX 530 365 6483

YALEY ENTERPRISES

☑ 011

MATERIAL SAFETY DATA SHEET

MSDS Name: T1-RD6615 RED

Revision Date: 01/31/05
Page Number: 4 of 6-----
% Volatile Volume: 0. %
Weight/Gallon: N/A
VOC None**SECTION X - STABILITY AND REACTIVITY**Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur**CONDITIONS TO AVOID**

Heat, sparks, and open flame.

INCOMPATIBILITIES

Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS

In the event of combustion, oxides of carbon and nitrogen will be formed.

SECTION XI - TOXICOLOGICAL INFORMATION

No toxicological studies have been conducted on this product.

SECTION XII - ECOLOGICAL INFORMATION

No studies have been conducted on this product.

SECTION XIII - DISPOSAL

Dispose of in accordance with local, state, and federal regulations.

SECTION XIV - TRANSPORT INFORMATIONUN Number NOT REGULATED
Packaging Group
Hazard Class
Shipping Name**SECTION XV - REGULATORY INFORMATION**

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
-----------------	------------	---------

06/21/2006 09:26 FAX 530 365 6483

YALEY ENTERPRISES

☐ 012

MATERIAL SAFETY DATA SHEET

MSDS Name: T1-RD6615 RED

Revision Date: 01/31/05
Page Number: 5 of 6-----
C.I. BASIC VIOLET 11:1, TETRACHLOROZINC- 73398-89-7 0.5 - 1.5
ATE (ZINC COMPOUND)OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200
This product is not considered hazardous as defined.SARA SECTIONS 311 AND 312
Reporting of this product is not required.TOXIC SUBSTANCES CONTROL ACT (TSCA)
All components in this product are listed, or are excluded from
listing on the U.S. Toxic Substances Control Act (TSCA) 8(b)
Inventory.CLEAN WATER ACT
This product contains no ingredients regulated by the Clean Water Act.CLEAN AIR ACT
This product contains no ingredients regulated by the Clean Air Act.HAZARDOUS AIR POLLUTANTS (HAPS)
This product contains no Hazardous Air Pollutants (HAP's)..CLEAN AIR ACT AMMENDMENTS (ODS)
No DAY-GLO product contains an ozone depleting substance (ODS), nor
are any of our products manufactured with them.COALITION OF NORTHEAST GOVERNORS (CONEG)
This product is in compliance with CONEG (i.e., total cadmium,
chromium, lead and mercury < 100 ppm).FDA 21 CFR
DAY-GLO Color Corp. products are not listed by the FDA for use under
21 CFR since potential applications are so numerous that specific
applications must be submitted to the FDA for inclusion in the 21 CFR
FDA listing.**SECTION XVI - OTHER INFORMATION****LABEL INFORMATION**

T1-RD6615 RED

HEALTH - 1 FLAMMABILITY - 1 REACTIVITY - 0

PRECAUTIONS: Can cause respiratory irritation. Avoid breath-
ing dust. Use & store with adequate ventilation. Dust ex-

06/21/2006 09:26 FAX 530 365 6483

YALEY ENTERPRISES

☑ 013

MATERIAL SAFETY DATA SHEET

MSDS Name: T1-RD6615 RED

Revision Date: 01/31/05

Page Number: 6 of 6

plosion hazard with ignition source.

FIRST AID: EYES: Flush with water for 15 minutes. SKIN: Wash with soap and water. INGESTION: Give water, do not induce vomiting. Call a physician.

FIRE FIGHTING USE: Water spray, dry chemical, foam or CO2 (Toxic fumes emitted on burning).

SPILL CONTROL: Sweep up & dispose according to local, state and federal regulations.

CONTAINS:

CAS NO. OR NJ TSRN:

RESIN

PROPRIETARY

C.I. BASIC VIOLET 11:1, TETRA-
CHLOROZINCATE

73398-89-7

TARGET ORGANS: NO ORGANS AFFECTED.

MATERIAL V.O.C.: NONE

NOTE - Additional information is available from your employer and the Material Safety Data Sheet.

DISCLAIMER

The information contained herein is believed to be accurate, but is not warranted. Nothing contained herein constitutes a specification, nor is it intended to warrant suitability for the intended use.

06/21/2006 09:26 FAX 530 365 6483

YALEY ENTERPRISES

☑ 015

<<<<<<<<<< MATERIAL SAFETY DATA SHEET >>>>>>>>>>

EFFECTIVE DATE SUPERSEDES03-22-01 08-15-00

SECTION 1 CHEMICAL IDENTIFICATION

C.I. NAME : SOLVENT BLUE 36
C.I. NUMBER : 61551
CAS NUMBER : 14233-37-5
CHEMICAL FAMILY : ANTHRAQUINONE DYE
PHYSICAL FORM : POWDER

SECTION 2 INGREDIENTS HAZARDOUS UNDER OSHA 29 CFR PART 1910.1200 APPENDIX A & B

COMPONENT NAME	CAS NUMBER	PEL	TLV	‡
SOLVENT BLUE 36*/**	14233-37-5	NE	NE	>1

*READ & UNDERSTAND SECTIONS 3, 8 & 11 FOR HEALTH & SAFETY INFORMATION. WEAR ALL PROTECTIVE EQUIPMENT AND CLOTHING DESCRIBED IN SECTION 8.

**SOLVENT BLUE 36/9,10-ANTHRACENEDIONE 1,4-BIS (METHYLETHYL)AMINO

SECTION 3 HAZARD IDENTIFICATION AND EMERGENCY OVERVIEW

HMIS RATINGS

HEALTH * 1
FLAMMABILITY 1
REACTIVITY 1
PROTECTION F, N

* DENOTES DELAYED/CHRONIC HEALTH HAZARD

EMERGENCY OVERVIEW:

POSSIBLE EXPOSURES: EYES, SKIN, BREATHING DUSTS, ACCIDENTAL SWALLOWING

POSSIBLE HEALTH EFFECTS:

EYE CONTACT: CAN IRRITATE.* 1
SKIN CONTACT: CAN IRRITATE FOLLOWING PROLONGED OR REPEATED CONTACT.* 1
BREATHING DUST: CAN IRRITATE THE LININGS OF THE NOSE, THROAT AND LUNGS.* 1
SWALLOWING: CAN IRRITATE STOMACH AND INTESTINES.* 1

* EXPECTATIONS BASED ON PRODUCT COMPONENTS. SEE SECTION 11.

EUROPEAN UNION RISK PHRASES: R36/37/38-IRRITATING TO EYES, RESPIRATORY SYSTEM & SKIN.

SENSITIZATION: NK

TARGET ORGANS: EYES, LUNGS, SKIN, NOSE, THROAT, STOMACH, INTESTINES 1

CANCER INFORMATION:

PRODUCT AND COMPONENTS NOT KNOWN TO US TO BE CARCINOGENS
NTP: NK
IARC: NK
OSHA: NR

1 PRECAUTIONS:

TO HELP PROTECT AGAINST EXPECTED OR UNEXPECTED IRRITATIONS OR REACTIONS, WEAR ALL PROPERLY SELECTED PROTECTIVE EQUIPMENT AND CLOTHING AS SHOWN IN THE EXPOSURE CONTROLS AND PERSONAL PROTECTION SECTION OF THIS MSDS. WASH HANDS AND FACE AFTER HANDLING AND BEFORE EATING, DRINKING, SMOKING OR USING RESTROOM FACILITIES. AFTER EACH SHIFT, CLEAN ALL PROTECTIVE EQUIPMENT, WASH ALL WORK CLOTHES, AND SHOWER. SEE SECTION 11, TOXICOLOGY INFORMATION.

UNUSUAL HAZARDS: IF MIXED WITH AIR IN SUFFICIENT AMOUNTS & PROPORTIONS, ORGANIC DUSTS CAN FORM FLAMMABLE OR EXPLOSIVE DUST/AIR MIXTURES. AS PRECAUTIONS, KEEP AREAS CLEAN AND AVOID DUST BUILD-UP. HAVE PLENTY OF GOOD VENTILATION. AVOID CREATING VERY DUSTY CONDITIONS. WHEN MIXING, POURING OR PROCESSING BULK AMOUNTS OF POWDERS, GROUND ALL CONTAINERS AND AVOID STATIC CHARGES, SPARKS, SMOKING, OPEN FLAMES, OR OTHER POSSIBLE CAUSES OF FIRE OR EXPLOSION.

SECTION 4 FIRST AID INSTRUCTIONS

Item Numbers: 61496-1001, 61496-1011

06/21/2006 09:27 FAX 530 365 6483

YALEY ENTERPRISES

016

EYE CONTACT: IMMEDIATELY RINSE WITH PLENTY OF CLEAN FLOWING WATER FOR AT LEAST 20 MINUTES, HOLDING EYELIDS OPEN TO RINSE COMPLETELY. CALL A DOCTOR, AND GET EMERGENCY MEDICAL HELP QUICKLY, AS A PRECAUTION.

SKIN CONTACT: REMOVE AFFECTED CLOTHING. WASH AFFECTED SKIN AREA WITH PLENTY OF SOAP AND WATER. RINSE WITH PLENTY OF WATER. WASH ALL WORK CLOTHES BEFORE WEARING AGAIN. IF ANY REDNESS, SWELLING, ITCHING, OR PAIN OF THE SKIN STARTS, SEE A DOCTOR QUICKLY.

BREATHING PRODUCT DUST: MOVE PERSON TO FRESH AIR. IF PERSON IS HAVING DIFFICULTY BREATHING, GIVE OXYGEN. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. GET EMERGENCY MEDICAL HELP QUICKLY. CALL 911 IF AVAILABLE IN YOUR AREA, OR OTHER MEDICAL EMERGENCY NUMBER.

SWALLOWING OF PRODUCT: IF SWALLOWED, CALL A POISON CONTROL CENTER, EMERGENCY ROOM, OR PHYSICIAN. UNLESS ADVISED OTHERWISE, INDUCE VOMITING BY GIVING EITHER SYRUP OF IPECAC FOLLOWED BY 2 GLASSES OF WATER OR BY STICKING FINGER DOWN THROAT. IF THE PERSON IS DROWSY OR UNCONSCIOUS, DO NOT GIVE ANYTHING BY MOUTH OR LEAVE ALONE. NEVER GIVE ANYTHING TO DRINK TO A PERSON WHO IS CONVULSING OR HAS NO GAG REFLEX. LOOSEN TIGHT FITTING CLOTHING, CLEAR THE AIRWAY, AND KEEP THE PERSON WARM.

NOTE TO PHYSICIAN: TREATMENT SHOULD BE DIRECTED AT PREVENTING ABSORPTION, ADMINISTERING TO THE SYMPTOMS AS THEY OCCUR, AND PROVIDING SUPPORTIVE THERAPY.

SECTION 5 FIRE FIGHTING INSTRUCTIONS

FLASH POINT : NA

EXTINGUISHING MEDIA:

SMALL FIRES: DRY CHEMICAL, CO₂, HALON, WATER SPRAY, OR FOAM

LARGE FIRES: WATER SPRAY, FOG, OR ALCOHOL FOAM

FIREFIGHTING DIRECTIONS: WEAR SELF-CONTAINED BREATHING APPARATUS TO PROTECT AGAINST POSSIBLY TOXIC FUMES. WEAR FULL FIRE-PROTECTIVE CLOTHING.

SECTION 6 ACCIDENTAL SPILL OR RELEASES

WEAR A NIOSH APPROVED DUST RESPIRATOR, WITH ALL PROTECTIVE CLOTHING AND EQUIPMENT AS DIRECTED IN SECTION 6.

CONTAIN AND CLEAN UP SPILL IMMEDIATELY. SWEEP POWDERS CAREFULLY, USING AN ABSORBENT (SWEEPING COMPOUND) TO KEEP DOWN THE DUST IN THE AREA. SCOOP MATERIAL & ABSORBENT INTO DISPOSAL DRUM, AND SEAL.

RCRA STATUS: SEE REGULATORY INFORMATION, SECTION 15.

ENVIRONMENTAL PROTECTION: PREVENT FROM ENTERING FLOOR DRAINS OR SEWERS. DO NOT RELEASE TO SEWER WITHOUT PROPER GOVERNMENT PERMISSION AT ALL LEVELS.

SEE SECTION 13, DISPOSAL CONSIDERATIONS/ENVIRONMENTAL PROTECTION PROCEDURES FOR ANY ADDITIONAL INFORMATION.

SECTION 7 HANDLING AND STORAGE

PROTECT PRODUCT FROM MOISTURE, STORE IN COOL, DRY PLACE UNDER LOW RELATIVE HUMIDITY, AWAY FROM EXCESSIVE HEAT. STORE IN ORIGINAL OR EQUIVALENT WATER-PROOF CONTAINERS. RESEAL CONTAINERS TIGHTLY AFTER EACH USE. KEEP OUT OF DIRECT SUNLIGHT.

SHELF LIFE: INDEFINITE WHEN STORED CAREFULLY AS INSTRUCTED ABOVE.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

NOTE: WHEN SELECTING PERSONAL PROTECTIVE EQUIPMENT AND CLOTHING, FOLLOW ALL MANUFACTURER SPECIFICATIONS AND RECOMMENDATIONS THAT APPLY TO YOUR SPECIFIC OPERATIONS AND PROCESSING CONDITIONS. TAKE INTO CONSIDERATION ALL CONDITIONS AND ALL CHEMICALS TO BE HANDLED OR PROCESSED

EYE PROTECTION: WEAR SPLASH-PROOF CHEMICAL SAFETY GOGGLES. CONTACT LENSES SHOULD NOT BE WORN WHEN WORKING WITH CHEMICALS.

SKIN PROTECTION: WEAR CHEMICALLY RESISTANT RUBBER GLOVES, SELECTED WITH YOUR SPECIFIC PROCESSING CONDITIONS AND CHEMICALS TO BE HANDLED IN MIND. WEAR COVERALLS AND BOOTS TO MINIMIZE SKIN CONTACT. AS PRECAUTIONS, WASH HANDS & FACE WITH MILD SOAP & WATER BEFORE EATING, DRINKING, SMOKING, OR USING RESTROOM. AFTER EACH SHIFT, CLEAN ALL PROTECTIVE EQUIPMENT, WASH WORK CLOTHES, AND SHOWER.

06/21/2006 09:27 FAX 530 365 6493

YALEY ENTERPRISES

☑ 017

LUNG, THROAT & NASAL PROTECTION: WEAR NIOSH APPROVED DUST RESPIRATOR FOR YOUR PARTICULAR OPERATION AND MATERIALS BEING HANDLED.

OTHER PROTECTION: EYE WASH FOUNTAINS & DRENCH SHOWERS SHOULD BE LOCATED WITHIN 100 FEET OR A 10 SECOND WALK OF THE WORK AREA PER ANSI Z358.1-1990

VENTILATION: LOCAL EXHAUST IS RECOMMENDED.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

DESCRIPTION : DARK BLUE POWDER; NO ODOR
MELTING POINT : NE
WATER SOLUBILITY : INSOLUBLE
PH : NE
BULK DENSITY : 0.203 g/cc
% TOTAL VOC'S : 0
% NON-VOLATILES : 100
% WATER : 0

SECTION 10 STABILITY AND REACTIVITY

STABILITY : STABLE
CONDITIONS TO AVOID : NK
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
INCOMPATIBLE MATERIALS : OXIDIZING AGENTS AND REDUCING AGENTS
HAZARDOUS DECOMPOSITION PRODUCTS: IF HEATED TO HIGH TEMPERATURES, THIS PRODUCT MAY EMIT OXIDES OF NITROGEN, SMOKE, SOOT, AND TOXIC FUMES (E.G. CARBON DIOXIDE AND CARBON MONOXIDE)

SECTION 11 TOXICOLOGY INFORMATION

FOR C.I. SOLVENT BLUE 36:
ORAL LD50 (RAT): > 5000 MG/KG
DERMAL LD50 (RABBIT): > 2000 MG/KG
INHALATION LC50 (RAT): NE

EYE EFFECTS (RABBIT): NE. TAKE PRECAUTIONS. 1
SKIN EFFECTS (RABBIT): NE. TAKE PRECAUTIONS. 1
BREATHING EFFECTS: NE. TAKE PRECAUTIONS. 1

1) AS A PRECAUTION IT IS RECOMMENDED THAT ALL PROTECTIVE EQUIPMENT AND CLOTHING SHOWN IN SECTION 8 OF THIS MSDS BE WORN. READ SECTION 8.

GENERAL PRECAUTIONS: ALWAYS PRACTICE GOOD INDUSTRIAL HYGIENE, HANDLE WITH CARE, AVOID PERSONAL CONTACT. DO NOT GET INTO EYES OR ON SKIN, DO NOT BREATHE DUST OF PRODUCT, DO NOT SWALLOW. WASH HANDS WITH SOAP AND WATER, AND RINSE WELL AFTER HANDLING PRODUCT. SHOWER AFTER EACH SHIFT. WASH ALL WORK CLOTHING AND COMPLETELY CLEAN ALL PROTECTIVE EQUIPMENT AFTER EACH SHIFT. SEE SECTION 2.

MUTAGENICITY: NK

ADDITIONAL INFORMATION: SEE SECTION 3, HAZARD IDENTIFICATION AND EMERGENCY OVERVIEW.

MEDICAL CONDITIONS WORSENER BY EXPOSURE: PERSONS WITH BREATHING AND LUNG PROBLEMS CAN BE AFFECTED BY BREATHING IN ANY TYPE OF DUSTY MATERIAL. PERSONS WITH ASTHMA, ALLERGIES, OR OTHER BREATHING-RELATED PROBLEMS SHOULD STAY AWAY FROM, NOT HANDLE, AND NOT BE EXPOSED TO ANY DUSTY PRODUCTS OR DUSTY CONDITIONS AS A PRECAUTIONARY MEASURE.

SECTION 12 ECOLOGICAL DATA

BOD 5: NE
COD: NE
FISH TOXICITY: NE
SEED TOXICITY: NE
CWA TOXIC POLLUTANTS: NK
BIOLOGICAL ELIMINATION: NE

SECTION 13 DISPOSAL CONSIDERATIONS/ENVIRONMENTAL PROTECTION PROCEDURES

DISPOSAL METHODS:

IT IS RECOMMENDED THAT YOU SELECT AN ALTERNATIVE BELOW ACCORDING TO THE FOLLOWING ORDER OF PREFERENCE, DEPENDING ON ENVIRONMENTAL IMPACT:

Item Numbers: 61496-1001, 61496-1011

06/21/2006 09:27 FAX 530 365 6483

YALEY ENTERPRISES

018

- 1) RECYCLE OR REWORK MATERIAL IF AT ALL POSSIBLE
- 2) INCINERATE MATERIAL AT AN APPROVED FACILITY
- 3) TREAT AT AN ACCEPTABLE WASTE TREATMENT FACILITY, OR MUNICIPAL WASTE TREATMENT PLANT AFTER PROPER TESTING & APPROVAL WASTE SAMPLES.

IF DISPOSED OF IN IT'S ORIGINAL UNUSED FORM, THIS MATERIAL SHOULD BE TREATED, AND DISPOSED OF AT AN APPROVED SITE OR FACILITY, IN COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE & LOCAL ENVIRONMENTAL REGULATIONS. YOU MUST CONTACT THE PROPER GOVERNMENT AGENCIES FOR ADDITIONAL DIRECTIONS. ALL WASTE MATERIAL & WASTE WATER SHOULD BE DISPOSED OF CORRECTLY, UNDER ALL FEDERAL, STATE, CITY & COUNTY LAWS.

RCRA STATUS: SEE SECTION 15, REGULATORY INFORMATION

DO NOT RELEASE DYE OR DYE SOLUTION INTO ANY WATERWAYS OR SEWER SYSTEMS WITHOUT PROPER GOVERNMENT PERMISSION AT ALL LEVELS.

CONTAINER REUSE: AN "EMPTY" CONTAINER CAN CONTAIN PRODUCT RESIDUE, AND SHOULD NOT BE REUSED. IF NOT PROFESSIONALLY CLEANED & RECONDITIONED, CRUSHING OR OTHER MEANS IS RECOMMENDED TO PREVENT UNAUTHORIZED REUSE.

SECTION 14 TRANSPORT INFORMATION

DOT STATUS (HIGHWAY AND RAIL): NR

IATA STATUS (AIR): NR

SECTION 15 REGULATORY INFORMATION

AICS (AUSTRALIA): COMPONENTS LISTED
CAL. PROP. 65: PRODUCT CONTAINS TRACES OF SUBSTANCES LISTED BY CALIFORNIA AS CAUSING CANCER OR REPRODUCTIVE TOXICITY. FOLLOWING PPM LEVELS ARE PRESENT: CADMIUM <0.50, TOTAL CHROMIUM <1.00, LEAD 11.20, MERCURY < 0.50. NOTE THAT CR+6 (HEXAVALENT CHROMIUM) IS A LISTED SUBSTANCE. MINUTE TRACES MAY BE PRESENT IN TOTAL PPM CHROMIUM. NOTE: ALL PPM LEVELS APPLY TO 100% COLOR. FOR COLOR USED AT A FEW PERCENT OR LESS, WHEN MAKING CAL. PROP. 65 DETERMINATION FOR END PRODUCTS, CALCULATE ACTUAL SUBSTANCE PRESENT. EXAMPLE: WITH 3% COLOR USED IN END PRODUCT, AND CHROMIUM PRESENT AT <10 PPM IN 100% DYE, ACTUAL AMOUNT PRESENT FROM COLOR = 0.30 PPM = 0.00005%.

CERCLA: NH

CLEAN AIR ACT:

TITLE III-HAP'S: NK

TITLE V-VOC'S: SEE SECTION 9

TITLE VI-ODC'S: NOT MANUFACTURED WITH NOR CONTAINING CLASS I OR II ODC'S

CONG-TYPICAL METALS PRESENT IN PPM: THE FOUR REGULATED HEAVY METALS

INCIDENTALLY PRESENT DO NOT EXCEED 100 PPM AS INDICATED BELOW.

CADMIUM <0.5

CHROMIUM <1.0 (TOTAL INCLUDING HEXAVALENT CR+6)

LEAD 11.2

MERCURY <0.5

DSL (CANADA): COMPONENTS LISTED

ECL (KOREA): SERIAL #KE-03278

EINECS (EUROPE): #238-101-9

ENCS (JAPAN): #5-5112

FDA STATUS: NL

OTHER TYPICAL DATA IN PPM:

ARSENIC <3

BARIUM 5

SELENIUM <3

SILVER <2

OTHER TRACE BACKGROUND MATERIALS:

PHOSPHORUS: 0

< = NOT FOUND AT TEST LEVEL SHOWN. IF PRESENT, UNMEASURABLE TRACE IS BELOW LEVEL INDICATED.

PICCS (PHILIPPINES): COMPONENTS LISTED

RCRA: NOT HAZARDOUS IN IT'S PURCHASED FORM. HOWEVER, UNDER RCRA, IT IS THE PRODUCT USER'S RESPONSIBILITY TO DETERMINE AT TIME OF DISPOSAL IF ANY MATERIAL CONTAINING THE PRODUCT OR DERIVED FROM THE PRODUCT IS A HAZARDOUS WASTE.

SARA 311/312: IMMEDIATE/ACUTE HEALTH HAZARD : YES
 DELAYED/CHRONIC HEALTH HAZARD : YES
 FIRE HAZARD : NO
 SUDDEN RELEASE OF PRESSURE HAZARD: NO
 REACTIVITY HAZARD : NO

SARA 313: NR
Item Numbers: 61496-1001, 61496-1011

06/21/2006 09:27 FAX 530 365 6483

YALEY ENTERPRISES

☑ 019

TSCA: COMPONENTS LISTED

USDA: NL

WHMIS: D-2-A; D-2-B

SECTION 16 OTHER INFORMATION

REASON FOR REVISION 08-15-00: SECTION 15. (MVP)

REASON FOR REVISION ON 10-15-99: ADJUSTMENT OF CAL. PROP. 65 INFORMATION IN SECTION 15.

Revised on 03-22-01 to add data in section 9 (WN)

CODE KEY

NA = NOT APPLICABLE TO THIS MATERIAL

NC = NOT CERTAIN, UNDETERMINED

ND = NO DATA IS CURRENTLY AVAILABLE

NE = NOT ESTABLISHED, NO TESTING IS PLANNED

NH = NOT HAZARDOUS UNDER CITED REGULATIONS

NK = NONE KNOWN, NO INFORMATION FOUND IN DATA SEARCHS

NL = NOT LISTED OR APPROVED UNDER THESE REGULATIONS

NR = NOT REGULATED OR REPORTABLE

NIOSH = NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN. THIS MATERIAL SAFETY DATA SHEET WAS PREPARED TO COMPLY WITH THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200, AND SUPERSEDES ANY PREVIOUS INFORMATION. PREVIOUSLY DATED SHEETS ARE INVALID & UNAPPLICABLE.

06/21/2006 09:27 FAX 530 365 6483

YALEY ENTERPRISES

020

YELLOW LIQUID CANDLE DYE

YALEY ENTERPRISES, INC.
 7664 Avianca Drive
 Redding, CA 96002

Material Safety Data Sheet

Section 1 Identification Effective Date: 02/05/02

Trade Name: Econosol[®] Yellow
 Synonym:

Emergency Chem-Tel Numbers:

USA: 800.255.3924
 Intl: 813.248.0585 "call collect"

CAS Number: Proprietary (Mixture)
 Formula: Proprietary
 Chemical Family: Proprietary
 Molecular Weight: Proprietary

HMS Ratings: Health: 1 Flammability: 2 Reactivity: 0

Components of this product are deemed proprietary; however, all pertinent health and safety information has been provided in this document per the requirements of the US Code of Federal Regulations and equivalent State standards.

Section 2 Composition/Information on Ingredients

Components	EINECS#	PERCENT	CAS #
Econosol [®] Yellow	-	>5%	Mixture
Proprietary Carrier	-	< 95%	Mixture

Section 3 Hazardous Identification

Overview: Warning! May be Harmful if Swallowed. May cause Permanent Eye Damage. May cause Skin and Respiratory Tract Irritation.

To the best of our understanding the toxicological properties of this compound have not been fully studied.

Route(s) of Entry: Inhalation: Yes Skin: Yes Ingestion: Yes

Signs and Symptoms of Exposure:

Eye: May cause eye irritation.

Skin: May cause skin irritation.

1 of 5

06/21/2006 09:27 FAX 530 365 6483

YALEY ENTERPRISES

021

Ingestion: May be harmful if swallowed.

Inhalation: May irritate the upper respiratory tract

Chronic: No information has been found

Medical Conditions Generally Aggravated by Exposure: N.A.

Section 4 First-Aid Measures

Inhalation: Remove at once to fresh air. If the casualty is not breathing, give artificial respiration at once. If the casualty has difficulty in breathing, give oxygen. Seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

Skin: Remove contaminated clothing and shoes immediately. Wash off immediately with water and soap. If redness of skin irritation occurs, seek medical attention immediately.

Eye: Flush immediately with plenty of water for at least 15 minutes and seek medical attention. Keep the eyelids wide apart with fingers and wash out the inside of the eyelids thoroughly.

Section 5 Fire Fighting Measures

Flash Point:	>90°C	LEL Lower:	N.A.
Flammable Limits:	N.A.	UEL Upper:	N.A.

Extinguishing Media: Dry Powder, Water, Chemical Foam, or Alcohol-Resistant Foam

Special Fire Fighting Procedure: Wear appropriate protective clothing with self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: N.A.

Section 6 Accidental Release and Disposal

Steps to be taken in Case of Accidental Release: Sweep up material, place in sealed non-permeable bag & wait for waste disposal.

Waste Disposal Information: Federal, State and Local laws and regulations will determine the proper waste disposal procedure.

2 of 5

06/21/2006 09:29 FAX 530 365 6493

YALEY ENTERPRISES

022

Section 7 Handling and Storage

Precautions to be taken in Handling: When handling material, wear full protective clothing and appropriate respirator. Wash thoroughly after handling. Always use adequate ventilation.

Precautions to be taken in Storage: Keep container well closed. Store in a cool dry location. Keep away from sparks and open flames.

Section 8 Exposure Controls/Personal Protection

Respiratory Protection: Wear appropriate MSHA/NIOSH approved respirators
Protective Gloves: Chemical resistant gloves
Eye Protection: Safety goggles

Ventilation	Local Exhaust:	Recommended
	Mechanical (General):	Recommended
	Special:	N.A.

Other Protection or Equipment: Protective clothing, safety shower and eye wash

Working/Hygienic Practice: Avoid prolonged or repeated exposure. Wash thoroughly after handling.

Section 9 Physical and Chemical Properties

Physical State:	Liquid
Appearance & Odor:	Yellow / Strong Odor
Boiling Point:	N.A.
Melting Point:	N.A.
Flash Point :	>90°C
Decomposition Temp:	N.A.
Viscosity:	N.A.
Solubility in water:	Insoluble

Section 10 Stability and Reactivity

Stability: Stable
Condition to Avoid: Open flames, heat, sparks.

Hazardous Polymerization: Will not occur
Condition to Avoid: N.A.

Incompatibility: Strong Oxidizing and Reducing Agents

Hazardous Combustion or Decomposition Products: Oxides of carbon and nitrogen

3 of 5

06/21/2006 09:29 FAX 530 365 6483

YALEY ENTERPRISES

023

Section 11 Toxicology Information

To the best of our understanding the toxicological properties of this compound have not been fully studied.

This product may contain trace amounts of Naphthalene a Cal Prop 65 suspect cancer causing agent (April 13, 2002)

RTECS#: N.A.

Toxicity Data: N.A.

Target Organs: None

Listed Carcinogen: *NTP*: No *IARC*: No *OSHA*: No

This product may contain trace amounts of Naphthalene a Cal Prop 65 and IARC suspect cancer causing agent

Section 12 Ecological Information

Environmental Fate: No information available

Environmental Toxicity: No information available

If >20,000 lbs of this material is released the incident is subject to the provisions of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) and must be reported to the National Response Center

Section 13 Disposal Considerations

Dispose of in a manner consistent with federal, state and local laws

Section 14 Transport Information

Not considered a dangerous good

Please consult with IMO, IATA, and RID/ADR, US DOT, and Canadian TDG before shipping.

4 of 5

06/21/2006 09:28 FAX 530 365 6483

YALEY ENTERPRISES

025

REGULAR WICKING

Yaley Enterprises
7664 Avianca Drive
Redding, CA 96002

Material Safety Data SheetRegular Wick

Emergency Telephone No: 1-800-837-7477
Customer Service: 1-800-837-7477
Supercedes: 1/01/97

Section 1. - Identity

Product Name: Regular Wick
Number of fiber types included in construction: 1 (one)

Fiber Material Family: Cellulose
Generic name: Plyed wick, Flat Braid

Section 2. Hazardous Ingredients

All components of this product are considered non-hazardous under OSHA 1910.1200

Section 3. - Physical and Chemical Characteristics

HMIS Ratings: Health 0 Flammability: 0 Reactivity: 0
No hazard in normal industrial use
No absorption hazard under normal industrial use
Physical State: Solid Physical Appearance: Natural to off white in color

Section 4. - Fire & Explosion Hazard

Flammable: Yes Extinguishing Media: Water and/or use media appropriate to surrounding fire
Emergency First Aid: Procedure for Burns

Inhalation: This material does not present a hazard if inhaled. Remove individual to fresh air after airborne exposure as a precaution.
Eyes: Flush eyes for 20 minutes in eyewash. Seek medical advice after flushing
Skin Contact: Wash with soap and water. Get medical attention if irritation develops.
Ingestion: No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop and provide medical care provider with this MSDS

No additional first aid information available.

Section 5. - Reactivity Data

Chemical Stability: Chemically Stable
Incompatibility to other substances (conditions to avoid): Water, humidity, and oil
Reactivity: Disintegration when burned
Hazardous Decomposition: None
Hazardous Emissions: None
Environmental Hazards: Dispose of scrap according to state laws

Hazardous Combustion Products: Carbon monoxide and carbon dioxide

Clean up: No special clean-up consideration. Collect and discard in the regular trash. Ensure clean-up measure are in compliance with OSHA (29 CFR 1910.1200).

06/21/2006 09:28 FAX 530 365 6483

YALEY ENTERPRISES

☑ 026

Section 6. -Toxicological Properties**Handling:** No special handling.**Storage:** No special requirements. Keep dry.

No additional toxicological information available

Section 7. -Exposure Control and personal protection**Engineering Controls:** No exposure control limits exist for this product and none likely to be required under normal conditions.**Respiratory Tract:** None required under normal use of this product- No respirator required.**Skin:** Not normally considered a skin hazard. Where skin contact is made practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking and when leaving the work area.**Section 8. -Transportation Information****U.S. Surface freight classification:** Cotton Sleeve, Cotton Candle Wicking**Precautions to be taking in handling & Storing:** Keep dry.**Section 9. -Additional Information****Users Responsibility**

The listed information is believed to be accurate and represents the best information currently available. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information. We assume no liability resulting from its use or from use of a finished product. Users should make their own investigation to determine the suitability of the information for their particular purpose.

06/21/2006 09:28 FAX 530 365 6483

YALEY ENTERPRISES

027

FRENCH VANILLA
#222203-0800

Date Prepared: 10-Mar-2004

Material Safety Data Sheet Hazardous Materials Information System
(HMIS) F=1 R=0 H=See MSDS

This form is regarded to be in compliance with 29CFR 1910.1200

SECTION 1 : IDENTIFICATION

YALEY ENTERPRISES
7664 AVIANCA DR.
REDDING CA 96002
☎ (530) 365-5252

Product Name.....
VANILLA GEL CND/SOAP FRAG
#222203-0800

Chemical Family: Proprietary Mixture

C.A.S #.....: Not Applicable

24 Hour Emergency
Contact - CHEMTREC : 1-800-424-9300
 1-703-527-3887
 (International/Collect)

SECTION 2 : PHYSICAL DATA

Specific Gravity 25/25.....	1.0509	Boiling Point.....	N.A.
Vapor Pressure.....	<1 mm Hg @ 20°C approx	Physical State.....	Liquid
Odour.....	Fragrant	Vapor Density [Air=1].....	> 1
Solubility in Water.....	Negligible (0.1%)		

SECTION 3 : FIRE AND EXPLOSION HAZARD DATA

Flash Point (Closed Cup F) : > 200°F
 NFPA Flammability Code: 1
 Extinguishing Media.....: [] Water [X] CO2 [X] Dry Chemical [X] Foam [X] Water Fog
 Special Fire Fighting Procedures: None Known
 Unusual Fire and Explosion Hazards...: None Known

SECTION 4 : REACTIVITY DATA

Stability
Presents no significant reactivity hazard. Not pyrophoric nor reactive with water. Usually stable even at elevated temperatures and pressures.

Incompatibility (materials to avoid)
Avoid strong oxidizers

Hazardous Combustion or Decomposition Products
Burning liberates CO, CO2 and smoke. Does not form explosive mixtures with organic materials. Does not undergo explosive decomposition and is shock stable. Is not an oxygen donor.

Hazardous Polymerization
Will not undergo spontaneous exothermic polymerization

NFPA Reactivity Code : 0

SECTION 5 : SPILL OR LEAKAGE PROCEDURES

Cleanup of spills or accidental release of material
Flush with water or soak up with suitable absorbant.

Waste Disposal Methods
Incineration or sanitary landfill in accordance with local, state and federal regulations and consistent with good ecological practices.

SECTION 6 : SPECIAL PROTECTION INFORMATION

Respiratory	None required
Ventilation	General mechanical
Protective Gloves	Oil resistant if skin contact is anticipated
Eye Protection	Splash proof goggles if handling methods warrant them
Other Protective Equipment...	None required

SECTION 7 : EMERGENCY AND FIRST AID PROCEDURES

Eye (contact) In the event of accidental contact with eyes, irrigate with copious amounts of water; If irritation persists obtain medical advice.

Skin (contact) Remove contaminated clothing. Flush exposed area with copious amounts of water. Wash with mild soap and water. Material may remove some of the natural oils in the skin. If irritation persists obtain medical advice.

Ingestion (swallowing) In the event of accidental ingestion, rinse mouth with water. Give up to a tumbler (half pint) of milk or water. Obtain medical advice immediately

06/21/2006 09:28 FAX 530 365 6483

YALEY ENTERPRISES

028

SECTION 8 : EXPOSURE DATA**Primary Route of Exposure :** Skin Contact**OSHA PEL ...:** Not determined**ACGIH TLV ...:** Not determined

Material does not exist on any known list of carcinogens such as NTP, IARC or by OSHA, nor does it contain any carcinogens found in these lists.

SECTION 9 : HEALTH HAZARDS

The identity of the Individual components of this mixture is proprietary information and is regarded to be a TRADE SECRET. In accordance with 29 CFR 1910.1200 we have to assume that the mixture presents the same health hazards as the individual components when they are present at greater than 1% concentration.

Listed below are the health hazards of all materials present over 1% concentration and that undiluted have health hazards associated with them. Please note that not all components of the mixture have health hazards associated with them. In the event of a medical emergency the identity of all the components will be divulged to a qualified health professional.

The following effects were concluded as a result of animal laboratory testing of one or more of the individual components. The relevancy to the mixture as a whole or to humans is unknown. Excessive exposure may cause similar effects.

Repeated daily oral dosing of large amounts to laboratory animals caused liver damage.

Repeated daily oral dosing of large amounts to laboratory animals caused reproductive effects.

Caused lung and kidney tumors to laboratory animals when administered by stomach tube. Similar effects not seen in humans.

The following effects were concluded as a result of human testing and observation of one or more of the individual components.

Liquid and vapor may be irritating to the skin and eyes.

Reportable under SARA Title III Notification

This product contains the following toxic chemicals that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments Reauthorization Act of 1986 and 40 CFR part 372:

This mixture does not contain any toxic elements

The information and recommendations in this data sheet are believed to be correct and reliable. However, the data sheet is offered for consideration and verification by the user and Belmay, Inc. offers no guarantee, warranty or representation as to its accuracy or completeness of data.

Prepared by:

Occupational Safety and Health Department