

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)  
PEBEO SAS

Version 8.1 (24/03/2023) - Page 1/11

Fantasy prisme : all colours - FDS166

**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1. Product identifier**

Product name : Fantasy prisme : all colours  
 Product code : FDS166.  
 See list of references in appendix.  
 UFI : W4C0-V008-100F-Y5TE

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Paints & Varnishes for artists

**1.3. Details of the supplier of the safety data sheet**

Registered company name : PEBEO SAS.  
 Address : CS 10106 .13881.GEMENOS CEDEX.FRANCE.  
 Telephone : 33 (0) 4.42.32.08.08. Fax : 33 (0) 4.42.32.01.70.  
 reglementation@pebeo.com  
 www.pebeo.com

**1.4. Emergency telephone number : +33 (0)1 45 42 59 59.**

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

**Other emergency numbers**

United Kingdom : 0870 600 6266 Ireland : 01 809 25 66

**SECTION 2 : HAZARDS IDENTIFICATION****2.1. Classification of the substance or mixture****In compliance with EC regulation No. 1272/2008 and its amendments.**

Flammable liquid, Category 3 (Flam. Liq. 3, H226).  
 Repeated exposure may cause skin dryness or cracking (EUH066).  
 Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).  
 This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

**2.2. Label elements****In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS02



GHS07

Signal Word :  
 WARNING

Product identifiers :  
 EC 919-857-5

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Hazard statements :

H226

Flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)  
PEBEO SAS

Version 8.1 (24/03/2023) - Page 2/11

**Fantasy prisme : all colours - FDS166**

## Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P271 Use only outdoors or in a well-ventilated area.

## Precautionary statements - Storage :

P405 Store locked up.

## Precautionary statements - Disposal :

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq$  0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq$  0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 64742-48-9 EC: 919-857-5 REACH: 01-2119463258-33 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	[1]	25 $\leq$ x % < 50
EC: 918-167-1 REACH: 01-2119472146-39 HYDROCARBONS, C11-C12, ISOALKANES, <2% AROMATICS	GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304		2.5 $\leq$ x % < 10
EC: 918-481-9 REACH: 01-2119457273-39 HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS	GHS08 Dgr Asp. Tox. 1, H304		0 $\leq$ x % < 2.5
CAS: 64216-15-5 EC: 264-731-9 CALCIUM 3,5,5-TRIMETHYLHEXANOATE	GHS07 Wng Acute Tox. 4, H302 Eye Irrit. 2, H319		0 $\leq$ x % < 2.5
CAS: 22464-99-9 EC: 245-018-1 2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT	GHS08 Wng Repr. 2, H361d	[2]	0 $\leq$ x % < 2.5

**Information on ingredients :**

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. description of first aid measures****In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilled, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

**Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limits :**

- Poland (Dz. U. z 2018 r. poz. 917, 1000 i 1076) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64742-48-9	300 mg/m <sup>3</sup>	900 mg/m <sup>3</sup>			

- Switzerland (Suva 2021) :

CAS	VME	VLE	Valeur plafond	Notations
64742-48-9	50 ppm 300 mg/m <sup>3</sup>	100 ppm 600 mg/m <sup>3</sup>		

**8.2. Exposure controls****Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.

**Fantasy prisme : all colours - FDS166**

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**- Respiratory protection**

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties****Physical state**

Physical state : Fluid liquid.

**Colour**

Unspecified

**Odour**

Odour threshold : Not stated.

**Melting point**

Melting point/melting range : Not relevant.

**Freezing point**

Freezing point / Freezing range : Not stated.

**Boiling point or initial boiling point and boiling range**

Boiling point/boiling range : 210 °C.

**Flammability**

Flammability (solid, gas) : Not stated.

**Lower and upper explosion limit**

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

**Flash point**

Flash Point : 35.90 °C.

**Auto-ignition temperature**

Self-ignition temperature : Not relevant.

**Decomposition temperature**

Decomposition point/decomposition range : Not relevant.

**pH**

pH : Not relevant.

pH (aqueous solution) : Not stated.

**Kinematic viscosity**

Viscosity : Not stated.

**Solubility**

Water solubility : Insoluble.

Fat solubility : Not stated.

**Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water : Not stated.

**Vapour pressure**

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)  
PEBEO SAS

Version 8.1 (24/03/2023) - Page 7/11

**Fantasy prisme : all colours - FDS166****Density and/or relative density**

Density : 0.98

**Relative vapour density**

Vapour density : Not stated.

**9.2. Other information**

VOC (g/l) : 363.38

**9.2.1. Information with regard to physical hazard classes**

No data available.

**9.2.2. Other safety characteristics**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

**10.5. Incompatible materials**

No data available.

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

**11.1.1. Substances****Acute toxicity :**NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)  
Oral route : LD50 > 5000 mg/kg

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)  
PEBEO SAS

Version 8.1 (24/03/2023) - Page 8/11

**Fantasy prisme : all colours - FDS166**

OECD Guideline 401 (Acute Oral Toxicity)  
Species : Rat (recommended by the CLP)

Dermal route :  
LD50 > 5000 mg/kg  
OECD Guideline 402 (Acute Dermal Toxicity)  
Species : Rabbit (recommended by the CLP)

Inhalation route (Vapours) :  
LC50 > 4951 mg/m3  
OECD Guideline 403 (Acute Inhalation Toxicity)  
Species : Rat (recommended by the CLP)

**Carcinogenicity :**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)  
Carcinogenicity Test :  
Negative.  
No carcinogenic effect.  
OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Reproductive toxicant :**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)  
No toxic effect for reproduction

OECD Guideline 414 (Prenatal Developmental Toxicity Study)  
OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

**Specific target organ systemic toxicity - repeated exposure :**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Oral route :  
Duration of exposure : 90 days  
C > 100 mg/kg body weight/day  
Duration of exposure : 90 days  
OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)  
Species : Rat (recommended by CLP)

Inhalation route (Vapours) :  
Duration of exposure : 90 days  
C > 1 mg/l/6hrs/day  
Duration of exposure : 90 days  
OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

**11.1.2. Mixture**

No toxicological data available for the mixture.

**11.2. Information on other hazards****Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 108-94-1 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.  
CAS 7631-86-9 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.  
CAS 13463-67-7 : IARC Group 2B : The agent is possibly carcinogenic to humans.

**SECTION 12 : ECOLOGICAL INFORMATION****12.1. Toxicity****12.1.1. Substances**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)  
Fish toxicity :  
LC50 > 1000 mg/l  
Species : Oncorhynchus mykiss  
Duration of exposure : 96 h

Crustacean toxicity :  
EC50 = 1000 mg/l



SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)  
PEBEO SAS

Version 8.1 (24/03/2023) - Page 9/11

**Fantasy prisme : all colours - FDS166**

Algae toxicity :

Species : Daphnia magna  
Duration of exposure : 48 h

ECr50 > 1000 mg/l  
Species : Pseudokirchnerella subcapitata  
Duration of exposure : 72 h

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability****12.2.1. Substances**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

No data available.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :**

20 01 27 \* paint, inks, adhesives and resins containing dangerous substances

15 01 02 plastic packaging

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

**14.1. UN number or ID number**

1263

**14.2. UN proper shipping name**

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

**14.3. Transport hazard class(es)**

- Classification :



3

**14.4. Packing group**

III

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	163 367 650	E1	3	D/E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	3	-	III	5 L	F-E. S-E	163 223 367 955	E1	Category A	-	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	3	-	III	355	60 L	366	220 L	A3 A72 A192	E1	
	3	-	III	Y344	10 L	-	-	A3 A72 A192	E1	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Maritime transport in bulk according to IMO instruments**

No data available.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

**- Container information:**

The mixture is contained in packaging that does not exceed 125 ml.

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):  
<https://echa.europa.eu/substances-restricted-under-reach>.**- Particular provisions :**

No data available.

**- Swiss ordinance on the incentive tax on volatile organic compounds :**108-94-1 cyclohexanone  
34590-94-8 2-(3-méthoxypropoxy)propane-1-ol**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.

**Abbreviations :**

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.  
 LC50 : The concentration of a test substance resulting in 50% lethality in a given period.  
 EC50 : The effective concentration of substance that causes 50% of the maximum response.  
 ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.  
 REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.  
 CMR: Carcinogenic, mutagenic or reprotoxic.  
 UFI : Unique formulation identifier.  
 STEL : Short-term exposure limit  
 TWA : Time Weighted Averages  
 TMP : French Occupational Illness table  
 TLV : Threshold Limit Value (exposure)  
 AEV : Average Exposure Value.  
 ADR : European agreement concerning the international carriage of dangerous goods by Road.  
 IMDG : International Maritime Dangerous Goods.  
 IATA : International Air Transport Association.  
 ICAO : International Civil Aviation Organisation  
 RID : Regulations concerning the International carriage of Dangerous goods by rail.  
 WGK : Wassergefährdungsklasse (Water Hazard Class).  
 GHS02 : Flame  
 GHS07 : Exclamation mark  
 PBT: Persistent, bioaccumulable and toxic.  
 vPvB : Very persistent, very bioaccumulable.  
 SVHC : Substances of very high concern.

Reference	Désignation Référence
756431	SET INITIATION FANTASY PRISME 6 FLACONS ASSORTIS DE 20 ML
757431	SET EXPLORATION FANTASY PRISME 12 FLACONS ASSORTIS 20 ML
758431	COFFRET COLLECTION FANTASY PRISME 10X45ML
166060	FANTASY PRISME 45 ML JAUNE FLUO
166061	FANTASY PRISME 45 ML ORANGE FLUO
166062	FANTASY PRISME 45 ML ROSE FLUO
166051	FANTASY PRISME 45 ML ONYX
166050	FANTASY PRISME 45 ML PIERRE DE LUNE
166040	FANTASY PRISME 45 ML TURQUOISE
166039	FANTASY PRISME 45 ML BLEU CARAÏBE
166038	FANTASY PRISME 45 ML MARINA
166036	FANTASY PRISME 45 ML BLEU NUIT
166032	FANTASY PRISME 45 ML VIEL OR
166029	FANTASY PRISME 45 ML FEUILLE
166025	FANTASY PRISME 45 ML VIOLINE NACRE
166024	FANTASY PRISME 45 ML BOUTON D'OR
166021	FANTASY PRISME 45 ML ROSE GLACE
166020	FANTASY PRISME 45 ML BLANC COQUILLE
166018	FANTASY PRISME 45 ML EMERAUDE
166014	FANTASY PRISME 45 ML FLEUR DE CERISIER
166013	FANTASY PRISME 45 ML ROUGE ANGLAIS
166012	FANTASY PRISME 45 ML VERMILLON