

### **Product identifier**

Product code 62GL11114

Product name

NAT. LATEX LOW AMMONIA

Recommended use Not available.

Manufacturer or distributor

# Distributor

Protech Chemicals Ltd. 7600 Henri-Bourassa West Saint-Laurent, Québec Canada, H4S 1W3 Tel:(514)745-0200 US tel: (862)702-3537 Fax:(514)745-5774

## Manufacturer

Chemionics Corporation a Division of Protech Powder Coatings inc. 390 Munroe Falls Rd. Tallmadge, OH 44278 USA Tel: (330) 733-8834

## E-Mail

info@protechpowder.com

## Emergency telephone

INFOTRAC: (800)535-5053

# Anti-Poison Centre

1-800-463-5060 / (418) 656-8090

# 2. Hazards Identification

# Classification of the substance or mixture

Classification according to 2012 OSHA HCS (29 CFR 1910.1200) Skin Irritation (Cat 2), H315

Eye Irritation (Cat 2), H319

Hazard to the Aquatic Environment, Acute Hazard (Cat 3), H402

# **OSHA** statement

Not classified.

Label elements

# Signal word

WARNING Hazard pictograms

GHS07



PROTECH CHEMICALS LTD. PROTECH POWDER COATINGS IN NORTH YORK, ON FAIRFIELD NJ, YORK PA Item Numbers: 00312-10022600012-1004, 00312-1045, 0086221642 CLEVELAND OH UNION CITY MI, USA OXYPLAST PROTECH OXYPLAST BELGIUM NV OPAVA, CZECH REPUBLIC

S.A. DE C.V. MEXICO, D.F

C PROTECH OXYPLAS PIASECZNO POLAND

MONTREAL, OC Pageabaot 7



1/7

# 62GL11114

Hazard statement(s)					
H315	Causes skin irritation.				
H319	Causes serious eye irritation.				
H402 Harmful to aquatic life.					
Precautionary statement(	s)				
P264	Wash thoroughly after handling.				
P273	Avoid release to the environment.				
P280	Wear protective gloves/protective clothing/eye protection/face protection.				
P302+P352	IF ON SKIN: Wash with plenty of soap and water.				
P321	Specific treatment (see on this label).				
P332+P313	If skin irritation occurs: Get medical advice/attention.				
P362	Take off contaminated clothing and wash before reuse.				
P501	Dispose of contents/container in accordance with local regulations.				

# Supplemental information

Not applicable.

Other hazards

Not applicable.

# 3. Composition / Information on Ingredients

## Mixtures

## Substances presenting a hazard within the meaning of 2012 OSHA HCS (29 CFR 1910.1200)

Component name	CAS No.	<u>% by weight</u>
Ammonium Hydroxide	1336-21-6	1 - 2

# 4. First - Aid Measures

# General

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

## Ingestion

Rinse mouth. Get medical attention if symptoms occur.

## Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

# Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

## Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

# 5. Fire - Fighting Measures

#### Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

## Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

# Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

## Special protective equipment and precautions for fire-fighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

## 20-Oct-21

_	PROTECH CHEMICALS LTD.	PROTECH POWDER COATINGS INC.	PROTECH MEXICANA	OXYPLAST	PROTECH OXYPLAST CZ	PROTECH OXYPLAST POLAND	PROLUX PAINTS INC.	
	NORTH YORK, ON	FAIRFIELD NJ, YORK PA	S.A. DE C.V. MEXICO, D.F.	BELGIUM NV	OPAVA,	PIASECZNO	MONTREAL, QC_	
Item Numbers: 00312-1002A00202-1004, 00312-1045, 008#2E1#02 CLEVELAND OH				CZECH REPUBLIC	POLAND	PageAdAOT 7		
	UNION CITY MI, USA						0	

## Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

#### Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

#### General fire hazards

No unusual fire or explosion hazards noted.

# 6. Accidental Release Measures

## Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

## **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# Methods and materials for containment and cleaning up

Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

# 7. Handling and Storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

#### Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure Controls / Personal Protection

Component name	CAS No.	Exposure guidelines	
Ammonium Hydroxide	1336-21-6	PEL: 50 ppm (OSHA) STEL: 35 ppm (ACGIH) STEL: 27 mg/m <sup>3</sup> (NIOSH) TWA: 25 ppm (ACGIH) TWA: 18 mg/m <sup>3</sup> (NIOSH)	

#### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

## Eye protection

Exposure controls

Splash goggles and adequate ventilation

#### Skin protection

Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

# **Respiratory protection**

Chemical respirator with organic vapor cartridge and full facepiece.

## Hygiene measures

20-Oct-21

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

PROTECH CHEMICALS LT	D. PROTECH POWDER COATINGS INC.	PROTECH MEXICANA	OXYPLAST	PROTECH OXYPLAST CZ	PROTECH OXYPLAST POLAND	PROLUX PAINTS INC.	
NORTH YORK, ON	FAIRFIELD NJ, YORK PA	S.A. DE C.V. MEXICO, D.F.	BELGIUM NV	OPAVA,	PIASECZNO	MONTREAL, QC_	
Item Numbers: 00312-1002A0031&-1004, 0	0312-1045, 008 R2E1 P02 CLEVELAND OH			CZECH REPUBLIC	POLAND	Page 3 of 7	
	UNION CITY MI, USA					0	



# 9. Physical and Chemical Properties

Appearance	
Liquid	
Color White	
Odour	
Ammoniacal	
Odour threshold Not available.	
рН	
Not available.	
Melting point Not available.	
Boiling point Not available.	
Flash point Not available.	
Evaporation rate	
Not available.	
Flammability (for solid and gas) Not applicable.	
Upper explosion limit Not available.	
Lower explosion limit Not available.	
Vapour pressure Not available.	
Vapour density Not available.	
Relative density Not available.	
Partition coefficient: n-octanol/water Not available.	
Auto-ignition temperature Not available.	
Decomposition temperature Not available.	
Specific gravity 1.00 g/cm <sup>3</sup>	
-	
Pounds per gallon 8.34 Lbs/Gal	
Percent volatiles Not available.	
VOC	
Not available.	
10. Stability and Reactivity	

# Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

# Chemical stability

Material is stable under normal conditions.

# 20-Oct-21

	PROTECH CHEMICALS LTD.	PROTECH POWDER COATINGS INC.	PROTECH MEXICANA	OXYPLAST	PROTECH OXYPLAST CZ	PROTECH OXYPLAST POLAND	PROLUX PAINTS INC.
	NORTH YORK, ON	FAIRFIELD NJ, YORK PA	S.A. DE C.V. MEXICO, D.F.	BELGIUM NV	OPAVA,	PIASECZNO	MONTREAL, QC_
Item Numbers: 00312-1002a 00302.1004, 00312-1045, 003#2E1#02 CLEVELAND OH				CZECH REPUBLIC	POLAND	Pagead AOT 7	
		UNION CITY MI, USA					0

# 62GL11114

5/7

# 62GL11114 Possibility of hazardous reactions Material is stable under normal conditions. Conditions to avoid Contact with incompatible materials. Incompatible materials Strong oxidizing agents. Hazardous decomposition products No hazardous decomposition products are known. 11. **Toxicological Information** Likely routes of exposure Inhalation, skin contact, eye contact and ingestion Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Acute toxicity Result LD50/LC50 Component name Ammonium Hydroxide LD50/Oral/Rat: >350 mg/kg Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye irritation Causes serious eye irritation. **Respiratory sensitization** Not classified. Skin sensitization Not classified. Germ Cell Mutagenicity Not classified. **Carcinogenicity classification** No hazardous ingredient. **Developmental toxicity** Not classified. Specific Target Organ Toxicity, Single Exposure Not classified. Specific Target Organ Toxicity, Repeated Exposure Not classified. Aspiration hazard Not classified. Chronic effects Prolonged inhalation may be harmful. 12. Ecological Information

Aquatic ecotoxicity

Harmful to aquatic life.

## Ecotoxicity

Component name

Ammonium Hydroxide

Result LD50/LC50

# Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

## **Bioaccumulative potential**

No data available.

Mobility in soil

#### No data available.

20-Oct-21

	PROTECH CHEMICALS LTD.	PROTECH POWDER COATINGS INC.	PROTECH MEXICANA	OXYPLAST	PROTECH OXYPLAST CZ	PROTECH OXYPLAST POLAND	PROLUX PAINTS INC.	
	NORTH YORK, ON	FAIRFIELD NJ, YORK PA	S.A. DE C.V. MEXICO, D.F.	BELGIUM NV	OPAVA,	PIASECZNO	PageA5A017	
1	Item Numbers: 00312-1002A0031&-1004, 00312-1045, 00812211402 CLEVELAND OH				CZECH REPUBLIC	POLAND	Pagleabaot /	
		UNION CITY MI, USA					0	

62GL11114

### Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal Considerations

## **Disposal instructions**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

## Local disposal regulations

Dispose in accordance with all applicable regulations.

### Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

## Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see Disposal instructions).

## Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

# Transport (DOT / IATA / IMDG) Classification

## DOT / TDG

Not controlled material.

ΙΑΤΑ

Not controlled material.

# IMDG

Not controlled material.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

# 15. Regulatory Information

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

CERCLA

Ammonium Hydroxide - 1336-21-6 : 1000 lbs/453.6kg

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

SARA 302 Extremely hazardous substance Not listed.

# SARA 313

This product contains the following chemical(s) subjected to the reporting requirements of Section 313 of the Emergency Planning and Community Rightto-Know Act of 1986 and to 40 CFR 372:

Ammonium hydroxide

# EPA/CAA

EPA/CWA

California prop. 65

# **16. Other Information**

# HMIS

Health : Health : \*1 Flammability: Flammability : 1 Physical hazard: Physical hazard : 0 Personal Protection: Personal protection : G

# NFPA

Health : HEALTH : 1 Fire: FIRE : 1 Reactivity: REACTIVITY : 0 Specific Hazard: SPECIFIC HAZARD :

20-Oct-21

PROTECH CHEMICALS LTD.	PROTECH POWDER COATINGS INC.	PROTECH MEXICANA	OXYPLAST	PROTECH OXYPLAST CZ	PROTECH OXYPLAST POLAND	PROLUX PAINTS INC.	
NORTH YORK, ON	FAIRFIELD NJ, YORK PA	S.A. DE C.V. MEXICO, D.F.	BELGIUM NV	OPAVA,	PIASECZNO	MONTREAL, QC_	
Item Numbers: 00312-1002a00201&-1004, 00312-1045, 008#2E1#02 CLEVELAND OH				CZECH REPUBLIC	POLAND	PageAGAOT 7	
LINION CITY MILLISA						0	

6/7

## 62GL11114

## Refer to NFPA 654, standard for the prevention of fire and dust explosions from the manufacturing, processing and handling of combustible particulate solids, for safe handling.

# Abbreviations

HMIS : Hazardous Materials Identification System

- Chronic Hazard, 0 - Minimal Hazard, 1 - Slight Hazard, 2 - Moderate Hazard, 3 - Serious Hazard, 4 - Severe Hazard

NFPA : National Fire Protection Association

Health: 4 – Deadly, 3 - Extreme danger, 2 – Hazardous, 1 - Slightly hazardous, 0 - Normal material Fire: 4 - Below 73°F - very flammable, 3 - 73 to 100F – flammable, 2 - 101 to 200F –combustible, 1 - Over 200F -slightly combustible, 0 - Will not Burn Reactivity: 4- May detonate, 3- Shock or heat may detonate, 2- violent chem. Reaction, 1- Unstable if heated, 0- Stable, W- Use no water Specific Hazard: OXY- Oxidizer, ACID- Acid, ALK- Alkali, COR- Corrosive, W- Use no water OSHA: Occupational Safety and Health Administration DOT: Department of Transportation

IMDG: International Maritime Dangerous Goods

IATA: International Air Transport association

TSCA: Toxic Substance Control Act

DSL: Domestic Substance List

SARA313: Superfund Amendments and Reauthorization Act - Toxic Chemical Release Inventory (Section 313)

NPRI : National Pollutant Release Inventory

## Date of preparations

05/06/2019

To the best of knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazard and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.