00423-3004

SAFETY DATA SHEET

MSDS #: 580

Emergency Medical Number: Poison Control 800-222-1222 Emergency Transport Number: Chemtrec 800-424-9300 or (01) 703-527-3887 (CCN4391)

General Inquiry Number: Chartpak 413-584-5446

Page 1 of 3

Chartpak, Inc. One River Road Leeds, MA 01053

Phone: 413-584-5446 or 800-628-1910

Date

PEL/TLV

1/31/20

Section One:

Product Information

Product Name:

Grumbacher Alkyl Painting Medium

Product Sizes:

2.5 oz.

Product Class: Medium

| Section Two: | Ingredients | | |
|--------------|-------------|------------|-------------|
| Ingredients | | CAS Number | % by Weight |

| Solvent 140-66 | 64742-88-7 | 50.0% | 100 mg/m3 | - |
|-------------------|------------|-------|------------|---|
| Petroluem Solvent | 64742-47-8 | 20.0% | 1470 mg/m3 | |
| Dipentene | 138-86-3 | 5.0% | N/A | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | i I | | | |

Section Three:

Hazards Identification

WARNING: COMBUSTIBLE. VAPOR HARMFUL. MAY BE HARMFUL IF SWALLOWED. SKIN IRRITANT. CANCER AGENT BASED

ON EXPERIMENTAL DATA.

CONTAINS: ETHYL BENZENE, PETROLEUM DISTILLATES

KEEP OUT OF REACH OF CHILDREN.

**WARNING: This product contains a chemical known to the State of California to cause cancer.

Section Four:

First Aid Measures

Inhalation:

Move to fresh air.

Skin Contact:

If skin contact occurs, wash with soap and water for 5 minutes.

Eye Contact:

Flush wth water for at least 15 minutes.

Ingestion:

If swallowed, get prompt medical attention

This Material Safety Data Sheet is applicable to the consumer use of the following colors: 5802

SAFETY DATA SHEET

MSDS #: 580

Page 2 of 3

Section Five: Fire Fighting Measures

Flash Point: 142F (TCC)

Flammability Limits (% by volume): Lower:

Not explosive Upper: Not explosvie

Extinguishing Media: Foam, carbon dioxide, dry chemical

Special Fire Fighting Measures: No special fire fighting procedures required

Unusual Fire and Explosion

Combustible Hazards:

Section Six:

Accidental Release Measures

Dike area to prevent spreading. Use absorbent material to clean. Keep out of water entries.

Section Seven: Handling and Storage

Use only with adequate ventilation. Handling:

Do not store or use near heat or flame. Storage:

Exposure Controls and Personal Protection Section Eight:

Use exhaust fan to remove vapors and assure adequate cross-ventilation. Respiratory Protection and

Special Ventilation Requirements:

Other Protective Equipment Splash goggles and chemical-resistant apron are recommended.

(Gloves, Goggles, Etc.):

ONS: Avoid prolonged contact with skin, and ingestion. Wash hands immediately after use. When using, wear impermeable protective gloves, or do not eat, drink, or smoke. Do not store or Work/Hygiene Practices: PRECAUTIONS:

use near heat or flame. Use only with adequate ventilation.

Physical and Chemical Properties Section Nine:

Not determined **Boiling Point:** 334F Melting Point:

Specific Gravity: 0.80 - 0.85 Vapor Pressure: Not determined

Evaporation Rate (Butyl Acetate = 1): Not determined Specific Vapor Density (AIR = 1): Not determined

Reactivity in Water: Non-reactive Solubility in Water: Insoluble

Beige liquid; mild solvent odor Appearance and Odor:

Section Ten: Stability and Reactivity

Stability: Stable

Excessive heat or open flames Conditions to Avoid:

Chemical Incompatibility: None known Hazardous Decomposition: None known Will not occur Hazardous Polymerization:

Page 2 of 3 Item Numbers: 00423-3004

SAFETY DATA SHEET

MSDS #: 580

Page 3 of 3

Section Eleven: Toxicological Information

ARC Monographs: No
National Toxicology Program: No
OSHA Regulated: No

Effects/Symptoms of Exposure may result in irritation of the eyes and chest. Acute Exposure:

Effects/Symptoms of Repeated and prolonged overexposure may lead to damage to the liver. Chronic Exposure:

Medical Conditions Usually Aggravated By Overexposure of This Product: Dermatitis

Section Twelve: Ecological Information

Not available

Section Thirteen: Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations

Section Fourteen: Transport Information

ORM-D Consumer Commodity Flammable Liquid, n.o.s. (petroleum distillates), 3, UN1993, III (120 °F TCC / 48.8 °C) Ltd Qtys, EmS# F-E, S-E Consumer Commodity, 9, ID8000, packing instruction 910

Section Fifteen: Regulatory Information

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

Section Sixteen: Other Information

HMIS Code

Health 2
Flammability 2
Reactivity 0

Personal Protection N/A

Chartpak, Inc. is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D-4236.

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Item Numbers: 00423-3004 Page 3 of 3