

00439-1015

Product Name: 30116 Blair Gloss Varnish
 Product Code: 06-955-12

Print Date: 11/3/20
 Total pages: Page 1 of 8

SAFETY DATA SHEET

1. Product and Company Identification

Product Name: Blair Matte Varnish
Product Code: 30116
Product Type: Aerosol
Product Use: Art Material

Distributed by: Creative Art Materials Ltd. **Revision Date:** 3/30/2019
Address: 1214 River Hwy **Emergency Phone:** 1-800-255-3924
 Mooresville, NC 28117 **Phone:** (704) 664-1427

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2. Hazard Identification

Classification of substance or mixture:

| | |
|---|-------------------------------------|
| Flammable Aerosols | Category 1 |
| Gases Under Pressure | Liquefied Gas |
| Skin Irritation | Category 2, |
| Skin Sensitization | Category 1 |
| Carcinogenicity | Category 1 |
| Germ Cell Mutagenicity | Category 1 |
| Toxic to Reproduction | Category 2 |
| Eye damage/irritation | Category 2A |
| Specific target organ toxicity, single exposure | Category 3 (Central nervous system) |
| Specific target organ toxicity repeated exposure | Category 1 (inhalation) |
| Aspiration hazard | Category 1 |
| Acute Toxicity Oral | Category 4 |
| Acute Toxicity Dermal | Category 4 |
| Acute Toxicity Inhalation | Category 4 |

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Pictograms



Signal Word: Danger

Hazard Statement(s)

Product Name: 30116 Blair Gloss Varnish
Product Code: 06-955-12

Print Date: 11/3/20
Total pages: Page 2 of 8

H222 Extremely flammable aerosol
H280 Contains gas under pressure; may explode if heated.
H315* Causes Skin irritation
H317* May cause an allergic skin reaction
H340 May cause genetic defects
H350 May cause cancer
H361* Suspected of damaging fertility or the unborn child
H336 * May cause drowsiness or dizziness
H373* May cause damage to organs through prolonged or repeated exposure
H319* Causes serious eye irritation
H304* May be fatal if swallowed and enters airways
H332 Harmful if inhaled
H302 Harmful if swallowed
H312 Harmful in contact with skin

Precautionary Statements:

Prevention

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood
P281 Use personal protective equipment as required.
P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/ gas/mist.
P264 Wash thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P271 Use only outdoors or in a well-ventilated area.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves//eye /face protection/clothing when using this product.

Response

P304+P340 If Inhaled: Remove victim to fresh air and keep comfortable for breathing.
P312 Call a poison center/doctor/if you feel unwell.
P301+P312 If swallowed: Immediately call a poison center or doctor/physician.
P331 Do not induce vomiting
P330 Rinse mouth
P302+P352 If on skin: wash with plenty of water and soap.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing and wash it before reuse.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P308+P313 If exposed or concerned: Get medical attention.

Storage and Disposal

P405 Store locked up
P403 Store in a well ventilated place
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container in accordance with local/regional regulations.

Product Name: 30116 Blair Gloss Varnish
Product Code: 06-955-12

Print Date: 11/3/20
Total pages: Page 3 of 8

3. Composition information on ingredients

| Ingredients | CAS # | Percent |
|--|------------|---------|
| Liquefied Petroleum Gas | 68476-86-8 | 20-30 % |
| Dammar resin | 9000-16-2 | 5-7 % |
| Naphtha, petroleum, hydrotreated heavy | 64742-48-9 | <1% |
| n-hexane | 110-54-3 | 20-30% |
| Hexane | mixtures | 15-20% |
| Mineral Spirits | 8052-41-3 | 5-15% |
| A-Pinene | 80-56-8 | 5-10% |
| B-Pinene | 127-91-3 | 1-3% |
| Isopropyl Alcohol | 67-63-0 | 3 |

4. First Aid Measures

Eye Contact:

Flush with warm water for 15 minutes. Seek medical attention.

Skin Contact:

Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.

Inhalation:

Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.

Ingestion:

Do not induce vomiting. Get medical attention immediately. DO NOT GIVE AN UNCONCIOUS OR CONVULSING PERSON ANYTHING BY MOUTH!

5. Fire Fighting Measures

Flash Point: Flash point of propellant <0 degrees F.

Flammable limits in air, % by volume:

Upper: 9.5 (VOL.) Gas in air (propellant portion)

Lower: 1.8 % (VOL.) Gas in air (propellant portion)

Extinguishing Media:

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

Unusual Fire & Explosion Hazards:

Product Name: 30116 Blair Gloss Varnish
Product Code: 06-955-12

Print Date: 11/3/20
Total pages: Page 4 of 8

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

Special Fire Fighting Procedures:

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

6. Accidental Release Measures

Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

7. Handling and Storage

Handling:

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

Storage:

Store in a cool, dry area, away form heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

8. Exposure Controls / Personal Protection

Protective Equipment:

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

Engineering Controls:

Product Name: 30116 Blair Gloss Varnish
Product Code: 06-955-12

Print Date: 11/3/20
Total pages: Page 5 of 8

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

Respiratory Protection:

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above 1000 ppm, an approved self-contained breathing apparatus or airline respirator with full face-piece is required

Other Suggested Equipment:

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

Discretion Advised:

We take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Exposure guidelines:

| Ingredients | CAS # | Percent | Exposure Limits |
|----------------------------------|------------|---------|--|
| Liquefied Petroleum Gas | 68476-86-8 | | OSHA (PEL) 1000 ppm ACGIH TLV 1000 ppm |
| N-haexane | 110-54-3 | | OSHA (PEL) 500 ppm ACGIH TWA) 50 ppm |
| Mineral Spirits | 8052-41-3 | | OSHA (PEL) 500 ppm ACGIH (TWA) 100 ppm |
| A-Pinene | 80-56-8 | | OSHA (PEL) 100 ppm ACGIH (TLV) 100 ppm |
| B-Pinene | 127-91-3 | | OSHA (PEL) 100 ppm ACGIH (TLV) 100 ppm |
| Isopropyl Alcohol | 67-63-0 | | OSHA (PEL) 400 ppm ACGIH (TWA) 200 ppm |
| Dammar resin | 9000-16-2 | NE | |
| Naphtha, petroleum, hydro. heavy | 64742-48-9 | NE | |

9. Physical and Chemical Properties

Appearance: Clear as dispensed from aerosol can.

Odor: Sweet, pungent

Evaporation Rate: Ether = 1 Slower

PH: NA

Melting/Freezing point: NE

Initial Boiling point and boiling range: NE

Flash Point: Flash point of propellant <0°F

Flammability: NA

Vapor pressure: >30 psi

Vapor density >1 (Air=1)

Relative density NE

Solubility: negligible

Product Name: 30116 Blair Gloss Varnish
Product Code: 06-955-12

Print Date: 11/3/20
Total pages: Page 6 of 8

Partition coefficient: NE
Decomposition temperature: NE
Flammable limits in air, % by volume: (propellant portion)
Upper: 9.5%(vol) Gas in Air
Lower: 1.8% (vol) Gas in Air

Auto-ignition temperature: NE
Viscosity: NA

10. Stability and Reactivity

Stability: Stable
Conditions to Avoid: Heat, spark, and open flame
Incompatibility: Strong-Oxidizing Agents
Hazardous Decomposition: Combustion will produce Carbon Monoxide, Carbon Dioxide and nitrogen-oxygen compounds.
Hazardous Polymerization: Will not occur

11. Toxicological Information

Component Toxicological Information:

Acute oral toxicity

Hexane Isomers LD 50 Rat: > 5,000 mg/kg
N-hexane LD 50 Rat: 25 g/kg
Mineral Spirits LD 50 Rat: > 5 g/kg
Isopropyl Alcohol LD 50 Rat: 5,045 mg/kg
Alpha Pinene LD50 rat 3700 mg/kg
Beta Pinene LD50 mg/kg >5000

Acute inhalation toxicity

Hexane Isomers LD 50 Rat: >3367 4 h
N-hexane LD 50 Rat: 48000, 4 h
Isopropyl Alcohol LD 50 Rat: 16,000 mg/l

Acute dermal toxicity

Hexane Isomers LD 50 Rabbit: > 2,000 mg/kg
N-hexane LD 50 Rabbit > 1.3 g/kg
Mineral Spirits LD 50 Rabbit: >3 g/kg
Isopropyl Alcohol LD 50 Rabbit: 12,800 mg/kg
Alpha Pinene LD50 rabbit 2000 mg/kg
Beta Pinene LD50 mg/kg 2000

12. Ecological Information

| Component | Ecotoxicity |
|---------------------------------------|---|
| Hexane | 96 Hr LC50 Pimephales promelas: 2.1- 2.98 mg/L [flow-through] |
| Naphtha petroleum, hydrotreated heavy | 96 hr LC50 Pemephales promelas: 2200 mg/L |

13. Disposal Considerations

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state

Product Name: 30116 Blair Gloss Varnish
Product Code: 06-955-12

Print Date: 11/3/20
Total pages: Page 7 of 8

and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14. Transport Information

Aerosols (limited quantity),
Class 2.1, ERG 126

AIR (IATA)
Aerosols (limited quantity),
Class 2.1, ERG 126, UN No. 1950
Vessel

Aerosol (Limited Quantity), Class 2.1, UN No 1950

15. Regulatory Information

Environmental Regulations

SARA 311/312:

Immediate () Delayed () Fire () Reactive () Sudden Release of Pressure ()

Section 313

This product contains:

n-hexane 110-54-3 25%

California Prop. 65: None

All the chemicals used in this product are TSCA listed.
Check with your local regulators to be sure all local regulations are met.

16. Other Information

Hazard ratings This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

NFPA: Level 3 Aerosol

HMIS: Health: 2 Flammability: 4 Reactivity: 0

RATING: 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

Note:

The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee

Product Name: 30116 Blair Gloss Varnish
Product Code: 06-955-12

Print Date: 11/3/20
Total pages: Page 8 of 8

that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.