00456-1211

Camplin

SAFETY DATA SHEET

1. Identification

Product identifier Gamvar Satin / Matte Picture Varnish

Other means of identification

Recommended use Final coating on artist paintings. **Recommended restrictions** Keep out of reach of children.

Manufacturer/Importer/Supplier/Distributor information Manufacturer/Supplier Gamblin Artists Colors

2734 SE Raymond St. Portland, OR 97202

USA

+1 503-235-1945 Telephone number

Website www.gamblincolors.com

Emergency Telephone For Chemical Emergency ONLY, call:

Number

+1 503-235-1945

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4 Health hazards Sensitization, skin Category 1 Aspiration hazard Category 1

OSHA defined hazards Not classified

Label elements



Signal word

Hazard statement Combustible liquid. May be fatal if swallowed and enters airways. May cause an allergic skin

reaction.

Precautionary statement

Prevention Keep away from flames and hot surfaces. - No smoking. Avoid breathing mist/vapors.

Contaminated work clothing must not be allowed out of the workplace. Wear protective

gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash Response

with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

None known.

classified (HNOC)

Supplemental information None.

3. Composition/information on ingredients

Mixtures

| Chemical name | CAS number | % |
|-------------------|------------|---------|
| Petroleum Naptha | 64742-48-9 | 55 - 65 |
| Hydrocarbon resin | 68441-37-2 | 30 - 40 |

Gamvar Satin / Matte Picture Varnish

| Silicone Dioxide | 112926-00-8 | 3 - 7 | |
|------------------|----------------|-----------|--|
| Beeswax | 8012-89-3 | 1 - 3 | |
| Tinuvin® 292 | Not available. | 0.3 - 0.6 | |

4. First-aid measures

Inhalation Skin contact

Eve contact

Ingestion

Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders. Seek medical attention and take along these instructions.

Rinse with water. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. May cause an allergic skin reaction. Dermatitis. Rash.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Gamvar Satin / Matte Picture Varnish

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Туре | Value | |
|---------------------------------------|----------------|-----------|--|
| Silicone Dioxide (CAS 112926-00-8) | TWA | 0.8 mg/m3 | |
| | | 20 mppcf | |
| US. NIOSH: Pocket Guide to Ch | emical Hazards | | |
| Components | Туре | Value | |
| Silicone Dioxide (CAS | TWA | 6 mg/m3 | |

112926-00-8) **Biological limit values**

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves.

Skin protection

Other Wear appropriate chemical resistant clothing.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Liquid. **Physical state** Liquid. Form Color Colorless. Odorless. Odor **Odor threshold** Not available. Ηа Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

365 - 412 °F (185 - 211.11 °C)

Flash point 167.0 °F (75.0 °C) Pensky-Martens Closed Cup

Evaporation rate

Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

5.3 %

Not available. Explosive limit - lower (%)

Gamvar Satin / Matte Picture Varnish SDS US Explosive limit - upper (%) Not available.

Vapor pressure 0.064 kPa @ 68°F (20°C) Vapor density 5.6 @ 101 kPa (calculated) 0.767 @ 59°F (15°C) Relative density

Solubility(ies)

Negligible. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

635 °F (335 °C) **Auto-ignition temperature Decomposition temperature** Not available.

Viscosity 20 mm²/s (separated)

104 °F (40 °C) Viscosity temperature

Other information

0.75 - 0.79 g/cm³ Density Not explosive. **Explosive properties**

Molecular formula 163

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous No dangerous reaction known under conditions of normal use.

reactions

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Strong oxidizing agents. Chlorine. Fluorine. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. Skin contact May cause an allergic skin reaction.

Direct contact with eyes may cause temporary irritation. Eye contact

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause an allergic skin reaction.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components **Test Results** Species

Petroleum Naptha (CAS 64742-48-9)

Acute Dermal Liquid

LD50 Rabbit > 5000 mg/kg

Inhalation Vapor

LC50 Rat > 5000 mg/m³, 4 hr

Oral Liquid

LD50 Rat > 5000 mg/kg

Gamvar Satin / Matte Picture Varnish SDS US

Species **Test Results** Components Silicone Dioxide (CAS 112926-00-8) **Acute Dermal** LD50 Rabbit > 2000 mg/kg Inhalation Rat > 2200 mg/m³, 4 hours LC50 Oral LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Not classifiable as to carcinogenicity to humans. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Petroleum Naptha (CAS 64742-48-9) 3 Not classifiable as to carcinogenicity to humans. Silicone Dioxide (CAS 112926-00-8) 3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified

May be fatal if swallowed and enters airways. Aspiration hazard

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | | Species | Test Results |
|-----------------------------|--------------|---|------------------------|
| Petroleum Naptha (CAS 647 | 742-48-9) | | |
| Aquatic | | | |
| Acute | | | |
| Algae | EL0 | Pseudokirchnerella subcapitata | 1000 mg/l, 72 hr |
| | NOELR | Pseudokirchnerella subcapitata | 1000 mg/l, 72 hr |
| Crustacea | EL0 | Daphnia magna | 1000 mg/l, 48 hr |
| Fish | LL0 | Oncorhynchus mykiss | 1000 mg/l, 96 hr |
| Chronic | | | |
| Crustacea | NOELR | Daphnia magna | 1 mg/l, 21 d |
| rsistence and degradability | No data is a | available on the degradability of any ingre | edients in the mixture |

Persistence and degradability

data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

No data available.

Mobility in soil

The product is insoluble in water.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Gamvar Satin / Matte Picture Varnish

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)All components of the mixture on the TSCA 8(b) inventory are designated "active"

Superfund Amendments and Reauthorization Act of 1986 (SARA) SARA 302 Extremely hazardous substance

RA 302 Extre

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

categories

Respiratory or skin sensitization

Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Silicone Dioxide (CAS 112926-00-8)

Gamvar Satin / Matte Picture Varnish

US. New Jersey Worker and Community Right-to-Know Act

Silicone Dioxide (CAS 112926-00-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Petroleum Naptha (CAS 64742-48-9)

US. Rhode Island RTK

Not regulated.

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Petroleum Naptha (CAS 64742-48-9)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date26-March-2020Revision date05-May-2023

Version # 04

HMIS® ratings
Health: 3*
Flammability: 2
Physical hazard: 0

NFPA ratings



List of abbreviations EC50: Effective Concentration, 50%.

LC50: Lethal Concentration, 50%. LD50: Lethal Dose, 50%.

STEL: Short-Term Exposure Limit. TWA: Time Weighted Average Value.

EL0: Effective level, 0%.

IC50: Inhibitory concentration, 50%.

LL0: Lethal level, 0%.

NOELR: No Observed Effect Loading Rate

Disclaimer The information in this Safety Data Sheet has been obtained from current and reliable sources.

However, the data is provided without warranty, express or implied, regarding its correctness or accuracy. It is the user's responsibility to determine safe conditions for use of this product and to assume liability for loss injury, damage, or expense resulting from improper use of this product.

Gamvar Satin / Matte Picture Varnish

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).