SAFETY DATA SHEET MSDS for #01040 - SCHMINCK & COLLA MEDIBLY ulation (EC) No. 1907/2006 (REACH)

01040-1033 Page 1 of 9

50 040 - MUSSINI Medium 3

Article No. Version	50040	5.1 (08.12.20)			.12.20 / 9
	SECTION 1	: Identification of	the substance/mixture	and of the	
		company	/undertaking		
1.1 Product Trade name Name INCI Name Ph. Eur	50 040 - MUSS	SINI Medium 3			
REACH regist UFI	UFI: 45KF-74MS	6-200M-QF19			
	eral use	substance or mixture and	uses advised against		
	Products for cre	ation of art.			
	s advised against If the supplier of the saf				
	Otto-Hahn-Stras D-40699 Erkrath Tel +49 (0) 211 Fax +49 (0) 211 info@schmincke www.schmincke Schmincke-lab: mo-th 8.00-16.3 tel. +49 (0) 211 labor@schminck	- 2509 - 0 L - 2509 - 479 e.de e.de 30, fr 8.00-13.30 -2509-474			
1.4 Emergen	cy telephone number				_
	Emergency Information	Emergencycall +49 30-306867 (24/7 counseli			
		SECTION 2: Ha	zards identification		
2.1 Classifica	ation of the substance o	or mixture			
Aqua Asp. Flam. STOT	tic Chronic 2 (M1); H411	spiratory irritation.	g lasting effects.		
2.2 Label ele	ements				
Labelling					
<u>Signal w</u>	ord Danger				
<u>Hazard s</u>		mable liquid and vapour.			
Item Numb	ers: 01040-1033, 01040-103#1335 May	be fatal if swallowed and en cause respiratory irritation. cause drowsiness or dizzine:		Pa	ge 1 of 9

icle No.	50040	Issue date:	08.12.20
sion	6.1 (08.12.20)	Page	2/9
	H411 Toxic to aquatic life with long lasting effects.		
Safety precautions	D102 Kass out of you should be a		
	P102 Keep out of reach of children.		
	P210 Keep away from heat, hot surfaces, sparks, open fla	ames and other ignition sources. No	
	smoking.		
	P260 Do not breathe vapours.		
	•		
	P273 Avoid release to the environment.		
	P301+P310 IF SWALLOWED: Immediately call a POISON		
	P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT	Γ induce vomiting.	
	P303+P361+P353 IF ON SKIN (or hair): Take off immedi	ately all contaminated clothing. Rinse	
	skin with water/or shower.		
Hazard components	for labelling		
Text for labelling (Cl	<u>_P)</u>		
	Repeated exposure may cause skin dryness or cracking. (I	EUH066)	

2.3 Other hazards

SECTION 3: Composition / information on ingredients

3.1 Substances

Chemical characterisation aldehyde resin Stand oil White spirit siccative CAS-Number EINECS / ELINCS / NLP EU index number Customs tariff number REACH registration No. RTECS-no. Hazchem-Code CI-Number

3.2 Mixtures

Substance 1

solvent naphtha (petroleum), light, aromatic: 25 - 50 % CAS: 64742-95-6 REACH: 01-2119455851-35 Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / -; EUH066 / Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE 3; H336

Substance 3

2-ethylhexanoic acid, zirconium salt: 0,1 - <1,0 % CAS: 22464-99-9 REACH: 01-2119979088-21-xxxx Repr. 2; H361d

Substance 2

naphta (petroleum), hydrotreated heavy: 2,5 - <5,0 % CAS: 64742-48-9 REACH: 01-2119457273-39-xxxx Asp. Tox. 1; H304 / -; EUH066

Additional information

Item Numbers: 01040-1033, 01040-1034

SECTION 4: First aid measures

Page 2 of 9

MSDS for #01040 - SCHMINCKECOldeMetalBetaulation (EC) No. 1907/2006 (REACH)

Article No.	50040		Issue date:	08.12.20
Version		6.1 (08.12.20)	Page	3/9

4.1 Description of first aid measures

General information

If you feel unwell, seek medical advice (show the label where possible).

In case of inhalation Provide fresh air. Seek medical attention if problems persist.

In case of skin contact

Remove residues with soap and water. In case of skin irritation, consult a physician.

After eye contact

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 10 -

15 minutes. Seek medical attention if irritation persists.

After swallowing

Rinse mouth with water. Do NOT induce vomiting. Immediately get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration!

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons

strong water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters

Use appropriate respiratory protection.

Additional information

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes, and clothing.

6.2 environmental precautions

Discharge into the environment must be avoided.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Collect spilled material using paper towels and dispose.

Additional information

6.4 Reference to other sections

Dispose of waste according to applicable legislation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Precautions against fire and explosion No special measures are required.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers

Page 3 of 9

Article No.	50040		Issue date:	08.12.20
Version		6.1 (08.12.20)	Page	4/9

Hints on joint storage

Storage class Further details

Protect from frost and exposure to sun.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

64742-8	32-1	naphtha (petroleum), hydr	odesulphurized heav	/y		
DEU	WEL		150,000	mg/m³	4 (II); AGS	
64742-48-9 naphta (petroleum), hydrotreated heavy						
DEU	WEL		300,000	mg/m³	-	
22464-99-9 2-ethylhexanoic acid, zirconium salt						
DEU	WEL		1,000	mg/m³	1(I); 10, DFG, Sah	

DNEL overview

64742-95-6 solvent naphtha (petroleum), light, aromatic

DNEL worker	Long-term - inhalation, system	150,00000	mg/m³
DNEL worker	Long-term - dermal, local effe	25,00000	mg/kg bw/day
DNEL Consumer	Long-term - oral, systemic eff	11,00000	mg/kg bw/day
DNEL Consumer	Long-term - inhalation, system	32,00000	mg/m³
DNEL Consumer	Long-term - dermal, systemic e	11,00000	mg/kg bw/day

8.2 Exposure controls

Occupational exposure controls

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection must be worn whenever the WEL levels have been exceeded. Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

Hand protection

Qualified materials: Nitrile rubber

Layer thickness > 0,35 mm

Breakthrough time > 480 min

Ultranitril 492 - MAPA GmbH, Industriestraße 21-25, D-27404 Zeven, Internet: www.mapa-pro.de

All information was derived in accordance with EU directive 89/686/EWG and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves. This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided.

Eye protection

Goggles

Body protection

Wear suitable protective clothing. Wash contaminated clothing prior to re-use.

General protection and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands thoroughly after handling.

SECTION 9: Physical and chemical properties

9.1 information on basic physical and chemical properties

Form	liquid
Colour	yellowish, clear
Odour	white spirit

Item Numbers: 01040-1033, 01040-1034

max

Page 4 of 9

Article No. 50040 Version	6.1 (08.12.20)		Issue date: Page	08.12.20 5/ 9
Initial boiling point and boiling range Melting point/freezing point Flash point/flash point range Flammability Ignition temperature Auto-ignition temperature Explosion limits Refraction index PH	45 °C	50 °C		
Viscosity Viscosity	11 mm²/s	12 mm²/s	40 °C	
Vapour pressure Density Partition coefficient: n-octanol/wate	r	0,88 g/ml	20 °C	

Danger of explosion

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

Product is stable under normal storage conditions.

10.2 Chemical stability

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Protect from frost and exposure to sun.

10.5 Incompatible materials

strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous vapours may form during fires.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological tests

64742-95-6 solvent naphtha (petroleum), light, aromatic

oral	LD50	Rat	>	2000,00000	mg/kg	-
inhalative	LC50	Rat	>	10,20000	mg/L	(4h)
dermal	LD50	Rat	>	2000,00000	mg/kg	-

Toxicological tests

64742-48-9 naphta (petroleum), hydrotreated heavy

oral	LD50	Rat	>	2000,00000	mg/kg	-
dermal	LD50	Rabbit	>	2000,00000	mg/kg	-

Acute toxicity

No data available

In case of inhalation

No data available

After swallowing No Watas available¹⁰⁴⁰⁻¹⁰³⁴

In case of skin contact

Page 5 of 9

MSDS for #01040 - SCHMINCKEccildMcDIBAgulation (EC) No. 1907/2006 (REACH)

50 040 - MUSSINI Medium 3

Article No.	50040		Issue date:	08.12.20
Version		6.1 (08.12.20)	Page	6/9

No data available

After eye contact No data available

Practical experience

<u>General remarks</u>

SECTION 12: Ecological information

12.1 Toxicity

Ecotoxicological effects

64742-95-6 solvent naphtha (petroleum), light, aromatic

[LC50	fish		9,20000	mg/L	(96h)
[EC50	Algae	>	2,60000	mg/L	(72h)
[EC50	Daphnia magna (Big water flea)		3,20000	mg/L	(48h)

Ecotoxicological effects

64742-48-9 naphta (petroleum), hydrotreated heavy

2

LC50	fish	>	1000,00000	mg/L	-
EC50	Algae	>	1000,00000	mg/L	-

Aquatic toxicity

No data available Water Hazard Class WGK catalog number General information

12.2 Persistence and degradability

Further details Product is partially biodegradable. Oxygen demand

12.3 Bioaccumulative potential

Bioconcentration factor (BCF) Partition coefficient: n-octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number 080111 Recommendation

11 080111* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging

Waste key number

Recommendation

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Page 6 of 9

SAFETY DATA SHEET MSDS for #01040 - SCHMINCKEcOldMcDIBMulation (EC) No. 1907/2006 (REACH)

50 040 - MUSSINI Medium 3

Article No. 50040 Version 6.1 (08.		12.20)	Issue date: Page	08.12.20 7/ 9
Additional inform	ation			
	SEC	TION 14: Transport informa	ition	
14.1 UN number				
	263			
14.2 UN proper shi	nning namo			
,	aint related material AINT RELATED MATERIAL			
IMDG, IATA	AINT RELATED MATERIAL			
14.3 Transport haz	<u>ard class(es)</u>			
ADR, ADN 3				
IMDG 3				
іата 3				
14.4 Packing group	<u>2</u>			
II	Ĩ			
14.5 Environmenta	l hazards			
Marine Pollutant -		Yes		
Marine Pollutant -				
14.6 Special precau	utions for user			
Land transport (A	DR/RID)			
Code: ADR/RID	<u> </u>	F1		
Kemmler-number		30		
Hazard label ADR		3		
Limited quantities		5L P001 - IBC03 - LP01 - R001		
-	kaging: Instructions kaging: Special provisions	PP1		
-	for packing together	MP19		
Portable tanks: In		T2		
Portable tanks: Sp	ecial provisions	TP1 - TP29		
Tank coding		LGBF		
Tunnel restriction		D/E		
Remarks		E1		
EQ Special provisions		163 - 367 - 650		
Special provisions		100 507 050		
<u>Sea transport (IM</u>	DG)			
EmS		F-E, S-E		
Special provisions		163 - 223 - 367 - 955		
Limited quantities		5L		
•	kaging: Instructions	P001 - LP01		
•	kaging: Special provisions	PP1		
IBC: Instructions IBC: Provisions		IBC03		
Tank instructions	ΙΜΟ	-		
Tank instructions		T2		
Tank instructions	Special provisions	TP1 - TP29		
Stowage and segre	-	category A		
Properties and obs	servations			
Remarks EQ		E1		
Air transport (IAT Item Numbers: 01040-103	A-DGR)			Page 7 of 9

m Numbers: 01040-1033, 01040-1034 Hazard

Flammable Liquid

Article No. Version	50040 6.1 (08.12.20)	Issue date: Page	08.12.20 8/ 9
Passenger	355 (60L)		
Passenger LQ	Y344 (10L)		
Cargo	366 (220L)		
ERG	3L		
Remarks			
EQ	E1		
Special Provisioning	A192		

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

<u>Europe</u>

Contents of VOC [%] Contents of VOC [g/L] Further regulations, limitations and legal requirements

<u>Germany</u>

Storage class Water Hazard Class 2 WGK catalog number Incident regulation Information on working limitations Further regulations, limitations and legal requirements

Denmark

Further regulations, limitations and legal requirements

<u>Hungary</u>

Further regulations, limitations and legal requirements

<u>Great Britain</u>

Further regulations, limitations and legal requirements

Switzerland

Contents of VOC [%] ~ 52,7 % Further regulations, limitations and legal requirements

<u>USA</u>

Further regulations, limitations and legal requirements Federal Regulations State Regulations

<u>Canada</u>

Further regulations, limitations and legal requirements

15.2 Chemical Safety Assessment

em Numbers: 01040-1033. 01040-1034

SECTION 16: Other information

Further information

Article No. Version	50040	6.1 (08.12.20)	Issue date: Page	08.12.20 9/ 9
Hazard statem	nents (CLP)	H226 Flammable liquid and vapour.		
		H304 May be fatal if swallowed and enters airways.		
		H335 May cause respiratory irritation.		
		H336 May cause drowsiness or dizziness.		
		H361d Suspected of damaging the unborn child		

H361d Suspected of damaging the unborn child. H411 Toxic to aquatic life with long lasting effects.

Further information

This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

Literature

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Reason of change

Additional information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Page 9 of 9