Version 4.2 (16/11/2022) - Page 1/10

PEBEO SAS

Glazing resin bio: part A - FDS216



### SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

### >SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### |> 1.1. Product identifier

Product name: Glazing resin bio: part A

Product code: FDS216.

See list of references in appendix. UFI: GQK0-D0R6-0000-6733

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Paints & Varnishes for artists

#### 1.3. Details of the supplier of the safety data sheet

Registered company name: PEBEO SAS.

Address: CS 10106 .13881.GEMENOS CEDEX.FRANCE. Telephone: 33 (0) 4.42.32.08.08. Fax: 33 (0) 4.42.32.01.70.

reglementation@pebeo.com

www.pebeo.com

#### 1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

#### Other emergency numbers

United Kingdom: 0870 600 6266 Ireland: 01 809 25 66

#### >SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

#### |> In compliance with EC regulation No. 1272/2008 and its amendments.

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

# 2.2. Label elements

### |> In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:







GHS05 Signal Word :

DANGER

Product identifiers :

EC 216-823-5 BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE
EC 236-211-1 1,2,3-TRIS (2,3-EPOXYPROPOXY) PROPANE
EC 219-371-7 1,4-BIS(2,3-EPOXYPROPOXY)BUTANE
EC 915-687-0 PENTAMETHYL PIPERIDYLSEBACATE

Additional labeling:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Version 4.2 (16/11/2022) - Page 2/10

### Glazing resin bio: part A - FDS216

Hazard statements:

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements - General:

P102 Keep out of reach of children.

Precautionary statements - Prevention:

P280 Wear protective gloves/protective clothing/eye protection/face

protection/hearing protection/ ...

### |> 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq$  0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances > = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

#### >SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

#### > Composition:

Identification	(EC) 1272/2008	Note	1%
CAS: 1675-54-3	( )		50 <= x % < 100
	GHS07, GHS09	[1]	30 <= x % < 100
EC: 216-823-5	Wng		
REACH: 01-2119456619-26-xxxx	Skin Irrit. 2, H315		
	Skin Sens. 1, H317		
BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROP	A Eye Irrit. 2, H319		
NE	Aquatic Chronic 2, H411		
CAS: 13236-02-7	GHS07, GHS05		$10 \le x \% < 25$
EC: 236-211-1	Dgr		
REACH: 01-2120804934-53-xxxx	Acute Tox. 4, H302		
	Eye Dam. 1, H318		
1,2,3-TRIS (2,3-EPOXYPROPOXY) PROPANI			
CAS: 28064-14-4			2.5 <= x % < 10
EC: 608-164-0	Aquatic Chronic 4, H413		
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
GLYCIDYL ETHER AND POLYMER OF			
PHENOL AND FORMALDEHYDE			
CAS: 2425-79-8	GHS07, GHS05		2.5 <= x % < 10
EC: 219-371-7	Dgr		2.3 4 % 70 4 10
REACH: 01-2119494060-45-XXXX	Acute Tox. 4, H302		
REACH: 01-2119494000-43-XXXX	Acute Tox. 4, H312		
1,4-BIS(2,3 EPOXYPROPOXY)BUTANE	Skin Irrit. 2, H315		
1,4-bis(2,5 erox i frofox i )bu iane			
	Skin Sens. 1, H317		
	Eye Dam. 1, H318		
	Acute Tox. 4, H332		
G16 1065226 01 5	Aquatic Chronic 3, H412		10 0/ 1
CAS: 1065336-91-5	GHS09, GHS07		$0 \le x \% < 1$
EC: 915-687-0	Wng		
REACH: 01-2119491304-40	Skin Sens. 1A, H317		
	Aquatic Acute 1, H400		
PENTAMETHYL PIPERIDYLSEBACATE	M Acute = 1		
	Aquatic Chronic 1, H410		
	M Chronic = 1		

Version 4.2 (16/11/2022) - Page 3/10

Glazing resin bio: part A - FDS216

|> Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 1675-54-3	Skin Irrit. 2: H315 >=5%	
EC: 216-823-5	Eye Irrit. 2: H319 C>= 5%	
REACH: 01-2119456619-26-xxxx		
BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPA		
NE .		

#### Information on ingredients:

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

#### >SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

#### 4.1. description of first aid measures

#### In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

### In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

### > In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

# |>SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

# 5.1. Extinguishing media

### |> Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

### |> Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

Version 4.2 (16/11/2022) - Page 4/10

PEBEO SAS

#### Glazing resin bio: part A - FDS216

#### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

#### 5.3. Advice for firefighters

No data available.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non first aid worker

Avoid any contact with the skin and eyes.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

#### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

#### 6.4. Reference to other sections

No data available.

### >SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

### |> 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

### |> Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

### |> Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture at all times.

Packages which have been opened must be reclosed carefully and stored in an upright position.

### Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

# 7.2. Conditions for safe storage, including any incompatibilities

No data available.

### |> Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Version 4.2 (16/11/2022) - Page 5/10

Glazing resin bio: part A - FDS216

#### **Packaging**

Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

No data available.

### >SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Occupational exposure limits:

- Netherlands / MAC-waarde (10 december 2014) :

CAS	TWA ·	STEL .	Cailing:	Definition:	Critoria :	
1675 54 3	5/2	BILL.	Cennig .	Definition :	D.	
16/5-54-3	3 mg/m3	I -	I -	I -	K	

### 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):







Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

### |> - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)

### |> - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Version 4.2 (16/11/2022) - Page 6/10

Glazing resin bio: part A - FDS216

### >SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state: Viscous liquid.

|> Colour

Unspecified

|> Odour

Odour threshold: Not stated.

|> Melting point

Melting point/melting range: Not relevant.

|> Freezing point

Freezing point / Freezing range: Not stated.

|> Boiling point or initial boiling point and boiling range

Boiling point/boiling range: Not relevant.

|> Flammability

Flammability (solid, gas): Not stated.

|> Lower and upper explosion limit

Explosive properties, lower explosivity limit (%): Not stated. Explosive properties, upper explosivity limit (%): Not stated.

|> Flash point

Flash Point Interval : FP > 100 °C.

Auto-ignition temperature

Self-ignition temperature: Not relevant.

**Decomposition temperature** 

Decomposition point/decomposition range: Not relevant.

|> pH

pH (aqueous solution):

Not stated.

pH:

Not relevant.

|> Kinematic viscosity

Viscosity: Not stated.

|> Solubility

Water solubility: Insoluble.
Fat solubility: Not stated.

|> Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water: Not stated.

Vapour pressure

Vapour pressure (50°C): Not relevant.

Density and/or relative density

Density: 1.18

|> Relative vapour density

Vapour density: Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

Version 4.2 (16/11/2022) - Page 7/10

Glazing resin bio: part A - FDS216

#### >SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### |> 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### 10.4. Conditions to avoid

No data available.

#### 10.5. Incompatible materials

No data available.

#### 10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

### >SECTION 11 : TOXICOLOGICAL INFORMATION

### |> 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful if swallowed.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

May cause an allergic reaction by skin contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and a respiratory tract sensitiser as well as an irritant.

Constituents with a low molecular weight irritate the eyes, mucous membranes and the skin

Repeated contact with the skin may cause irritation and hypersensitisation, possibly in combination with other epoxide compounds.

### 11.1.1. Substances

No toxicological data available for the substances.

### 11.1.2. Mixture

# ${\bf Respiratory\ or\ skin\ sensitisation:}$

Contains epoxy compounds. May cause an allergic reaction.

### 11.2. Information on other hazards

### Monograph(s) from the IARC (International Agency for Research on Cancer):

CAS 1675-54-3: IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

### SECTION 12: ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

Version 4.2 (16/11/2022) - Page 8/10

### Glazing resin bio: part A - FDS216

### 12.1. Toxicity

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

No data available.

#### 12.6. Endocrine disrupting properties

No data available.

#### 12.7. Other adverse effects

No data available.

#### SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

# Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

20 01 27 \* paint, inks, adhesives and resins containing dangerous substances

15 01 02 plastic packaging

### >SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

### 14.1. UN number or ID number

3082

# |> 14.2. UN proper shipping name

UN3082=ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(bis-[4-(2,3-epoxipropoxi)phenyl]propane, 1,2,3-tris (2,3-epoxypropoxy) propane)

### 14.3. Transport hazard class(es)

- Classification:



14.4. Packing group

III

Version 4.2 (16/11/2022) - Page 9/10

Glazing resin bio: part A - FDS216

#### 14.5. Environmental hazards

- Environmentally hazardous material:



### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	9	M6	III	9	90	5 L	274 335 375	E1	3	-
							601			

Not subject to this regulation if Q  $\leq$  5 1 / 5 kg (ADR 3.3.1 - DS 375)

**IMDG** Class 2°Label Pack gr. LO EMS Provis. EO Stowage Segregation Handling 5 L F-A. S-F 274 335 969 E1 Category A

Not subject to this regulation if  $Q \le 51/5 \text{ kg}$  (IMDG 3.3.1 - 2.10.2.7)

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	9	-	III	964	450 L	964	450 L	A97 A158	E1
								A197 A215	
	9	-	III	Y964	30 kg G	-	-	A97 A158	E1
								A197 A215	

Not subject to this regulation if  $Q \le 51/5 \text{ kg}$  (IATA 4.4.4 - DS A197)

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

Marine pollutant (IMDG 3.1.2.9):(bis-[4-(2,3-epoxipropoxi)phenyl]propane)

### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

### >SECTION 15: Regulatory information

# $15.1.\ Safety, health \ and \ environmental\ regulations/legislation\ specific\ for\ the\ substance\ or\ mixture$

### |> - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/1182 (ATP 15)

### |> - Container information:

The mixture is contained in packaging that does not exceed 125 ml.

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

### - Particular provisions :

No data available.

### 15.2. Chemical safety assessment

No data available.

### >SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Version 4.2 (16/11/2022) - Page 10/10

PEBEO SAS

### Glazing resin bio: part A - FDS216

### |> Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

### |> Abbreviations :

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

UFI: Unique formulation identifier. STEL: Short-term exposure limit TWA: Time Weighted Averages TLV: Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

 $WGK: Wasserge fahrdungsklasse \ (Water\ Hazard\ Class).$ 

GHS05: Corrosion GHS07: Exclamation mark GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern. |> Modification compared to the previous version

Références	Désignation Référence
766183	GÉDÉO KIT 750ML RÉSINE GLACAGE BIO
766181	GÉDÉO KIT 150ML RÉSINE GLACAGE BIO
107435	GEDEO KIT RESINE GLACAGE BIO 150ML /SCA
FDS216	Résine glaçage bio : partie A
766182	GÉDÉO KIT 300ML RÉSINE GLACAGE BIO
766189	GÉDÉO KIT 45ML RÉSINE GLACAGE BIO

Item Numbers: 01048-1014, 01048-1015, 01048-1023 Page 11 of 22

Version 4.2 (16/11/2022) - Page 1/10

PEBEO SAS

Glazing resin bio: part B - FDS215



#### SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

### >SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name: Glazing resin bio: part B

Product code: FDS215.

See list of references in appendix. UFI: NHK0-D0CD-D000-VHWY

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Paints & Varnishes for artists

### 1.3. Details of the supplier of the safety data sheet

Registered company name: PEBEO SAS.

Address: CS 10106 .13881.GEMENOS CEDEX.FRANCE. Telephone: 33 (0) 4.42.32.08.08. Fax: 33 (0) 4.42.32.01.70.

reglementation@pebeo.com

www.pebeo.com

### 1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

#### > Other emergency numbers

United Kingdom: 0870 600 6266 Ireland: 01 809 25 66

### >SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

### In compliance with EC regulation No. 1272/2008 and its amendments.

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).

Acute dermal toxicity, Category 4 (Acute Tox. 4, H312).

Skin corrosion, Category 1A (Skin Corr. 1A, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

### 2.2. Label elements

### |> In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:





GHS05

GHS07

Signal Word : DANGER

Product identifiers:

EC 220-666-8 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

EC 219-941-5 1,3-CYCLOHEXANEDIMETHANAMINE

Hazard statements:

H302 + H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage.

Version 4.2 (16/11/2022) - Page 2/10

### Glazing resin bio: part B - FDS215

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - General:

P102

Keep out of reach of children.

Precautionary statements - Prevention:

P280

Wear protective gloves/protective clothing/eye protection/face

protection/hearing protection/ ...

Precautionary statements - Response :

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Precautionary statements - Storage:

P405 Store locked up.

### |> 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

### >SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

> Composition :			
Identification	(EC) 1272/2008	Note	%
CAS: 2855-13-2	GHS07, GHS05		50 <= x % < 100
EC: 220-666-8	Dgr		
REACH: 01-2119514687-32-XXXX	Acute Tox. 4, H302		
	Acute Tox. 4, H312		
3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLO	Skin Corr. 1B, H314		
HEXYLAMINE	Skin Sens. 1, H317		
	Eye Dam. 1, H318		
	Aquatic Chronic 3, H412		
CAS: 100-51-6	GHS07	[1]	10 <= x % < 25
EC: 202-859-9	Wng		
REACH: 01-2119492630-38-XXXX	Acute Tox. 4, H302		
	Eye Irrit. 2, H319		
BENZYL ALCOHOL	Acute Tox. 4, H332		
CAS: 39423-51-3	GHS07, GHS05, GHS09		2.5 <= x % < 10
EC: 500-105-6	Dgr		
REACH: 01-2119556886-20-0000	Acute Tox. 4, H302		
	Acute Tox. 4, H312		
PROPYLIDYNETRIMETHANOL, REACTION	Eye Dam. 1, H318		
PRODUCTS WITH AMMONIA	Aquatic Chronic 2, H411		
CAS: 2579-20-6	GHS07, GHS05		10 <= x % < 25
EC: 219-941-5	Dgr		
REACH: 01-2119543741-41-XXXX	Acute Tox. 4, H302		
	Acute Tox. 4, H312		
1,3-CYCLOHEXANEDIMETHANAMINE	Skin Corr. 1A, H314		
	Aquatic Chronic 3, H412		

### Information on ingredients:

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

### >SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

Version 4.2 (16/11/2022) - Page 3/10

Glazing resin bio: part B - FDS215

### 4.1. description of first aid measures

### In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

#### In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

### |> In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

### >SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

#### 5.1. Extinguishing media

#### |> Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

### > Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

### 5.3. Advice for firefighters

No data available.

### >SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

### For non first aid worker

Avoid any contact with the skin and eyes.

Version 4.2 (16/11/2022) - Page 4/10

PEBEO SAS

### Glazing resin bio: part B - FDS215

### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

#### > 6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

Clean preferably with a detergent, do not use solvents.

#### 6.4. Reference to other sections

No data available.

#### >SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

#### |> 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

### |> Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

#### |> Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

### Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

### |> Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

### Packaging

Always keep in packaging made of an identical material to the original.

# 7.3. Specific end use(s)

No data available.

### >SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

# Occupational exposure limits:

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME:	VME :	Excess	Notes
100-51-6		5 ppm		2 (I)
		22 mg/m <sup>3</sup>		

<sup>-</sup> Finland (HTP-värden 2018):

Version 4.2 (16/11/2022) - Page 5/10

### Glazing resin bio: part B - FDS215

G + G	CENT 7.4	CEET	G 11:	D C	la
CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
100-51-6	10 ppm				
	45 mg/m <sup>3</sup>				
- Japan (JSOH, Reco	ommendation of	occupational ex	posure limits 20	)21-2022):	
CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
100-51-6	25 mg/m <sup>3</sup>				
- Poland (Dz. U. z 20	018 r. poz. 917,	1000 i 1076) :			
CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
100-51-6	240 mg/m <sup>3</sup>				
- Czech Republic (R	egulation No. 30	51/2007):			
CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
100-51-6	40 mg/m <sup>3</sup>	80 mg/m <sup>3</sup>			
- Switzerland (Suva	2021):				
CAS	VME	VLE	Valeur plafond	Notations	
100-51-6	5 ppm				
	22 mg/m <sup>3</sup>				
- USA / AIHA WEE	L (American In	dustrial Hygiene	e Association, W	orkplace Environ	onmental Expos
CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:

### 8.2. Exposure controls

100-51-6

### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):



10 ppm







Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

# - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

### |> - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Natural latex
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

### |> - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

Version 4.2 (16/11/2022) - Page 6/10

Glazing resin bio: part B - FDS215

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Suitable type of protective boots:

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Not relevant.

Not stated. 11.60 .

Strongly basic.

Work clothing worn by personnel shall be laundered regularly.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
9.1. Information on basic physical and chemical properties

After contact with the product, all parts of the body that have been soiled must be washed.

stri inioi mution on susic physical and elemical properties	
Physical state	
Physical state:	Fluid liquid.
> Colour	
Unspecified	
> Odour	
Odour threshold:	Not stated.
> Melting point	
Melting point/melting range:	Not relevant.
> Freezing point	
Freezing point / Freezing range:	Not stated.
> Boiling point or initial boiling point and boiling range	
Boiling point/boiling range:	Not relevant.
> Flammability	
Flammability (solid, gas):	Not stated.
> Lower and upper explosion limit	
Explosive properties, lower explosivity limit (%):	Not stated.
Explosive properties, upper explosivity limit (%):	Not stated.
Flash point	
Flash Point Interval:	FP > 100°C.
Auto-ignition temperature	
Self-ignition temperature :	Not relevant.
Decomposition temperature	

|> Kinematic viscosity

pH (aqueous solution):

Viscosity: Not stated.

|> Solubility

pH:

|> pH

Water solubility: Insoluble.
Fat solubility: Not stated.

|> Partition coefficient n-octanol/water (log value)

Decomposition point/decomposition range:

Partition coefficient: n-octanol/water: Not stated.

Vapour pressure

Vapour pressure (50°C): Not relevant.

Density and/or relative density

Density: 0.99

Version 4.2 (16/11/2022) - Page 7/10

PEBEO SAS

Glazing resin bio: part B - FDS215

#### |> Relative vapour density

Vapour density:

Not stated.

#### 9.2. Other information

No data available.

### 9.2.1. Information with regard to physical hazard classes

No data available.

#### 9.2.2. Other safety characteristics

No data available.

### >SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### > 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### |> 10.4. Conditions to avoid

No data available.

#### |> 10.5. Incompatible materials

No data available.

#### |> 10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

### >SECTION 11 : TOXICOLOGICAL INFORMATION

### > 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful if swallowed.

Harmful in contact with skin.

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May cause an allergic reaction by skin contact.

### 11.1.1. Substances

No toxicological data available for the substances.

### 11.1.2. Mixture

No toxicological data available for the mixture.

### 11.2. Information on other hazards

### **SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

Version 4.2 (16/11/2022) - Page 8/10

PEBEO SAS

#### Glazing resin bio: part B - FDS215

### 12.1. Toxicity

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

No data available.

# 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

No data available.

#### 12.6. Endocrine disrupting properties

No data available.

#### 12.7. Other adverse effects

No data available.

#### SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

### Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste):

20 01 27 \* paint, inks, adhesives and resins containing dangerous substances

15 01 02 plastic packaging

### >SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

# 14.1. UN number or ID number

# |> 14.2. UN proper shipping name

UN2735=AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine)

# 14.3. Transport hazard class(es)

- Classification:



### 14.4. Packing group

II

### 14.5. Environmental hazards

Tunnel

Cat.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Code

Version 4.2 (16/11/2022) - Page 9/10

EO

PEBEO SAS

|>

### Glazing resin bio: part B - FDS215

Ident.

### 14.6. Special precautions for user

ADR/RID Class

		8	C7	II	8	80	1 L	274	E2	2	E
_	IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage	Segregation	ĺ
-									Handling		ĺ
		8	-	II	1 L	F-A. S-B	274	E2	Category A	SGG18 SG35	ĺ
	IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	[
		8	-	II	851	1 L	855	30 L	A3 A803	E2	ĺ
		8	-	II	Y840	0.5 L	-	-	A3 A803	E2	ĺ

LO

Provis.

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

Pack gr. Label

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

#### >SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/1182 (ATP 15)

#### > - Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

#### - Particular provisions :

No data available.

# 15.2. Chemical safety assessment

No data available.

### >SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

### Wording of the phrases mentioned in section 3:

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### |> Abbreviations :

Item Numbers: 01048-1014, 01048-1015, 01048-1023

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

UFI: Unique formulation identifier.

Version 4.2 (16/11/2022) - Page 10/10

Glazing resin bio: part B - FDS215

STEL: Short-term exposure limit TWA: Time Weighted Averages

TLV: Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS05: Corrosion

GHS07: Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.

|> Modification compared to the previous version

Références	Désignation Référence
766183	GÉDÉO KIT 750ML RÉSINE GLACAGE BIO
766181	GÉDÉO KIT 150ML RÉSINE GLACAGE BIO
107435	GEDEO KIT RESINE GLACAGE BIO 150ML /SCA
FDS215	Résine glaçage bio : partie B
766182	GÉDÉO KIT 300ML RÉSINE GLACAGE BIO
766189	GÉDÉO KIT 45ML RÉSINE GLACAGE BIO

Item Numbers: 01048-1014, 01048-1015, 01048-1023 Page 22 of 22