

**1 Identification**

- **Product identifier**
- **Trade name:** *MONTANA GOLD Spray Paint all colors, fluo and shock*
- **Article number:**  
283604 - 285844, 285899, 285905, 285929, 364945, 419331, 419348, 419355, 419362, 419379, 419386, 419393, 419409, 419416, 419423, 419430, 419447, 419454, 419461, 419478, 430060, 439537
- **Application of the substance / the mixture** *Lacquer*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*MONTANA CANS*  
*Häusserstr. 36*  
*D-69115 Heidelberg*  
*Tel. +49-6221-36333-30*  
*Fax +49-6221-36333-33*  
*info@montana-cans.de*  
*www.montana-cans.com*
- **Information department:** *Department Product Safety*
- **Emergency telephone number:**  
*Tel.: +49 6266-75-310*  
*Fax +49 6266-75-362*  
*(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)*

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS02 Flame

*Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.*

GHS07

*Eye Irrit. 2A H319 Causes serious eye irritation.*  
*STOT SE 3 H336 May cause drowsiness or dizziness.*

- **Label elements**
- **GHS label elements**  
*The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**  
*ethyl acetate*  
*acetone*
- **Hazard statements**  
*Extremely flammable aerosol. Pressurized container: May burst if heated.*  
*Causes serious eye irritation.*  
*May cause drowsiness or dizziness.*
- **Precautionary statements**  
*Keep away from heat/sparks/open flames/hot surfaces. No smoking.*  
*Do not spray on an open flame or other ignition source.*

(Contd. on page 2)

USA

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 1)

Do not pierce or burn, even after use.  
 Do not breathe spray.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents / container in accordance with local/regional/national/international regulations.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients**

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 115-10-6 RTECS: PM 4780000	dimethyl ether Flam. Gas 1, H220 Press. Gas, H280	12.5-<20%
CAS: 141-78-6 RTECS: AH 5425000	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	12.5-<20%
CAS: 67-64-1 RTECS: AL 3150000	acetone Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	5-<10%
CAS: 74-98-6 RTECS: TX 2275000	propane Flam. Gas 1, H220 Press. Gas, H280	5-<10%
CAS: 106-97-8 RTECS: EJ 4200000	butane Flam. Gas 1, H220 Press. Gas, H280	5-<10%
CAS: 13463-67-7	titanium dioxide Carc. 2, H351	2.5-<5.0%
CAS: 64742-94-5	Solvent naphtha (petroleum), heavy arom. Asp. Tox. 1, H304	2.5-<5.0%
CAS: 108-65-6	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5-<5.0%
CAS: 9004-70-0	cellulose nitrate Flam. Sol. 1, H228	2.5-<5.0%
	xylene, mixture of isomers Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-<5.0%

(Contd. on page 3)

USA

Trade name: **MONTANA GOLD Spray Paint all colors, fluo and shock**

		(Contd. of page 2)
CAS: 75-28-5 RTECS: TZ 4300000	isobutane ⚠ Flam. Gas 1, H220 ⚠ Press. Gas, H280	<2.5%
CAS: 67-63-0 RTECS: NT 8050000	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	<2.5%
CAS: 100-41-4 RTECS: DA 0700000	ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332	≤0.5%

**Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex IA 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

#### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters** -

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.

(Contd. on page 4)

USA

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 3)

- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

<b>115-10-6 dimethyl ether</b>	
WEEL	Long-term value: 1000 ppm
<b>141-78-6 ethyl acetate</b>	
PEL	Long-term value: 1400 mg/m <sup>3</sup> , 400 ppm
REL	Long-term value: 1400 mg/m <sup>3</sup> , 400 ppm
TLV	Long-term value: 1440 mg/m <sup>3</sup> , 400 ppm
<b>67-64-1 acetone</b>	
PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm
	BEI
<b>74-98-6 propane</b>	
PEL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV	refer to Appendix F in TLVs&BEIs book; NIC-EX
<b>106-97-8 butane</b>	
REL	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TLV	Short-term value: (2370) mg/m <sup>3</sup> , (1000) ppm NIC-EX
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
WEEL	Long-term value: 50 ppm
<b>xylene, mixture of isomers</b>	
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm
	BEI

(Contd. on page 5)

USA

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 4)

**75-28-5 isobutane**

TLV Short-term value: (2370) mg/m<sup>3</sup>, (1000) ppm  
NIC-EX

**67-63-0 propan-2-ol**

PEL Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
REL Short-term value: 1225 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
TLV Short-term value: 984 mg/m<sup>3</sup>, 400 ppm  
Long-term value: 492 mg/m<sup>3</sup>, 200 ppm  
BEI

**100-41-4 ethylbenzene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
REL Short-term value: 545 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
TLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm  
BEI

**· Ingredients with biological limit values:****67-64-1 acetone**

BEI 50 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Acetone (nonspecific)

**xylene, mixture of isomers**

BEI 1.5 g/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Methylhippuric acids

**67-63-0 propan-2-ol**

BEI 40 mg/L  
Medium: urine  
Time: end of shift at end of workweek  
Parameter: Acetone (background, nonspecific)

**100-41-4 ethylbenzene**

BEI 0.7 g/g creatinine  
Medium: urine  
Time: end of shift at end of workweek  
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
Medium: end-exhaled air  
Time: not critical  
Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

**· Breathing equipment:**

Filter AX

(Contd. on page 6)

USA

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 5)

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products



Protective gloves

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Butyl rubber, BR

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Safety glasses

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Aerosol

Color:

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

Not applicable, as aerosol.

· **Flash point:**

Not applicable, as aerosol.

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

235 °C (455 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:

2.1 Vol %

Upper:

18.6 Vol %

· **Vapor pressure at 20 °C (68 °F):**

5200 hPa (3900 mm Hg)

· **Density at 20 °C (68 °F):**

0.96 g/cm<sup>3</sup> (8.011 lbs/gal)

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

(Contd. on page 7)

USA

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 6)

· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC-USA</b>	62.2 % 652.0 g/l / 5.44 lb/gl
<b>Solids content:</b>	36.2 %
· <b>Other information</b>	No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

<b>115-10-6 dimethyl ether</b>		
Inhalative	LC50/4 h	308 mg/l (rat)
<b>141-78-6 ethyl acetate</b>		
Oral	LD50	5620 mg/kg (rabbit)
Inhalative	LC50/4 h	1600 mg/l (rat)
<b>67-64-1 acetone</b>		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
<b>106-97-8 butane</b>		
Inhalative	LC50/4 h	658 mg/l (rat)
<b>13463-67-7 titanium dioxide</b>		
Oral	LD50	>20000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
<b>64742-94-5 Solvent naphtha (petroleum), heavy arom.</b>		
Oral	LD50	>5000 mg/kg (rat)
Inhalative	LC50	<1-10 mg/l (oncorhynchus mykiss / Regenbogenforelle)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
Oral	LD50	8532 mg/kg (rat)

(Contd. on page 8)

USA

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 7)

Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50	134 mg/l (oncorhynchus mykiss / Regenbogenforelle) (OECD-Prüfrichtlinie203)
	LC50/4 h	35.7 mg/l (rat)
<b>xylene, mixture of isomers</b>		
Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	6350 mg/l (rat)
<b>67-63-0 propan-2-ol</b>		
Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)
<b>100-41-4 ethylbenzene</b>		
Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Vapors have narcotic effect.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
	xylene, mixture of isomers	3
67-63-0	propan-2-ol	3
7631-86-9	silicon dioxide, chemically prepared	3
100-41-4	ethylbenzene	2B
14808-60-7	Quartz (SiO <sub>2</sub> )	1
100-42-5	styrene	2B

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

· **Toxicity**

· **Aquatic toxicity:**

<b>64742-94-5 Solvent naphtha (petroleum), heavy arom.</b>	
EC50 (24h)	>10-100 mg/l (bacteria)
	>1-10 mg/l (daphnia)
	>1-10 mg/l (Pseudokirchneriella subcapitata)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
EC 10	>1000 mg/l (bel) (ISO 8192)
EC50 / 48h	>500 mg/l (daphnia magna / Wasserfloh) (Richtlinie 67/548/EWG. Anhang V, C.2))

(Contd. on page 9)

USA



Printing date 03/28/2017

Reviewed on 03/28/2017

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 8)

EC50/72h	>1000 mg/l ( <i>Selenastrum capricornutum</i> ) (OECD-Prüfrichtlinie 201)
NOEC	≥100 mg/l ( <i>daphnia magna</i> / Wasserfloh) (OECD-Prüfrichtlinie 202)
	47.5 mg/l ( <i>Oryzias latipes</i> ) (OECD-Prüfrichtlinie 204)

**xylene, mixture of isomers**

LC50/96h	7.6 mg/l ( <i>oncorhynchus mykiss</i> / Regenbogenforelle)
EC50 (24h)	>175 mg/l (bacteria)
EC50 / 48h	3.82 mg/l ( <i>daphnia magna</i> / Wasserfloh)
EC50/72h	4.7 mg/l ( <i>Pseudokirchneriella subcapitata</i> )

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** UN1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

· **Transport hazard class(es)**· **DOT**

- **Class** 2.1

(Contd. on page 10)

USA

Printing date 03/28/2017

Reviewed on 03/28/2017

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 9)

· **Label** 2.1· **ADR**· **Class** 2 5F Gases· **Label** 2.1· **IMDG, IATA**· **Class** 2.1· **Label** 2.1· **Packing group**· **DOT, ADR, IMDG, IATA** Void· **Environmental hazards:** Not applicable.· **Special precautions for user** Warning: Gases· **Danger code (Kemler):** -· **EMS Number:** F-D,S-U· **Stowage Code** SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.· **Transport/Additional information:**· **ADR**· **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity· **IMDG**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1**15 Regulatory information**· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

(Contd. on page 11)

USA

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 10)

· Section 313 (Specific toxic chemical listings):

	xylene, mixture of isomers
67-63-0	propan-2-ol
100-41-4	ethylbenzene
95-63-6	1,2,4-trimethylbenzene
98-82-8	cumene
85-44-9	phthalic anhydride
100-42-5	styrene

· TSCA (Toxic Substances Control Act):

106-97-8	butane
141-78-6	ethyl acetate
67-64-1	acetone
74-98-6	propane
13463-67-7	titanium dioxide
64742-94-5	Solvent naphtha (petroleum), heavy arom.
108-65-6	2-methoxy-1-methylethyl acetate
9004-70-0	cellulose nitrate
67-63-0	propan-2-ol
7631-86-9	silicon dioxide, chemically prepared
100-41-4	ethylbenzene
64742-95-6	Solvent naphtha (petroleum), light arom.
95-63-6	1,2,4-trimethylbenzene
123-86-4	n-butyl acetate
108-67-8	mesitylene

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1	acetone	I
	xylene, mixture of isomers	I
100-41-4	ethylbenzene	D
98-82-8	cumene	CBD

· TLV (Threshold Limit Value established by ACGIH)

67-64-1	acetone	A4
13463-67-7	titanium dioxide	A4
	xylene, mixture of isomers	A4
67-63-0	propan-2-ol	A4
100-41-4	ethylbenzene	A3
14808-60-7	Quartz (SiO2)	A2

(Contd. on page 12)

USA

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 11)

85-44-9	phthalic anhydride	A4
100-42-5	styrene	A4
<b>· MAK (German Maximum Workplace Concentration)</b>		
13463-67-7	titanium dioxide	3A
100-41-4	ethylbenzene	3A
14808-60-7	Quartz (SiO <sub>2</sub> )	I
100-42-5	styrene	5
<b>· NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
13463-67-7	titanium dioxide	
14808-60-7	Quartz (SiO <sub>2</sub> )	

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H228 Flammable solid.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Date of preparation / last revision** 03/28/2017 / 3

### · Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- BEI: Biological Exposure Limit
- Flam. Gas 1: Flammable gases – Category 1
- Flam. Aerosol 1: Aerosols – Category 1
- Press. Gas: Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 13)

USA

**Safety Data Sheet**

MSDS for #01425 - MONTANA GOLD ACRYLIC *acc. to OSHA HCS*

Printing date 03/28/2017

Reviewed on 03/28/2017

**Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 12)

- Flam. Liq. 3: Flammable liquids – Category 3*
- Flam. Sol. 1: Flammable solids – Category 1*
- Acute Tox. 4: Acute toxicity – Category 4*
- Skin Irrit. 2: Skin corrosion/irritation – Category 2*
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*
- Carc. 2: Carcinogenicity – Category 2*
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*
- Asp. Tox. 1: Aspiration hazard – Category 1*

USA