

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: EX014H0102 - MTN HARDCORE GOLD

Other means of identification:

UFI: SOC0-P0NM-K00S-GAMP

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Spray paint

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

MONTANA COLORS, S.L.

Pol. Ind. Pla de les Vives C/ Anaïs Nin 6
 08295 Sant Vicenç de Castellet - Barcelona - España
 Phone: +34 938332760 (9:00- 16:00h GMT +1:00)
 msds@montanacolors.com
<https://www.montanacolors.com>

1.4 Emergency telephone number: +34 938332760 (Mon- frid 9:00- 16:00h GMT +1:00)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Pressurised container: May burst if heated., H229

Aerosol 1: Flammable aerosols, Category 1, H222

Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Irrit. 2: Eye irritation, Category 2, H319

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Aerosol 1: H229 - Pressurised container: May burst if heated.

Aerosol 1: H222 - Extremely flammable aerosol.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe spray.

P271: Use only outdoors or in a well-ventilated area.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents/container according to the separated collection system used in your municipality.

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 2: HAZARDS IDENTIFICATION (continued)

Substances that contribute to the classification

Reaction mass of ethylbenzene and m-xylene and p-xylene

UFI: SOC0-P0NM-K00S-GAMP

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aerosol

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | | Concentration |
|--|--|---|----------------------|
| CAS: Non-applicable EC: 905-562-9 Index: Non-applicable REACH: 01-211955267-33-XXXX | Reaction mass of ethylbenzene and m-xylene and p-xylene (1) | Self-classified | 30 - <50 % |
| | Regulation 1272/2008 | Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger | ! 🔥 🚫 |
| CAS: 106-97-8 EC: 203-448-7 Index: 601-004-00-0 REACH: 01-2119474691-32-XXXX | Butane (2) | ATP CLP00 | 10 - <20 % |
| | Regulation 1272/2008 | Flam. Gas 1A: H220; Press. Gas: H280 - Danger | 🔥 🔮 |
| CAS: 74-98-6 EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21-XXXX | Propane (2) | ATP CLP00 | 10 - <20 % |
| | Regulation 1272/2008 | Flam. Gas 1A: H220; Press. Gas: H280 - Danger | 🔥 🔮 |
| CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX | acetone (1) | ATP CLP00 | 5 - <10 % |
| | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger | ! 🔥 |
| CAS: 7440-50-8 EC: 231-159-6 Index: 029-024-00-X REACH: 01-2119480154-42-XXXX | Copper powder (1) | Self-classified | 5 - <10 % |
| | Regulation 1272/2008 | Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 2: H411 - Warning | ! 🔮 |
| CAS: 75-28-5 EC: 200-857-2 Index: 601-004-00-0 REACH: 01-2119485395-27-XXXX | Isobutane (2) | ATP CLP00 | 5 - <10 % |
| | Regulation 1272/2008 | Flam. Gas 1A: H220; Press. Gas: H280 - Danger | 🔥 🔮 |
| CAS: 7440-66-6 EC: 231-175-3 Index: 030-002-00-7 REACH: 01-2119467174-37-XXXX | Zinc powder - zinc dust (stabilised) (< 30-35 µm) (1) | Self-classified | 1 - <2,5 % |
| | Regulation 1272/2008 | Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Flam. Sol. 1: H228 - Danger | 🔥 🔮 |

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

(2) Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

| Identification | M-factor | |
|---------------------------------|----------|----|
| Copper powder CAS: 7440-50-8 | Acute | 10 |
| EC: 231-159-6 | Chronic | 1 |

SECTION 4: FIRST AID MEASURES

- CONTINUED ON NEXT PAGE -



SECTION 4: FIRST AID MEASURES (continued)

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

- CONTINUED ON NEXT PAGE -



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the split product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

It is recommended to transfer at a slow speed to avoid the creation of electrostatic charges that could affect flammable products. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 120 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification | | | Occupational exposure limits | | |
|----------------------------|--------------|---------|------------------------------|--|--|
| acetone | IOELV (8h) | 500 ppm | 1210 mg/m ³ | | |
| CAS: 67-64-1 EC: 200-662-2 | IOELV (STEL) | | | | |

DNEL (Workers):

| Identification | Short exposure | | Long exposure | |
|---|----------------|-----------------------|------------------------|------------------------|
| | Systemic | Local | Systemic | Local |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | Oral | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 212 mg/kg |
| | Inhalation | 442 mg/m ³ | 442 mg/m ³ | 221 mg/m ³ |
| acetone CAS: 67-64-1 EC: 200-662-2 | Oral | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 186 mg/kg |
| | Inhalation | Non-applicable | 2420 mg/m ³ | 1210 mg/m ³ |
| Copper powder CAS: 7440-50-8 EC: 231-159-6 | Oral | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | 273 mg/kg | Non-applicable | 137 mg/kg |
| | Inhalation | Non-applicable | Non-applicable | Non-applicable |
| Zinc powder - zinc dust (stabilised) (< 30-35 µm) CAS: 7440-66-6 EC: 231-175-3 | Oral | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 83 mg/kg |
| | Inhalation | Non-applicable | Non-applicable | 5 mg/m ³ |

DNEL (General population):

| Identification | Short exposure | | Long exposure | |
|---|----------------|-----------------------|-----------------------|------------------------|
| | Systemic | Local | Systemic | Local |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | Oral | Non-applicable | 12,5 mg/kg | Non-applicable |
| | Dermal | Non-applicable | 125 mg/kg | Non-applicable |
| | Inhalation | 260 mg/m ³ | 260 mg/m ³ | 65,3 mg/m ³ |
| acetone CAS: 67-64-1 EC: 200-662-2 | Oral | Non-applicable | 62 mg/kg | Non-applicable |
| | Dermal | Non-applicable | 62 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 200 mg/m ³ | Non-applicable |
| Copper powder CAS: 7440-50-8 EC: 231-159-6 | Oral | Non-applicable | 0,041 mg/kg | Non-applicable |
| | Dermal | 273 mg/kg | Non-applicable | 137 mg/kg |
| | Inhalation | Non-applicable | 1 mg/m ³ | Non-applicable |
| Zinc powder - zinc dust (stabilised) (< 30-35 µm) CAS: 7440-66-6 EC: 231-175-3 | Oral | Non-applicable | 0,83 mg/kg | Non-applicable |
| | Dermal | Non-applicable | 83 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 2,5 mg/m ³ | Non-applicable |

PNEC:

| Identification | | | | |
|---|--------------|----------------|-------------------------|-------------|
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | STP | 6,58 mg/L | Fresh water | 0,327 mg/L |
| | Soil | 2,31 mg/kg | Marine water | 0,327 mg/L |
| | Intermittent | 0,327 mg/L | Sediment (Fresh water) | 12,46 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 12,46 mg/kg |
| acetone CAS: 67-64-1 EC: 200-662-2 | STP | 100 mg/L | Fresh water | 10,6 mg/L |
| | Soil | 29,5 mg/kg | Marine water | 1,06 mg/L |
| | Intermittent | 21 mg/L | Sediment (Fresh water) | 30,4 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 3,04 mg/kg |
| Copper powder CAS: 7440-50-8 EC: 231-159-6 | STP | 0,23 mg/L | Fresh water | 0,0078 mg/L |
| | Soil | 65 mg/kg | Marine water | 0,0052 mg/L |
| | Intermittent | Non-applicable | Sediment (Fresh water) | 87 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 676 mg/kg |

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification | | | | | |
|---|--------------|----------------|-------------------------|-------------|--|
| Zinc powder - zinc dust (stabilised) (< 30-35 µm) | STP | 0,1 mg/L | Fresh water | 0,0206 mg/L | |
| CAS: 7440-66-6 | Soil | 106,8 mg/kg | Marine water | 0,0061 mg/L | |
| EC: 231-175-3 | Intermittent | Non-applicable | Sediment (Fresh water) | 235,6 mg/kg | |
| | Oral | Non-applicable | Sediment (Marine water) | 121 mg/kg | |

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|--|---|---|---|
|  | Filter mask for gases, vapours and particles |  | EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998 | Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected. |

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|--|---|--|
|  | NON-disposable chemical protective gloves |  | EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010 | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|-------------|---|---|---|
|  | Face shield |  | EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|---|---|---|---|
|  | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties |  | EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
|  | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties |  | EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| | |
|---------------------------|---------------------------|
| V.O.C. (Supply): | 75,75 % weight |
| V.O.C. density at 20 °C: | 598,43 kg/m³ (598,43 g/L) |
| Average carbon number: | 6,81 |
| Average molecular weight: | 94,75 g/mol |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|--|
| Physical state at 20 °C: | Aerosol |
| Appearance: | Not available |
| Colour: |  Gold |
| Odour: | Not available |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|--|----------------------|
| Boiling point at atmospheric pressure: | -1 °C (Propellant) |
| Vapour pressure at 20 °C: | Non-applicable * |
| Vapour pressure at 50 °C: | <300000 Pa (300 kPa) |
| Evaporation rate at 20 °C: | Non-applicable * |

Product description:

| | |
|--|------------------|
| Density at 20 °C: | 790 kg/m³ |
| Relative density at 20 °C: | 0,79 |
| Dynamic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 40 °C: | Non-applicable * |
| Concentration: | Non-applicable * |
| pH: | Non-applicable * |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Non-applicable * |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |
| Recipient pressure: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Flammability:

| | |
|----------------------------|---------------------|
| Flash Point: | Non-applicable |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 365 °C (Propellant) |
| Lower flammability limit: | Non-applicable * |
| Upper flammability limit: | Non-applicable * |

Particle characteristics:

| | |
|-----------------------------|----------------|
| Median equivalent diameter: | Non-applicable |
|-----------------------------|----------------|

9.2 Other information:

Information with regard to physical hazard classes:

| | |
|--|------------------|
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |
| Corrosive to metals: | Non-applicable * |
| Heat of combustion: | Non-applicable * |
| Aerosols-total percentage (by mass) of flammable components: | Non-applicable * |

Other safety characteristics:

| | |
|---------------------------|------------------|
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Precaution | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Reaction mass of ethylbenzene and m-xylene and p-xylene (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|---|-----------------|------------------|--------|
| Copper powder | LD50 oral | 500 mg/kg (ATEI) | |
| CAS: 7440-50-8 | LD50 dermal | >2000 mg/kg | |
| EC: 231-159-6 | LC50 inhalation | >5 mg/L | |
| Zinc powder - zinc dust (stabilised) (< 30-35 µm) | LD50 oral | >2000 mg/kg | |
| CAS: 7440-66-6 | LD50 dermal | >2000 mg/kg | |
| EC: 231-175-3 | LC50 inhalation | >5 mg/L | |
| acetone | LD50 oral | 5800 mg/kg | Rat |
| CAS: 67-64-1 | LD50 dermal | 7426 mg/kg | Rabbit |
| EC: 200-662-2 | LC50 inhalation | 76 mg/L (4 h) | Rat |

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

| Identification | Acute toxicity | | Genus |
|---|-----------------|----------------|-------|
| Reaction mass of ethylbenzene and m-xylene and p-xylene | LD50 oral | 5627 mg/kg | Mouse |
| CAS: Non-applicable | LD50 dermal | 1100 mg/kg | Rat |
| EC: 905-562-9 | LC50 inhalation | 11 mg/L (ATEi) | |
| Butane | LD50 oral | >2000 mg/kg | |
| CAS: 106-97-8 | LD50 dermal | >2000 mg/kg | |
| EC: 203-448-7 | LC50 inhalation | 658 mg/L (4 h) | Rat |
| Propane | LD50 oral | >2000 mg/kg | |
| CAS: 74-98-6 | LD50 dermal | >2000 mg/kg | |
| EC: 200-827-9 | LC50 inhalation | >5 mg/L | |
| Isobutane | LD50 oral | >2000 mg/kg | |
| CAS: 75-28-5 | LD50 dermal | >2000 mg/kg | |
| EC: 200-857-2 | LC50 inhalation | >5 mg/L | |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

| Identification | Concentration | | Species | Genus |
|---|---------------|------------------|-----------------------|------------|
| Reaction mass of ethylbenzene and m-xylene and p-xylene | LC50 | >10 - 100 (96 h) | | Fish |
| CAS: Non-applicable | EC50 | >10 - 100 (48 h) | | Crustacean |
| EC: 905-562-9 | EC50 | >10 - 100 (72 h) | | Algae |
| acetone | LC50 | 5540 mg/L (96 h) | Oncorhynchus mykiss | Fish |
| CAS: 67-64-1 | EC50 | 8800 mg/L (48 h) | Daphnia pulex | Crustacean |
| EC: 200-662-2 | EC50 | 3400 mg/L (48 h) | Chlorella pyrenoidosa | Algae |
| Copper powder | LC50 | >0.1 - 1 (96 h) | | Fish |
| CAS: 7440-50-8 | EC50 | >0.1 - 1 (48 h) | | Crustacean |
| EC: 231-159-6 | EC50 | >0.1 - 1 (72 h) | | Algae |

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Concentration | | Species | Genus |
|--|---------------|------------------|---------------|------------|
| Zinc powder - zinc dust (stabilised) (< 30-35 µm) CAS: 7440-66-6 EC: 231-175-3 | LC50 | 0,31 mg/L (96 h) | N/A | Fish |
| | EC50 | 1,22 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | Non-applicable | | |

Chronic toxicity:

| Identification | Concentration | | Species | Genus |
|--|---------------|----------------|---------------------|------------|
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | NOEC | 1,3 mg/L | Oncorhynchus mykiss | Fish |
| | NOEC | 1,17 mg/L | Ceriodaphnia dubia | Crustacean |
| acetone CAS: 67-64-1 EC: 200-662-2 | NOEC | Non-applicable | | |
| | NOEC | 2212 mg/L | Daphnia magna | Crustacean |
| Zinc powder - zinc dust (stabilised) (< 30-35 µm) CAS: 7440-66-6 EC: 231-175-3 | NOEC | 0,44 mg/L | Oncorhynchus mykiss | Fish |
| | NOEC | 0,031 mg/L | Daphnia magna | Crustacean |

12.2 Persistence and degradability:

| Identification | Degradability | | Biodegradability | |
|--|---------------|----------------|------------------|----------|
| | BOD5 | Non-applicable | Concentration | 100 mg/L |
| acetone CAS: 67-64-1 EC: 200-662-2 | COD | Non-applicable | Period | 28 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 96 % |

12.3 Bioaccumulative potential:

| Identification | Bioaccumulation potential | | |
|---|---------------------------|----------|--|
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | BCF | 9 | |
| | Pow Log | 2.77 | |
| | Potential | Low | |
| Butane CAS: 106-97-8 EC: 203-448-7 | BCF | 33 | |
| | Pow Log | 2.89 | |
| | Potential | Moderate | |
| Propane CAS: 74-98-6 EC: 200-827-9 | BCF | 13 | |
| | Pow Log | 2.86 | |
| | Potential | Low | |
| acetone CAS: 67-64-1 EC: 200-662-2 | BCF | 1 | |
| | Pow Log | -0.24 | |
| | Potential | Low | |
| Isobutane CAS: 75-28-5 EC: 200-857-2 | BCF | 27 | |
| | Pow Log | 2.76 | |
| | Potential | Low | |

12.4 Mobility in soil:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Absorption/desorption | | Volatility | |
|--|-----------------------|----------------------|------------|----------------------------------|
| Butane CAS: 106-97-8 EC: 203-448-7 | Koc | 900 | Henry | 96258,75 Pa·m ³ /mol |
| | Conclusion | Low | Dry soil | Yes |
| | Surface tension | 1,187E-2 N/m (25 °C) | Moist soil | Yes |
| Propane CAS: 74-98-6 EC: 200-827-9 | Koc | 460 | Henry | 71636,78 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | 7,02E-3 N/m (25 °C) | Moist soil | Yes |
| acetone CAS: 67-64-1 EC: 200-662-2 | Koc | 1 | Henry | 2,93 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | Yes |
| | Surface tension | 2,304E-2 N/m (25 °C) | Moist soil | Yes |
| Isobutane CAS: 75-28-5 EC: 200-857-2 | Koc | 35 | Henry | 120576,75 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | Yes |
| | Surface tension | 9,84E-3 N/m (25 °C) | Moist soil | Yes |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 16 05 04* | gases in pressure containers (including halons) containing hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN1950
14.2 UN proper shipping name: AEROSOLS
14.3 Transport hazard class(es): 2
 Labels: 2.1
14.4 Packing group: N/A
14.5 Environmental hazards: Yes
14.6 Special precautions for user
 Special regulations: 190, 327, 344, 625
 Tunnel restriction code: D
 Physico-Chemical properties: see section 9
 Limited quantities: 1 L
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:



14.1 UN number or ID number: UN1950
14.2 UN proper shipping name: AEROSOLS
14.3 Transport hazard class(es): 2
 Labels: 2.1
14.4 Packing group: N/A
14.5 Marine pollutant: Yes
14.6 Special precautions for user
 Special regulations: 63, 959, 190, 277, 327, 344
 EmS Codes: F-D, S-U
 Physico-Chemical properties: see section 9
 Limited quantities: 1 L
 Segregation group: Non-applicable
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



14.1 UN number or ID number: UN1950
14.2 UN proper shipping name: AEROSOLS
14.3 Transport hazard class(es): 2
 Labels: 2.1
14.4 Packing group: N/A
14.5 Environmental hazards: Yes
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Copper powder (Product-type 2, 5, 11, 21)

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EX014H0102 - MTN HARDCORE GOLD



SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|-----------------------|-------------------------|-------------------------|
| P3a | FLAMMABLE AEROSOLS | 150 | 500 |
| E1 | ENVIRONMENTAL HAZARDS | 100 | 200 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

- H400: Very toxic to aquatic life.
- H411: Toxic to aquatic life with long lasting effects.
- H315: Causes skin irritation.
- H335: May cause respiratory irritation.
- H373: May cause damage to organs through prolonged or repeated exposure.
- H229: Pressurised container: May burst if heated.
- H222: Extremely flammable aerosol.
- H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H302 - Harmful if swallowed.
 Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
 Aquatic Acute 1: H400 - Very toxic to aquatic life.
 Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
 Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
 Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
 Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
 Eye Irrit. 2: H319 - Causes serious eye irritation.
 Flam. Gas 1A: H220 - Extremely flammable gas.
 Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
 Flam. Liq. 3: H226 - Flammable liquid and vapour.
 Flam. Sol. 1: H228 - Flammable solid.
 Press. Gas: H280 - Contains gas under pressure, may explode if heated.
 Skin Irrit. 2: H315 - Causes skin irritation.
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
 STOT SE 3: H335 - May cause respiratory irritation.
 STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Aquatic Acute 1: Calculation method
 Aquatic Chronic 2: Calculation method
 Skin Irrit. 2: Calculation method
 STOT SE 3: Calculation method
 STOT RE 2: Calculation method
 Aerosol 1: Calculation method
 Aerosol 1: Calculation method
 Eye Irrit. 2: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
 IMDG: International maritime dangerous goods code
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organisation
 COD: Chemical Oxygen Demand
 BOD5: 5day biochemical oxygen demand
 BCF: Bioconcentration factor
 LD50: Lethal Dose 50
 LC50: Lethal Concentration 50
 EC50: Effective concentration 50
 LogPOW: Octanol/water partition coefficient
 Koc: Partition coefficient of organic carbon
 UFI: unique formula identifier
 IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -