






































































		MTN 94 Code: AC0140003		  									
Version: 7		Revision: 30/06/2017		Previous revision: 23/06/2017									
Date of printing: 26/10/2018													
<b>SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING</b>													
1.1	<u>PRODUCT IDENTIFIER:</u>		MTN 94 Code: AC0140003										
1.2	<u>RELEVANT IDENTIFIED USES AND USES ADVISED AGAINST:</u>		[ ] Industrial [X] Professional [X] Consumers										
	<u>Intended uses (main technical functions):</u> Paint. <u>Sectors of use:</u> Consumer uses (SU21). <u>Uses advised against:</u> This product is not recommended for any use or sector of use industrial, professional or consume other than those previously listed as 'Intended or identified uses'. <u>Restrictions on manufacture, placing on market and use:</u> Nor restricted.												
1.3	<u>DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:</u>												
	MONTANA COLORS, S.L. Pol. Ind. Pla de les Vives - c/An aïs Nin 6 - 08295 Sant Vicenç de Castellet (Barcelona) ESPAÑA Phone: +34 93 8332760 - Fax: +34 93 8332761 - www.montanacolors.com <u>E-mail address of the person responsible for the safety data sheet:</u> e-mail: msds@montanacolors.com												
1.4	<u>EMERGENCY TELEPHONE NUMBER:</u> +34 93 8332787 (9:00-17:00 h.) (working hours)												
<b>SECTION 2 : HAZARDS IDENTIFICATION</b>													
2.1	<u>CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:</u>												
	<u>HMIS Hazard Ratings:</u>		<table border="1"> <tr><td>3</td><td>HEALTH</td></tr> <tr><td>4</td><td>FLAMMABILITY</td></tr> <tr><td>1</td><td>REACTIVITY</td></tr> <tr><td>G</td><td>PPE</td></tr> </table>			3	HEALTH	4	FLAMMABILITY	1	REACTIVITY	G	PPE
3	HEALTH												
4	FLAMMABILITY												
1	REACTIVITY												
G	PPE												
			(3) Serious chronic health hazard (4) Very high flammability hazard (1) Low physicochemical hazard (G) Safety glasses, gloves and vapor respirator										
	Note: HMIS Hazard Ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of the material, all the information contained in this SDS must be considered.												
	<u>Classification in accordance with Regulation (EU) No. 1272/2008-1221/2015 (CLP):</u> DANGER: Flam. Aerosol 1:H222+H229   Skin Irrit. 2:H315   Eye Irrit. 2:H319   STOT SE (narcosis) 3:H336   STOT RE 2:H373i   EUH066												
	<u>Danger class</u>	<u>Classification of the mixture</u>	<u>Cat.</u>	<u>Routes of exposure</u>	<u>Target organs</u>								
	<u>Physicochemical:</u> 	Flam. Aerosol 1:H222+H229 Skin Irrit. 2:H315 Eye Irrit. 2:H319	Cat.1 Cat.2 Cat.2	- Skin Eyes	- Skin Eyes								
	<u>Human health:</u> 	STOT SE (narcosis) 3:H336 STOT RE 2:H373i EUH066	Cat.3 Cat.2 -	Inhalation Inhalation Skin	CNS Systemic Skin								
	<u>Environment:</u> Not classified				Irritation Irritation Narcosis Damage Dryness, Cracking								
	Full text of hazard statements mentioned is indicated in section 16.												
	Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.												
2.2	<u>LABEL ELEMENTS:</u>												
	  		This product is labelled with the signal word DANGER										
	<u>Hazard statements:</u>												
	H222		Extremely flammable aerosol.										
	H229		Pressurized container: may burst if heated.										
	H373i		May cause damage to organs through prolonged or repeated exposure if inhaled.										
	H319		Causes serious eye irritation.										
	H315		Causes skin irritation.										
	H336		May cause drowsiness or dizziness.										
	<u>Precautionary statements:</u>												
	P101		If medical advice is needed, have product container or label at hand.										
	P102		Keep out of reach of children.										
	P103		Read label before use.										
	P210		Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.										
	P211		Do not spray on an open flame or other ignition source.										
	P251		Do not pierce or burn, even after use.										
	P271-P260d		Use only outdoors or in a well-ventilated area. Do not breathe aerosol.										
	P410+P412		Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.										
	P501a		Dispose of contents/container in accordance with local regulations.										
	<u>Supplementary statements:</u>												
	EUH208		Contains polyhydroxyalkylamides, 2-butanone-oxime. May produce an allergic reaction.										

## SAFETY DATA SHEET

In accordance with the requirements of the OSHA Hazard Communication Standard, 29CFR 1910.1200

Revision: 30/06/2017 Page 2 / 12

	<p>MTN 94 Code: AC0140003</p>	  																		
	<p><u>Substances that contribute to classification:</u> Xylene (mixture of isomers) Ethyl acetate Ethylbenzene</p>																			
2.3	<p><u>OTHER HAZARDS:</u> Hazards which do not result in classification but which may contribute to the overall hazards of the mixture: <u>Other physicochemical hazards:</u> Vapours may form with air a mixture potentially flammable or explosive. <u>Other adverse human health effects:</u> No other relevant adverse effects are known. <u>Other negative environmental effects:</u> No other adverse effects are known.</p>																			
<b>SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS</b>																				
3.1	<p><u>SUBSTANCES:</u> Not applicable (mixture).</p>																			
3.2	<p><u>MIXTURES:</u> This product is a mixture. <u>Chemical description:</u> Aerosol.</p> <p><u>HAZARDOUS INGREDIENTS:</u> Substances taking part in a percentage higher than the exemption limit:</p> <table border="1" data-bbox="138 619 1518 1302"> <tr> <td data-bbox="138 619 284 693">15 &lt; 20 % </td> <td data-bbox="284 619 1518 693"> <p><b>Butane</b> CAS: 106-97-8 , EC: 203-448-7 Danger: Flam. Gas 1:H220   Press. Gas:H280</p> </td> </tr> <tr> <td data-bbox="138 693 284 787">15 &lt; 20 %   </td> <td data-bbox="284 693 1518 787"> <p><b>Xylene (mixture of isomers)</b> CAS: 1330-20-7 , EC: 215-535-7 Danger: Flam. Liq. 3:H226   Acute Tox. (inh.) 4:H332   Acute Tox. (skin) 4:H312   Skin Irrit. 2:H315   Eye Irrit. 2:H319   STOT SE (irrit.) 3:H335   STOT RE 2:H373i   Asp. Tox. 1:H304</p> </td> </tr> <tr> <td data-bbox="138 787 284 861">15 &lt; 20 %  </td> <td data-bbox="284 787 1518 861"> <p><b>Ethyl acetate</b> CAS: 141-78-6 , EC: 205-500-4 Danger: Flam. Liq. 2:H225   Eye Irrit. 2:H319   STOT SE (narcosis) 3:H336   EUH066</p> </td> </tr> <tr> <td data-bbox="138 861 284 934">5 &lt; 10 % </td> <td data-bbox="284 861 1518 934"> <p><b>Propane</b> CAS: 74-98-6 , EC: 200-827-9 Danger: Flam. Gas 1:H220   Press. Gas:H280</p> </td> </tr> <tr> <td data-bbox="138 934 284 1008">5 &lt; 10 % </td> <td data-bbox="284 934 1518 1008"> <p><b>Isobutane</b> CAS: 75-28-5 , EC: 200-857-2 Danger: Flam. Gas 1:H220   Press. Gas:H280</p> </td> </tr> <tr> <td data-bbox="138 1008 284 1102">1 &lt; 2 %   </td> <td data-bbox="284 1008 1518 1102"> <p><b>Ethylbenzene</b> CAS: 100-41-4 , EC: 202-849-4 Danger: Flam. Liq. 2:H225   Acute Tox. (inh.) 4:H332   STOT RE 2:H373iE   Asp. Tox. 1:H304   Aquatic Chronic 3:H412</p> </td> </tr> <tr> <td data-bbox="138 1102 284 1176">1 &lt; 2 %  </td> <td data-bbox="284 1102 1518 1176"> <p><b>n-butyl acetate</b> CAS: 123-86-4 , EC: 204-658-1 Warning: Flam. Liq. 3:H226   STOT SE (narcosis) 3:H336   EUH066</p> </td> </tr> <tr> <td data-bbox="138 1176 284 1249">&lt; 0,15 %  </td> <td data-bbox="284 1176 1518 1249"> <p><b>Polyhydroxyalkylamides</b> EC: 430-050-2 Warning: Skin Sens. 1:H317   Aquatic Chronic 2:H411</p> </td> </tr> <tr> <td data-bbox="138 1249 284 1302">&lt; 0,15 %   </td> <td data-bbox="284 1249 1518 1302"> <p><b>2-butanone-oxime</b> CAS: 96-29-7 , EC: 202-496-6 Danger: Acute Tox. (skin) 4:H312   Eye Dam. 1 H318   Skin Sens. 1:H317   Carc. 2:H351</p> </td> </tr> </table> <p><u>Impurities:</u> Does not contain other components or impurities which will influence the classification of the product.</p> <p><u>Stabilizers:</u> None</p> <p><u>Reference to other sections:</u> For more information on hazardous ingredients, see sections 8, 11, 12 and 16.</p>		15 < 20 % 	<p><b>Butane</b> CAS: 106-97-8 , EC: 203-448-7 Danger: Flam. Gas 1:H220   Press. Gas:H280</p>	15 < 20 %   	<p><b>Xylene (mixture of isomers)</b> CAS: 1330-20-7 , EC: 215-535-7 Danger: Flam. Liq. 3:H226   Acute Tox. (inh.) 4:H332   Acute Tox. (skin) 4:H312   Skin Irrit. 2:H315   Eye Irrit. 2:H319   STOT SE (irrit.) 3:H335   STOT RE 2:H373i   Asp. Tox. 1:H304</p>	15 < 20 %  	<p><b>Ethyl acetate</b> CAS: 141-78-6 , EC: 205-500-4 Danger: Flam. Liq. 2:H225   Eye Irrit. 2:H319   STOT SE (narcosis) 3:H336   EUH066</p>	5 < 10 % 	<p><b>Propane</b> CAS: 74-98-6 , EC: 200-827-9 Danger: Flam. Gas 1:H220   Press. Gas:H280</p>	5 < 10 % 	<p><b>Isobutane</b> CAS: 75-28-5 , EC: 200-857-2 Danger: Flam. Gas 1:H220   Press. Gas:H280</p>	1 < 2 %   	<p><b>Ethylbenzene</b> CAS: 100-41-4 , EC: 202-849-4 Danger: Flam. Liq. 2:H225   Acute Tox. (inh.) 4:H332   STOT RE 2:H373iE   Asp. Tox. 1:H304   Aquatic Chronic 3:H412</p>	1 < 2 %  	<p><b>n-butyl acetate</b> CAS: 123-86-4 , EC: 204-658-1 Warning: Flam. Liq. 3:H226   STOT SE (narcosis) 3:H336   EUH066</p>	< 0,15 %  	<p><b>Polyhydroxyalkylamides</b> EC: 430-050-2 Warning: Skin Sens. 1:H317   Aquatic Chronic 2:H411</p>	< 0,15 %   	<p><b>2-butanone-oxime</b> CAS: 96-29-7 , EC: 202-496-6 Danger: Acute Tox. (skin) 4:H312   Eye Dam. 1 H318   Skin Sens. 1:H317   Carc. 2:H351</p>
15 < 20 % 	<p><b>Butane</b> CAS: 106-97-8 , EC: 203-448-7 Danger: Flam. Gas 1:H220   Press. Gas:H280</p>																			
15 < 20 %   	<p><b>Xylene (mixture of isomers)</b> CAS: 1330-20-7 , EC: 215-535-7 Danger: Flam. Liq. 3:H226   Acute Tox. (inh.) 4:H332   Acute Tox. (skin) 4:H312   Skin Irrit. 2:H315   Eye Irrit. 2:H319   STOT SE (irrit.) 3:H335   STOT RE 2:H373i   Asp. Tox. 1:H304</p>																			
15 < 20 %  	<p><b>Ethyl acetate</b> CAS: 141-78-6 , EC: 205-500-4 Danger: Flam. Liq. 2:H225   Eye Irrit. 2:H319   STOT SE (narcosis) 3:H336   EUH066</p>																			
5 < 10 % 	<p><b>Propane</b> CAS: 74-98-6 , EC: 200-827-9 Danger: Flam. Gas 1:H220   Press. Gas:H280</p>																			
5 < 10 % 	<p><b>Isobutane</b> CAS: 75-28-5 , EC: 200-857-2 Danger: Flam. Gas 1:H220   Press. Gas:H280</p>																			
1 < 2 %   	<p><b>Ethylbenzene</b> CAS: 100-41-4 , EC: 202-849-4 Danger: Flam. Liq. 2:H225   Acute Tox. (inh.) 4:H332   STOT RE 2:H373iE   Asp. Tox. 1:H304   Aquatic Chronic 3:H412</p>																			
1 < 2 %  	<p><b>n-butyl acetate</b> CAS: 123-86-4 , EC: 204-658-1 Warning: Flam. Liq. 3:H226   STOT SE (narcosis) 3:H336   EUH066</p>																			
< 0,15 %  	<p><b>Polyhydroxyalkylamides</b> EC: 430-050-2 Warning: Skin Sens. 1:H317   Aquatic Chronic 2:H411</p>																			
< 0,15 %   	<p><b>2-butanone-oxime</b> CAS: 96-29-7 , EC: 202-496-6 Danger: Acute Tox. (skin) 4:H312   Eye Dam. 1 H318   Skin Sens. 1:H317   Carc. 2:H351</p>																			
<p>Item Numbers: 01440-3100, 01440-3110, 01440-3120, 01440-4030, 01440-4040, 01440-4500, 01440-4530, 01440-5590, 01440-5610, 01440-5620, 01440-5630, 01440-5640, 01440-5650, 01440-5660, 01440-5670, 01440-5680, 01440-5690, 01440-5700, 01440-5710, 01440-5720, 01440-5730, 01440-5730, 01440-6530, 01440-6540, 01440-6550, 01440-6560, 01440-6580, 01440-6620, 01440-6630, 01440-6660, 01440-6670, 01440-6680, 01440-7280, 01440-7300, 01440-7310, 01440-7320, 01440-7330, 01440-7350, 01440-7370, 01440-7510, 01440-7940, 01440-7950, 01440-7960, 01440-7970, 01440-7980, 01440-7990, 01440-8010, 01440-8020, 01440-8030, 01440-8040, 01440-8050, 01440-8290</p>																				

 MTN 94 Code: AC0140003		  	
<b>SECTION 4 : FIRST AID MEASURES</b>			
4.1	<b>DESCRIPTION OF FIRST-AID MEASURES:</b>  Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.		
	<b>Route of exposure</b>	<b>Symptoms and effects, acute and delayed</b>	<b>Description of first-aid measures</b>
	<b>Inhalation:</b> 	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
	<b>Skin:</b> 	Skin contact causes redness. In case of prolonged contact, the skin may become dry.	Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.
	<b>Eyes:</b> 	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
	<b>Ingestion:</b>	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek immediate medical attention. Do not induce vomiting. Keep the patient at rest.
4.2	<b>MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:</b> The main symptoms and effects are indicated in sections 4.1 and 11		
4.3	<b>INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:</b> <b>Notes to physician:</b> Treatment should be directed at the control of symptoms and the clinical condition of the patient. <b>Antidotes and contraindications:</b> Specific antidote not known.		
<b>SECTION 5 : FIRE-FIGHTING MEASURES</b>			
5.1	<b>EXTINGUISHING MEDIA:</b> Extinguishing powder or CO <sub>2</sub> . In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.		
5.2	<b>SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:</b> Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide. Harmful. Irritant. Exposure to combustion or decomposition products may be a hazard to health.		<b>ANSI/NFPA 704:</b> Health: 2 Flammability: 4 Reactivity: 0 Special key: -
5.3	<b>ADVICE FOR FIREFIGHTERS:</b> <b>Special protective equipment:</b> Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or not used, combat fire from a sheltered position or at a safe distance. The standard EN469 provides a basic level of protection for chemical incidents. <b>Other recommendations:</b> Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.		
<b>SECTION 6 : ACCIDENTAL RELEASE MEASURES</b>			
6.1	<b>PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:</b> Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.		
6.2	<b>ENVIRONMENTAL PRECAUTIONS:</b> Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.		
6.3	<b>METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:</b> Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). Avoid use of solvents. Keep the remains in a closed container.		

**SAFETY DATA SHEET**

In accordance with the requirements of the OSHA Hazard Communication Standard, 29CFR 1910.1200

Revision: 30/06/2017 Page 4 / 12



MTN 94  
Code: AC0140003



**SECTION 7 : HANDLING AND STORAGE**

**7.1** PRECAUTIONS FOR SAFE HANDLING:  
Comply with the existing legislation on health and safety at work.  
General recommendations:  
Avoid any type of leakage or escape.  
Recommendations for the prevention of fire and explosion risks:  
Pressurised container. Protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not smoke.  
- Flash point : -82\* °C  
- Autoignition temperature : 421\* °C  
- Upper/lower flammability or explosive limits : 1.8\* - 9.0 % Volume 25°C  
Recommendations for the prevention of toxicological risks:  
Do not eat, drink or smoke in application and drying areas. After handling, wash hands with soap and water. Avoid applying the product directly to people, animals, plants or foodstuffs. For exposure controls and personal protection measures, see section 8.  
Recommendations for the prevention of environmental contamination:  
It is not considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6.

**7.2** CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:  
Prevent unauthorized access. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. For more information, see section 10.  
Class of store : According to current legislation.  
Maximum storage period : 24. months  
Temperature interval : min: 5. °C, max: 50. °C (recommended).  
Incompatible materials:  
Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.  
Type of packaging:  
According to current legislation.



MTN 94  
Code: AC0140003



### SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

#### OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2015	Year	TLV-TWA		TLV-STEL		Remarks
		ppm	mg/m3	ppm	mg/m3	
Butane	2012	1000.	-	-	-	
Xylene (mixture of isomers)	1996	100.	434.	150.	651.	A4 , BEI
Ethyl acetate	1996	400.	1440.	-	-	
Propane	2004	1000.	-	-	-	
Isobutane	2012	1000.	-	-	-	
Ethylbenzene	2002	100.	434.	125.	543.	A3 , BEI
n-butyl acetate	2015	50.	237.	150.	713.	

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.

A3 - Carcinogenic in animals.

A4 - Non classified as carcinogenic in humans.

BEI - Biological exposure index (biological monitoring).

#### BIOLOGICAL EXPOSURE INDICES (BEI):

This preparation contains the following substances that have established a biological limit value:

- Xylenes (technical or commercial grade) (2011): Biological determinant: methylhippuric acids in urine, BEI: 1.5 g/g creatinine, Sampling time: end of shift (2).

- Ethylbenzene (2013): Biological determinant: sum of mandelic acid and phenylglycolic acid in urine, BEI: 0.15 g/g creatinine Sampling time: end of shift (2), Notation: (Ns).

(2) When the end of the exposition not coincide with the end of the working day, the sample will be taken as soon as possible after the real exposition ceases.

(Ns) Non-specific. The determinant is non-specific, since it is also observed after exposure to other chemicals.



MTN 94  
Code: AC0140003



**8.2 EXPOSURE CONTROLS:**

**ENGINEERING MEASURES:**



Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

Protection of respiratory system: Avoid the inhalation of vapours.

Protection of eyes and face: It is recommended to dispose of water taps or sources with clean water close to the working area.

Protection of hands and skin: It is recommended to dispose of water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

**OCCUPATIONAL EXPOSURE CONTROLS: Directive 89/686/EEC-96/58/EC:**

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding EC marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, etc.), you should consult the informative brochures provided by the manufacturers of PPE.

Mask:



Suitable combined filter mask for gases, vapours and particles (OSHA 29CFR 1910.134 and ANSI Z88.2). Classe 1: low capacity up to 1000 ppm, Classe 2: medium capacity up to 5000 ppm, Classe 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume.

Goggles:



Safety goggles with suitable lateral protection (OSHA 29CFR 1910.133). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.

Face shield:

No.

Gloves:



Gloves resistant against chemicals (OSHA 29CFR 1910.132). There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard OSHA 29CFR 1910.132. Due to the wide variety of circumstances and possibilities, we must have in mind the manual of instructions from manufacturers of gloves. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.

Boots:

No.

Apron:

No.

Clothing:

Advisable.

Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

Spills on the soil: Prevent contamination of soil.

Spills in water: Do not allow to escape into drains, sewers or water courses.

Emissions to the atmosphere: Because of volatility, emissions to the atmosphere while handling and use may result. When possible, avoid solvent release to the atmosphere; do not pulverize more than is strictly necessary.

- VOC : 595.9 g/l (-H2O-es) ASTM D-3960



MTN 94  
Code: AC0140003



## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

<u>Appearance</u>			
- Physical state	:	Aerosol.	
- Colour	:	Diverse.	
- Odour	:	Characteristic	
- Odour threshold	:	Not available (mixture).	
<u>pH-value</u>			
- pH	:	Not applicable (non-aqueous media).	
<u>Change of state</u>			
- Melting point	:	Not applicable (mixture).	
- Initial boiling point	:	Not applicable	
<u>Density</u>			
- Vapour density	:	Not available	
- Relative density	:	0.804* at 20/4°C	Relative water
<u>Stability</u>			
- Decomposition temperature	:	Not available (technical impossibility to obtain the data).	
<u>Viscosity:</u>			
- Viscosity (flow time)	:	Not applicable	
<u>Volatility:</u>			
- Evaporation rate	:	Not applicable	
- Vapour pressure	:	Not available	
<u>Solubility(ies)</u>			
- Liposolubility	:	Not applicable	
- Partition coefficient: n-octanol/water	:	Not applicable (mixture).	
<u>Flammability:</u>			
- Flash point	:	-82* °C	
- Upper/lower flammability or explosive limits	:	1.8* - 9.0 % Volume 25°C	
- Autoignition temperature	:	421* °C	
<u>Explosive properties:</u>			
Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.			
<u>Oxidizing properties:</u>			
Not classified as oxidizing product.			

\*Estimated values based on the substances composing the mixture.

## 9.2 OTHER INFORMATION:

- Heat of combustion	:	8738* Kcal/kg
- Solids	:	25.9 % Weight
- VOC (supply)	:	74.1 % Weight

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the technical data sheet of the same. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

## SECTION 10 : STABILITY AND REACTIVITY

## 10.1 REACTIVITY:

Corrosivity to metals: It is not corrosive to metals.  
Pyrophorical properties: It is not pyrophoric.

## 10.2 CHEMICAL STABILITY:

Stable under recommended storage and handling conditions.

## 10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Possible dangerous reaction with oxidizing agents, acids, alkalis, amines, peroxides.

## 10.4 CONDITIONS TO AVOID:

Heat: Keep away from sources of heat.  
Light: Avoid direct contact with sunlight.  
Air: The product is not affected by exposure to air, but should not be left the containers open.  
Humidity: Avoid extreme humidity conditions.  
Pressure: Not relevant.  
Shock: The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.

## 10.5 INCOMPATIBLE MATERIALS:

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

## 10.6 HAZARDOUS DECOMPOSITION PRODUCTS:

As consequence of thermal decomposition, hazardous products may be produced: carbon monoxide.



MTN 94  
Code: AC0140003



## SECTION 11 : TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008-1221/2015 (CLP).

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:ACUTE TOXICITY:

<u>Dose and lethal concentrations for individual ingredients :</u>	<u>DL50 (OECD 401)</u> mg/kg oral	<u>DL50 (OECD 402)</u> mg/kg cutaneous	<u>CL50 (OECD 403)</u> mg/m3.4h inhalation
Butane			> 100000 Rat
Xylene (mixture of isomers)	4300. Rat	1700. Rabbit	> 22080. Rat
Ethyl acetate	5620. Rat	18000. Rabbit	> 44000. Rat
Ethylbenzene	3500. Rat	15400. Rabbit	> 17400. Rat
n-butyl acetate	10768. Rat	17600. Rabbit	> 23400. Rat
Polyhydroxyalkylamides	> 5000. Rat	> 2000. Rat	
2-butanone-oxime	2400. Rat	1840. Rabbit	> 4830. Rat

No observed adverse effect level

	<u>NOAEL Oral</u> mg/kg bw/d	<u>NOAEL Cutaneous</u> mg/kg bw/d	<u>NOAEL Inhalation</u> mg/m3
2-butanone-oxime	125. Rat		90. Rat

Lowest observed adverse effect level

	<u>LOAEL Oral</u> mg/kg bw/d	<u>LOAEL Cutaneous</u> mg/kg bw/d	<u>LOAEL Inhalation</u> mg/m3
2-butanone-oxime	40. Rat		

INFORMATION ON LIKELY ROUTES OF EXPOSURE : Acute toxicity:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed
<u>Inhalation:</u> Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).
<u>Skin:</u> Not classified	ATE > 2000 mg/kg	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).
<u>Eyes:</u> Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).
<u>Ingestion:</u> Not classified	ATE > 5000 mg/kg	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed
<u>Respiratory corrosion/irritation:</u> Not classified	-	-	Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).
<u>Skin corrosion/irritation:</u> 	Skin 	Cat.2	IRRITANT: Causes skin irritation.
<u>Serious eye damage/irritation:</u> 	Eyes 	Cat.2	IRRITANT: Causes serious eye irritation.
<u>Respiratory sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).
<u>Skin sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).

ASPIRATION HAZARD:


Danger class	Target organs	Cat.	Main effects, acute and/or delayed
<u>Aspiration hazard:</u> Not classified	-	-	Not applicable.








**SAFETY DATA SHEET**

In accordance with the requirements of the OSHA Hazard Communication Standard, 29CFR 1910.1200

Revision: 30/06/2017 Page 9 / 12

	MTN 94 Code: AC0140003	
--	---------------------------	---

**SPECIFIC TARGET ORGANS TOXICITY (STOT) : Single exposure (SE) and/or Repeated exposure (RE):**

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed
<u>Systemic:</u> 	RE	Systemic 	Cat.2	HARMFUL: May cause damage to organs through prolonged or repeated exposure if inhaled.
<u>Cutaneous:</u>	RE	Skin 	-	DEFATTENING: Repeated exposure may cause skin dryness or cracking.
<u>Neurological:</u> 	SE	CNS 	Cat.3	NARCOSIS: May cause drowsiness or dizziness if inhaled.

**CMR EFFECTS:**

Carcinogenic effects: Is not considered as a carcinogenic product.  
Genotoxicity: Is not considered as a mutagenic product.  
Toxicity for reproduction: Do not harm fertility. Do not harm the fetus developing.  
Effects via lactation: Not classified as a hazardous product for children breast-fed.

**DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:**

Routes of exposure: May be absorbed by inhalation of vapour, through the skin and by ingestion.  
Short-term exposure: Harmful by inhalation. Harmful in contact with skin. Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours.  
Long-term or repeated exposure: Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Repeated exposure may cause skin dryness or cracking.

**INTERACTIVE EFFECTS:**

Not available.

**INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:**

Dermal absorption: Not available.  
Basic toxicokinetics: Not available.

**ADDITIONAL INFORMATION:**

Not available.

**SECTION 12 : ECOLOGICAL INFORMATION**

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~1221/2015 (CLP).

12.1	<u>TOXICITY:</u>			
	<u>Acute toxicity in aquatic environment for individual ingredients :</u> Xylene (mixture of isomers) Ethyl acetate Ethylbenzene n-butyl acetate Polyhydroxyalkylamides 2-butanone-oxime	<u>CL50 (OECD 203)</u> mg/l.96hours 14. Fishes 212. Fishes 12. Fishes 18. Fishes > 1000. Fishes 843. Fishes	<u>CE50 (OECD 202)</u> mg/l.48hours 16. Daphnia 164. Daphnia 1.8 Daphnia 44. Daphnia 16. Daphnia 750. Daphnia	<u>CE50 (OECD 201)</u> mg/l.72hours > 10. Algae > 100. Algae 33. Algae 675. Algae 4.1 Algae 83. Algae
	<u>No observed effect concentration</u> n-butyl acetate 2-butanone-oxime	<u>NOEC (OECD 210)</u> mg/l.28days 50. Fishes	<u>NOEC (OECD 211)</u> mg/l.21days 23. Daphnia > 100. Daphnia	<u>NOEC (OECD 201)</u> mg/l.72hours
	<u>Lowest observed effect concentration</u> Not available			





12.2	<u>PERSISTENCE AND DEGRADABILITY:</u> Not available.			
	<u>Aerobic biodegradation for individual ingredients :</u> Butane Xylene (mixture of isomers) Ethyl acetate Propane Isobutane Ethylbenzene n-butyl acetate Polyhydroxyalkylamides 2-butanone-oxime	<u>DQO</u> mgO2/g 3577. 2620. 1540. 3629. 3577. 3164. 2204.	<u>%DBO/DQO</u> 5 days 14 days 28 days ~ 52. ~ 81. ~ 88. ~ 62. ~ 69. ~ 94. ~ 30. ~ 68. ~ 79. ~ 80. ~ 82. ~ 83. 72.	<u>Biodegradability</u> Easy Easy Easy Easy Not available Easy Easy Easy Inherently

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

**SAFETY DATA SHEET**

In accordance with the requirements of the OSHA Hazard Communication Standard, 29CFR 1910.1200

Revision: 30/06/2017 Page 10 / 12

	MTN 94 Code: AC0140003	  
--	---------------------------	---

12.3	<p><b>BIOACCUMULATIVE POTENTIAL:</b> Not available.</p>																																											
	<p><u>Bioaccumulation for individual ingredients:</u></p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:45%;"></th> <th style="width:15%; text-align: center;"><u>logPow</u></th> <th style="width:15%; text-align: center;"><u>BCF</u> L/kg</th> <th style="width:25%; text-align: center;"><u>Potential</u></th> </tr> </thead> <tbody> <tr> <td>Butane</td> <td></td> <td></td> <td>Not available</td> </tr> <tr> <td>Xylene (mixture of isomers)</td> <td style="text-align: center;">3.16</td> <td style="text-align: center;">57. (calculated)</td> <td>Not available</td> </tr> <tr> <td>Ethyl acetate</td> <td style="text-align: center;">0.730</td> <td style="text-align: center;">3.2 (calculated)</td> <td>Not available</td> </tr> <tr> <td>Propane</td> <td style="text-align: center;">2.36</td> <td></td> <td>Not available</td> </tr> <tr> <td>Isobutane</td> <td></td> <td></td> <td>Not available</td> </tr> <tr> <td>Ethylbenzene</td> <td style="text-align: center;">3.15</td> <td style="text-align: center;">56. (calculated)</td> <td>Not available</td> </tr> <tr> <td>n-butyl acetate</td> <td style="text-align: center;">1.81</td> <td style="text-align: center;">6.9 (calculated)</td> <td>Not available</td> </tr> <tr> <td>Polyhydroxyalkylamides</td> <td></td> <td></td> <td>Not available</td> </tr> <tr> <td>2-butanone-oxime</td> <td style="text-align: center;">0.590</td> <td style="text-align: center;">3.2 (calculated)</td> <td>Not available</td> </tr> </tbody> </table>		<u>logPow</u>	<u>BCF</u> L/kg	<u>Potential</u>	Butane			Not available	Xylene (mixture of isomers)	3.16	57. (calculated)	Not available	Ethyl acetate	0.730	3.2 (calculated)	Not available	Propane	2.36		Not available	Isobutane			Not available	Ethylbenzene	3.15	56. (calculated)	Not available	n-butyl acetate	1.81	6.9 (calculated)	Not available	Polyhydroxyalkylamides			Not available	2-butanone-oxime	0.590	3.2 (calculated)	Not available			
	<u>logPow</u>	<u>BCF</u> L/kg	<u>Potential</u>																																									
Butane			Not available																																									
Xylene (mixture of isomers)	3.16	57. (calculated)	Not available																																									
Ethyl acetate	0.730	3.2 (calculated)	Not available																																									
Propane	2.36		Not available																																									
Isobutane			Not available																																									
Ethylbenzene	3.15	56. (calculated)	Not available																																									
n-butyl acetate	1.81	6.9 (calculated)	Not available																																									
Polyhydroxyalkylamides			Not available																																									
2-butanone-oxime	0.590	3.2 (calculated)	Not available																																									

12.4 **MOBILITY IN SOIL:**  
Not available.

12.6 **OTHER ADVERSE EFFECTS:**  
Ozone depletion potential: Not available.  
Photochemical ozone creation potential: Not available.  
Earth global warming potential: In case of fire or incineration liberates CO2.  
Endocrine disrupting potential: Not available.

**SECTION 13 : DISPOSAL CONSIDERATIONS**



13.1 **WASTE TREATMENT METHODS: Directive 2008/98/EC-Regulation (EU) no. 1357/2014:**  
 Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose of at an authorised waste collection point. Waste should be handled and disposed of in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers:  
 Emptied containers and packaging should be disposed of in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification. With contaminated containers and packaging, adopt the same measures as for the product in itself. Ensure the container is completely empty before throwing it away.

Procedures for neutralising or destroying the product:  
 In accordance with local regulations. Do not incinerate closed containers.

**SAFETY DATA SHEET**

In accordance with the requirements of the OSHA Hazard Communication Standard, 29CFR 1910.1200

	MTN 94 Code: AC0140003	  
--	---------------------------	---

**SECTION 14 : TRANSPORT INFORMATION**

14.1	<b>UN NUMBER:</b> 1950
14.2	<b>UN PROPER SHIPPING NAME:</b> AEROSOLS
14.3 14.4	<p><b>TRANSPORT HAZARD CLASS(ES) AND PACKING GROUP:</b></p> <p><u>Transport by road (ADR 2017) and Transport by rail (RID 2017):</u></p> <ul style="list-style-type: none"> <li>- Class: 2</li> <li>- Packaging group: -</li> <li>- Classification code: 5F</li> <li>- Tunnel restriction code: (D)</li> <li>- Transport category: 2, max. ADR 1.1.3.6. 333 L</li> <li>- Limited quantities: 1 L (see total exemptions ADR 3.4)</li> <li>- Transport document: Consignment paper.</li> <li>- Instructions in writing: ADR 5.4.3.4</li> </ul> <p><u>Transport by sea (IMDG 37-14):</u></p> <ul style="list-style-type: none"> <li>- Class: 2 (Division 2.1)</li> <li>- Packaging group: -</li> <li>- Emergency Sheet (EmS): F-D,S-U</li> <li>- First Aid Guide (MFAG): 620*</li> <li>- Marine pollutant: No.</li> <li>- Transport document: Shipping Bill of lading.</li> </ul> <p><u>Transport by air (ICAO/IATA 2016):</u></p> <ul style="list-style-type: none"> <li>- Class: 2 (Division 2.1)</li> <li>- Packaging group: -</li> <li>- Transport document: Air Bill of lading.</li> </ul> <p><u>Transport by inland waterways (ADN):</u> Not available.</p>
14.5	<b>ENVIRONMENTAL HAZARDS:</b> Not applicable (not classified as hazardous for the environment).
14.6	<b>SPECIAL PRECAUTIONS FOR USER:</b> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.
14.7	<b>TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:</b> Not applicable.

**SECTION 15 : REGULATORY INFORMATION**

15.1	<p><b>USA REGULATIONS:</b></p> <p><u>Occupational Safety and Health Act (OSHA):</u> This product is considered to be hazardous under the OSHA Hazard Communication Standard.</p> <p><u>Clean Air Act:</u></p> <ul style="list-style-type: none"> <li>- 112(r) Hazardous air pollutants (HAP) (40CFR 68):</li> <li>Butane: Threshold quantity (TQ): 10000 lbs.</li> <li>Propane: Threshold quantity (TQ): 10000 lbs.</li> <li>Isobutane: Threshold quantity (TQ): 10000 lbs.</li> </ul> <p>The TQ applies to the quantity of substance in a release process, not at the facility as a whole.</p> <p><u>Clean Water Act:</u></p> <ul style="list-style-type: none"> <li>- 307 Hazardous water priority pollutants (HWPP):</li> <li>Ethylbenzene</li> </ul> <p><u>Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):</u> This product contains the following Hazardous Substances for Emergency release notification (40CFR 302):</p> <ul style="list-style-type: none"> <li>Xylene (mixture of isomers): Reportable quantity (RQ): 100 lbs.</li> <li>Ethyl acetate: Reportable quantity (RQ): 5000 lbs.</li> <li>Ethylbenzene: Reportable quantity (RQ): 1000 lbs.</li> <li>n-butyl acetate: Reportable quantity (RQ): 5000 lbs.</li> </ul> <p>Releases of CERCLA hazardous substances, in quantities equal to or greater than their reportable quantity (RQ). are subject to reporting to the National Response Center under CERCLA. Such releases are also subject to state and local reporting under section 304 of Emergency Planning and Community Right-to-Know Act (EPCRA), also known as SARA Title III.</p> <p><u>Superfund Amendments and Reauthorization Act (SARA Title III):</u></p> <ul style="list-style-type: none"> <li>- 302/304 Extremely Hazardous Substances (EHS) for Emergency release notification (40CFR 355): No.</li> <li>- 313 Reportable Ingredients (40CFR 372):</li> <li>Xylene (mixture of isomers)</li> <li>Ethylbenzene</li> </ul> <ul style="list-style-type: none"> <li>- 311/312 Hazard Categories (40CFR 370): Yes.</li> </ul> <p><u>Toxic Substance Control Act (TSCA):</u> All chemical substances in this product comply with all applicable rules or order under TSCA.</p> <p><u>California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):</u> This product contains the following chemicals known to the CA State to cause cancer or reproductive toxicity:</p> <p>Ethylbenzene: Cancer</p> <p><b>OTHER REGULATIONS:</b></p> <p><u>Other local legislations:</u></p>
------	--

The receiver should verify the possible existence of local regulations applicable to the chemical.

Item Numbers: 01440-3100, 01440-3110, 01440-3120, 01440-4030, 01440-4040, 01440-4500, 01440-4530, 01440-5590, 01440-5610, 01440-5620, 01440-5630, 01440-5640, 01440-5650, 01440-5660, 01440-5670, 01440-5680, 01440-5690, 01440-5700, 01440-5710, 01440-5720, 01440-5730, 01440-6530, 01440-6540, 01440-6550, 01440-6560, 01440-6580, 01440-6620, 01440-6630, 01440-6660, 01440-6670, 01440-6680, 01440-7280, 01440-7300, 01440-7310, 01440-7320, 01440-7330, 01440-7350, 01440-7370, 01440-7510, 01440-7940, 01440-7950, 01440-7960, 01440-7970, 01440-7980, 01440-7990, 01440-8010, 01440-8020, 01440-8030, 01440-8040, 01440-8050, 01440-8290

**SAFETY DATA SHEET**

In accordance with the requirements of the OSHA Hazard Communication Standard, 29CFR 1910.1200

Revision: 30/06/2017 Page 12 / 12

MTN 94  
Code: AC0140003**SECTION 16 : OTHER INFORMATION****TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:****Hazard statements according the Regulation (EU) No. 1272/2008-1221/2015 (CLP), Anexo III:**

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure: may explode if heated. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H351 Suspected of causing cancer. H373i May cause damage to organs through prolonged or repeated exposure if inhaled. H373iE May cause damage to hearing organs through prolonged or repeated exposure if inhaled.

**ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:**

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of material safety data sheets and labelling of products as well.

**MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:**

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2015).
- European agreement on the international carriage of dangerous goods by road, (ADR 2017).
- International Maritime Dangerous Goods Code IMDG including Amendment 37-14 (IMO, 2014).

**ABBREVIATIONS AND ACRONYMS:**

List of abbreviations and acronyms that can be used (but not necessarily used) in this material safety data sheet:

- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials).
- VOC: Volatile Organic Compounds.
- LD50: Letal dose, 50 percent.
- LC50: Letal concentration, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangeous goods by road.
- RID: Regulations concerning the international transport of dangeous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organizatio n.

**SAFETY DATA SHEET REGULATIONS:**

Safety Data Sheet in accordance with the requirements of the OSHA Hazard Communication Standard, 29CFR 1910.1200.

**HISTORY:****Revision:**Version: 6  
Version: 723/06/2017  
30/06/2017**Modifications with respect to the previous Material Safety Data Dheet:**

# *The possible legislative, contextual, numerical, methodological and normative changes with respect to the previous version are highlighted in this Material Safety Data Sheet by a mark # in red and italic.*

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Material Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.

Item Numbers: 01440-3100, 01440-3110, 01440-3120, 01440-4030, 01440-4040, 01440-4500, 01440-4530, 01440-5590, 01440-5610, 01440-5620, 01440-5630, 01440-5640, 01440-5650, 01440-5660, 01440-5670, 01440-5680, 01440-5690, 01440-5700, 01440-5710, 01440-5720, 01440-5730, 01440-6530, 01440-6540, 01440-6550, 01440-6560, 01440-6580, 01440-6620, 01440-6630, 01440-6660, 01440-6670, 01440-6680, 01440-7280, 01440-7300, 01440-7310, 01440-7320, 01440-7330, 01440-7350, 01440-7370, 01440-7510, 01440-7940, 01440-7950, 01440-7960, 01440-7970, 01440-7980, 01440-7990, 01440-8010, 01440-8020, 01440-8030, 01440-8040, 01440-8050, 01440-8290