

Safety data sheet

This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

EX014PR1054 - MTN PRO Paint stripper



SECT	ION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
1.1	Product identifier: EX014PR1054 - MTN PRO Paint stripper
	Other means of identification:
	Non-applicable
1.2	Relevant identified uses of the substance or mixture and uses advised against:
	Relevant uses: Solvent
	Uses advised against: All uses not specified in this section or in section 7.3
1.3	Details of the supplier of the safety data sheet:
	MONTANA COLORS, S.L. Pol. Ind. Pla de les Vives C/ Anaïs Nin 6 08295 Sant Vicenç de Castellet - Barcelona - España Phone.: +34 938332760 (9:00- 16:00h GMT +1:00) msds@montanacolors.com https://www.montanacolors.com
1.4	Emergency telephone number: +34 938332760 (Mon- frid 9:00- 16:00h GMT +1:00)
SECE	TON 2: HAZARDS IDENTIFICATION
2.1	Classification of the substance or mixture:
	CLP Regulation (EC) No 1272/2008:
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
2.2	Aerosol 1: Pressurised container: May burst if heated., H229 Aerosol 1: Flammable aerosols, Category 1, H222 Eye Irrit. 2: Eye irritation, Category 2, H319 Label elements:
	CLP Regulation (EC) No 1272/2008:
	Danger
	Hazard statements:
	Aerosol 1: H229 - Pressurised container: May burst if heated. Aerosol 1: H222 - Extremely flammable aerosol. Eye Irrit. 2: H319 - Causes serious eye irritation.
	Precautionary statements:
	 P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Do not spirace or burn, even after use.
	P260: Do not breathe spray. P271: Use only outdoors or in a well-ventilated area. P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F P501: Dispose of contents/container according to the separated collection system used in your municipality.
	UFI: UR40-R08N-700N-6E2Y
2.3	Other hazards:
	Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -				
Printing: 16/06/2021 (Replaced 1)	Date of compilation: 20/10/2020	Revised: 16/06/2021	Version: 2	Page 1/13
,				



EX014PR1054 - MTN PRO Paint stripper



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Non-applicable

3.2 Mixture:

Chemical description: Aerosol

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification				
CAS:	646-06-0	1,3-dioxolane ⁽¹⁾	Self-classified			
EC: 211-463-5 Index: Non-applicable REACH: 01-2119490744-29- XXXX		Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225 - Danger		30 - <50 %	
CAS:	115-10-6	dimethyl ether ⁽²⁾		ATP CLP00		
EC: Index: REACH:	204-065-8 603-019-00-8 01-2119472128-37- XXXX	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	n. Gas 1A: H220; Press. Gas: H280 - Danger		
	108-32-7 203-572-1 607-194-00-1 01-2119537232-48- XXXX	propylene carbonate	(1)	ATP CLP00		
Index: 6 REACH: 0		Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	\$	10 - <20 %	
	67-56-1	methanol ⁽¹⁾		ATP CLP00		
Index: REACH:	200-659-6 603-001-00-X 01-2119433307-44- XXXX	Regulation 1272/2008	Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger	<u>ک</u> ک	1 - <2,5 %	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830
⁽²⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:


Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

- CONTINUED ON NEXT PAGE -

Printing: 16/06/2021 (Replaced 1)	Date of compilation: 20/10/2020	Revised: 16/06/2021	Version: 2	Page 2/13
				Page 2 of



ww.montanacolors.com

EX014PR1054 - MTN PRO Paint stripper



SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). **Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

- C.- Technical recommendations to prevent ergonomic and toxicological risks
- Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.
- D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

- CONTINUED ON NEXT PAGE -					
Printing: 16/06/2021 (Replaced 1)	Date of compilation: 20/10/2020	Revised: 16/06/2021	Version: 2	Page 3/13	
Item Numbers: 01468-1002				Page 3 of 13	

ww.montanacolors.com

EX014PR1054 - MTN PRO Paint stripper



SECTION 7: HANDLING AND STORAGE (continued)

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 120 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits			
dimethyl ether	IOELV (8h)	1000 ppm	1920 mg/m ³	
CAS: 115-10-6 EC: 204-065-8	IOELV (STEL)			
methanol	IOELV (8h)	200 ppm	260 mg/m ³	
CAS: 67-56-1 EC: 200-659-6	IOELV (STEL)			

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
1,3-dioxolane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 646-06-0	Dermal	Non-applicable	Non-applicable	1,18 mg/kg	Non-applicable
EC: 211-463-5	Inhalation	Non-applicable	Non-applicable	3,306 mg/m ³	Non-applicable
dimethyl ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 115-10-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-065-8	Inhalation	Non-applicable	Non-applicable	1894 mg/m ³	Non-applicable
propylene carbonate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-32-7	Dermal	Non-applicable	Non-applicable	20 mg/kg	Non-applicable
EC: 203-572-1	Inhalation	Non-applicable	Non-applicable	70,53 mg/m ³	20 mg/m ³
methanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-56-1	Dermal	20 mg/kg	Non-applicable	20 mg/kg	Non-applicable
EC: 200-659-6	Inhalation	130 mg/m ³	130 mg/m ³	130 mg/m ³	130 mg/m ³

DNEL (General population):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
dimethyl ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 115-10-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-065-8	Inhalation	Non-applicable	Non-applicable	471 mg/m ³	Non-applicable
propylene carbonate	Oral	Non-applicable	Non-applicable	10 mg/kg	Non-applicable
CAS: 108-32-7	Dermal	Non-applicable	Non-applicable	10 mg/kg	Non-applicable
EC: 203-572-1	Inhalation	Non-applicable	Non-applicable	17,4 mg/m ³	10 mg/m ³
methanol	Oral	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable
CAS: 67-56-1	Dermal	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable
EC: 200-659-6	Inhalation	26 mg/m ³	26 mg/m ³	26 mg/m ³	26 mg/m ³

- CONTINUED ON NEXT PAGE -

Printing: 16/06/2021

Date of compilation: 20/10/2020

Revised: 16/06/2021

Version: 2

Page 4/13

(Replaced 1)





EX014PR1054 - MTN PRO Paint stripper

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
1,3-dioxolane	STP	1 mg/L	Fresh water	19,7 mg/L
CAS: 646-06-0	Soil	2,62 mg/kg	Marine water	1,97 mg/L
EC: 211-463-5	Intermittent	0,95 mg/L	Sediment (Fresh water)	77,7 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,77 mg/kg
dimethyl ether	STP	160 mg/L	Fresh water	0,155 mg/L
CAS: 115-10-6	Soil	0,045 mg/kg	Marine water	0,016 mg/L
EC: 204-065-8	Intermittent	1,549 mg/L	Sediment (Fresh water)	0,681 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,069 mg/kg
propylene carbonate	STP	7400 mg/L	Fresh water	0,9 mg/L
CAS: 108-32-7	Soil	0,81 mg/kg	Marine water	0,09 mg/L
EC: 203-572-1	Intermittent	9 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
methanol	STP	100 mg/L	Fresh water	20,8 mg/L
CAS: 67-56-1	Soil	100 mg/kg	Marine water	2,08 mg/L
EC: 200-659-6	Intermittent	1540 mg/L	Sediment (Fresh water)	77 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,7 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Compulsory use of face mask	Filter mask for particles		EN 149:2001+A1:2009	Replace when an increase in resistence to breathing is observed.
C	C Specific protection for the hands				
	Pictogram	PPE	Labelling	CEN Standard	Remarks
	[I]]				Replace gloves in case of any sign of damage. For

Mandatory hand	Protective gloves against minor risks	CATI	Replace gioves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+ A1:2010 and EN ISO 374-1:2016+A1:2018
----------------	--	------	---

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E	Body protection				
	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.

	- CONTINI	UED ON NEXT PAGE -		
Printing: 16/06/2021 (Replaced 1)	Date of compilation: 20/10/2020	Revised: 16/06/2021	Version: 2	Page 5/13
Item Numbers: 01468-1002				Page 5 of 13

13





EX014PR1054 - MTN PRO Paint stripper

D : 1			ION (continued)		
Pictogram	PPE	Labelling	CEN Standard		Remarks
Mandatory foot protection	Safety footwear with antistatic and heat resistan properties		EN ISO 13287:2013 EN ISO 20345:2011	Re	place boots at any sign of deterioration
F Additional emerg	jency measures				
Emergency me	easure	Standards	Emergency measu	ıre	Standards
Emergency sh	ISO 3864-1:2	NSI Z358-1 2011, ISO 3864-4:20	011 Eyewash stations	s	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:201
Environmental exp	posure controls:				
spillage of both the p Volatile organic co	product and its container	. For additional i	nformation see subsection		nmended to avoid environmenta
-	tive 2010/75/EU, this pro		llowing characteristics:		
V.O.C. (Supply):		3 % weight	、 、		
V.O.C. density at		kg/m³ (404 g/l -	-)		
Average carbon r Average molecula		59 g/mol			
		5,			
For complete informa	asic physical and chen		s:		
Appearance:		tasheet.			
Appearance: Physical state at 20 °		tasheet. Aerc	osol		
		Aerc	osol available		
Physical state at 20 °		Aerc Not			
Physical state at 20 G Appearance:		Aerc Not Colo	available		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold:		Aerc Not Colo Not	available ourless		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold: Volatility:	°C:	Aerc Not Colo Not	available ourless available -applicable *		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo	°C: pspheric pressure:	Aerc Not Colo Not Non	available ourless available -applicable * °C (Propellant)		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2	°C: ospheric pressure: 20 °C:	Aerc Not Colo Not -25 - Non-	available uurless available -applicable * °C (Propellant) -applicable *		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 5	°C: ospheric pressure: 20 °C: 50 °C:	Aerc Not Colo Not -25 ^d Non <30	available nurless available -applicable * °C (Propellant) -applicable * 0000 Pa (300 kPa)		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 5 Evaporation rate at 2	°C: ospheric pressure: 20 °C: 50 °C: 20 °C:	Aerc Not Colo Not -25 ^d Non <30	available uurless available -applicable * °C (Propellant) -applicable *		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 2 Evaporation rate at 2 Product descriptio	°C: ospheric pressure: 20 °C: 50 °C: 20 °C:	Aerc Not Colo Not -25 Non- <30 Non-	available ourless available -applicable * °C (Propellant) -applicable * 0000 Pa (300 kPa) -applicable *		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 2 Evaporation rate at 2 Product descriptio Density at 20 °C:	°C: pspheric pressure: 20 °C: 50 °C: 20 °C: 20 °C: 50 °C: 50 °C: 50 °C:	Aerc Not Colo Not -25 Non <30 Non	available ourless available -applicable * PC (Propellant) -applicable * 0000 Pa (300 kPa) -applicable *		
Physical state at 20 G Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 2 Vapour pressure at 2 Product descriptio Density at 20 °C: Relative density at 20	°C: pspheric pressure: 20 °C: 50 °C: 20 °C: 0 °C:	Aerc Not Colo Not -25 Non <30 Non 912 Non	available ourless available -applicable * °C (Propellant) -applicable * 0000 Pa (300 kPa) -applicable * kg/m ³ -applicable *		
Physical state at 20 G Appearance: Colour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 2 Product descriptio Density at 20 °C: Relative density at 20 Dynamic viscosity at	°C: pspheric pressure: 20 °C: 20 °C: 0 °C: 20 °C: 20 °C:	Aerc Not Colo Not -25 Non <30 Non 912 Non	available ourless available -applicable * °C (Propellant) -applicable * 0000 Pa (300 kPa) -applicable * kg/m ³ -applicable * -applicable *		
Physical state at 20 C Appearance: Colour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 2 Product descriptio Density at 20 °C: Relative density at 20 Dynamic viscosity at Kinematic viscosity at	•C: pspheric pressure: 20 •C: 50 •C: 20 •C: 0 •C: 20 •C: 20 •C: 20 •C: 20 •C: 20 •C:	Aerc Not Colo Not -25 Non <30 Non 912 Non Non	available ourless available -applicable * °C (Propellant) -applicable * 0000 Pa (300 kPa) -applicable * kg/m ³ -applicable * -applicable * -applicable *		
Physical state at 20 G Appearance: Colour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 2 Product descriptio Density at 20 °C: Relative density at 20 Dynamic viscosity at Kinematic viscosity a	•C: pspheric pressure: 20 •C: 50 •C: 20 •C: 0 •C: 20 •C: 20 •C: 20 •C: 20 •C: 20 •C:	Aerc Not Colo Not -25 Non <30 Non 912 Non Non	available ourless available -applicable * °C (Propellant) -applicable * 0000 Pa (300 kPa) -applicable * kg/m ³ -applicable * -applicable * -applicable * -applicable *		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 2 Vapour pressure at 2 Product descriptio Density at 20 °C: Relative density at 20 Dynamic viscosity at Kinematic viscosity at Kinematic viscosity at	•C: pspheric pressure: 20 •C: 50 •C: 20 •C: 0 •C: 20 •C: 20 •C: 20 •C: 20 •C: 20 •C:	Aerc Not Colo Not -25 Non <30 Non 912 Non Non	available available -applicable * °C (Propellant) -applicable * 0000 Pa (300 kPa) -applicable * kg/m ³ -applicable * -applicable * -applicable * -applicable * -applicable *		
Physical state at 20 G Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 2 Vapour pressure at 2 Product descriptio Density at 20 °C: Relative density at 20 Dynamic viscosity at Kinematic viscosity at Kinematic viscosity at Concentration: pH:	•C: poppheric pressure: 20 •C: 50 •C: 20 •C: 50 •C: 50 •C: 50 •C: 50 •C: 51 •	Aerc Not Colo Not -25 Non <30 Non 912 Non Non Non	available available -applicable * °C (Propellant) -applicable * 0000 Pa (300 kPa) -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable *		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 2 Vapour pressure at 2 Product descriptio Density at 20 °C: Relative density at 20 Dynamic viscosity at Kinematic viscosity at Kinematic viscosity at Concentration: pH: Vapour density at 20	•C: pspheric pressure: 20 °C: 50 °C: 20 °C: •n: •0 •C: •20 °C: •at 20 °C: •at 40 °C: •0 °C:	Aero Not Colo Not Non <30 Non 912 Non Non Non	available available -applicable * °C (Propellant) -applicable * 0000 Pa (300 kPa) -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable *		
Physical state at 20 C Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmo Vapour pressure at 2 Vapour pressure at 2 Vapour pressure at 2 Product descriptio Density at 20 °C: Relative density at 20 Dynamic viscosity at Kinematic viscosity at Kinematic viscosity at Concentration: pH: Vapour density at 20	•C: poppheric pressure: 20 •C: 50 •C: 20 •C: 50 •C: 50 •C: 50 •C: 50 •C: 51 •	Aero Not Colo Not Non <30 Non 912 Non Non Non	available available -applicable * °C (Propellant) -applicable * 0000 Pa (300 kPa) -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable *		

Printing: 16/06/2021 (Replaced 1)

- CONTINUED ON NEXT PAGE -

Revised: 16/06/2021

Date of compilation: 20/10/2020

Version: 2

Page 6/13



EX014PR1054 - MTN PRO Paint stripper



SECT	TION 9: PHYSICAL AND CHEMICAL PR	OPERTIES (continued)	
	Solubility in water at 20 °C:		
	Solubility properties:	Non-applicable *	
	Decomposition temperature:	Non-applicable *	
	Melting point/freezing point:	Non-applicable *	
	Recipient pressure:	Non-applicable *	
	Explosive properties:	Non-applicable *	
	Oxidising properties:	Non-applicable *	
	Flammability:		
	Flash Point:	-41 °C (Propellant)	
	Heat of combustion:	Non-applicable *	
	Flammability (solid, gas):	Non-applicable *	
	Autoignition temperature:	240 °C (Propellant)	
	Lower flammability limit:	Non-applicable *	
	Upper flammability limit:	Non-applicable *	
	Explosive:		
	Lower explosive limit:	Non-applicable *	
	Upper explosive limit:	Non-applicable *	
9.2	Other information:		
	Surface tension at 20 °C:	Non-applicable *	
	Refraction index:	Non-applicable *	
	*Not relevant due to the nature of the product, not	providing information property of its hazards.	

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

	Shock and friction	friction Contact with air Increa		vith air Increase in temperature Sunlight			
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable		
;	Incompatible materials:						
	Acids	Water	Oxidising materials	Combustible materials	Others		

Actors Water Oxidising materials Combustible materials Others Avoid strong acids Not applicable Avoid direct impact Not applicable Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

 Printing: 16/06/2021
 Date of compilation: 20/10/2020
 Revised: 16/06/2021
 Version: 2
 Page 7/13

 (Replaced 1)
 Page 7/13
 Page 7/13
 Page 7/13
 Page 7/13

Item Numbers: 01468-1002

10.5



EX014PR1054 - MTN PRO Paint stripper



	11: TOXICOLOGICAL INFORMATION ** (continued)			
	11. TOXICOLOGICAL INFORMATION ·· (continued)			
tha	ntains glycols. It is recommended not to breathe the vapours for prolon it are hazardous to the health . ngerous health implications:	nged periods of tim	e due to the possibility	of effects
adv	case of exposure that is repetitive, prolonged or at concentrations higheverse effects on health may result, depending on the means of exposure Ingestion (acute effect):		nended occupational ex	posure limits,
	 Acute toxicity : Based on available data, the classification criteria ar as dangerous for consumption. For more information see section 3. Corrosivity/Irritability: Based on available data, the classification crit classified as dangerous for this effect. For more information see section Inhalation (acute effect): 	eria are not met, a		
C-	 Acute toxicity : Based on available data, the classification criteria ar as dangerous for inhalation. For more information see section 3. Corrosivity/Irritability: Based on available data, the classification crit classified as dangerous for this effect. For more information see sectior Contact with the skin and the eyes (acute effect): 	eria are not met, a		
D -	 Contact with the skin: Based on available data, the classification crit classified as dangerous for skin contact. For more information see secti Contact with the eyes: Produces eye damage after contact. CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction) 	on 3.	However, it contains su	bstances
	 Carcinogenicity: Based on available data, the classification criteria ar as dangerous for the effects mentioned. For more information see sect IARC: Non-applicable Mutagenicity: Based on available data, the classification criteria are dangerous for this effect. For more information see section 3. Reproductive toxicity: Based on available data, the classification criter classified as dangerous for this effect. For more information see section Sensitizing effects: 	ion 3. not met, as it does eria are not met, a	s not contain substance	s classified as
F-	 Respiratory: Based on available data, the classification criteria are not dangerous with sensitising effects. For more information see section 3. Cutaneous: Based on available data, the classification criteria are not dangerous for this effect. For more information see section 3. Specific target organ toxicity (STOT) - single exposure: 			
G-	Based on available data, the classification criteria are not met. However, dangerous as a result of a single exposure. For more information see sufficient target organ toxicity (STOT)-repeated exposure:		substances which are c	assified as
	 Specific target organ toxicity (STOT)-repeated exposure: Based on a it does not contain substances classified as dangerous for this effect. F Skin: Based on available data, the classification criteria are not met, dangerous for this effect. For more information see section 3. Aspiration hazard: 	or more informatio	n see section 3.	
	Based on available data, the classification criteria are not met, as it doe this effect. For more information see section 3. her information:	es not contain subs	stances classified as dat	ngerous for
	n-applicable			
	ecific toxicology information on the substances:			
•	Identification	Acu	te toxicity	Genus
dim	nethyl ether	LD50 oral	>2000 mg/kg	Genus
	S: 115-10-6	LD50 dermal	>2000 mg/kg	
	: 204-065-8	LC50 inhalation	308,5 mg/L (4 h)	Rat

** Changes with regards to the previous version

EC: 204-065-8

	- CONTINU	JED ON NEXT PAGE -		
Printing: 16/06/2021 (Replaced 1)	Date of compilation: 20/10/2020	Revised: 16/06/2021	Version: 2	Page 8/13
Item Numbers: 01468-1002				Page 8 of 13

308,5 mg/L (4 h)



EX014PR1054 - MTN PRO Paint stripper



SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Identification	A	Acute toxicity	
propylene carbonate	LD50 oral	29000 mg/kg	Rat
CAS: 108-32-7	LD50 dermal	>2000 mg/kg	
EC: 203-572-1	LC50 inhalation	>20 mg/L (4 h)	
1,3-dioxolane	LD50 oral	>2000 mg/kg	
CAS: 646-06-0	LD50 dermal	>2000 mg/kg	
EC: 211-463-5	LC50 inhalation	68,4 mg/L (4 h)	Rat
methanol	LD50 oral	100 mg/kg	Rat
CAS: 67-56-1	LD50 dermal	300 mg/kg	Rabb
EC: 200-659-6	LC50 inhalation	3 mg/L (4 h)	Rat

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Ide	ntification	Acute toxicity		Species	Genus	
1,3-dioxolane		LC50	Non-applicable			
CAS: 646-06-0		EC50	772 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 211-463-5		EC50	877 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae	
propylene carbonate		LC50	5300 mg/L (96 h)	Leuciscus idus	Fish	
CAS: 108-32-7		EC50	500 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 203-572-1		EC50	Non-applicable			
methanol		LC50	15400 mg/L (96 h)	Lepomis macrochirus	Fish	
CAS: 67-56-1		EC50	12000 mg/L (96 h)	Nitrocra spinipes	Crustacean	
EC: 200-659-6		EC50	530 mg/L (168 h)	Microcystis aeruginosa	Algae	

12.2 Persistence and degradability:

Identification	Degr	adability	Biodegradability	
1,3-dioxolane	BOD5	Non-applicable	Concentration	3 mg/L
CAS: 646-06-0	COD	Non-applicable	Period	35 days
EC: 211-463-5	BOD5/COD	Non-applicable	% Biodegradable	3,7 %
propylene carbonate	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 108-32-7	COD	Non-applicable	Period	28 days
EC: 203-572-1	BOD5/COD	Non-applicable	% Biodegradable	80 %
methanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-56-1	COD	1,42 g O2/g	Period	14 days
EC: 200-659-6	BOD5/COD	Non-applicable	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Identification	Bioac	cumulation potential
1,3-dioxolane	BCF	
CAS: 646-06-0	Pow Log	-0.37
EC: 211-463-5	Potential	
propylene carbonate	BCF	3
CAS: 108-32-7	Pow Log	-0.41
EC: 203-572-1	Potential	Low
methanol	BCF	3
CAS: 67-56-1	Pow Log	-0.77
EC: 200-659-6	Potential	Low

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE Printing: 16/06/2021 Date of compilation: 20/10/2020 Revised: 16/06/2021 Version: 2
(Replaced 1)

Item Numbers: 01468-1002

Page 9 of 13

Page 9/13



EX014PR1054 - MTN PRO Paint stripper



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Absorp	Absorption/desorption		Volatility	
1,3-dioxolane	Кос	3.46	Henry	Non-applicable	
CAS: 646-06-0	Conclusion	Very High	Dry soil	Non-applicable	
EC: 211-463-5	Surface tension	Non-applicable	Moist soil	Non-applicable	
dimethyl ether	Кос	Non-applicable	Henry	Non-applicable	
CAS: 115-10-6	Conclusion	Non-applicable	Dry soil	Non-applicable	
EC: 204-065-8	Surface tension	1,136E-2 N/m (25 °C)	Moist soil	Non-applicable	
methanol	Кос	Non-applicable	Henry	Non-applicable	
CAS: 67-56-1	Conclusion	Non-applicable	Dry soil	Non-applicable	
EC: 200-659-6	Surface tension	2,355E-2 N/m (25 °C)	Moist soil	Non-applicable	

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances Dangerous	

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

	Jerous goods by land: 2021 and RID 2021:	
5	4.1 UN number:	UN1950
· · · · · · · · · · · · · · · · · · ·	4.2 UN proper shipping name:	AEROSOLS, flammable
	4.3 Transport hazard class(es):	2
	Labels:	2.1
1	4.4 Packing group:	N/A
2 1	4.5 Environmental hazards:	No
1	4.6 Special precautions for user	
	Special regulations:	190, 327, 344, 625
	Tunnel restriction code:	D
	Physico-Chemical properties:	see section 9
	Limited quantities:	1 L
1	4.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

- CONTINUED ON NEXT PAGE -

Printing: 16/06/2021 (Replaced 1)	Date of compilation: 20/10/2020	Revised: 16/06/2021	Version: 2	Page 10/13
Item Numbers: 01468-1002				Page 10 of 13



EX014PR1054 - MTN PRO Paint stripper




Transport of	dangero	us goods by sea:			
With regard to	IMDG 39	-18:			
	14.1	UN number:	UN1950		
•	14.2	UN proper shipping name:	AEROSOLS, flammable		
J.	14.3	Transport hazard class(es):	2		
		Labels:	2.1		
		Packing group:	N/A		
2		Marine pollutant:	No		
•	14.0	Special precautions for user Special regulations:	63, 959, 190, 277, 327, 344		
		EmS Codes:	F-D, S-U		
		Physico-Chemical properties:	see section 9		
		Limited quantities:	1 L		
		Segregation group:	Non-applicable		
	14.7	Transport in bulk according	Non-applicable		
		to Annex II of Marpol and			
T		the IBC Code:			
-	-	us goods by air:			
With regard to	-				
		UN number:	UN1950		
		UN proper shipping name:	AEROSOLS, flammable		
$\langle - \rangle$	14.3	Transport hazard class(es):	2		
2	14.4	Labels: Packing group:	2.1 N/A		
\checkmark		Environmental hazards:	No		
		Special precautions for user	110		
		Physico-Chemical properties:	see section 9		
	14.7	Transport in bulk according	Non-applicable		
		to Annex II of Marpol and the IBC Code:			
CTION 15: REGU	LATORY	' INFORMATION			
1 Safety health	and on	vironmental regulations /legisl	ation specific for the substance or	mixture	
			on (EC) No 1907/2006 (REACH): Non-a		
		-	n List") and sunset date: Non-applicable	•	
		•	,	2	
			ete the ozone layer: Non-applicable		
Article 95, REGL	JLATION	(EU) No 528/2012: Non-applicable	2		
REGULATION (E	EU) No 64	9/2012, in relation to the import a	and export of hazardous chemical produ	ucts: Non-applica	able
Seveso III:					
Section		Description	n	Lower-tier requirements	Upper-tier requirement
P3a FLA	MMABLE A	EROSOLS		150	500
	comme	rcialisation and the use of cert	tain dangerous substances and mix	ctures (Annex	XVII REACH
etc):	d in:				

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Contains methanol. Shall not be placed on the market to the general public after 9 May 2019 in windscreen washing or defrosting fluids, in a concentration equal to or greater than 0,6 % by weight

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

- CONTINUED ON NEXT PAGE -				
Printing: 16/06/2021 (Replaced 1)	Date of compilation: 20/10/2020	Revised: 16/06/2021	Version: 2	Page 11/13
Item Numbers: 01468-1002				Page 11 of 13



ww.montanacolors.com

EX014PR1054 - MTN PRO Paint stripper



SECTIO	DN 15: REGULATORY INFORMATION (continued)
a P	t is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk ssessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this roduct. Other legislation:
т	he product could be affected by sectorial legislation
	Chemical safety assessment:
I	he supplier has not carried out evaluation of chemical safety.
SECTIO	DN 16: OTHER INFORMATION
L	egislation related to safety data sheets:
T h	he SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet as been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 Regulation (EC) No 2015/830).
	Nodifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12): · New declared substances
	1,3-dioxolane (646-06-0) · Removed substances 1,3-dioxolane (646-06-0)
	exts of the legislative phrases mentioned in section 2:
F	I319: Causes serious eye irritation. I229: Pressurised container: May burst if heated. I222: Extremely flammable aerosol.
т	exts of the legislative phrases mentioned in section 3:
ir	he phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3
	CLP Regulation (EC) No 1272/2008:
E F F	Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled. Eye Irrit. 2: H319 - Causes serious eye irritation. Filam. Gas 1A: H220 - Extremely flammable gas. Filam. Liq. 2: H225 - Highly flammable liquid and vapour. Fress. Gas: H280 - Contains gas under pressure, may explode if heated. FIOT SE 1: H370 - Causes damage to organs.
	Classification procedure:
E A	ye Irrit. 2: Calculation method erosol 1: Calculation method erosol 1: Calculation method
	dvice related to training:
С	linimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their omprehension and interpretation of this safety data sheet, as well as the label on the product.
	Yrincipal bibliographical sources: ttp://echa.europa.eu
	ttp://eur-lex.europa.eu
	bbreviations and acronyms:
I	DR: European agreement concerning the international carriage of dangerous goods by road MDG: International maritime dangerous goods code
I C	ATA: International Air Transport Association CAO: International Civil Aviation Organisation :OD: Chemical Oxygen Demand
В	OD5: 5day biochemical oxygen demand CF: Bioconcentration factor D50: Lethal Dose 50
L	C50: Lethal Concentration 50
	C50: Effective concentration 50
К	ogPOW: Octanolwater partition coefficient oc: Partition coefficient of organic carbon IFI: unique formula identifier

- CONTINUED ON NEXT PAGE -

Printing: 16/06/20)21 I
(Replaced 1)	

Date of compilation: 20/10/2020 Revised: 16/06/2021

Version: 2

Page 12/13



EX014PR1054 - MTN PRO Paint stripper



The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified. - END OF SAFETY DATA SHEET -

Printing: 16/06/2021 (Replaced 1) Date of compilation: 20/10/2020

Revised: 16/06/2021

Version: 2

Page 13/13