01520-1004

SAFETY DATA SHEET

MSDS #: 557

Emergency Medical Number: Poison Control 800-222-1222 Page 1 of 3 Emergency Transport Number: Chemtrec 800-424-9300

or (01) 703-527-3887 (CCN4391) General Inquiry Number: Chartpak 413-584-5446

Chartpak, Inc. One River Road

Leeds, MA 01053 Phone: 413-584-5446 or 800-628-1910

e: 413-584-5446 or t	300-020-1310		Date	:	1/31/20	
Section One:	nation					
Product Name:	Grumbacher Japan Drier					
Product Sizes:	2.5 oz					
Product Class: Me	ediums					
Section Two:	Ingredients					
Ingredients		CAS Number	% by Weight	PEL/TLV		
Petroleum Distillat	es	N/A	66%	N/A		
Section Three:	Hazards Identi	fication		•		

WARNING: COMBUSTIBLE. VAPOR HARMFUL. MAY BE HARMFUL IF SWALLOWED. CANCER AGENT BASED ON EXPERIMENTAL DATA.

CONTAINS: NAPHTHALENE, PETROLEUM DISTILLATES.

KEEP OUT OF REACH OF CHILDREN.

Section Four:	First Aid Measures	
Inhalation:	Move to fresh air.	

Skin Contact: Wash with soap and water.

Eye Contact: Flush with copious amounts of water.

Ingestion: If swallowed, get prompt medical attention.

This Material Safety Data Sheet is applicable to the consumer use of the following colors: 5572

Page 1 of 3 Item Numbers: 01520-1004

SAFETY DATA SHEET

MSDS #: 557

Page 2 of 3

Section Five: Fire Fighting Measures

Flash Point:

Flammability Limits (% by volume):

Not explosive

Not explosive Upper:

Extinguishing Media:

Foam, carbon dioxide, or dry chemical

Special Fire Fighting Measures:

No special fire fighting procedures required

Unusual Fire and Explosion

Hazards:

Combustible

129F

Lower:

Accidental Release Measures Section Six:

Wipe up with absorbent material.

Section Seven: **Handling and Storage**

Handling: Use only with adequate ventilation.

Do not store or use near heat or flame. Storage:

Exposure Controls and Personal Protection Section Eight:

Respiratory Protection and **Special Ventilation Requirements:**

Use exhaust fan to assure adequate cross-ventilation.

Other Protective Equipment

(Gloves, Goggles, Étc.):

None

Work/Hygiene Practices:

PRECAUTIONS: Avoid ingestion. Wash hands immediately after use. When using, do not eat, drink,

or smoke. Do not store or use near heat or flame. Use only with adequate ventilation.

Physical and Chemical Properties Section Nine:

Boiling Point:

Not determined

Melting Point:

Not determined

Vapor Pressure:

Not determined

Specific Gravity:

Not determined

Specific Vapor Density (AIR = 1):

Not determined

Evaporation Rate (Butyl Acetate = 1):

Not determined

Solubility in Water:

Negligible

Reactivity in Water:

Non-reactive

Dark yellow liquid; petroleum odor Appearance and Odor:

Section Ten: Stability and Reactivity

Stability:

Stable

Conditions to Avoid:

None known

Chemical Incompatibility:

None known

Hazardous Decomposition:

None known

Hazardous Polymerization:

Will not occur

Page 2 of 3 Item Numbers: 01520-1004

SAFETY DATA SHEET

MSDS #: 557

Page 3 of 3

Section Eleven: Toxicological Information

IARC Monographs: No
National Toxicology Program: No
OSHA Regulated: No

Effects/Symptoms of Irritation of eyes or chest

Acute Exposure:

Effects/Symptoms of None expected

Chronic Exposure:

Medical Conditions Usually Aggravated By Overexposure of This Product: None known

Section Twelve: Ecological Information

Not available

Section Thirteen: Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations

Section Fourteen: Transport Information

ORM-D Consumer Commodity

Flammable Liquid, n.o.s. (petroleum distillates), 3, UN1993, III (120°F TCC / 48.8 °C) Ltd Qtys, EmS# F-E, S-E Consumer Commodity, 9, ID8000, packing instruction 910

Section Fifteen: Regulatory Information

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

Section Sixteen: Other Information

С

HMIS Code

Flammability 2

Reactivity 0

Health 2

Personal Protection

Chartpak, Inc. is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D-4236.

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Item Numbers: 01520-1004 Page 3 of 3