EN 11

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 1 / 11 Replaced revision:94 (Dated 22/02/2022)

## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

INDUSTRIA MAIMERI S.P.A.

#### 1.1. Product identifier

58606 Code:

**AUXILIARY PRODUCTS** 58606 Rectified turpentine essence Product name

650-002-00-6 INDEX number 232-350-7 EC number 8006-64-2 CAS number Registration Number 01-2119553060-53

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Thinner for oil painting.

## 1.3. Details of the supplier of the safety data sheet

INDUSTRIA MAIMERI S.P.A. Name Via Gianni Maimeri, 1 Full address

District and Country 20076 Mediglia (MI)

Italia

Tel. +39 02 906981 Fax +39 02 90698999

e-mail address of the competent person responsible for the Safety Data Sheet schedesicurezza@maimeri.it

INDUSTRIA MAIMERI S.P.A. VIA G.MAIMERI 1 20076 BETTOLINO DI MEDIGLIA (MI) Supplier:

**ITALY** 

#### 1.4. Emergency telephone number

For urgent inquiries refer to Australia: 131126 USA: 1 800 222 1222

Regno Unito NHS Direct (UK): +44 (0) 845 46 47

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

H226 Flammable liquid and vapour. Flammable liquid, category 3 Acute toxicity, category 4 H302 Harmful if swallowed. Acute toxicity, category 4 H312 Harmful in contact with skin. Acute toxicity, category 4 H332 Harmful if inhaled. Aspiration hazard, category 1 H304 May be fatal if swallowed and enters airways. Eye irritation, category 2 H319 Causes serious eye irritation. Skin irritation, category 2 H315 Causes skin irritation. Skin sensitization, category 1 H317 May cause an allergic skin reaction. Hazardous to the aquatic environment, chronic H411 Toxic to aquatic life with long lasting effects.

@EPY 11.3.0 - SDS 1004.14

toxicity, category 2

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 2 / 11 Replaced revision:94 (Dated 22/02/2022)

## SECTION 2. Hazards identification .../>>

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:









Signal words: Danger

Hazard statements:

H411

Flammable liquid and vapour. H226

Harmful if swallowed, in contact with skin or if inhaled. H302+H312+H332

May be fatal if swallowed and enters airways. H304

H319 Causes serious eve irritation.

H315 Causes skin irritation. H317 May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

Precautionary statements:

Dispose of contents / container to in accordance with local and national norms. . . P501

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P331 Do NOT induce vomiting.

Wear protective gloves/ protective clothing / eye protection / face protection. P280 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER / doctor / . . .

Contains: Turpentine Essence

INDEX 650-002-00-6

#### 2.3. Other hazards

The substance does not have persistence, bioaccumulation and toxicity (PBT) properties and is not very persistent and very bioaccumulative. (vPvB).

The substance does not have endocrine disrupting properties.

## **SECTION 3. Composition/information on ingredients**

#### 3.1. Substances

Contains:

Identification Conc. % Classification (EC) 1272/2008 (CLP)

**Turpentine Essence** 

650-002-00-6 Flam. Liq. 3 H226, Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, INDEX 100

Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317,

Aquatic Chronic 2 H411

232-350-7 STA Oral: 500 mg/kg, STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 EC

mg/l, STA Inhalation mists/powders: 1,5 mg/l

8006-64-2 CAS REACH Reg. 01-2119553060-53

The full wording of hazard (H) phrases is given in section 16 of the sheet.

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 3 / 11 Replaced revision:94 (Dated 22/02/2022)

#### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor

#### 4.2. Most important symptoms and effects, both acute and delayed

Information not available

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

LINSUITABLE EXTINGUISHING FOURMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

## 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters

**GENERAL INFORMATION** 

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6. Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

## 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 4 / 11 Replaced revision:94 (Dated 22/02/2022)

## SECTION 6. Accidental release measures .../>

13

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

## **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory References:

EU OEL EU Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU)

2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive

2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive

91/322/EEC.

TLV-ACGIH ACGIH 2021

Turpentine Essence									
Threshold Limit Value									
Туре	Country	TWA/8h mg/m3	ppm	STEL/15r mg/m3	nin ppm	Remarks / Obs	ervations		
OEL TLV-ACGIH	EU	112 111	20 20				(sens), A4		
Predicted no-effect concentration - PNEC									
Normal value in fresh water   88									
Health - Derived no-effect level - DNEL / DMEL									
	Effects on consumers						Effects on workers		
Route of exposu	re Acute local	syst	emic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		590 µg/k	g bw/d		110 µg/kg bw/d				
Inhalation		120 µg/r			18 μg/m3	10,3 mg/m3	51,6 mg/m3	3,9 mg/m3	780 µg/m3
Skin						9,51 mg/cm2	9,51 mg/cm2	3,17 mg/cm2	1,6 mg/cm2

Legend

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

## 8.2. Exposure controls

@EPY 11.3.0 - SDS 1004.14

Item Numbers: 01565-1015, 01565-1036, 01565-1039 Page 4 of 11

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 5 / 11 Replaced revision:94 (Dated 22/02/2022)

### SECTION 8. Exposure controls/personal protection .../>>

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

## SECTION 9. Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

**Properties** Appearance liquid colourless Colour Odour characteristic 100 ppm (ACGIH, 1991) Odour threshold Melting point / freezing point °C Initial boiling point °C 154 Boiling range 154-170°C Flammability not applicable Lower explosive limit not applicable Upper explosive limit not applicable Flash point 34 Auto-ignition temperature 255 °C

Decomposition temperature not applicable not applicable pH not applicable not applicable Ninematic viscosity not available Dynamic viscosity 1.30 mPa.s a 25 °C (read-across)

Solubility soluble in organic solvents
Partition coefficient: n-octanol/water Log Kow (Pow): 4.49 a 25 °C

(metodo del dibattimento in pallone)

Vapour pressure 3,89282mmHg

Density and/or relative density 0,86

Relative vapour density not applicable Particle characteristics not applicable Information

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 6 / 11 Replaced revision:94 (Dated 22/02/2022)

## SECTION 9. Physical and chemical properties .../>>

#### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Evaporation rate not applicable

VOC (Directive 2010/75/EU) 100,00 % - 860,00 g/litre VOC (volatile carbon) 100,00 % - 860,00 g/litre

Explosive properties not applicable Oxidising properties not applicable

## **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

#### 10.5. Incompatible materials

Information not available

### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## **SECTION 11. Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

## ACUTE TOXICITY

Turpentine Essence STA (Oral):

STA (Dermal): STA (Inhalation mists/powders): STA (Inhalation vapours): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP 11 mg/l estimate from table 3.1.2 of Annex I of the CLP

Acute toxicity, category 4. Harmful if swallowed, in contact with skin or if inhaled.

@EPY 11.3.0 - SDS 1004.14

Page 6 of 11

Item Numbers: 01565-1015, 01565-1036, 01565-1039

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 7 / 11 Replaced revision:94 (Dated 22/02/2022)

## SECTION 11. Toxicological information .../>>

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

## 11.2. Information on other hazards

Based on the available data, the substance is not listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## **SECTION 12. Ecological information**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

## 12.1. Toxicity

Information not available

## 12.2. Persistence and degradability

Information not available

## 12.3. Bioaccumulative potential

Information not available

## 12.4. Mobility in soil

Information not available

## 12.5. Results of PBT and vPvB assessment

The substance does not have persistence, bioaccumulation and toxicity (PBT) properties and is not very persistent and very bioaccumulative. (vPvB).

@EPY 11.3.0 - SDS 1004.14

Item Numbers: 01565-1015, 01565-1036, 01565-1039 Page 7 of 11

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 8 / 11 Replaced revision:94 (Dated 22/02/2022)

## SECTION 12. Ecological information .../>>

#### 12.6. Endocrine disrupting properties

Based on the available data, the substance is not listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

## **SECTION 13. Disposal considerations**

## 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information**

#### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1299

## 14.2. UN proper shipping name

ADR / RID: TURPENTINE IMDG: TURPENTINE IATA: TURPENTINE

## 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



## 14.4. Packing group

ADR / RID, IMDG, IATA:

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 9 / 11 Replaced revision:94 (Dated 22/02/2022)

## SECTION 14. Transport information .../>>

#### 14.5. Environmental hazards

ADR / RID: Environmentally Hazardous

IMDG: Marine Pollutant

IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

TURPENTINE.

#### 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30 Limited Quantities: 5 L Tunnel restriction code: (D/E)

Special provision: -

IMDG: EMS: F-E, S-E Limited Quantities: 5 L
IATA: Cargo: Maximum quantity: 220 L

Cargo: Maximum quantity: 220 L Packaging instructions: 366
Pass.: Maximum quantity: 60 L Packaging instructions: 355

Special provision:

## 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 4
Contained substance
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

#### Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment

Has not been performed / is not yet available a chemical safety assessment for the substance.

@EPY 11.3.0 - SDS 1004.14

Item Numbers: 01565-1015, 01565-1036, 01565-1039 Page 9 of 11

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 10 / 11 Replaced revision:94 (Dated 22/02/2022)

#### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3
Acute Tox. 4 Acute toxicity, category 4
Asp. Tox. 1 Aspiration hazard, category 1
Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2
Skin Sens. 1 Skin sensitization, category 1

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

**H226** Flammable liquid and vapour.

**H302** Harmful if swallowed.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H312 Harmful in contact with skin.
H332 Harmful if inhaled.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)

@EPY 11.3.0 - SDS 1004.14

Page 10 of 11

58606 - AUXILIARY PRODUCTS

58606 Rectified turpentine essence

Revision nr.95 Dated 05/09/2022 Printed on 05/09/2022 Page n. 11 / 11 Replaced revision:94 (Dated 22/02/2022)

## SECTION 16. Other information .../>>

- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP) 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

03 / 09 / 11.