INDUCTOR MAIMEDIC DA

01565-1254 Revision or 11

		01565-1254
INDUSTRIA MA		Revision nr.11 E Dated 03/09/2021 Printed on 03/09/2021
58666 - AUXILIARY PRODUCTS	58666 Painting	g varnish Page n. 1 / 12 Replaced revision:10 (Dated 09/06/2020)
	Safaty Data S	shoot
Acc	Safety Data S ording to Annex II to REACH - Re	
	C C	- -
SECTION 1. Identification of the subs	stance/mixture and of t	he company/undertaking
.1. Product identifier		
Code: Product name Chemical name and synonym	58666 AUXILIARY PRODUCTS Hydrocarbon isoparaffinic	58666 Painting varnish
I.2. Relevant identified uses of the substance or m	ixture and uses advised agains	st
Intended use	Thinner for oil painting.	
I.3. Details of the supplier of the safety data sheet		
Name Full address District and Country	INDUSTRIA MAIMERI S.P.A. Via Gianni Maimeri, 1 20076 Mediglia	(MI)
	Italia Tel. +39 02 906981 Fax +39 02 90698999	
e-mail address of the competent person responsible for the Safety Data Sheet	schedesicurezza@maimeri.it	
Product distribution by:	INDUSTRIA MAIMERI S.P.A. \ ITALY	/IA G.MAIMERI 1 20076 BETTOLINO DI MEDIGLIA (MI)
.4. Emergency telephone number		
For urgent inquiries refer to	Australia : 131126 USA: 1 800 222 1222 Regno Unito NHS Direct (UK)	: +44 (0) 845 46 47
SECTION 2. Hazards identification		
2.1. Classification of the substance or mixture		
The product is classified as hazardous pursuant to the amendments and supplements). The product thus re 2015/830. Any additional information concerning the risks for h	equires a safety datasheet that co	mplies with the provisions of (EU) Regulation
Hazard classification and indication:		
Flammable liquid, category 3 Specific target organ toxicity - single exposure,	H226 H336	Flammable liquid and vapour. May cause drowsiness or dizziness.
category 3		
category 3	08 (CLP) and subsequent amend	Iments and supplements.
category 3 2.2. Label elements	08 (CLP) and subsequent amenc	lments and supplements.
category 3 2.2. Label elements Hazard labelling pursuant to EC Regulation 1272/20	08 (CLP) and subsequent amend	Iments and supplements.
category 3 2.2. Label elements Hazard labelling pursuant to EC Regulation 1272/20	08 (CLP) and subsequent amenc	Iments and supplements.
category 3 2.2. Label elements Hazard labelling pursuant to EC Regulation 1272/20 Hazard pictograms: Signal words: Warning Hazard statements:		Iments and supplements.
category 3 2.2. Label elements Hazard labelling pursuant to EC Regulation 1272/20 Hazard pictograms:	ipour.	Iments and supplements.

58666 Painting varnish

SECTION 2. Hazards identification ... / >>

58666 - AUXILIARY PRODUCTS

P501	Dispose of contents / container to in accordance with local and national norms
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P271	Use only outdoors or in a well-ventilated area.
P101	If medical advice is needed, have product container or label at hand.

Contains: 1-METHOXY-2-PROPANOL

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
1-METHOXY-2-PROPA		
CAS EC	62 ≤ x < 66	Flam. Liq. 3 H226, STOT SE 3 H336
INDEX		
Reg. no. 2-Methoxy-1-propanol		
CAS	0,15 ≤ x < 0,2	Flam. Liq. 3 H226, Repr. 1B H360D, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335
EC INDEX		
Reg. no.		
CYCLOHEXANONE		
CAS EC	$0 \le x < 0.05$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315
INDEX		
Reg. no.		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Cas/Index/Ce - KETONE RESIN - 25054-06-2 - 15% Cas/Index/Ce - ACRYLIC RESIN - 25054-06-2 - 9,999% Cas/Index/Ce - Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) - 64742-82-1 - 65,002% Cas/Index/Ce - SAFFLOWER OIL - 8001-23-8 - 9,999%

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again. INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

@EPY 10.5.1 - SDS 1004.13

Item Numbers: 01565-1254

Page 2 of 12

58666 - AUXILIARY PRODUCTS

58666 Painting varnish

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak. UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

@EPY 10.5.1 - SDS 1004.13

INDUSTRIA MAIMERI S.P.A. 58666 - AUXILIARY PRODUCTS

58666 Painting varnish

SECTION 7. Handling and storage ... / >>

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory	References:
------------	-------------

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und
		Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung
		gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2019
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH
		HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των
		οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας
		2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με
		την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία''»
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i
		arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og
		grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3,
NED	Recondition	eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os
	ronagai	agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os
		riscos ligados à exposição durante o trabalho a agentes cancerigenos ou mutagénicos
POL	Polska	Rozporządzenie Ministra Rodziny, Pracy i Polityki Społecznej z dnia 12 czerwca 2018 r. w
TOL	T OISKA	sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w
		sprawie najwyzszych obpuszczannych stężeni matężeni czynników szkodniwych dla zdrówia w środowisku pracy
ROU	România	Hotararea 157/2020 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea
ROU	Romania	cerintelor minime de securitate si sănătate în muncă pentru asigurarea protecției lucrătorilor
		împotriva riscurilor legate de prezența agenților chimici, precum și pentru modificarea și
		completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate
		și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți
0.4/5		cancerigeni sau mutageni la locul de muncă
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska
		gränsvärden (AFS 2018:1)
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik
		12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU)
		2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive
		2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

@EPY 10.5.1 - SDS 1004.13

INDUSTRIA MAIMERI S.P.A. 58666 - AUXILIARY PRODUCTS

58666 Painting varnish

Revision nr.11 Dated 03/09/2021 Printed on 03/09/2021 Page n. 5 / 12 Replaced revision:10 (Dated 09/06/2020)

SECTION 8. Exposure controls/personal protection ... / >>

nreshold Limit V	alue			I-IVIE I HOX	(Y-2-PROPANO	· L			
Type	Country	TWA		STEL/1		Remarks / O	bservations		
	17.0	mg/m		mg/m3	ppm				
VLEP	ITA	375	100	568	150				
OEL	EU	375	100	568	150				
TLV-ACGIH			100		150				
redicted no-effeo			PNEC						
Normal value in	fresh wate	r					10	mg/l	
Normal value in	marine wa	ter					1	mg/l	
Normal value fo	r fresh wate	er sedime	ent				52,3	mg/kg/d	
Normal value fo	r marine wa	ater sedir	ment				5,2	mg/kg/d	
Normal value fo	r water, inte	ermittent	release				100	mg/l	
Normal value of	STP micro	organism	าร				100	mg/l	
Normal value fo	r the terres	trial com	partment				4,59	mg/kg/d	
ealth - Derived n							.,		
20111041			onsumers			Effects on wor	kers		
Route of exposu			Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
Route of exposi	loc			local	systemic	local	systemic	local	
0	100	ai	systemic			local	systemic	local	systemic
Oral				33	33				
				40.0	mg/kg bw/d				000
Inhalation				43.9	43,9	553,5	553,5		369
					mg/m3	mg/m3	mg/m3		mg/m3
Skin				78	78			183	183
					mg/kg bw/d				mg/kg
					-				bw/d
				CYCLO	OHEXANONE				
nreshold Limit V		TWA	/9b	STEL/1	Emin	Remarks / O	h		
Туре	Country					Remarks / O	bservations		
A () A (DELL	mg/m		mg/m3	ppm	OKINI			
AGW	DEU	80	20	80	20	SKIN	_		
TLV	DNK	41	10			SKIN	E		
VLA	ESP	41	10	82	20	SKIN			
VLEP	FRA	40,8	10	81,6	20				
HTP	FIN	41	10	82	20	SKIN			
TLV	GRC	200	50	400	100				
VLEP	ITA	40,8	10	81,6	20	SKIN			
TLV	NOR	40	10	80	20	SKIN			
TGG	NLD			50		SKIN			
VLE	PRT	40,8	10	81,6	20	SKIN			
NDS/NDSCh	POL	40	10	80	20	SKIN			
TLV	ROU	40,8	10	81,6	20	SKIN			
NGV/KGV	SWE	41	10	81	20	SKIN			
ESD	TUR	40,8	10	81,6	20	SKIN			
WEL	GBR	41	10	82	20	SKIN			
OEL	EU	40,8	10	81,6	20	SKIN			
TLV-ACGIH		80	20	201	50	SKIN			
redicted no-effect			PNEC						
Normal value in	fresh wate	r					32,9	µg/l	
Normal value in	marine wa	ter					3,29	µg/l	
Normal value fo	r fresh wate	er sedime	ent				249	µg/kg	
Normal value fo							24,9	µg/kg	
Normal value fo							329	µg/l	
Normal value of							10	mg/l	
								ug/ka	
Normal value fo							30,4	µg/kg	
ealth - Derived n						Effects in			
Dente			onsumers		0	Effects on wor		0	0
Route of exposu			Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loc	al	systemic	local	systemic	local	systemic	local	systemic
Oral			1,5		1,5				
			mg/kg bw/d		mg/kg bw/d				
Inhalation	40		20	20	10	80	80	40	40
	ma	/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3
Skin			1	-	1	-	4	-	4
			mg/kg bw/d		mg/kg bw/d		mg/kg		mg/kg
			.gg				bw/d		bw/d
							2		2
									@EPY 10.5.1 - SDS 1004.13

58666 - AUXILIARY PRODUCTS 58666 Painting varnish

Revision nr.11 Dated 03/09/2021 Printed on 03/09/2021 Page n. 6 / 12 Replaced revision:10 (Dated 09/06/2020)

SECTION 8. Exposure controls/personal protection ... / >>

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends

on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value Information
Appearance	liquid
Colour	colourless
Odour	ALCOOL-ETHER ODOUR
Odour threshold	Not applicable
pH	Not applicable
Melting point / freezing point	Not applicable
Initial boiling point	Not available
Boiling range	Not applicable
Flash point	23 ≤ T ≤ 60 °C
Evaporation Rate	Not applicable
Flammability of solids and gases	not applicable
Lower inflammability limit	Not applicable
Upper inflammability limit	Not applicable
Lower explosive limit	Not applicable
Upper explosive limit	Not applicable
Vapour pressure	Not applicable
Vapour density	Not applicable
Relative density	0,87
Solubility	SOLUBLE WITH ALCOOL AND GLYCOL ETHER
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not applicable
Viscosity	30-50 cps
Explosive properties	not applicable
Oxidising properties	not applicable

@EPY 10.5.1 - SDS 1004.13

ем 12

58666 - AUXILIARY PRODUCTS	58666 Painting varnish	Printed on 03/09/2021 Page n. 7 / 12 Replaced revision:10 (Dated 09/06/2020)
SECTION 9. Physical and chemical properties	/>>	
9.2. Other information		
	65,00 % - 565,50 g/litre 65,00 % - 565,50 g/litre	
SECTION 10. Stability and reactivity		
10.1. Reactivity		
There are no particular risks of reaction with other sul	ostances in normal conditions of use.	
CYCLOHEXANONE Attacks various types of plastic materials. May condense under the effect of heat to form res	inous compounds.	
10.2. Chemical stability		
The product is stable in normal conditions of use and	storage.	
10.3. Possibility of hazardous reactions		
The vapours may also form explosive mixtures with the	e air.	
CYCLOHEXANONE Risk of explosion on contact with: hydrogen perox explosive mixtures with: air. 10.4. Conditions to avoid	de,nitric acid,heat,mineral acids.May react violently	with: oxidising agents.Forms
Avoid overheating. Avoid bunching of electrostatic ch	arges. Avoid all sources of ignition.	
CYCLOHEXANONE Avoid exposure to: sources of heat,naked flames. 10.5. Incompatible materials		
Information not available		
10.6. Hazardous decomposition products		
In the event of thermal decomposition or fire, gases a	nd vapours that are potentially dangerous to health	may be released.
SECTION 11. Toxicological informatio	n	
In the absence of experimental data for the product it: contains, using the criteria specified in the applicable It is therefore necessary to take into account the cond toxicological effects of exposure to the product.	self, health hazards are evaluated according to the regulation for classification.	
11.1. Information on toxicological effects		
Metabolism, toxicokinetics, mechanism of action and	other information	
Information not available		
Information not available		
Information on likely routes of exposure		
Information on likely routes of exposure		
Information on likely routes of exposure Information not available Delayed and immediate effects as well as chronic effe		
Information on likely routes of exposure Information not available Delayed and immediate effects as well as chronic effe Information not available		
Information on likely routes of exposure Information not available Delayed and immediate effects as well as chronic effe Information not available Interactive effects		
Information on likely routes of exposure Information not available Delayed and immediate effects as well as chronic effe Information not available Interactive effects Information not available		
Information on likely routes of exposure Information not available Delayed and immediate effects as well as chronic effe Information not available Interactive effects Information not available ACUTE TOXICITY	ects from short and long-term exposure	© EPY 10.5.1 - SDS 1004.12

58666 - AUXILIARY PRODUCTS 58666 Painting varnish Revision nr.11 Dated 03/09/2021 Printed on 03/09/2021 Page n. 8 / 12 Replaced revision:10 (Dated 09/06/2020)

SECTION 11. Toxicological information	n/>>
ATE (Dermal) of the mixture:	Not classified (no significant component)
SKIN CORROSION / IRRITATION	
Does not meet the classification criteria for t	this hazard class
SERIOUS EYE DAMAGE / IRRITATION	
Does not meet the classification criteria for t	this hazard class
RESPIRATORY OR SKIN SENSITISATION	1
Does not meet the classification criteria for t	this hazard class
GERM CELL MUTAGENICITY	
Does not meet the classification criteria for t	this hazard class
CARCINOGENICITY	
Does not meet the classification criteria for t	this hazard class
REPRODUCTIVE TOXICITY	
Does not meet the classification criteria for t	this hazard class
STOT - SINGLE EXPOSURE	
May cause drowsiness or dizziness	
STOT - REPEATED EXPOSURE	
Does not meet the classification criteria for t	this hazard class
ASPIRATION HAZARD	
Does not meet the classification criteria for t	this hazard class
SECTION 12. Ecological information	ation
Use this product according to good working or contaminate soil or vegetation.	practices. Avoid littering. Inform the competent authorities, should the product reach waterways
2.1. Toxicity	
Information not available	
2.2. Persistence and degradability	
CYCLOHEXANONE Solubility in water Rapidly degradable	0,1 - 100 mg/l
2.3. Bioaccumulative potential	
CYCLOHEXANONE Partition coefficient: n-octanol/water	0,86
I2.4. Mobility in soil	
CYCLOHEXANONE Partition coefficient: soil/water	1,18
	@EPY 10.5.1 - SDS 1004

en 12

INDUSTRIA MAIMERI S.P.A. 58666 - AUXILIARY PRODUCTS

58666 Painting varnish

SECTION 12. Ecological information ... / >>

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID. IMDG. IATA: 3092

14.2. UN proper shipping name

14.3. Transport hazard class(es)

ADR / RID:	Class: 3	Label: 3
IMDG:	Class: 3	Label: 3
IATA:	Class: 3	Label: 3

14.4. Packing group

ADR / RID, IMDG, IATA: ш

14.5. Environmental hazards

ADR / RID:	NO
IMDG:	NO
IATA:	NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30 Special provision: -	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-D	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special provision:	-	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

@EPY 10.5.1 - SDS 1004.13

Item Numbers: 01565-1254



58666 - AUXILIARY PRODUCTS

58666 Painting varnish

EN 12

	ulatory infor	mation		
Safoty boalth and	onvironmontal ro	gulations/legislation specific for the substance or mixture		
-				
Seveso Category - Di	ECTIVE 2012/10/EC.			
estrictions relating to Product Point		tained substances pursuant to Annex XVII to EC Regulation 1907/2006		
Contained substance	3 - 40 e			
Point	30-75	2-Methoxy-1-propanol Reg. no.:		
Point	75	Isobutyl methacrylate Req. no.:		
Point	72-75	Formaldehyde sol >25% Reg. no.:		
Point	75	CYCLOHEXANONE Reg. no.:		
equiation (EC) No. 2	019/1148 - on the r	narketing and use of explosives precursors		
lot applicable				
ubstances in Candid In the basis of availa		ACH)		
ubstances subject to				
lone				
,	exportation reporting	ng pursuant to (EC) Reg. 649/2012:		
lone				
Substances subject to Jone	the Rotterdam Cor	ivention:		
Substances subject to	the Stockholm Cor	ivention:		
None				
		nust not undergo health checks, provided that available risk-assessment data prov are modest and that the 98/24/EC directive is respected.	e that the risks	
2. Chemical safety a				
-		on performed for the properties for the substances indicated in cestion 2		
Chemical safety ass	ssment has not be	en performed for the preparation/for the substances indicated in section 3.		
CTION 16. Oth	er informatio	n		
ext of hazard (H) ind	cations mentioned i	in section 2-3 of the sheet:		
Flam. Liq. 3	Flammab	e liquid, category 3		
Repr. 1B	Reproductive toxicity, category 1B			
Acute Tox. 4 Eye Dam. 1	Acute toxicity, category 4 Serious eye damage, category 1			
Skin Irrit. 2	Serious eye damage, category 1 Skin irritation, category 2			
STOT SE 3	Skerific target organ toxicity - single exposure, category 3			
H226		le liquid and vapour.		
H360D	May damage the unborn child.			
H312	Harmful in contact with skin.			
H332	Harmful i			
H318		serious eye damage.		
		kin irritation.		
H315		se respiratory irritation. se drowsiness or dizziness.		
H315 H335 H336				
H335 H336				
H335 H336 EGEND:	ement concerning t	the carriage of Dangerous goods by Road		

58666 - AUXILIARY PRODUCTS

58666 Painting varnish

SECTION 16. Other information ... / >>

- CAS NUMBER: Chemical Abstract Service Number CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP - LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP) 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- 17. Regulation (EU) 2019/521 (X
- 18. Regulation (EU) 2020/217 (XIV Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

EPY 10.5.1 - SDS 1004.13

58666 - AUXILIARY PRODUCTS

58666 Painting varnish

SECTION 16. Other information ... / >>

CALCULATION METHODS FOR CLASSIFICATIONChemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9. Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 01 / 08 / 15.

@EPY 10.5.1 - SDS 1004.13

Item Numbers: 01565-1254