58682 - AUXILIARY PRODUCTS

58682 Mastic varnish

Revision nr.7 Dated 27/09/2019 Printed on 14/10/2020 Page n. 1 / 10 Replaced revision:6 (Dated 01/12/2018)

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

58682 Code:

AUXILIARY PRODUCTS 58682 Mastic varnish Product name

INDUSTRIA MAIMERI S.p.A.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Final varnish. Intended use

1.3. Details of the supplier of the safety data sheet

INDUSTRIA MAIMERI S.p.A. Name Full address Via Gianni Maimeri, 1

District and Country 20060 Mediglia (MI)

Italia

+39 02 906981 Tel. +39 02 90698999 Fax

e-mail address of the competent person responsible for the Safety Data Sheet

schedesicurezza@maimeri.it

Product distribution by: INDUSTRIA MAIMERI S.P.A. VIA G.MAIMERI 1 20060 BETTOLINO DI MEDIGLIA (MI)

1.4. Emergency telephone number

Australia: 131126 For urgent inquiries refer to USA: 1 800 222 1222

Regno Unito NHS Direct (UK): +44 (0) 845 46 47

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication: Flammable liquid, category 3

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Acute toxicity, category 4	H302	Harmful if swallowed.
Acute toxicity, category 4	H312	Harmful in contact with skin.
Acute toxicity, category 4	H332	Harmful if inhaled.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic	H411	Toxic to aquatic life with long lasting effects.
toxicity, category 2		

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:









@EPY 9.10.3 - SDS 1004.13

Page 1 of 10 Item Numbers: 01565-1275

EN 10

58682 - AUXILIARY PRODUCTS

58682 Mastic varnish

Revision nr.7 Dated 27/09/2019 Printed on 14/10/2020 Page n. 2 / 10 Replaced revision:6 (Dated 01/12/2018)

SECTION 2. Hazards identification .../>>

Danger Signal words:

Hazard statements:

H226 Flammable liquid and vapour.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P501 Dispose of contents / container to in accordance with local and national norms...

Keep out of reach of children. P102

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do NOT induce vomiting. P331

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER / doctor / . . .

Contains: Turpentine Essence

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

Turpentine Essence

Flam. Liq. 3 H226, Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, CAS $66 \le x < 70$

Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317,

Aquatic Chronic 2 H411

EC INDEX Reg. no.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

@EPY 9.10.3 - SDS 1004.13

Page 2 of 10 Item Numbers: 01565-1275

58682 - AUXILIARY PRODUCTS

58682 Mastic varnish

Revision nr.7 Dated 27/09/2019 Printed on 14/10/2020 Page n. 3 / 10 Replaced revision:6 (Dated 01/12/2018)

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

@EPY 9.10.3 - SDS 1004.13

Item Numbers: 01565-1275 Page 3 of 10

58682 - AUXILIARY PRODUCTS

58682 Mastic varnish

Revision nr.7 Dated 27/09/2019 Printed on 14/10/2020 Page n. 4 / 10 Replaced revision:6 (Dated 01/12/2018)

SECTION 7. Handling and storage .../>>

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

EU OEL EU Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC;

Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2019

Turpentine Essence											
Threshold Limit Value											
Туре	Country	TWA/8h									
		mg/m3	ppm	mg/m3	ppm						
OEL	EU	112	20								
TLV-ACGIH		111	20				(sens), A4				
Predicted no-effect concentration - PNEC											
Normal value in							88	μg/L			
Normal value in marine water 0,88 µg/L											
Normal value for fresh water sediment 2,27 mg/kg											
Normal value for marine water sediment 0,227 mg/kg											
Normal value for water, intermittent release NPI											
Normal value of STP microorganisms 6,6 mg/l											
Normal value for the food chain (secondary poisoning) 1,35 mg/kg											
Normal value for the terrestrial compartment 0,45 mg/kg											
Health - Derived no-effect level - DNEL / DMEL											
Effects on consumers Effects on w							kers				
Route of exposu	ure Acut	e Ac	ute	Chronic	Chronic	Acute	Acute	Chronic	Chronic		
•	local	sys	stemic	local	systemic	local	systemic	local	systemic		
Oral		59	0		110						
		μg	/kg bw/d		μg/kg bw/d						
Inhalation		12	0		18	10,3	51,6	3,9	780		
		μg	/m3		μg/m3	mg/m3	mg/m3	mg/m3	μg/m3		
Skin						9,51	9,51	3,17	1,6		
						mg/cm2	mg/cm2	mg/cm2	mg/cm2		
						-	-	-	=		

_egend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

@EPY 9.10.3 - SDS 1004.13

Item Numbers: 01565-1275 Page 4 of 10

58682 - AUXILIARY PRODUCTS

58682 Mastic varnish

Revision nr.7 Dated 27/09/2019 Printed on 14/10/2020 Page n. 5 / 10 Replaced revision:6 (Dated 01/12/2018)

SECTION 8. Exposure controls/personal protection

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited. If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Value **Properties** LIQUID Appearance colourless Colour Odour WHITE SPIRIT Not applicable Odour threshold Not applicable Not applicable Melting point / freezing point Initial boiling point Not available Not applicable 23 ≤ T ≤ 60 Boiling range °C Flash point **Evaporation Rate** Not applicable not applicable Flammability of solids and gases Lower inflammability limit Not applicable Upper inflammability limit Not applicable Lower explosive limit Not applicable Upper explosive limit Not applicable Vapour pressure Not applicable Vapour density Not applicable Relative density Solubility SOLUBLE IN WHITE SPIRIT Partition coefficient: n-octanol/water Not applicable Auto-ignition temperature Not applicable Decomposition temperature Not applicable Viscosity 50-60 cps not applicable Explosive properties not applicable Oxidising properties

Information

9.2. Other information

VOC (Directive 2010/75/EC): 68,45 % - 684,52 g/litre VOC (volatile carbon): 68,45 % g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

@EPY 9.10.3 - SDS 1004.13

Page 5 of 10 Item Numbers: 01565-1275

58682 - AUXILIARY PRODUCTS

58682 Mastic varnish

Revision nr.7 Dated 27/09/2019 Printed on 14/10/2020 Page n. 6 / 10 Replaced revision:6 (Dated 01/12/2018)

SECTION 10. Stability and reactivity .../>>

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: LD50 (Oral) of the mixture: LD50 (Dermal) of the mixture: 15,71 mg/l 714,29 mg/kg 1571,43 mg/kg

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

@EPY 9.10.3 - SDS 1004.13

Item Numbers: 01565-1275 Page 6 of 10

58682 - AUXILIARY PRODUCTS

58682 Mastic varnish

Revision nr.7 Dated 27/09/2019 Printed on 14/10/2020 Page n. 7 / 10 Replaced revision:6 (Dated 01/12/2018)

SECTION 11. Toxicological information .../>>

ASPIRATION HAZARD

Toxic for aspiration

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment

12.1. Toxicity

Information not available

12.2. Persistence and degradability

Information not available

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name

ADR / RID: PAINT OF PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL (Turpentine Essence)

IATA: PAINT or PAINT RELATED MATERIAL

@EPY 9.10.3 - SDS 1004.13

Item Numbers: 01565-1275 Page 7 of 10

58682 - AUXILIARY PRODUCTS

58682 Mastic varnish

Revision nr.7 Dated 27/09/2019 Printed on 14/10/2020 Page n. 8 / 10 Replaced revision:6 (Dated 01/12/2018)

SECTION 14. Transport information .../>>

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

IATA:

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID: **Environmentally Hazardous**

IMDG: Marine Pollutant

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID: Limited Quantities: 5 L HIN - Kemler: 30 Tunnel restriction code: (D/E)

Special Provision: -IMDG:

NO

EMS: F-E, <u>S-E</u> Limited Quantities: 5 L IATA: Cargo: Maximum quantity: 220 L

Packaging instructions: 366 Pass.: Maximum quantity: 60 L Packaging instructions: 355

Special Instructions: A3, A72, A192

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point

Contained substance

Point 28c Turpentine Essence

Reg. no.:

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

Substances subject to the Rotterdam Convention:

@EPY 9.10.3 - SDS 1004.13

Page 8 of 10 Item Numbers: 01565-1275

58682 - AUXILIARY PRODUCTS

58682 Mastic varnish

Revision nr.7 Dated 27/09/2019 Printed on 14/10/2020 Page n. 9 / 10 Replaced revision:6 (Dated 01/12/2018)

SECTION 15. Regulatory information .../>>

None

Substances subject to the Stockholm Convention:

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flammable liquid, category 3 Flam. Lig. 3 Acute Tox. 4 Acute toxicity, category 4 Aspiration hazard, category 1 Asp. Tox. 1 Eve Irrit. 2 Eye irritation, category 2 Skin irritation, category 2 Skin Irrit. 2 Skin Sens. 1 Skin sensitization, category 1

Hazardous to the aquatic environment, chronic toxicity, category 2 **Aquatic Chronic 2**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level - EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

@EPY 9.10.3 - SDS 1004.13

Page 9 of 10 Item Numbers: 01565-1275

58682 - AUXILIARY PRODUCTS

58682 Mastic varnish

Revision nr.7 Dated 27/09/2019 Printed on 14/10/2020 Page n. 10 / 10 Replaced revision:6 (Dated 01/12/2018)

SECTION 16. Other information .../>>

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 848/2013 (IV Atp. CLP) of the European Parliament

- Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

- 10. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP) 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

03 / 08 / 09 / 15.

@EPY 9.10.3 - SDS 1004.13