

Article No.: 114XXX016 TURPENTINE OIL THINNER
Print date 13.09.2016 Revision date 11.07.2016 EN
Version 1.0 Issue date 11.07.2016 Page 1 / 7

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier): 114XXX016
Identification of the substance or mixture TURPENTINE OIL THINNER
CONFORMS TO ASTM D4236

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:
Artists supply and hobby preparations
Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor):
Daler-Rowney Ltd
Peacock Lane Telephone: +44 (0) 1344 461083
Bracknell, RG12 8SS Telefax: +44 (0) 1344 486511
ENGLAND

Dept. responsible for information:

E-mail Philip.Gray@daler-rowney.com

1.4. Emergency telephone number

Emergency telephone: +44 (0) 1344 461000

2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]


Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	respiratory or skin sensitisation	May cause an allergic skin reaction.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H226 Flammable liquid and vapour.
H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P270 Do not eat, drink or smoke when using this product.

Article No.: 114XXX016 TURPENTINE OIL THINNER
 Print date 13.09.2016 Revision date 11.07.2016 EN
 Version 1.0 Issue date 11.07.2016 Page 2 / 7

- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P331 Do NOT induce vomiting.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P337 + P313 If eye irritation persists: Get medical advice/attention.
- P362 + P364 Take off contaminated clothing and wash it before reuse.
- P370 + P378 In case of fire: Use foam to extinguish.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local legislation.

contains:

turpentine, oil

Supplemental Hazard information (EU)

n.a.

2.3. Other hazards

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

3. Composition / Information on ingredients

3.1. Substances

Description Painting Medium for Oil-Colour

Hazardous ingredients

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC No.	REACH No.	Wt %
CAS No.	Chemical name	Remark
INDEX No.	classification:	
232-350-7		
8006-64-2	turpentine, oil	50 - 100
650-002-00-6	Flam. Liq. 3 H226 / Acute Tox. 4 H332 / Acute Tox. 4 H312 / Acute Tox. 4 H302 / Asp. Tox. 1 H304 / Eye Irrit. 2 H319 / Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411	

Additional information

Full text of classification: see section 16

4. First-aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

Article No.:	114XXX016	TURPENTINE OIL THINNER	
Print date	13.09.2016	Revision date	11.07.2016
Version	1.0	Issue date	11.07.2016
			EN
			Page 3 / 7

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage. Vapours form explosive mixtures with air.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Cool closed containers that are near the source of the fire.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations. Vapours form explosive mixtures with air.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13).

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

7. Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSivO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect

Article No.: 114XXX016 TURPENTINE OIL THINNER
 Print date 13.09.2016 Revision date 11.07.2016 EN
 Version 1.0 Issue date 11.07.2016 Page 4 / 7

from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

8. Exposure controls / Personal protection

8.1. Control parameters

Occupational exposure limit values:

turpentine, oil

INDEX No. 650-002-00-6 / EC No. 232-350-7 / CAS No. 8006-64-2

TWA: 566 mg/m³; 100 ppm

STEL: 850 mg/m³; 150 ppm

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance: liquid
Physical state liquid
Colour refer to label
Odour characteristic

Safety relevant basis data	Unit	Method	Remark
Flash point:	< 50 °C	DIN 53213	
Ignition temperature in °C:	220 °C		
Lower explosion limit	0,7 Vol-%		
Upper explosion limit	6,1 Vol-%		
Vapour pressure at 20 °C:	2,50 mbar		
Density at 20 °C:	1,00 g/cm ³		
Water solubility (g/L)	insoluble		
pH at 20 °C:	-		
Viscosity at 20 °C	< 50 mPa·s		

Article No.: 114XXX016 TURPENTINE OIL THINNER
Print date 13.09.2016 Revision date 11.07.2016 EN
Version 1.0 Issue date 11.07.2016 Page 5 / 7

Solvent separation test (%) < 3 %
boiling point in °C at 101,3 kPa 150 °C

9.2. **Other information:**

10. Stability and reactivity

10.1. **Reactivity**

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. Vapours form explosive mixtures with air.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

11. Toxicological information

Classification according to Regulation (EC) No. 1272/2008 [CLP]
No data on preparation itself available.

11.1. **Information on toxicological effects**

Acute toxicity

turpentine, oil
oral, LD50, Rat: 5760 mg/kg

skin corrosion/irritation; Serious eye damage/eye irritation

turpentine, oil
Skin (4 h)
Irritating to skin.

Respiratory or skin sensitisation

turpentine, oil
Skin:
May cause sensitization by skin contact.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:
Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

12. Ecological information

Article No.: 114XXX016 TURPENTINE OIL THINNER
Print date 13.09.2016 Revision date 11.07.2016
Version 1.0 Issue date 11.07.2016 EN
Page 6 / 7

overall evaluation

Classification according to Regulation (EC) No. 1272/2008 [CLP]
There is no information available on the preparation itself .
Do not allow to enter into surface water or drains.

12.1. Toxicity

turpentine, oil
Daphnia toxicity, EC50: 14,1 mg/L (48 h)

Long-term Ecotoxicity

turpentine, oil
Fish toxicity, LC50: (96 h)

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Other adverse effects

13. Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

140603 other solvents and solvent mixtures

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. Send to a collecting point for used paints.

14. Transport information

14.1. UN number

UN 1299

14.2. UN proper shipping name

Land transport (ADR/RID): Turpentine
Sea transport (IMDG): TURPENTINE
Air transport (ICAO-TI / IATA-DGR): Turpentine

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID) UMWELTGEFÄHRDEND
Marine pollutant p / turpentine

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

Additional information

Article No.: 114XXX016 TURPENTINE OIL THINNER
Print date 13.09.2016 Revision date 11.07.2016
Version 1.0 Issue date 11.07.2016 EN
Page 7 / 7

Land transport (ADR/RID)

tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 860

VOC-value (in g/L) ASTM D 2369: 860

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

16. Other information

Full text of classification in section 3:

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Skin Sens. 1 / H317	respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Additional information

Classification according to Regulation (EC) No. 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.