

Article No.: 114XXX002 MATT & CLEAR PICTURE VARNISH  
Print date 14.09.2016 Revision date 06.09.2016 EN  
Version 1.2 Issue date 06.09.2016 Page 1 / 8

**1. Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifiers**

Article No. (manufacturer/supplier): 114XXX002  
Identification of the substance or mixture MATT & CLEAR PICTURE VARNISH  
CONFORMS TO ASTM D4236

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses:**  
Artists supply and hobby preparations  
Coatings and paints, thinners, paint removers

**1.3. Details of the supplier of the safety data sheet**

**Supplier (manufacturer/importer/downstream user/distributor):**  
Daler-Rowney Ltd  
Peacock Lane Telephone: +44 (0) 1344 461083  
Bracknell, RG12 8SS Telefax: +44 (0) 1344 486511  
ENGLAND

**Dept. responsible for information:**

E-mail Philip.Gray@daler-rowney.com

**1.4. Emergency telephone number**

Emergency telephone: +44 (0) 1344 461000

**2. Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

The product is classified and labelled according to EC directives or corresponding national laws.

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Warning**

**Hazard statements**

H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.  
H304 May be fatal if swallowed and enters airways.  
H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P102 Keep out of reach of children.  
P103 Read label before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P331 Do NOT induce vomiting.

Article No.: 114XXX002 MATT & CLEAR PICTURE VARNISH  
Print date 14.09.2016 Revision date 06.09.2016 EN  
Version 1.2 Issue date 06.09.2016 Page 2 / 8

P370 + P378 In case of fire: Use foam to extinguish.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container in accordance with local legislation.

**contains:**

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

**Supplemental Hazard information (EU)**

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. **Other hazards**

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

**3. Composition / Information on ingredients**

3.2. **Mixtures**

**Product description / chemical characterization**

**Description** Alkydharz-Lack

**Hazardous ingredients**

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

EC No. CAS No. INDEX No.	REACH No. Chemical name classification:	Wt % Remark
919-446-0 64742-82-1 649-330-00-2	01-2119458049-33 Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT SE 3 H336 / Aquatic Chronic 2 H411	25 - 50
203-539-1 107-98-2 603-064-00-3	1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	2,5 - 5

**Additional information**

Full text of classification: see section 16

**4. First-aid measures**

4.1. **Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

**5. Firefighting measures**

5.1. **Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Article No.: 114XXX002 MATT & CLEAR PICTURE VARNISH  
Print date 14.09.2016 Revision date 06.09.2016  
Version 1.2 Issue date 06.09.2016

EN  
Page 3 / 8

**Extinguishing media which must not be used for safety reasons:**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage. Vapours form explosive mixtures with air.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Cool closed containers that are near the source of the fire.

**6. Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations. Vapours form explosive mixtures with air.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13).

**6.4. Reference to other sections**

Observe protective provisions (see chapter 7 and 8).

**7. Handling and storage**

**7.1. Precautions for safe handling**

**Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

**Precautions against fire and explosion:**

Vapours are heavier than air. Vapours form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSivO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

**7.3. Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**8. Exposure controls / Personal protection**

**8.1. Control parameters**

**Occupational exposure limit values:**

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

Article No.: 114XXX002 MATT & CLEAR PICTURE VARNISH  
Print date 14.09.2016 Revision date 06.09.2016  
Version 1.2 Issue date 06.09.2016

EN  
Page 4 / 8

TWA: 375 mg/m<sup>3</sup>; 100 ppm  
STEL: 560 mg/m<sup>3</sup>; 150 ppm

**Additional information**

TWA : long-term occupational exposure limit value  
STEL : short-term occupational exposure limit value  
Ceiling : peak limitation

**DNEL:**

1-methoxy-2-propanol  
INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2  
DNEL long-term dermal (systemic), Workers: 50,6 mg/kg  
DNEL acute inhalative (local), Workers: 553,5 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 369 mg/m<sup>3</sup>  
DNEL long-term dermal (systemic), Consumer: 18,1 mg/kg  
DNEL long-term inhalative (systemic), Consumer: 43,9 mg/m<sup>3</sup>

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

INDEX No. 649-330-00-2 / EC No. 919-446-0 / CAS No. 64742-82-1  
DNEL long-term dermal (systemic), Workers: 44 mg/kg bw/day  
DNEL long-term inhalative (systemic), Workers: 330 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 26 mg/kg bw/day  
DNEL long-term dermal (systemic), Consumer: 26 mg/kg bw/day  
DNEL long-term inhalative (systemic), Consumer: 71 mg/m<sup>3</sup>

**PNEC:**

1-methoxy-2-propanol  
INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2  
PNEC aquatic, freshwater: 10 mg/L  
PNEC aquatic, marine water: 1 mg/L  
PNEC sediment, freshwater: 41,6 mg/kg  
PNEC sediment, marine water: 4,17 mg/kg  
PNEC sewage treatment plant (STP): 100 mg/L

8.2. **Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Occupational exposure controls**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)  
Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.  
Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374  
Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye protection**

Wear closely fitting protective glasses in case of splashes.

**Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

**9. Physical and chemical properties**

9.1. **Information on basic physical and chemical properties**

**Appearance:** liquid

Article No.: 114XXX002 MATT & CLEAR PICTURE VARNISH  
Print date 14.09.2016 Revision date 06.09.2016 EN  
Version 1.2 Issue date 06.09.2016 Page 5 / 8

**Physical state** liquid  
**Colour** refer to label  
**Odour** characteristic

Safety relevant basis data	Unit	Method	Remark
Flash point:	= 40 °C	DIN 53213	
Ignition temperature in °C:	235 °C		
Lower explosion limit	0,6 Vol-%		
Upper explosion limit	12,0 Vol-%		
Vapour pressure at 20 °C:	1,89 mbar		
Density at 20 °C:	1,00 g/cm <sup>3</sup>		
Water solubility (g/L)	partially soluble		
pH at 20 °C:	-		
Viscosity at 20 °C	< 20 mPa·s		
Solvent separation test (%)	< 3 %		
boiling point in °C at 101,3 kPa	120 °C		

9.2. **Other information:**

**10. Stability and reactivity**

10.1. **Reactivity**

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. Vapours form explosive mixtures with air.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**11. Toxicological information**

Classification according to Regulation (EC) No. 1272/2008 [CLP]  
No data on preparation itself available.

11.1. **Information on toxicological effects**

**Acute toxicity**

1-methoxy-2-propanol

oral, LD50, Rat: 4016 mg/kg

dermal, LD50, Rabbit: 2000 mg/kg

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

oral, LD50, Rat: > 15000 mg/kg

Method: OECD 401

dermal, LD50, Rat: 3400 mg/kg

inhalative (vapours), LC50, Rat: 13100 mg/L (4 h)

Vapours may cause drowsiness and dizziness.

**skin corrosion/irritation; Serious eye damage/eye irritation**

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Skin (4 h)

Repeated exposure may cause skin dryness or cracking.

**Respiratory or skin sensitisation**

Toxicological data are not available.

**Specific target organ toxicity**

Toxicological data are not available.

Article No.: 114XXX002 MATT & CLEAR PICTURE VARNISH  
Print date 14.09.2016 Revision date 06.09.2016 EN  
Version 1.2 Issue date 06.09.2016 Page 6 / 8

#### Aspiration hazard

Toxicological data are not available.

#### Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### Remark

There is no information available on the preparation itself .

### 12. Ecological information

#### overall evaluation

Classification according to Regulation (EC) No. 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

1-methoxy-2-propanol

Fish toxicity, LC50, *Leuciscus idus* (golden orfe): 6812 mg/L (96 h)

Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 23300 mg/L (48 h)

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 10 - 22 mg/L (48 h)

Method: OECD 202

Algae toxicity, ErC50, *Pseudokirchneriella subcapitata*: 4,6 - 10 mg/L

Method: OECD 201

#### Long-term Ecotoxicity

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Fish toxicity, LC50, *Oncorhynchus mykiss*: 10 mg/L (96 h)

#### 12.2. Persistence and degradability

Toxicological data are not available.

#### 12.3. Bioaccumulative potential

1-methoxy-2-propanol

Distribution coefficient (n-octanol / water) (log P O/W): -0,44

Method: Log KOC

#### 12.4. Mobility in soil

Toxicological data are not available.

#### 12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

### 13. Disposal considerations

#### 13.1. Waste treatment methods

##### Appropriate disposal / Product

##### Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

##### List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or other dangerous substances

#### packaging

Article No.: 114XXX002 MATT & CLEAR PICTURE VARNISH  
 Print date 14.09.2016 Revision date 06.09.2016 EN  
 Version 1.2 Issue date 06.09.2016 Page 7 / 8

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. Send to a collecting point for used paints.

**14. Transport information**

- 14.1. **UN number** UN 1866
- 14.2. **UN proper shipping name**  
 Land transport (ADR/RID): Resin solution  
 Sea transport (IMDG): RESIN SOLUTION  
 Air transport (ICAO-TI / IATA-DGR): Resin solution
- 14.3. **Transport hazard class(es)** 3
- 14.4. **Packing group** III
- 14.5. **Environmental hazards**  
 Land transport (ADR/RID) UMWELTGEFÄHRDEND  
 Marine pollutant p / Kohlenwasserstoffe, C9-C12, n-Alkane, iso-Alkane, cyclische Verbindungen, Aromaten (2 - 25 %)
- 14.6. **Special precautions for user**  
 Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.  
 Advices on safe handling: see parts 6 - 8

**Additional information**

**Land transport (ADR/RID)**

tunnel restriction code D/E

**Sea transport (IMDG)**

EmS-No. F-E, S-E

- 14.7. **Transport in bulk according to Annex II of MARPOL and the IBC Code**  
 not applicable

**SECTION 15: Regulatory information**

- 15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).**

VOC-value (in g/L) ISO 11890-2: 332  
 VOC-value (in g/L) ASTM D 2369: 332

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**Other regulations, restrictions and prohibition regulations**

- 15.2. **Chemical Safety Assessment**

**For the following substances of this preparation a chemical safety assessment has been carried out:**

EC No.	Chemical name	REACH No.
919-446-0	Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics	01-2119458049-33
64742-82-1	(2-25%)	

**16. Other information**

**Full text of classification in section 3:**

Flam. Liq. 3 / H226 flammable liquids Flammable liquid and vapour.  
 Asp. Tox. 1 / H304 Aspiration hazard May be fatal if swallowed and enters airways.

Article No.:	114XXX002	MATT & CLEAR PICTURE VARNISH	
Print date	14.09.2016	Revision date 06.09.2016	EN
Version	1.2	Issue date 06.09.2016	Page 8 / 8

---

STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
------------------	--	------------------------------------

Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
--------------------------	--------------------------------------	--

**Abbreviations and acronyms**

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

**Additional information**

Classification according to Regulation (EC) No. 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.