

01597-0002 Cadmium

HAR1602 JUNE 1, 2015 Page 1 of 9

MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING CAPMIUM PIGMENTS

1. Identification of the Preparation and of The Company

MICHAEL HARDING ARTIST OIL COLORS -COLORS CONTAINING CADMIUM

Product Name and/or code:

PIGMENTS

Effective Date:

1-Jun-15

Manufacturer:

Michael Harding Art Materials, Ltd. 36 Springdale Industrial Estate Cwmbran, Gwent NP44 -5BD, Wales

Information Contact:

North America: 978-549-4029; UK/Europe: 44 (0) 1633 - 484-700

Emergency Contact:

Contact your local Poison Control Center

Product Use:

ART MATERIAL - Consumer Product

2. Hazards Identification

Information pertaining to particular dangers for man and environment.

This product has been classified as dangerous according to OSHA Hazard

Communication Standard (29 CFR 1910.1200)

Emergency Overview

WARNING! HARMFUL IF SWALLOWED. Cancer Hazard. Contains insoluble cadmium compounds which can cause cancer by ingestion and inhalation of excessive fumes or dust. Effects of ingestion are cumulative due to slow elimination of absorbed cadmium. May cause harm to kidneys, testes, and developing fetus. Prolonged or repeated skin contact may cause irritation and dermatitis.

Label Elements

Conforms to ASTM D-4236

Pictograms







For Cadmium compounds GHS07, GHS08, GHS09

Signal Word

WARNING!

Hazard Statement

Contains insoluble cadmium compounds which can cause cancer by ingestion and inhalation of excessive fumes or dust. Effects of ingestion are cumulative due to slow elimination of absorbed cadmium. May cause harm to kidneys, testes, and developing fetus. Prolonged or repeated skin contact may cause

irritation and dermatitis.

Precaution Statement

Do not eat. Wash hands and face before eating or smoking. Ensure fresh air entry during application and drying. Avoid dust or prolonged or repeated skin contact.

Children's Statement

KEEP OUT OF REACH OF CHILDREN.

Classification of the Product:

NFPA

Health 3 - Warning. Corrosive or toxic. Avoid skin contact or inhalation.

Flammability 1- Combustible if heated.

Reactivity 0 - Stable

HMIS

Health 3 - Serious

Flammability 1 - Slight Hazard



HAR1602 JUNE 1, 2015 Page 2 of 9

MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING CADMIUM PIGMENTS

Regulation (EC) No. 1272/2008

Physical Hazard 0 - Minimal Hazard

Cadmium compounds are classified in Annex VI of the Classification Labeling and

Packaging

Export and Import of Dangerous Chemicals Regulation (EC)No. 649/2012

The ingredients of this product are listed in the Annex I of the regulation.

649/2012 Directive 67/548/EEC & Directive

Cadmium compounds, major components of these products are classified as following:

Cadmium Sulfide (CAS 1306-23-6): Acute Tox. 4 H302, Muta. 2 H341, Carc. 1B H350, STOT RE 1 H372, Aquatic Chronic 4

Cadmium Sulfoselenide Orange (CAS 12656-57-4): Not classified.

Cadmium Sulfoselenide Red (CAS 58339-34-7): Acute Tox. 4 H302, H312, H332

As per the manufacture of the cadmium pigments, James M. Brown: Cadmium pigments are less hazardous than other cadmium compounds as they are less soluble: this greatly reduces the risk of absorption of cadmium into the body and also greatly reduces their environmental hazard. These products contain no PBT or vPvB substance or anything listed on the "candidate list". They contain no persistent organic pollutants or anything capable of causing damage to the ozone layer. These products do not offer any dust explosion hazard.

3.Composition/Information on Ingredients:

Substances:

1999/45/EC

The various products listed under Section 16 contain non-hazardous natural drying oils, organic and inorganic pigments, additives.

Hazardous Ingredients - Cadmium

Cadmium Sulfide (CAS 1306-23-6)-----60.0 - 90.0%

compounds:

Cadmium Sulfoselenide Orange (CAS 12656-57-4)----60.0 - 90.0%

Cadmium Sulfoselenide Red (CAS 58339-34-7): ------60.0 - 90.0%

Risk and Safety Phrases:

Ingredients are marked according to CLP Regulation (CLP-Regulation (EC) No 1272/2008) and according to DSD (Dangerous Substances Directive (67/548/EEC)) and DPD (Dangerous Preparations Directive (1999/45/EC)). These ingredients are regarded as trade secrets.

4. First Aid Measures Inhalation Supply fresh air. If required, prov

nhalation Supply fresh air. If required, provide artificial respiration. Consult with a doctor,

physician or qualified health professional if symptoms persist. In case of unconsciousness place patient securely in side position for transportation (if

needed).

Skin Contact Remove any contaminated clothing. Wash affected area immediately with

water and soap and rinse thoroughly.

Item Numbers: 01597-3092, 01597-3093, 01597-3202, 01597-3203, 01597-3323, 01597-3333, 01597-3333, 01597-4123, 01597-4182, 01597-4185, 01597-4185, 01597-4203, 01597-4203, 01597-4205, 01597-4282, 01597-4282, 01597-4293, 0159



HAR1602 JUNE 1, 2015 Page 3 of 9

MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING CADMIUM PIGMENTS

Eye Contact

Flush area with water, lifting the upper and lower lids until no evidence of product remains. Get medical attention. Do not wear contact lenses while

handling.

Ingestion

Drink water or milk to dilute. Do not induce vomiting. Contact a physician.

Most important symptoms and effects, both acute and delayed

Typical clinical manifestations of lead poisoning include weakness, irritability, asthenia, nausea, abdominal pain with constipation, and anemia.

	5. Firefighting Measures
Extinguishing Media	Water, foam, carbon dioxide or dry chemical equipment.
Fire/Explosion Hazards	This product is not known to present any fire hazard.
Flashpoint/Flammability	This product is not known to be flammable but as a precaution keep product in cool place. It can be combustible if heated.
Special hazards arising from the substance or mixture	May give off toxic fumes in case of fire, including lead fumes.
	6. Accidental Release Measures
Environmental precautions	No product should be released to the environment without due care.
Methods and Materials for	Contain spill. Recover as much as possible with sand, soil or similar product.
Containment and Cleaning up	Place into closed container and store in a safe location to await disposal. Wash the spill area with soap and water.
	7. Handling and Storage
Safe Handling	Do not eat, drink or smoke when using these materials. Wash hands after use. Remove contaminated clothing and protective equipment before entering eating areas. Minimize dust in the workplace atmosphere caused by rough handling. Do not mix or use with acids or powerful oxidizing agents. Avoid spills and ensure that these products do not enter drains or watercourses during use or as a result of any spillage.
Storage	Store away from food, drink and animal feeding stuffs. Store under normal warehouse conditions away from sources of ignition, concentrated acids and

8. Exposure Controls/Personal Protection

when not in use.

Personal Protective Equipment

Wear safety goggles and protective gloves to avoid dust contact.

powerful oxidizing agents. Store only in original containers and keep sealed



HAR1602 JUNE 1, 2015 Page 4 of 9

MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING CADMIUM PIGMENTS

Exposure Limits

Component	CAS-No.	Value	Control parameters	Basis	
Cadmium sulphide	1306-23-6	TWA	0.01 mg/m3	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Kidney damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Suspected human carcinogen			
		TWA	0.010000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)	
		Kidney damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Suspected human carcinogen varies TWA 0.002 mg/m3 USA. ACGIH Threshold Limit Values			
	1	Kidney dar	mage	(TLV)	
		Substance (see BEI®	s for which there is	s a Biological Exposure Index or Indices	
	TWA	0.002000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)		
		Kidney damage Substances for which there is a Biological Exposure Index of (see BEI® section) Suspected human carcinogen varies Potential Occupational Carcinogen See Appendix A			
			occupational Carcin	nogen	
		PEL	0.005000 mg/m3	OSHA Specifically Regulated Chemicals/Carcinogens	
		1910.1027 This standard applies to all occupational exposures to cadmium and cadmium compounds, in all forms, and in all industries covered by the Occupational Safety and Health Act, except the construction-related industries, which are covered under 29 CFR 1926.63. OSHA specifically regulated carcinogen			
		PEL	0.005000 mg/m3	OSHA Specifically Regulated Chemicals/Carcinogens	
		1910.1027 This standard applies to all occupational exposures to cadmium and cadmium compounds, in all forms, and in all industries covered by the Occupational Safety and Health Act, except the construction-related industries, which are covered under 29 CFR 1926.63. OSHA specifically regulated carcinogen			



HAR1602 **JUNE 1, 2015** Page 5 of 9

MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING CADMIUM PIGMENTS

Biological occupational limits

Biological occupational exposure limits					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Cadmium sulphide	1306-23-6	cadmium	5 µg/l	In blood	ACGIH - Biological Exposure Indices (BEI)
	Remarks	Not critical			
		cadmium	5µg/g creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
		Not critical			

Respiratory and Ventilation

Wear approved NIOSH/MSHA respirator if exposure to mist or vapor exceed applicable PEL/TLV limits. Use in accordance with manufacturer's use limitations and OSHA STANDARD 1910-34. Local ventilation may be used to prevent routine inhalation.

Skin Protection

Handle with non-porous nitrile gloves. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full Contact Material: Nitrile rubber

Data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an Industrial Hygienist familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific

use scenario.

Eye Protection

Safety glasses conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).



HAR1602 JUNE 1, 2015 Page 6 of 9

MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING CADMIUM PIGMENTS

As per the manufacture of the cadmium pigments, James M. Brown: Use under local exhaust ventilation whenever possible to minimize dust levels. An air face velocity of 0.5 - 1 m sec⁻¹ is suggested. If LEV is not available, or is thought to be insufficient, then use of a dust mask complying with EN 149 type P1 is suggested. If mixtures containing these products are being sprayed, use of efficient LEV is strongly advised, together with a P1 dust mask: if LEV is not available, use of a P2 or P3 mask is strongly advised. Whenever spraying is being carried out, care needs to be taken to ensure that other persons in the area are also suitably protected.

9. Ph	vsical and	Chemical	Pro	perties
-------	------------	----------	-----	---------

Appearance Viscous colored oil paints

Physical State Solid - Paste

Color See product list in Section 16

Odor Slightly aromatic.

Boiling Point Greater than 100°C/ 212°F

Freezing Point
State (pH)
Specific Gravity
Not applicable
8.5 - 9.2
1.0 - 2.0

Viscosity Not determined (Viscous material)

Flashpoint Greater than 230°C/ 446°F

Vapor Pressure

Vapor Density

Solubility in water

Not applicable

Not Miscible

10. Stability and Reactivity

Reactivity: Not expected to be reactive.

Chemical Stability Stable

Conditions to Avoid Keep away from heat, sparks and flame. Incompatible materials Combustible material (eg. Cotton)

Hazardous Decomposition Products May give off toxic fumes in case of fire, including lead fumes.

11. Toxicological Information

Health Effects Studies have not been performed on this particular mixture. The information

below is based on data on the individual ingredients.

Oral Low Acute Toxicity, but High Chronic hazard, not otherwise quantifiable.

Inhalation Overexposure my cause symptoms of chronic lung disease and lead poisoning.

Dermal This product is not a primary skin irritant.

Eye Effects May cause physical irritation and inflammation.



HAR1602 JUNE 1, 2015 Page 7 of 9

MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING CADMIUM PIGMENTS

As per the manufacture of the cadmium pigments, James M. Brown: These products i.e. pigments are of a lower toxicity than other cadmium compounds due to their extreme insolubility. A range of values have been reported for oral LD $_{50}$ s for several species exposed to these products: the values are normally greater than 5000 mg/kg. Gross overexposure over many years may lead to kidney damage, but this should never happen given modern working conditions. On the basis of the available data, it is not judged that these products offer a skin irritation/skin sensitization hazard.

12. Ecological Information			
Aquatic toxicity	No information available.		
Persistence and degradability	No information available.		
Mobility in soil	No information available.		

13. Disposal Considerations

Dispose of all waste material in accordance with all applicable federal, state and local regulations for the disposal of hazardous waste. Must be disposed as hazardous chemical waste. Do not allow product to reach sewage system.

Uncontaminated packaging may be safely reused. Do not burn or reuse contaminated packaging- this must be done following the requirements of the Environmental Protection Act 1990 and observing the "Duty of Care". Outside the UK, all relevant national and local legislation must be complied with.

14. Transport Information

The following transportation categories do not apply to this mixture sold as a consumer use product (non-bulk). **DOT Non-Bulk**

Shipping Name

Environmetally hazardous substances, solid, n.o.s. (Cadmium sulfide)

Technical Shipping Name

Environmetally hazardous substances, solid, n.o.s. (Cadmium sulfide)

Hazard Class 9 **UN Number** 3077 **Packing Group** Ш

<u>IMDG</u>

Shipping Name Environmetally hazardous substances, solid, n.o.s. (Cadmium sulfide)

Technical Shipping Name

Environmetally hazardous substances, solid, n.o.s. (Cadmium sulfide)

Hazard Class UN Number 3077 Packing Group 111

EmS Number Not applicable

Marine Pollutant EHS/Marine Pollutant Mark required

ICAO/IATA

Shipping Name Environmetally hazardous substances, solid, n.o.s. (Cadmium sulfide)



HAR1602 **JUNE 1, 2015** Page 8 of 9

MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING CADMIUM PIGMENTS

Environmetally hazardous substances, solid, n.o.s. (Cadmium sulfide) **Technical Shipping Name**

9 **Hazard Class** 3077 **UN Number** Ш **Packing Group**

Michael Harding Art Materials Ltd. are IATA certified through the UK CAA.

This information is not intended to convey all specific regulatory or operational requirements/information relating to

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture.

SARA Not applicable

Section 355 (extremely hazardous

substances) Not applicable Section 313 (Specific toxic chemical Not applicable

listing)

TSCA (Toxic Substance Control Act) All ingredients are listed.

The Safe Drinking Water and Toxic

Proposition 65

As of June 1, 2015 this product contains cadmium compounds known to the Enforcement Act of 1986 - California State of California to cause cancer, at levels which would require a warning

under the statue.

Cadmium Compounds Chemicals known to cause cancer

Chemicals known to cause reproductive toxicity for females None of the ingredients are listed as of 6/1/15.

Chemicals known to cause reproductive toxicity for males

None of the ingredients are listed as of 6/1/15.

Chemicals known to cause developmental toxicity

None of the ingredients are listed as of 6/1/15.

Carcinogenicity categories

EPA (Environmental Protection

Agency)

Possible human carcinogen

TLV (Threshold Limit Value established by ACGIH)

Possible human carcinogen

MAK (German Maximum Workplace No information available

Concentration)

NOISH-Ca (National Institute for Occupational Safety & Health)

OSHA-Ca (Occupational Safety &

Health Administration)

Possible human carcinogen

Possible human carcinogen



HAR1602 JUNE 1, 2015 Page 9 of 9

MICHAEL HARDING ARTIST OIL COLORS COLORS CONTAINING CADMIUM PIGMENTS

16. Other Information

<u> २०५० वर्ष भग्ना भारतार (०००० ४ स्तान</u>	2Finentification
401 Cadmium Yellow Lemon	PY 35 Cadmium Sulphide
402 Cadmium Yellow	PY 35 Cadmium Sulphide
403 Cadmium Golden Yellow	PY 35 Cadmium Sulphide
404 Cadmium Yellow Deep	PY 35 Cadmium Sulphide
502 Cadmium Orange	PO 20 Cadmium Sulphoselenide
503 Cadmium Red Light	PR 108 Cadmium Sulphoselenide
504 Cadmium Red	PR 108 Cadmium Sulphoselenide
505 Cadmium Red Deep	PR 108 Cadmium Sulphoselenide

H Statements

H302 Harmful if swallowed. H332 Harmful if inhaled.

H312 Harmful in contact with skin.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

Supersedes MSDS

11-Oct-13

Reason for Issue: Prepared by:

GHS Format

Rudolph J. Jaeger, Ph.D., DABT, ERT (UK)

Chief Toxicologist and President ENVIRONMENTAL MEDICINE, INC.

263 CENTER AVENUE WESTWOOD, NJ 07675 jaegerr@envmed.com 201-666-7929 x13

The information contained in this Safety Data Sheet was compiled using the latest and most reliable information available to Michael Harding Art Materials, Ltd. The information is provided without any warranty, express or implied regarding its correctness or accuracy nor will Michael Harding Art Materials, Ltd assume any liability for any loss or damage arising out of the use of this information including without limitation direct or indirect losses or expenses. To the extent permitted by law, no warranty express or implied regarding the product described herein shall be created by or inferred from any state or omission for this SDS. It is solely the responsibility of the user to determine safe conditions for use of this product and to assume liability for any loss, damage or expense whatsoever arising out of the product's improper use.