

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version 1.1 (28/03/2025) - Page 1/11

BLICK ART MATERIALS

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product name : BLICK ACRYLIC PAINT - NAPLES YELLOW WARM

Product code : N131711.563.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint for artist

1.3. Details of the supplier of the safety data sheet

Registered company name : BLICK ART MATERIALS.

Address : GALESBURG IL 61401...USA.

Telephone : 800-447-8192. Fax : .

DickBlick.com

1.4. Emergency telephone number : .

Association/Organisation : .

SECTION 2 : HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture****In compliance with EC regulation No. 1272/2008 and its amendments.**

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements**In compliance with EC regulation No. 1272/2008 and its amendments.**

Additional labeling :

EUH208

Contains REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

EUH208

Contains 2-MÉTHYL-2H-ISOTHIAZOLE-3-ONE. May produce an allergic reaction.

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read carefully and follow all instructions.

2.3. Other hazardsThe mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 59 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
BLICK ART MATERIALS

Version 1.1 (28/03/2025) - Page 2/11

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures****Composition :**

Identification	Classification (EC) 1272/2008	Note	%
CAS: 57-55-6 EC: 200-338-0 REACH: 01-2119456809-23-XXXX PROPANE-1,2-DIOL		[i]	2.5 <= x % < 10
CAS: 14808-60-7 EC: 238-878-4 QUARTZ		[i]	2.5 <= x % < 10
CAS: 13463-67-7 EC: 236-675-5 TITANIUM DIOXIDE [IN POWDER FORM CONTAINING 1 % OR MORE OF PARTICLES WITH AERODYNAMIC DIAMETER <= 10 µM]	GHS08 Wng Carc. 2, H351 EUH212	[i] [10]	2.5 <= x % < 10
CAS: 107-21-1 EC: 203-473-3 REACH: 01-2119456816-28-XXXX MONOETHYLENE GLYCOL	GHS07, GHS08 Wng Acute Tox. 4, H302 STOT RE 2, H373	[i]	0.1 <= x % < 1
CAS: 1309-37-1 EC: 215-168-2 REACH: 05-2114135294-54-0000 TRIOXYDE DE DIFER		[i]	0 <= x % < 0.1
INDEX: 613-167-00-5 CAS: 55965-84-9 REACH: 01-2120764691-48 REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 100 Aquatic Chronic 1, H410 M Chronic = 100 EUH071	B	0 <= x % < 0.1
CAS: 2682-20-4 EC: 220-239-6 REACH: 01-2120764690-50-XXXX 2-MÉTHYL-2H-ISOTHIAZOLE-3-ONE	GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Chronic 2, H411 Aquatic Acute 1, H400 M Acute = 10		0 <= x % < 0.1

Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 14808-60-7 EC: 238-878-4 QUARTZ		oral: ATE = 500 mg/kg BW

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
BLICK ART MATERIALS

Version 1.1 (28/03/2025) - Page 3/11

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563

INDEX: 613-167-00-5 CAS: 55965-84-9 REACH: 01-2120764691-48 REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	Skin Corr. 1C: H314 C $\geq$ 0.6% Skin Irrit. 2: H315 0.06% $\leq$ C < 0.6% Eye Dam. 1: H318 C $\geq$ 0.6% Eye Irrit. 2: H319 0.06% $\leq$ C < 0.6% Skin Sens. 1A: H317 C $\geq$ 0.0015%	
CAS: 2682-20-4 EC: 220-239-6 REACH: 01-2120764690-50-XXXX 2-MÉTHYL-2H-ISOTHIAZOLE-3-ONE	Skin Sens. 1A: H317 C $\geq$ 0.0015%	

Information on ingredients :

(Full text of H-phrases: see section 16)

[i] Substance for which maximum workplace exposure limits are available.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq$ 10 μ m.**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures**In the event of exposure by inhalation :**

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
BLICK ART MATERIALS

Version 1.1 (28/03/2025) - Page 4/11

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
BLICK ART MATERIALS

Version 1.1 (28/03/2025) - Page 5/11

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limits :**

- European Union :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
107-21-1	52	20	104	40	Peau

- UK :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
57-55-6	10 mg/m3				
14808-60-7	0.3 mg/m3	-	-	-	R
13463-67-7	4 mg/m3				
107-21-1	20 ppm 52 mg/m3	40 ppm 104 mg/m3		Sk	
1309-37-1	5 mg/m3	10 mg/m3	-	-	-

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard ISO 16321.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Physical state**

Physical state : Viscous liquid.

Colour

Unspecified

Odour

Odour threshold : Not stated.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
BLICK ART MATERIALS

Version 1.1 (28/03/2025) - Page 6/11

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563**Melting point**

Melting point/melting range : Not specified.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not specified.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) Not stated.

:

Explosive properties, upper explosivity limit (%) Not stated.

:

Flash point

Flash Point : 101.00 °C.

Auto-ignition temperature

Self-ignition temperature : Not specified.

Decomposition temperature

Decomposition point/decomposition range : Not specified.

pHpH : Not stated.
Slightly basic.

pH (aqueous solution) : Not stated.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Dilutable.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Not relevant.

Density and/or relative density

Density : > 1

Relative vapour density

Vapour density : Not stated.

Particle characteristics

The mixture does not contain nanoforms.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version 1.1 (28/03/2025) - Page 7/11

BLICK ART MATERIALS

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****11.1.1. Substances****a) Acute toxicity :**

TRIOXYDE DE DIFER (CAS: 1309-37-1)

Oral route :

LD50 > 5000 mg/kg body weight

Species : Rat (recommended by the CLP)

QUARTZ (CAS: 14808-60-7)

Oral route :

LD50 = 500 mg/kg body weight

Species : Rat

PROPANE-1,2-DIOL (CAS: 57-55-6)

Oral route :

LD50 > 2000 mg/kg body weight

Species : Rat (recommended by the CLP)

b) Skin corrosion/skin irritation :

No data available.

c) Serious damage to eyes/eye irritation :

No data available.

d) Respiratory or skin sensitisation :

No data available.

e) Germ cell mutagenicity :

TRIOXYDE DE DIFER (CAS: 1309-37-1)

Ames test (in vitro) :

Positive.

With or without metabolic activation.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2. Mixture**11.1.2.1 Information on hazard classes**

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
BLICK ART MATERIALS

Version 1.1 (28/03/2025) - Page 8/11

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563**a) Acute toxicity :**

Oral route : No data available.
No data available.

Dermal route : No data available.

Inhalation route (Dusts/mist) :

b) Skin corrosion/skin irritation :

No data available.

c) Serious damage to eyes/eye irritation :

Splashes in the eyes may cause irritation and reversible damage

d) Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2.2 Other information**11.2. Information on other hazards****Endocrine disrupting properties**

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

SECTION 12 : ECOLOGICAL INFORMATION**12.1. Toxicity****12.1.1. Substances**

TRIOXYDE DE DIFER (CAS: 1309-37-1)

Fish toxicity :

LC50 > 1000 mg/l

Species : Leuciscus idus

Duration of exposure : 48 h

PROPANE-1,2-DIOL (CAS: 57-55-6)

Fish toxicity :

LC50 > 500 mg/l

Duration of exposure : 96 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability**12.2.1. Substances**

TRIOXYDE DE DIFER (CAS: 1309-37-1)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

PROPANE-1,2-DIOL (CAS: 57-55-6)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
BLICK ART MATERIALS

Version 1.1 (28/03/2025) - Page 9/11

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563**12.3. Bioaccumulative potential**

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number or ID number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Maritime transport in bulk according to IMO instruments

-

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2024/2564. (ATP 22)

Container information:

The mixture is contained in packaging that does not exceed 125 ml.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
BLICK ART MATERIALS

Version 1.1 (28/03/2025) - Page 10/11

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563**Particular provisions :**

No data available.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):
<https://echa.europa.eu/substances-restricted-under-reach>.

Authorisations agreed under Title VII of Regulation (EC) No.1907/2006 (REACH):

The mixture does not contain any substance subject to authorisation according to Annex XIV of REACH Regulation (EC) No 1907/2006: <https://echa.europa.eu/fr/authorisation-list>.

Substances that deplete the ozone layer (EC Regulation No. 1005/2009, Montreal Protocol) :

The mixture does not contain any substance posing a risk to the ozone layer.

Persistent organic pollutants (POP) (Regulation (EU) 2019/1021):

The mixture does not contain a persistent organic pollutant.

PIC Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (Rotterdam Convention):

The mixture is not subject to the Prior Informed Consent (PIC) procedure.

Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H351	Suspected of causing cancer .
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH212	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

STEL : Short-term exposure limit

TWA : Time Weighted Averages

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
BLICK ART MATERIALS

Version 1.1 (28/03/2025) - Page 11/11

BLICK ACRYLIC PAINT - NAPLES YELLOW WARM - N131711.563

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IATA : International Air Transport Association.

IMDG : International Maritime Dangerous Goods.

ICAO : International Civil Aviation Organisation

PBT: Persistent, bioaccumulable and toxic.

PIC: Prior Informed Consent.

POP: Persistent Organic Pollutant.

RID : Regulations concerning the International carriage of Dangerous goods by rail.

SVHC : Substances of very high concern.

vPvB : Very persistent, very bioaccumulable.