Page 1 of 9

01745-1080



SAFETY DATA SHEET

BALSAM RESIN GLAZE

1. Identification of the Preparation and of The Company		
Product Name and/or code:	BALSAM RESIN GLAZE	
	PM 6	
	100 ML, 250 ML, 1 L	
Effective Date:	29-Jul-22	
Manufacturer:	Michael Harding Art Formulas Ltd	
	Unit K Springvale Industrial Estate	
	Cwmbran, UK NP44 5BE	
Website Address	www.michaelharding.co.uk	
Information Contact:	North America: 978-376-2497	
	UK/Europe: 44 (0) 1633 - 484-700	
Emergency Contact (Health) :	For health emergencies call the Poison Control Center: 1-800-222-	
	1222	
Product Use:	ART MATERIAL - CONSUMER PRODUCT. Artist professional medium.	
	For application to a substrate. Not intended for spray application,	
	sanding, or other operations which generate dust or airborne	
	concentrations.	
2. Hazards Identification		

Emergency Overview

FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED. CAUSES EYE AND SKIN IRRITATION.

Classification of the Product: Label Elements

Conforms to ASTM D-4236 (USA)



GHS Signal Word

GHS Hazard Statement

GHS Hazard Pictograms

Flammable liquids, Category 3 Acute Toxicity Oral, Category 4 Acute Toxicity Inhalation, Category 4 Acute Toxicity Dermal, Category 4 Aspiration toxicant, Category 1 Skin Irritation (mild), Category 3 Eye Irritation, Category 2A Aquatic (Acute) Category 2 Aquatic (Chronic) Category 2

y 3H226: Flammable liquid and vapor.y 4H302: Harmful if swallowed.ategory 4H332: Harmful if inhaled.gory 4H312: Harmful in contact with skin.ry 1H304: May be fatal if swallowed and enters airways.ory 3H316: Causes mild skin irritation.H319: Causes serious eye irritationH401: Toxic to aquatic life.2H411: Toxic to aquatic life with long lasting effects.



GHS Precautionary Statements

SAFETY DATA SHEET

Page 2 of 9

BALSAM RESIN GLAZE

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P280 Wear protective gloves/ eye protection/ face protection. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P264 + p265 Wash skin thoroughly after handling. Do not touch eyes. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a wellventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P331 Do NOT induce vomiting. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391 Collect spillage.

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/ container to an approved waste disposal plant.

Art Material - Consumer Product Label

Hazard Statement

May be fatal if swallowed. VAPOR HARMFUL. Inhalation of vapors may affect the brain, nervous system, respiratory system, causing dizziness, headache, nausea or respiratory irritation. MAY CAUSE ALLERGIC SKIN REACTION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

MI	SAFETY DATA SHEET	Page 3 of 9
Michael Harding	BALSAM RESIN GLAZE	
Precaution Statement:	Keep away from heat, sparks and flame. To avoid spontaneous combustion during temporary storage, soak soiled rags and wa immediately after use in a water-filled, closed metal container may cause flash fire. Use only with adequate ventilation and pr fresh air cross-ventilation. Avoid breathing vapors. Use a NIOSH properly fitted respirator. Do not eat, drink or smoke when usin eye and skin contact. Wash thoroughly after handling. Pregnant should avoid exposure to solvents.	• Vapors ovide approved g. Avoid
Children's Statement	KEEP OUT OF THE REACH OF CHILDREN.	
NFPA	Health: 2 Flammability: 3 Reactivity : 0	
HMIS	Health : 2* Flammability: 2 Physical Hazard: 1	
This product s	hould not be used for any other purpose than the intended use.	
	3.Composition/Information on Ingredients:	
Substances: Mixture of the following chemic		
	Linseed Stand Oil (CAS 67746-08-1) < 23% Wood Distillates of natural origin (mixture) < 17%	
The remainder of th	e formulation is composed of proprietary non-hazardous ingredients.	
	4. First Aid Measures	
	to the doctor in attendance. Symptoms of poisoning may appear severa not leave person unattended. Move out of dangerous area.	al hours
Inhalation	If you experience difficulty in breathing, leave the area to obtain Contact a physician immediately. If unconscious, place in recove position and contact medical attention immediately.	
Skin Contact	In case of skin contact, remove contaminated clothing and shoe immediately. Wash thoroughly with soap and plenty of water. C physician immediately if irritation occurs.	
Eye Contact	In case of eye contact, flush thoroughly with plenty of water for minutes. Contact a physician immediately if irritation occurs. Co rinsing eyes during transport to a medical facility.	
	If swallowed, do not induce vomiting. Rinse mouth. Contact a p	hysician
Ingestion	immediately.	
-	ted, material may be aspirated into the lungs and cause chemical pneum Treat appropriately.	nonitis.
-	ted, material may be aspirated into the lungs and cause chemical pneum	nonitis.

Michael Harding	SAFETY DATA SHEET Page 4 of 9 BALSAM RESIN GLAZE
Fire/Explosion Hazards	Combustible liquid and vapor. Hazardous decomposition products due to incomplete combustion.
Flashpoint/Flammability	Flammable liquid and vapor. Hazardous decomposition products due to incomplete combustion.
Fire-fighting Procedures	Fire-Fighters should wear appropriate protective equipment and self- contained breathing apparatus with a full face-piece operated in positive pressure mode. Containers may explode when heated. Do not allow run-off from fire fighting to enter drains or water courses.
	6. Accidental Release Measures
Methods and Materials for Containment and Cleaning up	Ensure adequate ventilation. Spills may produce slippery conditions. Contain spill. Recover as much as possible. Absorb remainder with non- combustible material, vermiculite or other inert material. Place into closed container and store in a safe location to await disposal. Wash the spill area with soap and water. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.
	7. Handling and Storage
Safe Handling	Prevent static build-up and discharge. Keep away from possible sources of ignition. Use under ventilated conditions. Avoid eye and skin contact. For personal protection, we recommend that employees wash thoroughly after handling product. Always wash before eating, smoking or using toilet facilities. Keep container closed when not in use. Keep container upright to prevent leakage. Do not smoke while handling this product.
Environmental precautions	No product should be released to the environment. Keep container closed when not in use. Keep container upright to prevent leakage. If the product contaminates rivers and lakes or drains inform respective authorities. Keep away from drains.
Storage	Avoid fire, flames and strong oxidizers. Handle with care. Avoid formation of aerosol. Keep in a well ventilated area. Observe label precautions. Store in a cool place. Keep in a sealed container. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed metal container.

Item Numbers: 01745-1080, 01745-1082



SAFETY DATA SHEET

Page 5 of 9

BALSAM RESIN GLAZE

	8. Exposure Controls	/Personal Protection		
Personal Protective Equipmen	occur. Wear w amounts. Use	itting safety goggles where vater resistant impervious g respirators and componen tandards such as NIOSH (U	gloves if handling bulk ts tested and approved un	
Exposure Limits (USA)	Not determin	ed for this mixture		
The values listed	below are based on publish	ed literature values for the p	oure components.	
	OSHA PEL	NIOSH REL	ACGHI TLV	1
Substance	8 hr TWA	Up to 10-hour TWA	8-hour TWA	
	(ST)	STEL (c)Ceiling(IHL) Inhala	ble	
Gum Turpentine	100 ppm (560 mg/m ³)	100 ppm (560 mg/m ³)	20 ppm [2001]	1
Respiratory and Ventilation	exceed applic manufacturer	ed NIOSH/MSHA respirator able PEL/TLV limits. Use in a 's use limitations and OSHA ay be used to prevent routin	accordance with STANDARD 1910-34. Loca	
Skin Protection	Wear water re	esistant impervious gloves i	f handling bulk amounts.	
Eye Protection	Wear goggles	where spills or splashing m	nay occur.	
	9. Physical and Cl	nemical Properties		
Appearance	Liquid			
Physical State	Liquid			
Color	Clear			
Odor	Turpentine			
State (pH)	Not applicable	e		
Specific Gravity	Not determin	ed for the mixture.		
Viscosity	5,000 - 5,500	mPas		
Flashpoint	81 ° F			
Melting point / freezing point Boiling Point (range)	Not determine	ed for the mixture. <i>(Turpen</i> ed for the mixture. <i>(Turpen max. 170 °C (ASTM D 233-1</i>	tine: initial: 156 °C (ASTM	D
Evaporation Rate		ed for the mixture. <i>(Turper</i>)
Upper Explosion Limit		ed for the mixture. <i>(Turper</i>		
Lower Explosion Limit		ed for the mixture. <i>(Turpen</i>		
Auto Ignition Temperature		ed for the mixture. <i>(Turper</i>	,	
Relative Density	Not determin ASTM D 233-1	ed for the mixture. <i>(Turpen</i> !1 at 25 °C)	tine: 0.855-0.868 g/cm ³	
Relative Vapor Density		ed for the mixture.		
Density	Not determin	ed for the mixture.		

Page 6 of 9



SAFETY DATA SHEET

BALSAM RESIN GLAZE

Vapor Pressure	Not determined for the mixture. <i>(Turpentine: 504 Pa at 20 °C, 3,623</i> Pa at 50°C)	
Solubility in water	Not determined for the mixture. (Turpentine: < 0.1%)	
10. Stability and Reactivity		
Reactivity:	No dangerous reaction known under conditions of normal use. Refer to Section 5 through 8.	
Chemical Stability	Stable under recommended storage conditions.	
Conditions to Avoid Incompatible materials	Avoid all sources of ignition (Heat, sparks and flames). Keep away from sources of ignition. Incompatible with strong oxidizing agents.	
Hazardous Decomposition Products	Hazardous decomposition products due to incomplete combustion. Carbon Oxide. Smoke. Decomposition products depend on conditions.	

11. Toxicological Information

Studies have not been performed on this particular mixture.

When used and handled according to specifications, the product is not expected to have any harmful effects.

Harmful if swallowed. Causes eye and skin irritation.
elow are based on published literature values for the pure components.
LD50 (Rat) > 3,200 mg/kg
LD50 (Rabbit) > 2,000 mg/kg
13.5 mg/liter
LD50 (Rat) > 4,897 mg/kg
LD50 (Rat) > 2,000 mg/kg
No data available.
Harmful if swallowed. Aspiration hazard. MAY BE FATAL IF ENTERS AIR WAYS.
Causes eye irritation.
Causes skin irritation.
May be harmful if inhaled. Overexposure may affect the brain or nervous system causing dizziness, headache or nausea. May cause throat irritation.

NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Sensitization	No effects are likely to occur during the foreseeable and reasonable
	use of the product.
Ingestion	If ingested, material may be aspirated into the lungs.

NJI	SAFETY DATA SHEET Page 7 of 9
Michael Harding	BALSAM RESIN GLAZE
Chronic Effects	None known for the usual and ordinary uses of this product. If ingested, material may be aspirated into the lungs. Aspiration hazard. MAY BE FATAL ENTERS AIR WAYS.
Additional toxicological information:	When used and handled according to specifications, the product is not expected to have any harmful effects according to past experience and the information provided.
<u>NTP</u> <u>IARC</u> <u>ACGIH</u> OSHA	Not applicable to product. Not applicable to product. Not applicable to product. Not applicable to product.
	12. Ecological Information
Toxicity:	No product should be released to the environment. It is not expected to have significant environmental effects when used and disposed as directed.
Aquatic toxicity	Studies have not been performed on this particular mixture.
The toxicity information listed be	low are based on published literature values for the pure components.
Gum Turpentine	
Aquatic toxicity	Classified as toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment.
Fish toxicity:	LC-0: 26 mg/l; LC-50: 33 mg/l; LC-100: 43 mg/l
Daphnia toxicity:	10-100mg/I (WAF) 24/48 hour
Algae toxicity:	>100mg/l (WAF) 72 hour Eb/ErC50
Persistence and degradability	>100mg/l (WAF) 72 hour Eb/ErC50 Complete in 28 days.
	Complete in 28 days.
	Complete in 28 days. OECD 301E - readily biodegradable material modified screening test.
Persistence and degradability	Complete in 28 days. OECD 301E - readily biodegradable material modified screening test.
Persistence and degradability Linseed Stand Oil	Complete in 28 days. OECD 301E - readily biodegradable material modified screening test. OECD 302C - inherent biodegradability modified MITI test (no. 2). LC50 (Brachydanio rerio (zebrafish)): 1,000 mg/L
Persistence and degradability Linseed Stand Oil Fish toxicity:	Complete in 28 days. OECD 301E - readily biodegradable material modified screening test. OECD 302C - inherent biodegradability modified MITI test (no. 2). LC50 (Brachydanio rerio (zebrafish)): 1,000 mg/L Exposure time: 96 h EL50 > 100 mg/L
Persistence and degradability Linseed Stand Oil Fish toxicity: Daphnia toxicity: Algae toxicity: Persistence and degradability	Complete in 28 days. OECD 301E - readily biodegradable material modified screening test. OECD 302C - inherent biodegradability modified MITI test (no. 2). LC50 (Brachydanio rerio (zebrafish)): 1,000 mg/L Exposure time: 96 h EL50 > 100 mg/L Exposure time: 48 h EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/L Exposure time: 72 h Not readily biodegradable
Persistence and degradability Linseed Stand Oil Fish toxicity: Daphnia toxicity: Algae toxicity: Persistence and degradability Bioaccumulate potential	Complete in 28 days. OECD 301E - readily biodegradable material modified screening test. OECD 302C - inherent biodegradability modified MITI test (no. 2). LC50 (Brachydanio rerio (zebrafish)): 1,000 mg/L Exposure time: 96 h EL50 > 100 mg/L Exposure time: 48 h EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/L Exposure time: 72 h Not readily biodegradable No data available.
Persistence and degradability Linseed Stand Oil Fish toxicity: Daphnia toxicity: Algae toxicity: Persistence and degradability	Complete in 28 days. OECD 301E - readily biodegradable material modified screening test. OECD 302C - inherent biodegradability modified MITI test (no. 2). LC50 (Brachydanio rerio (zebrafish)): 1,000 mg/L Exposure time: 96 h EL50 > 100 mg/L Exposure time: 48 h EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/L Exposure time: 72 h Not readily biodegradable



SAFETY DATA SHEET

Page 8 of 9

BALSAM RESIN GLAZE

13. Disposal Considerations

Dispose of all waste material in accordance with all applicable federal, state and local regulations. Handle with care. Do not dispose of waste into sewer.

14. Transport Information	
LAND DOT	
Proper Shipping Name	Turpentine
Hazard Class & Division	3
UN Number	1299
	IMCO No. 3133
Packaging Group	111
IMDG	
Proper Shipping Name	Turpentine
Transport Hazard Class	3
Packaging Group	///
EmS Codes	F-E, S-E
ICAO/IATA	
Proper Shipping Name	Turpentine
Transport Hazard Class	3
Packaging Group	<i>III</i>
This information is not intended	to convoy all specific regulatory or operational requirements (information

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the materials.

15. Regulatory Information		
Safety, health and environmental regulations/legislation specific for the substance or mixture.		
SARA	Fire Hazard , Acute Health Hazard	
Section 313 (specific toxic chemical listing)	Not applicable to this mixture.	
TSCA (Toxic Substance Control Act)	All ingredients are listed.	
California Proposition 65	WARNING: This product can expose you to chemicals including methyleugenol, estragole, safrole, pulegone, and myrcen, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.	
	WARNING: This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.	
Carcinogenicity categories EPA (Environmental Protection Agency)	Not applicable to this mixture. Not applicable to this mixture.	

Page 9 of 9



SAFETY DATA SHEET

BALSAM RESIN GLAZE

TLV (Threshold Limit Value established
by ACGIH)Not applicable to this mixture. Refer to Section 8.NIOSH (National Institute for
Occupational Safety & Health)Not applicable to this mixture.OSHA (Occupational Safety & Health
Administration)Not applicable to this mixture.

	16. Other Information
Reason for Issue:	New GHS SDS
Prepared by:	ENVIRONMENTAL MEDICINE, INC.
	778 Carver Avenue
	WESTWOOD, NJ 07675
	jaegerr@envmed.com
	201-666-7929 x13

The information contained in this Safety Data Sheet was compiled using the latest and most reliable information available to the preparer from the manufacturer. The information is provided without any warranty, express or implied regarding its correctness or accuracy nor will the manufacturer assume any liability for any loss or damage arising out of the use of this information including without limitation direct or indirect losses or expenses. To the extent permitted by law, no warranty expressed or implied regarding the product described herein shall be created by or inferred from any state or omission for this SDS. It is solely the responsibility of the user to determine safe conditions for use of this product and to assume liability for any loss, damage or expense whatsoever arising out of the product's improper use.

Abbreviations and acronyms:

Abbieviations and actoryms.	
NFPA (SCALE 0-4) National Fire	
Protection Association (USA)	
Health:	2 Warning: May be harmful if inhaled or absorbed.
Fire:	3 Warning: Flammable liquid flash point below 100°F
Reactivity:	0 Stable: Not reactive when mixed with water.
HMIS (SCALE 0-4) Hazardous Materials	
Identification System (USA)	
Health:	2 Moderate Hazard: Temporary or minor injury may occur.
	* Chronic (long-term) health effects may result from repeated over
	exposure.
Fire:	2 Moderate Hazard: Materials which must be moderately heated or
	exposed to high ambient temperatures before ignition will occur.
	Includes liquids having a flash point at or above 100 F but below 200 F
	(Classes II & IIIA).
Physical Hazard:	1 Slight Hazard. Materials that are normally stable, but can become
	unstable (self-react) at high temperatures and pressures. Materials
	may react non-violently with water or undergo hazardous
	polymerization in the absence of inhibitors.